Notation

Rubem Vasconcelos Pacelli rubem.engenharia@gmail.com

Department of Teleinformatics Engineering, Federal University of Ceará. Fortaleza, Ceará, Brazil.

Version: June 10, 2023

Contents

1	Fon	t notation			
2	Signals and functions				
	2.1	Time indexing			
	2.2	Common signals			
	2.3	Common functions			
	2.4	Operations and symbols			
	2.5	Digital signal processing			
	2.6	Transformations			
3	Probability, statistics, and stochastic processes				
	3.1	Operators and symbols			
	3.2	Stochastic processes			
	3.3				
	3.4	Distributions			
4	Ma	chine learning, optimization theory, and			
	stat	sistical signal processing			
	4.1	Matrix Calculus (in denominator layout)			
	4.2	Estimated terms			
	4.3	Signals, (hyper) parameters, system performance, and criteria $$			
5	Lin	ear Algebra			
	5.1	Common matrices and vectors			
	5.2	Indexing			
	5.3	General operations			
	5.4	Operations with matrices and tensors			
	5.5	Operations with vectors			
	5.6				

	5.7 Spaces and sets
	5.7.1 Common spaces and sets
	5.7.2 Convex sets (or spaces)
	5.7.3 Spaces from matrices or vectors
	5.8 Set operations
	5.9 Inequalities
6	Communication systems
	6.1 Common symbols
	6.2 Fading multipath channels
7	Discrete mathematics
	7.1 Quantifiers, inferences
	7.2 Propositional Logic
	7.3 Operations
8	Vector Calculus
9	Electromagnetic waves
10	Generic mathematical symbols
11	Abbreviations

1 Font notation

$a, b, c, \ldots, A, B, C, \ldots$	Scalars
a, b, c, \dots	Vectors
A, B, C, \dots	Matrices
$\mathcal{A}, \mathcal{B}, \mathcal{C}, \dots$	Tensors
$A, B, C, \ldots, \mathcal{A}, \mathcal{B}, C, \ldots, \mathbb{A}, \mathbb{B}, \mathbb{C}, \ldots$	Sets

2 Signals and functions

2.1 Time indexing

x(t)	Continuous-time t
$x[n],x[k],x[m],x[i],\ldots$	Discrete-time n, k, m, i, \ldots (parenthe-
$x_n, x_k, x_m, x_i, \dots$	sis should be adopted only if there
$x(n), x(k), x(m), x(i), \dots$	are no continuous-time signals in the
	context to avoid ambiguity)
$x[((n-m))_N][32], x((n-m))_N[26]$	Circular shift in m samples within a
	N-samples window

2.2 Common signals

$\delta(t)$	Delta function
$\delta[n], \delta_{i,j}$	Kronecker function $(n = i - j)$
h(t), h[n]	Impulse response (continuous and
	discrete time)
$\tilde{x}[n], \tilde{x}(t)$	Periodic discrete- or continuous-time
	signal
$\hat{x}[n], \hat{x}(t)$	Estimate of $x[n]$ or $x(t)$
$\dot{x}[m]$	Interpolation of $x[n]$

2.3 Common functions

$O(\cdot), O(\cdot)$	Big-O notation
$\Gamma(\cdot)$	Gamma function
$Q(\cdot)$	Quantization function
$\operatorname{sgn}(\cdot)$	Signum function
$\tanh(\cdot)$	Hyperbolic tangent function
$I_{lpha}(\cdot)$	Modified Bessel function of the first
	kind and order α

1	n	Binomial coefficient
(k	Dinomial coefficient

2.4 Operations and symbols

$f:A \to B$	A function f whose domain is A and codomain is B
$\mathbf{f}:A\to\mathbb{R}^n$	A vector-valued function \mathbf{f} , i.e., $n \geq 2$
$f^n, x^n(t), x^n[k]$	<i>n</i> th power of the function f , $x[n]$ or
	x(t)
$f^{(n)}, x^{(n)}(t)$	nth derivative of the function f or
	x(t)
$f', f^{(1)}, x'(t)$	1th derivative of the function f or
	x(t)
$f'', f^{(2)}, x''(t)$	2th derivative of the function f or
	x(t)
$arg \max f(x)$	Value of x that minimizes x
$x \in \mathcal{A}$	
$ \underset{x \in \mathcal{A}}{\operatorname{arg min}} f(x) $	Value of x that minimizes x
$\frac{x \in \mathcal{A}}{f(\mathbf{x}) = \inf_{\mathbf{y} \in \mathcal{A}} g(\mathbf{x}, \mathbf{y})}$	Infimum, i.e., $f(\mathbf{x}) =$
$\mathbf{y} \in \mathcal{A}$	$\min \{ g(\mathbf{x}, \mathbf{y}) \mid \mathbf{y} \in \mathcal{A} \land (\mathbf{x}, \mathbf{y}) \in \text{dom}(g) \},$
	which is the greatest lower bound of
	this set [10]
$f(\mathbf{x}) = \sup g(\mathbf{x}, \mathbf{y})$	Supremum, i.e., $f(\mathbf{x}) =$
$\mathbf{y} \in \mathcal{H}$	$\max \{g(\mathbf{x}, \mathbf{y}) \mid \mathbf{y} \in \mathcal{A} \land (\mathbf{x}, \mathbf{y}) \in \text{dom}(g)\},$
	which is the least upper bound of
	this set [10]
$f \circ g$	Composition of the functions f and
	g
*	Convolution (discrete or continuous)
⊗ [17], N [32]	Circular convolution

2.5 Digital signal processing

W_N	Twiddle factor, $e^{-j\frac{2\pi}{N}}$ [26]
N	Number of samples in the DFT/FFT
Ω [26]	Continuous angular frequency (in rad/s)

ω	Discrete angular frequency. As ω is
w	also used to denote continuous angu-
	lar frequency outside the DSP con-
	text, it is always convenient to state
	that it denotes the discrete frequency
	when it does
f	
$\frac{\int c}{c}$	Continuous linear frequency (in Hz)
J	Discrete linear frequency. As f is also
	used to denote continuous linear fre-
	quency outside the DSP context, it
	is always convenient to state that it
	denotes the discrete frequency when
	it does
$\mathcal{R}_N[n]$	Rectangular window used to cut off
	the discrete sequences [26]
$T[32], T_s$	Sampling period
f_s Ω_s	Sampling frequency (in Hz), i.e., $1/T$
Ω_s	Sampling frequency (in rad/s), i.e.,
	$2\pi f_s$
Ω_N [32], B	One-sided effective bandwidth of the
	continuous-time signal spectrum
ω_s	Stop frequency [26]
ω_p	Pass frequency [26]
$\Delta\omega$	$\omega_s - \omega_p$ [26]
ω_c	Cutoff frequency [26]
s(t)	Impulse train
$\operatorname{gdr}\left[H(e^{j\omega})\right]$ [32]	Group delay of $H(e^{j\omega})$
$\angle H(e^{j\omega})$ [32]	Phase response of $H(e^{j\omega})$
$H(e^{j\omega})$ [32]	Magnitude (or gain) of $H(e^{j\omega})$
$x_c(t)$ [32], $x(t)$	Continuous-time signal
$x_s(t)$	Sampled version of $x(t)$, i.e., $x(t)s(t)$
$x_r(t)$	Reconstruction of $x(t)$ from interpo-
• •	lation
$\tilde{x}[n]$	Periodic extension of the the aperi-
	odic signal $x[n]$

2.6 Transformations

$\mathcal{F}\left\{ \cdot ight\}$	Fourier transform (FT)
$\overline{\mathrm{DTFT}\left\{\cdot\right\},\mathrm{DFS}\left\{\cdot\right\},\mathrm{FFT}\left\{\cdot\right\}}$	Discrete-time Fourier Transform
	(DTFT), Discrete Fourier Trans-
	form (DFT), Discrete Fourier Series
	(DFS), respectively

$\mathcal{L}\left\{ \cdot ight\}$	Laplace transform
∠ {·}	z-transform
$\hat{x}(t), \hat{x}[n]$	Hilbert transform of $x(t)$ or $x[n]$
X(s)	Laplace transform of $x(t)$
X(f)	Fourier transform (FT) (in linear fre-
	quency, Hz) of $x(t)$
$X(j\omega)$	Fourier transform (FT) (in angular
	frequency, rad/sec) of $x(t)$
$X(e^{j\omega})$	Discrete-time Fourier transform
	(DTFT) of $x[n]$
$X[k], X(k), X_k$	Discrete Fourier transform (DFT) or
	fast Fourier transform (FFT) of $x[n]$,
	or even the Fourier series (FS) of the
	periodic signal $x(t)$
$\tilde{X}[k], \tilde{X}(k), \tilde{X}_k$	Discrete Fourier series (DFS) of $\tilde{x}[n]$
X(z)	z-transform of $x[n]$

${\bf 3}\quad {\bf Probability, statistics, and stochastic processes}$

3.1 Operators and symbols

$\mathbf{E}\left[\cdot\right],\mathbf{E}\left[\cdot\right]\left[31\right],E\left[\cdot\right],\mathbb{E}\left[\cdot\right]$	Statistical expectation operator [16]
$\mathbf{E}_{u}\left[\cdot\right],\mathbf{E}_{u}\left[\cdot\right]\left[31\right],E_{u}\left[\cdot\right],\mathbb{E}_{u}\left[\cdot\right]$	Statistical expectation operator with
	respect to u
$\overline{\langle \cdot \rangle}$	Ensemble average
$\operatorname{var}\left[\cdot\right], \operatorname{VAR}\left[\cdot\right]$	Variance operator [9, 25, 30, 34]
$\operatorname{var}_{u}\left[\cdot\right]\left[\cdot\right], \operatorname{VAR}_{u}\left[\cdot\right]$	Variance operator with respect to u
$cov[\cdot], COV[\cdot]$	Covariance operator [9]
$\operatorname{cov}_{u}[\cdot], \operatorname{COV}_{u}[\cdot]$	Covariance operator with respect to
	u
μ_{x}	Mean of the random variable x
μ_{x}, m_{x}	Mean vector of the random variable
	x [11]
μ_n	nth-order moment of a random vari-
	able
$\frac{\sigma_x^2, \kappa_2}{\mathcal{K}_x, \mu_4}$	Variance of the random variable x
\mathcal{K}_x, μ_4	Kurtosis (4th-order moment) of the
	random variable x
κ_n	nth-order cumulant of a random vari-
	able
$\rho_{x,y}$	Pearson correlation coefficient be-
	tween x and y

$a \sim P$	Random variable a with distribution P
\mathcal{R}	Rayleigh's quotient

3.2 Stochastic processes

$r_X(\tau), R_X(\tau)$	Autocorrelation function of the signal
	x(t) or x[n] [31]
$S_x(f), S_x(j\omega)$	Power spectral density (PSD) of $x(t)$
	in linear (f) or angular (ω) frequency
$S_{x,y}(f), S_{x,y}(j\omega)$	Cross PSD of $x(t)$ and $y(t)$ in linear
	or angular (ω) frequency
R _x	(Auto)correlation matrix of $\mathbf{x}(n)$
$r_{x,d}(\tau), R_{x,d}(\tau)$	Cross-correlation between $x[n]$ and
	d[n] or $x(t)$ and $d(t)$ [31]
R _{xy}	Cross-correlation matrix of $\mathbf{x}(n)$ and
	$\mathbf{y}(n)$
$\mathbf{p}_{\mathbf{x}d}$	Cross-correlation vector
	between $\mathbf{x}(n)$ and $d(n)$
	$[{ m diniz Adaptive Filtering 1997}]$
$c_x(\tau), C_x(\tau)$	Autocovariance function of the signal
	x(t) or $x[n]$ [31]
$C_x, K_x, \Sigma_x, \text{cov}[x]$	(Auto)covariance matrix of x [9, 25,
	30, 34, 41
$c_{xy}(\tau), C_{xy}(\tau)$	Cross-covariance function of the sig-
	$\operatorname{nal} x(t) \text{ or } x[n] [31]$
$C_{xy}, K_{xy}, \Sigma_{xy}$	Cross-covariance matrix of x and y

3.3 Functions

$Q(\cdot)$	Q -function, i.e., $P[\mathcal{N}(0,1) > x]$ [34]
$erf(\cdot)$	Error function [34]
$\operatorname{erfc}(\cdot)$	Complementary error function i.e.,
	$\operatorname{erfc}(x) = 2Q(\sqrt{2}x) - \operatorname{erf}(x)$ [34]
P[A]	Probability of the event or set A [30]
$p(\cdot), f(\cdot)$	Probability density function (PDF)
	or probability mass function (PMF)
	[30]
$p(x \mid A)$	Conditional PDF or PMF [30]
$F(\cdot)$	Cumulative distribution function
	(CDF)

$\Phi_{X}(\omega), M_{X}(j\omega), E\left[e^{j\omega X}\right]$	First characteristic function (CF) of x [34, 40]
$M_X(t), \Phi_X(-jt), E\left[e^{tx}\right]$	Moment-generating function (MGF) of x [34, 40]
$\Psi_{x}(\omega), \ln \Phi_{x}(\omega), \ln E\left[e^{j\omega x}\right]$	Second characteristic function
$K_X(t), \ln E\left[e^{tx}\right], \ln M_X(t)$	Cumulant-generating function (CGF) of x [25]

3.4 Distributions

$\mathcal{N}(\mu, \sigma^2)$	Gaussian distribution of a random variable with mean μ and variance σ^2
$\mathcal{CN}(\mu, \sigma^2)$	Complex Gaussian distribution of a random variable with mean μ and variance σ^2
$\mathcal{N}(\mu, \Sigma)$	Gaussian distribution of a vector random variable with mean μ and covariance matrix Σ
$\mathcal{CN}(\mu, \Sigma)$	Complex Gaussian distribution of a vector random variable with mean μ and covariance matrix Σ
$\frac{\mathcal{U}(a,b)}{\chi^2(n),\chi_n^2}$	Uniform distribution from a to b Chi-square distribution with n degree of freedom (assuming that the Gaus- sians are $\mathcal{N}(0,1)$)
$\operatorname{Exp}(\lambda)$	Exponential distribution with rate parameter λ
$\Gamma(\alpha, \beta)$	Gamma distribution with shape parameter α and rate parameter β
$\Gamma(lpha, heta)$	Gamma distribution with shape parameter α and scale parameter $\theta = 1/\beta$
$\operatorname{Nakagami}(m,\Omega)$	Nakagami-m distribution with shape parameter or fading figure m and spread, scale, or shape parameter Ω
$\operatorname{Rayleigh}(\sigma)$	Rayleigh distribution with scale parameter σ
$\operatorname{Rayleigh}(\Omega)$	Rayleigh distribution with the second moment $\Omega = E[x^2] = 2\sigma^2$
$\mathrm{Rice}(s,\sigma)$	Rice distribution with noncentrality parameter s and σ . s^2 represent the specular component power

$\operatorname{Rice}(\Omega, K), \operatorname{Rice}(A, K)$	Rice distribution with Rice factor
	$K = s^2/2\sigma^2$ and scale parameter $\Omega =$
	$A = s^2 + 2\sigma^2 = 2\sigma^2(K+1)$ (Ω is pref-
	ered over A)

4 Machine learning, optimization theory, and statistical signal processing

4.1 Matrix Calculus (in denominator layout)

$\mathbf{g}, \nabla f, \frac{\partial f}{\partial \mathbf{w}}$	Gradient descent vector, "used" in the steepest (or gradient) descent method
$\mathbf{g}_{\mathbf{x}}, \nabla_{\mathbf{w}} f, \frac{\partial f}{\partial \mathbf{w}}$	Gradient descent vector with respect \mathbf{w} [9]
$\mathbf{J}, rac{\partial \mathbf{y}^{\scriptscriptstyle ext{ iny }}}{\partial \mathbf{x}}$	Jacobian matrix.
$ \frac{\mathbf{J}, \frac{\partial \mathbf{y}^{\top}}{\partial \mathbf{x}}}{\mathbf{H}, \frac{\partial^{2} f}{\partial \mathbf{w}^{2}}, \nabla^{2} f [24], \nabla \nabla f [9]} $	Hessian matrix. The notation ∇^2 is sometimes used in Matrix Calculus to denote the second-order vector derivative. However, it must be avoided since, in Vector Calculus, ∇^2 also denotes the Laplacian operator which in turn may be scalar or vector Laplacian operator depending on whether f is scalar- or vector-valued, respectively. Some discussion about can be found in [5–7]

4.2 Estimated terms

\mathbf{g} (or $\hat{\mathbf{g}}$ if the gradient vector is \mathbf{g})	Stochastic gradient descent (SGD),
	i.e., instantaneous approximation of
	gradient descent vector
$\hat{x}(t)$ or $\hat{x}[n]$	Estimate of $x(t)$ or $x[n]$
$\hat{\boldsymbol{\mu}}_{\chi},\hat{\mathbf{m}}_{\chi}$	Sample mean of $x[n]$ or $x(t)$
$\hat{\mu}_{ ext{x}},\hat{ ext{m}}_{ ext{x}}$	Sample mean vector of $\mathbf{x}[n]$ or $\mathbf{x}(t)$
$\hat{r}_{\scriptscriptstyle X}(au), \hat{R}_{\scriptscriptstyle X}(au)$	Estimated autocorrelation function
	of the signal $x(t)$ or $x[n]$ [31]

$\hat{S}_x(f), \hat{S}_x(j\omega)$	Estimated power spectral density (PSD) of $x(t)$ in linear (f) or angular
	(ω) frequency
$\hat{\mathbf{R}}_{\mathbf{x}}$	Sample (auto)correlation matrix
$\hat{r}_{x,d}(au), \hat{R}_{x,d}(au)$	Estimated cross-correlation between $x[n]$ and $d[n]$ or $x(t)$ and $d(t)$
$\hat{S}_{x,y}(f), \hat{S}_{x,y}(j\omega)$	Estimated cross PSD of $x(t)$ and $y(t)$ in linear or angular (ω) frequency
$\hat{\mathbf{R}}_{\mathbf{x}\mathbf{y}}$	Sample cross-correlation matrix of $\mathbf{R}_{\mathbf{x}\mathbf{y}}$
$\hat{c}_x(au), \hat{C}_x(au)$	Estimated autocovariance function of the signal $x(t)$ or $x[n]$
$\hat{\mathbf{C}}_{\mathbf{x}}, \hat{\mathbf{K}}_{\mathbf{x}}, \hat{\mathbf{\Sigma}}_{\mathbf{x}}$	Sample (auto)covariance matrix
$\hat{c}_{xy}(\tau), \hat{C}_{xy}(\tau)$	Estimated cross-covariance function
	of the signal $x(t)$ or $x[n]$
$\hat{ ext{C}}_{ ext{xy}}, \hat{ ext{K}}_{ ext{xy}}, \hat{ ext{\Sigma}}_{ ext{xy}}$	Sample cross-covariance matrix
Ĥ	Estimate of the Hessian matrix

${\bf 4.3}\quad {\bf Signals,\,(hyper) parameters,\,system\,\,performance,\,and}\\ {\bf criteria}$

N	Number of instances (or samples),
	i.e., $n \in \{1, 2, \dots, N\}$
$N_{ m trn}$	Number of instances in the training
	set, i.e., $n \in \{1, 2,, N_{\text{trn}}\}$
$N_{ m tst}$	Number of instances in the test set,
	i.e., $n \in \{1, 2, \dots, N_{\text{tst}}\}$
$N_{ m val}$	Number of instances in the validation
	set, i.e., $n \in \{1, 2,, N_{\text{val}}\}$
N_e	Number of epochs
N_a	Number os attributes
K [24]	Number of classes (which is the num-
	ber of outputs in multiclass prob-
	lems). Use k to iterate over it
L	Number of layers, i.e., the depth of
	the network. Use l to iterate over it

$M_l, m_l [24], J [24]$	Number of neurons at the l th layer. You might prefer J in the case of the single-layer perceptron (use j to iterate over it). If you want to iterate through it, a sensible variation of Haykin notation is M_l , where m_l can be used as an iterator. m_0 is the length of the input vector without the bias.
$\mathbf{x}(n), \mathbf{x}_n$	Input signal (in \mathbb{R}^{N_a+1})
$x_0(n)$	Dummy input of the bais, which is usually ± 1 . $+1$ is preferred [9, 24].
$\varphi(\cdot)[24], h(\cdot)[9]$	Activation function
$\frac{\varphi(\cdot)[24], \ h(\cdot)[9]}{\varphi'(v_{m_l}^{(l)}(n))[24], \ \frac{\partial y_{m_l}^{(l)}(n)}{\partial v_{m_l}^{(l)}(n)}} [24]$	Partial derivative of the activation function with respect to $v_{m_l}^{(l)}(n)$ $(m_l$ neuron at l th layer)
$y_{m_l}^{(l)}(n), \varphi\left(v_{m_l}^{(l)}(n)\right)$	Output signal of the m_l th neuron at the l th layer
$\mathbf{y}^{(l)}(n)$	Output signal of the <i>l</i> th layer
$\frac{\mathbf{y}^{(l)}(n)}{\mathbf{y}(n), \mathbf{y}^{(L)}(n)}$ $\frac{\mathbf{d}(n), \mathbf{d}_n}{\mathbf{d}(n)}$	Output of the neural network
$\mathbf{d}(n), \mathbf{d}_n$	Desired label (in case of supervised learning). For multiclass classification, one-hot encoding is usually used. For binary (scalar) classification, however antipodal encoding, i.e., {-1,1} is more recommended [24].
$e_{m_l}(n)$	Error signal of the neuron m_l at the
	lth layer
$\frac{\mathbf{e}(n), \mathbf{d}(n) - \mathbf{y}(n)}{\mathbf{w}_{m_l}^{(l)}(n), \mathbf{\theta}_{m_l}^{(l)}(n)}$	Error signal
$\mathbf{w}_{m_{l}}^{(l)}(n), \mathbf{\theta}_{m_{l}}^{(l)}(n)$ $\begin{bmatrix} w_{m_{l},0}^{(l)}(n) & w_{m_{l},1}^{(l)}(n) & \dots & w_{m_{l},m_{l-1}}^{(l)}(n) \end{bmatrix}$	Parameters, coefficients, or synaptic weights vector in the <i>l</i> th layer. In the case of Single Layer Perceptrons or adaptive filters, the superscript is
	omitted
$w_{m_l,0}^{(l)}(n), b_{m_l}^{(l)}(n)$	Bias (the first term of the weight vector) of the <i>l</i> th layer
$\mathbf{W}(n), \begin{bmatrix} \mathbf{w}(1) & \mathbf{w}(2) & \cdots & \mathbf{w}(N) \end{bmatrix}^{T}$	Matrix of the synaptic weights
$\widetilde{\mathbf{W}}(n)$	Matrix of the synaptic weights, but without the bias

$v_{m_l}^{(l)}(n), \mathbf{w}_{m_l}^{(l)\top}(n)\mathbf{y}_{m_{l-1}}^{(l-1)}(n)$	Induced local field or activation potential. At the first layer $\mathbf{y}_{m_0}^{(0)}(n) = \mathbf{x}(n)$ [9]
$\mathbf{v}^{(l)}(n), \mathbf{W}^{(l)}(n)\mathbf{y}_{m_{l-1}}^{(l-1)}(n)$	Vector of the local fields at the <i>l</i> th layer
$\mathbf{w}^{\star}, \mathbf{w}_{o}, \mathbf{\theta}^{\star}, \mathbf{\theta}_{o}$	Optimum value of the parameters, coefficients, or synaptic weights vector (\mathbf{w}^* is also used [9] but it is not recommended as it may be confused with the conjugation operator)
$\delta_{m_l}^{(l)}(n),rac{\partial \mathscr{E}(n)}{\partial v_{m_l}^{(l)}(n)}$	Local gradient of the m_l th neuron of the l th layer.
$\boldsymbol{\delta}^{(l)}(n)$	Vector of the local gradients of all neurons at the l th layer
$\mathbf{X}, \begin{bmatrix} \mathbf{x}(1) & \mathbf{x}(2) & \cdots & \mathbf{x}(N) \end{bmatrix}$	Data matrix
$\frac{\eta(n)}{\mathscr{R}}$	Learning rate hyperparameter [24]
<u>R</u>	Bayes risk or average risk [24]
c_{ij}, C_{ij}	Misclassification cost in deciding in favor of class \mathcal{C}_i (represented in the subspace \mathcal{K}_i) when the \mathcal{C}_j is the true class (used in Bayes classifiers/detectors) [12, 24]
\mathcal{C}_{1}	kth class [24]
$\frac{\mathscr{C}_k}{\mathscr{T}[24], \mathbb{X}[22]}$	Training set, i.e., the set $\{\mathbf{x}(n), d(n)\}$ that is used in the training phase.
\mathcal{H}_k	Subspace of the training vector belonging to the class \mathcal{C}_k
${\cal H}$	Complete space of the input vector, i.e., $\mathcal{H}_1 \cup \mathcal{H}_2 \cup \cdots \mathcal{H}_K$
\mathcal{X} [24]	Set of all vectors in the training, batch, validation, or test dataset that was misclassified
$\mathscr{E}(\mathbf{w}), \mathscr{E}(\mathbf{w}(n)), \mathscr{E}(n)$	Cost function or objective function (the way it is written depends on the purpose of the text)
$J(\mathbf{w}), J(\mathbf{w}(n)), J(n)$	Alternative to the cost function
$ \Delta \mathcal{E}(\mathbf{w}(n)), \Delta \mathcal{E}(n), \mathcal{E}(\mathbf{w}(n+1)) - \mathcal{E}(\mathbf{w}(n)) $	Cost function or objective function (the way it is written depends on the purpose of the text)
$\mathscr{E}_{\mathrm{av}}(\cdot)$	Error energy averaged over the training sample or the empirical risk [9]
$\Lambda(\cdot)$	Likelihood function
$\Lambda_l(\cdot)$	Log-likelihood function

$\hat{ ho}_{x,y}$	Estimated Pearson correlation coeffi-
	cient between x and y
$\overline{\rho}$	Distance of the margin of separation
	between two classes (Support Vector
	Machine, SVM)
$g(\cdot)$	Discriminant function, i.e., $g(\mathbf{w}^*) = 0$

5 Linear Algebra

5.1 Common matrices and vectors

W, D	Diagonal matrix
P	Projection matrix; Permutation ma-
	trix
J	Jordan matrix
L	Lower matrix
U	Upper matrix
C	Cofactor matrix
$\mathbf{C}_{\mathbf{A}}, \operatorname{cof}\left(\mathbf{A}\right)$	Cofactor matrix of A
S	Symmetric matrix
Q	Orthogonal matrix
$\overline{\mathbf{I}_N}$	$N \times N$ -dimensional identity matrix
$0_{M imes N}$	$M \times N$ -dimensional null matrix
0_N	N-dimensional null vector
$1_{M imes N}$	$M \times N$ -dimensional ones matrix
1_N	N-dimensional ones vector
0	Null matrix, vector, or tensor (di-
	mensionality understood by context)
1	Ones matrix, vector, or tensor (di-
	mensionality understood by context)

5.2 Indexing

$x_{i_1,i_2,,i_N}, [X]_{i_1,i_2,,i_N}$	Element in the position (i_1, i_2, \ldots, i_N) of the tensor X
$X^{(n)}$	nth tensor of a nontemporal sequence
$X_n, X_{:n}$	nth column of the matrix X
\mathbf{x}_{n} :	nth row of the matrix X
$\mathbf{X}_{i_1,,i_{n-1},:,i_{n+1},,i_N}$	Mode- n fiber of the tensor X
$\mathbf{x}_{:,i_{2},i_{3}}$	Column fiber (mode-1 fiber) of the
	thrid-order tensor $\boldsymbol{\mathcal{X}}$

$X_{i_1,:,i_3}$	Row fiber (mode-2 fiber) of the thrid-
	order tensor $\boldsymbol{\mathcal{X}}$
$X_{i_1,i_2,:}$	Tube fiber (mode-3 fiber) of the
	thrid-order tensor $\boldsymbol{\mathcal{X}}$
$\mathbf{X}_{i_1,:,:}$	Horizontal slice of the thrid-order
	tensor $\boldsymbol{\mathcal{X}}$
$X_{:,i_2,:}$	Lateral slices slice of the thrid-order
	tensor $\boldsymbol{\mathcal{X}}$
$\mathbf{X}_{i_3}, \mathbf{X}_{:,:,i_3}$	Frontal slices slice of the thrid-order
	tensor $\boldsymbol{\mathcal{X}}$

5.3 General operations

$\langle \mathbf{a}, \mathbf{b} angle , \mathbf{a}^ op \mathbf{b}, \mathbf{a} \cdot \mathbf{b}$	Inner or dot product
$\mathbf{a} \circ \mathbf{b}, \mathbf{a} \mathbf{b}^{ op}$	Outer product
⊗	Kronecker product
· ·	Hadamard (or Schur) (elementwise)
	product
.⊙n	nth-order Hadamard power
$\circ \frac{1}{n}$	nth-order Hadamard root
$\bigcirc \frac{1}{n}$	nth-order Hadamard root Hadamard (or Schur) (elementwise)
	Hadamard (or Schur) (elementwise)
	Hadamard (or Schur) (elementwise) division

5.4 Operations with matrices and tensors

\mathbf{A}^{-1}	Inverse matrix
$\mathbf{A}^+,\mathbf{A}^\dagger$	Moore-Penrose left pseudoinverse
$\mathbf{A}^{T}, \mathbf{A}^{T}, \mathbf{A}^{t}, \mathbf{A}^{'}$ [37]	Transpose
$\mathbf{A}^{-\top}$	Transpose of the inverse, i.e.,
	$\left(\mathbf{A}^{-1}\right)^{T} = \left(\mathbf{A}^{T}\right)^{-1} [21, 33]$
A *	Complex conjugate
\mathbf{A}^{H}	Hermitian
$\ \mathbf{A}\ _{\mathrm{F}}$	Frobenius norm
$\ \mathbf{A}\ $	Matrix norm
$ \mathbf{A} , \det(\mathbf{A})$	Determinant
$diag(\mathbf{A})$	The elements in the diagonal of A
E [A]	Vectorization: stacks the columns of
	the matrix A into a long column vec-
	tor

$\mathbf{E}_d\left[\mathbf{A}\right]$	Extracts the diagonal elements of a
	square matrix and returns them in a
	column vector
$\mathbf{E}_{l}\left[\mathbf{A} ight]$	Extracts the elements strictly below
	the main diagonal of a square matrix
	in a column-wise manner and returns
	them into a column vector
$\mathbf{E}_{u}\left[\mathbf{A}\right]$	Extracts the elements strictly above
	the main diagonal of a square matrix
	in a column-wise manner and returns
	them into a column vector
$\overline{\mathbf{E}_{b}\left[\mathbf{A} ight]}$	Block vectorization operator: stacks
	square block matrices of the input
	into a long block column matrix
unvec (A)	Reshapes a column vector into a ma-
	trix
$-\operatorname{tr}\{\mathbf{A}\}$	trace
$X_{(n)}$	n-mode matricization of the tensor X

5.5 Operations with vectors

$\ \mathbf{a}\ $	l_1 norm, 1-norm, or Manhattan norm
$\ \mathbf{a}\ , \ \mathbf{a}\ _2$	l_2 norm, 2-norm, or Euclidean norm
$\ \mathbf{a}\ _p$	l_p norm, p -norm, or Minkowski norm
$\ \mathbf{a}\ _{\infty}$	l_{∞} norm, ∞ -norm, or Chebyshev
	norm
diag (a)	Diagonalization: a square, diagonal matrix with entries given by the vec-
	tor a

5.6 Decompositions

Λ	Eigenvalue matrix [39]
Q	Eigenvectors matrix; Orthogonal ma-
	trix of the QR decomposition[39]
R	Upper triangular matrix of the QR
	decomposition[39]
U	Left singular vectors[39]
$\overline{\mathbf{U}_r}$	Left singular nondegenerated vectors
Σ	Singular value matrix
Σ_r	Singular value matrix with nonzero
	singular values in the main diagonal

<u>Σ</u> ⁺	Singular value matrix of the poor
	Singular value matrix of the pseu-
	doinverse [39]
Σ_r^+	Singular value matrix of the pseu-
	doinverse with nonzero singular val-
	ues in the main diagonal
V	Right singular vectors [39]
$\overline{V_r}$	Right singular nondegenerated vec-
	tors
$eig(\mathbf{A})$	Set of the eigenvalues of A [13, 30,
	33]
$\llbracket A, B, C, \ldots bracket$	CANDECOMP/PARAFAC (CP) de-
	composition of the tensor $\boldsymbol{\mathcal{X}}$ from the
	outer product of column vectors of \mathbf{A} ,
	$\mathbf{B}, \mathbf{C}, \dots$
$\boxed{\llbracket \boldsymbol{\lambda}; \mathbf{A}, \mathbf{B}, \mathbf{C}, \ldots \rrbracket}$	Normalized CANDE-
	COMP/PARAFAC (CP) decom-
	position of the tensor $\boldsymbol{\mathcal{X}}$ from the
	outer product of column vectors of
	A, B, C, \dots

5.7 Spaces and sets

5.7.1 Common spaces and sets

\mathbb{R}	Set of real numbers
a,b	Closed interval of a real set from a to
	b
(a,b)	Opened interval of a real set from a
	to b
$\overline{[a,b),(a,b]}$	Half-opened intervals of a real set
	from a to b
\mathbb{C}	Set of complex numbers
\mathbb{Z}	Set of integer number
$\overline{\{1,2,\ldots,n\}}$	Discrete set containing the integer el-
	ements $1, 2, \ldots, n$
$\mathbb{B} = \{0, 1\}$	Boolean set
Ø	Empty set
N	Set of natural numbers
$\mathbb{K} \in \{\mathbb{R}, \mathbb{C}\}$	Real or complex space (field)
$\mathbb{K}^{I_1 \times I_2 \times \cdots \times I_N}$	$I_1 \times I_2 \times \cdots \times I_N$ -dimensional real (or
	complex) space
\mathbb{K}_{+}	Nonnegative real (or complex) space
	[10]

\mathbb{K}_{++}	Positive real (or complex) space, i.e.,
	$\mathbb{K}_{++} = \mathbb{K}_+ \setminus \{0\} \ [10]$
\overline{U}	Universe
2^A	Power set of A

5.7.2 Convex sets (or spaces)

\mathbb{S}^{n} [15], \mathcal{S}^{n} [10]	Conic set of the symmetric matrices in $\mathbb{R}^{n \times n}$
On On	
$\mathbb{S}^n_+,\mathcal{S}^n_+$	Conic set of the symmetric positive
	semidefinite matrices in $\mathbb{R}^{n \times n}$ [10]
$\mathbb{S}^n_{++}, \mathcal{S}^n_{++}$	Conic set of the symmetric positive
	definite matrices in $\mathbb{R}^{n \times n}$, i.e., \mathbb{S}^n_{++} =
	$\mathbb{S}^n_+ \setminus \{0\} \ [10]$
\mathbb{H}^n	Set of all hermitian matrices in $\mathbb{C}^{n\times n}$
conv C	Convex hull
aff C	Affune hull
\mathcal{R}	Ray
Н	Hyperplane
$\mathcal{H}_+,\mathcal{H}$	Positive/negative halfspace
$B(\mathbf{x}_c, r)$	Euclidean ball with radium r and
	centered at \mathbf{x}_c
8	Ellipsoid
C	Norm cone
K	Proper cone
	Dual cone
\mathcal{P}	Polyhedra
S	Simplex
C_{α}	α -sublevel set
epi f	Epigraph of the function f
hypo f	Hypograph of the function f

5.7.3 Spaces from matrices or vectors

$\operatorname{span}\left\{\mathbf{a}_{1},\mathbf{a}_{2},\ldots,\mathbf{a}_{n}\right\}$	Vector space spanned by the argu-
	ment vectors [21]
$C(\mathbf{A})$, columnspace(\mathbf{A}), range(\mathbf{A}),	Columnspace, range or image, i.e.,
$\operatorname{span} \{\mathbf{A}\}, \operatorname{image}(\mathbf{A})$	the space span $\{\mathbf{a}_1, \mathbf{a}_2, \dots, \mathbf{a}_n\}$, where
	\mathbf{a}_i is the ith column vector of the ma-
	trix A [31, 39]
$C(\mathbf{A}^{H})$	Row space (also called left
<u> </u>	columnspace) [31, 39]

$N(\mathbf{A})$, nullspace(\mathbf{A}), null(\mathbf{A}), kernel	(A) Nullspace (or kernel space) [31, 39,
	40]
$N(\mathbf{A}^{H})$	Left nullspace
rank A	Rank, that is, $\dim(\operatorname{span}\{A\}) =$
	$\dim \left(\mathrm{C} \left(\mathbf{A} \right) \right) \left[31 \right]$
nullity (A)	Nullity of \mathbf{A} , i.e., dim $(N(\mathbf{A}))$

5.8 Set operations

A + B	Set addition (Minkowski sum), i.e.,
	$\{\mathbf{v} \in \mathbb{R}^n \mid \mathbf{v} = \mathbf{x} + \mathbf{y}, \ \forall \ \mathbf{x} \in \mathcal{X} \land \mathbf{y} \in \mathcal{Y}\}$
	[28]
A - B	Minkowski difference, i.e.,
	$\{\mathbf{v} \in \mathbb{R}^n \mid \mathbf{v} = \mathbf{x} - \mathbf{y}, \ \forall \ \mathbf{x} \in \mathcal{X} \land \mathbf{y} \in \mathcal{Y}\}$
$A\ominus B$	Pontryagin difference, i.e.,
	$\{\mathbf{v} \in \mathbb{R}^n \mid \mathbf{v} + \mathbf{y} \in \mathcal{X}, \ \forall \ \mathbf{y} \in \mathcal{Y}\}\ [28]$
$A \setminus B, A - B$	Set difference or set subtraction, i.e.,
	$A \setminus B = \{x x \in A \land x \notin B\}$ the set con-
	taining the elements of A that are not
	in B [36]
$A \cup B$	Set of union
$A \cap B$	Set of intersection
$A \times B$	Cartesian product
A^n	$A \times A \times \cdots \times A$
	n times
A^{\perp}	Orthogonal complement of A , e.g.,
	$N(\mathbf{A}) = C(\mathbf{A}^{T})^{\perp} [10]$
a ⊥ b	a is orthogonal to b
_ a ∠ b	a is not orthogonal to b
$A \oplus B$	Direct sum, i.e., each $\mathbf{v} \in$
	$\{\sum \mathbf{a}_i \mid \mathbf{a}_i \in S_i, i = 1, \dots, k\}$ has a
	unique representation of $\sum \mathbf{a}_i$ with
	$\mathbf{a}_i \in S_i$. That is, they expand to a
	space. Note that $\{S_i\}$ might not be
1	orthogonal each other [21]
$A\stackrel{ ightharpoonup}{\oplus} B$	Direct sum of two spaces that are or-
	thogonal and span a n -dimensional
	space, e.g., $C(\mathbf{A}^{T}) \stackrel{\perp}{\oplus} C(\mathbf{A}^{T})^{\perp} =$
	\mathbb{R}^n (this decomposition of \mathbb{R}^n is
	called the orthogonal decomposition
	induced by \mathbf{A}) [10]
\overline{A}, A^c	Complement set (given U)
· · · · · · · · · · · · · · · · · · ·	1 (0 /

#A, A	Cardinality of A
$a \in A$	a is element of A
$a \notin A$	a is not element of A

5.9 Inequalities

$X \le 0$	Nonnegative tensor
$a \leq_K b$	Generalized inequality meaning that
	$\mathbf{b} - \mathbf{a}$ belongs to the conic subset K in
	the space $\mathbb{R}^n[10]$
$a <_K b$	Strict generalized inequality meaning
	that $\mathbf{b} - \mathbf{a}$ belongs to the interior of
	the conic subset K in the space $\mathbb{R}^n[10]$
$a \le b$	Generalized inequality meaning that
	$\mathbf{b} - \mathbf{a}$ belongs to the nonnegative or-
	thant conic subset, \mathbb{R}^n_+ , in the space
	$\mathbb{R}^{n}.[10]$
a < b	Strict generalized inequality meaning
	that $\mathbf{b} - \mathbf{a}$ belongs to the positive or-
	thant conic subset, \mathbb{R}^n_{++} , in the space
	$\mathbb{R}^n[10]$
$\mathbf{A} \leq_K \mathbf{B}$	Generalized inequality meaning that
	${\bf B}-{\bf A}$ belongs to the conic subset K
	in the space $\mathbb{S}^n[10]$
$\mathbf{A} \prec_K \mathbf{B}$	Strict generalized inequality meaning
	that ${\bf B}-{\bf A}$ belongs to the interior of
	the conic subset K in the space $\mathbb{S}^n[10]$
$A \leq B$	Generalized inequality meaning that
	$\mathbf{B} - \mathbf{A}$ belongs to the positive semidef-
	inite conic subset, \mathbb{S}_{+}^{n} , in the space
	$\mathbb{S}^n[10]$
A < B	Strict generalized inequality meaning
	that $\mathbf{B} - \mathbf{A}$ belongs to the positive or-
	thant conic subset, \mathbb{S}_{++}^n , in the space
	$\mathbb{S}^n[10]$

6 Communication systems

6.1 Common symbols

В	One-sided bandwidth of the trans-
	mitted signal, in Hz

$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	\overline{W}	One-sided bandwidth of the trans-
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		
$ \begin{array}{c} x_q \\ f_c, f_{RF} \\ \\ f_L \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	x_i	
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	· · · · · · · · · · · · · · · · · · ·	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$, <u>, , , , , , , , , , , , , , , , , , </u>	1 0
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	f_{IF}	Intermediate frequency (in Hertz)
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	f_s	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		(in Hertz)
R Bit rate T Bit interval/duration/period T_c Chip interval/duration/period T_{sy}, T_{sym} Symbol/signaling[34] interval/duration/period S_{RF} Transmitted signal in RF S_{FI} Transmitted signal in FI s, s_l Lowpass (or baseband) equivalent signal or envelope complex of transmitted signal r_{RF} Received signal in RF r_{FI} Received signal in FI r, r_l Lowpass (or baseband) equivalent signal or envelope complex of received signal ϕ Signal phase ϕ_0 Initial phase η_{RF}, w_{RF} Noise in RF η_{FI}, w_{FI} Noise in FI η, w Noise in baseband τ Timing delay $\Delta \tau$ Timing error (delay - estimated) ϕ Phase offset $\Delta \varphi$ Phase error (offset - estimated) f_d Linear Doppler frequency Δf_d Frequency error (Doppler frequency - estimated) ν Angular Doppler frequency σ Frequency error (Doppler frequency - estimated)	T_s	Sampling time interval/duration/pe-
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$, , , , , , , , , , , , , , , , ,
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	R	Bit rate
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	T	Bit interval/duration/period
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\overline{T_c}$	Chip interval/duration/period
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	T_{SV}, T_{SVm}	Symbol/signaling[34] interval/dura-
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		tion/period
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	SRF	Transmitted signal in RF
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	SFI	Transmitted signal in FI
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\overline{s, s_l}$	Lowpass (or baseband) equivalent
r_{RF} Received signal in RF r_{FI} Received signal in FI r, r_{I} Lowpass (or baseband) equivalent signal or envelope complex of received signal ϕ Signal phase ϕ_{0} Initial phase η_{RF}, w_{RF} Noise in RF η_{FI}, w_{FI} Noise in FI η, w Noise in baseband τ Timing error (delay - estimated) φ Phase offset $\Delta \varphi$ Phase error (offset - estimated) f_d Linear Doppler frequency Δf_d Frequency error (Doppler frequency - estimated) ν Angular Doppler frequency $\Delta \nu$ Frequency error (Doppler frequency - estimated)		signal or envelope complex of trans-
r_{FI} Received signal in FI r, r_l Lowpass (or baseband) equivalent signal or envelope complex of received signal ϕ Signal phase ϕ_0 Initial phase η_{RF}, w_{RF} Noise in RF η_{FI}, w_{FI} Noise in baseband τ Timing delay $\Delta \tau$ Timing error (delay - estimated) φ Phase offset $\Delta \varphi$ Phase error (offset - estimated) f_d Linear Doppler frequency Δf_d Frequency error (Doppler frequency - estimated) ν Angular Doppler frequency $\Delta \nu$ Frequency error (Doppler frequency - estimated)		
$ r, r_l \qquad \qquad \text{Lowpass (or baseband) equivalent signal or envelope complex of received signal } $	r_{RF}	O O
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	r_{FI}	<u> </u>
$\begin{array}{cccc} ceived signal \\ \phi & Signal phase \\ \phi_0 & Initial phase \\ \eta_{RF}, w_{RF} & Noise in RF \\ \eta_{FI}, w_{FI} & Noise in FI \\ \eta, w & Noise in baseband \\ \tau & Timing delay \\ \Delta\tau & Timing error (delay - estimated) \\ \varphi & Phase offset \\ \Delta\varphi & Phase error (offset - estimated) \\ f_d & Linear Doppler frequency \\ \Delta f_d & Frequency error (Doppler frequency - estimated) \\ \nu & Angular Doppler frequency \\ \Delta \nu & Frequency error (Doppler frequency - estimated) \\ \end{array}$	r, r_l	- \ / -
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		
$\begin{array}{cccc} \phi_0 & & & & & & & \\ \eta_{RF}, w_{RF} & & & & & & \\ Noise in RF & & & & & \\ \eta_{FI}, w_{FI} & & & & & \\ Noise in FI & & & & \\ \eta, w & & & & & \\ \Delta \tau & & & & & \\ Timing delay & & \\ \Delta \tau & & & & & \\ Timing error (delay - estimated) & \\ \varphi & & & & & \\ Phase offset & \\ \Delta \varphi & & & & & \\ Phase error (offset - estimated) & \\ f_d & & & & & \\ Linear Doppler frequency & \\ \Delta f_d & & & & \\ Frequency error (Doppler frequency - estimated) & \\ \nu & & & & & \\ \Delta v & & & & \\ Frequency error (Doppler frequency - estimated) & \\ \end{array}$		<u> </u>
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	ϕ	
	ϕ_0	<u>-</u>
η, w Noise in baseband τ Timing delay $\Delta \tau$ Timing error (delay - estimated) φ Phase offset $\Delta \varphi$ Phase error (offset - estimated) f_d Linear Doppler frequency Δf_d Frequency error (Doppler frequency - estimated) ν Angular Doppler frequency $\Delta \nu$ Frequency error (Doppler frequency - estimated)	η_{RF}, w_{RF}	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	η_{FI}, w_{FI}	
$\begin{array}{cccc} \Delta \tau & & & & & & & \\ \hline \varphi & & & & & & \\ \hline \varphi & & & & & \\ \hline \Delta \varphi & & & & & \\ \hline \Delta \varphi & & & & & \\ \hline \Delta hase error (offset - estimated) \\ \hline f_d & & & & \\ \hline \Delta f_d & & & \\ \hline \Delta f_d & & & \\ \hline \Delta f_d & & & \\ \hline Frequency error (Doppler frequency - estimated) \\ \hline \nu & & & & \\ \hline \Delta v & & & \\ \hline \Delta v & & & \\ \hline \Delta v & & & \\ \hline Erequency error (Doppler frequency - estimated) \\ \hline \end{array}$	η, w	
$\begin{array}{ccc} \varphi & & \text{Phase offset} \\ \Delta \varphi & & \text{Phase error (offset - estimated)} \\ f_d & & \text{Linear Doppler frequency} \\ \Delta f_d & & \text{Frequency error (Doppler frequency - estimated)} \\ \nu & & \text{Angular Doppler frequency} \\ \Delta \nu & & \text{Frequency error (Doppler frequency - estimated)} \end{array}$	τ	
$ \begin{array}{cccc} \Delta \varphi & & \text{Phase error (offset - estimated)} \\ f_d & & \text{Linear Doppler frequency} \\ \Delta f_d & & \text{Frequency error (Doppler frequency - estimated)} \\ \nu & & \text{Angular Doppler frequency} \\ \Delta \nu & & \text{Frequency error (Doppler frequency - estimated)} \\ \end{array} $	Δau	
$ \begin{array}{ccc} f_d & & \text{Linear Doppler frequency} \\ \Delta f_d & & \text{Frequency error (Doppler frequency -} \\ & & \text{estimated)} \\ \nu & & \text{Angular Doppler frequency} \\ \Delta \nu & & \text{Frequency error (Doppler frequency -} \\ & & \text{estimated)} \\ \end{array} $		
$ \begin{array}{ccc} \Delta f_d & & \text{Frequency error (Doppler frequency -} \\ & & \text{estimated)} \\ \nu & & \text{Angular Doppler frequency} \\ \Delta \nu & & \text{Frequency error (Doppler frequency -} \\ & & & \text{estimated)} \\ \end{array} $	$\Delta arphi$	
$\begin{array}{ccc} & & & \text{estimated}) \\ \nu & & & \text{Angular Doppler frequency} \\ \Delta\nu & & & \text{Frequency error (Doppler frequency -} \\ & & & & \text{estimated}) \end{array}$		
$ \nu $ Angular Doppler frequency Frequency error (Doppler frequency - estimated)	Δf_d	
$\Delta \nu$ Frequency error (Doppler frequency - estimated)		
estimated)		
	Δu	
γ, A Transmitted signal amplitude		,
	γ, A	Transmitted signal amplitude

γ_0, A_0	Combined effect of the path loss and
	antenna gain

6.2 Fading multipath channels

$t \stackrel{\mathcal{F}}{\leftrightarrow} \lambda \ [34]$	Support temporal of the signal. λ is obtained after taking the Fourier transform on t .
$\tau \stackrel{\mathcal{F}}{\leftrightarrow} f \ [34]$	Second support temporal of the signal $(c(t))$ varies with with the input at the time τ). f is obtained after taking the Fourier transform on τ .
$c(t,\tau) [34]$	Complex envelope of the channel response at the time t due to an impulse applied at the $t-\tau$
C(f,t) [34]	Transfer function of $c(t, \tau)$ in τ
$\frac{C(f,t) [34]}{\alpha(t,\tau) [34]}$	Attenuation of $c(t,\tau)$, i.e., $c(t,\tau) = \alpha(t,\tau)e^{e\pi f_c\tau}$
$R_c(\tau_1, \tau_2, \Delta t)$ [34]	Autocorrelation function of
	$c(t,\tau)$, i.e., $R_c(\tau_1,\tau_2,\Delta t) = \mathbf{E}\left[c^*(t,\tau_1),c^*(t+\Delta t,\tau_2)\right]$
$R_c(\tau, \Delta t)$ [34]	Autocorrelation function of $c(t, \tau)$ as-
	suming uncorrelated scattering
$R_c(\tau), R_c(\tau, \Delta t)\Big _{\Delta t=0}$ [34]	Multipath intensity profile or delay
	power spectrum
$R_C(\Delta f, \Delta t), R_C(f_1, f_2; \Delta t),$	Spaced-frequency, spaced-time corre-
$\mathbf{E}\left[C(f_1,t),C(f_2,t+\Delta t)\right],$	lation function $(\Delta f = f_2 - f_1)$
$\mathcal{F}_{\tau}\left\{R_{c}(\tau,\Delta t)\right\} [20]$	
$ \frac{\mathcal{F}_{\tau} \left\{ R_{c}(\tau, \Delta t) \right\} [20]}{R_{C}(\Delta f), R_{C}(\Delta f, \Delta t) \Big _{\Delta t = 0}} \qquad [34], $ $ \mathcal{F} \left\{ R_{c}(\tau) \right\} [20] $	Spaced-frequency correlation function
$(\Delta f)_c$	Coherence bandwidth of $c(t)$, that
	is, the frequency interval in which
	$R_C(\Delta f)$ is nonzero [34]
T_m	Multipath spread of the channel, that
	is, the time interval in which $R_c(\tau)$ is
	nonzero $(T_m \approx 1/(\Delta f)_c)$ [34]
$R_C(\Delta t), R_C(\Delta f, \Delta t) _{\Delta f=0}$	Spaced-time correlation function [34]
$\frac{\left. R_C(\Delta t), R_C(\Delta f, \Delta t) \right _{\Delta f = 0}}{S_C(\lambda) [34], \mathcal{F} \left\{ R_C(\Delta t) \right\} [20]}$	Doppler power spectrum
$(\Delta t)_c$	Coherence time of $c(t)$, that is, the
	time interval in which $R_C(\Delta t)$ is
	nonzero [34]

B_m	Multipath spread of the channel, th	$\overline{\mathrm{at}}$
	is, the frequency interval in whi	ich
	$S_c(\lambda)$ is nonzero $(B_d \approx 1/(\Delta t)_c)$ [3-	4]
$S_C(\tau,\lambda)$ [34], \mathcal{F}_{Δ}	$\{R_C(\Delta f, \Delta t)\}$ Scattering function	
[20]		

7 Discrete mathematics

7.1 Quantifiers, inferences

\forall	For all (universal quantifier) [23]
3	There exists (existential quantifier)
	[23]
<u></u> ∄ ∃!	There does not exist [23]
3!	There exists an unique [23]
\exists_n	There exists exactly n [36]
€ ∉	Belongs to [23]
∉	Does not belong to [23]
·	Because [23]
<u> ,:</u>	Such that, sometimes that parenthe-
	ses is used [23]
$\overline{}$,,(·)	Used to separate the quantifier with
	restricted domain from its scope, e.g.,
	$\forall x < 0 (x^2 > 0) \text{ or } \forall x < 0, x^2 > 0$
	[23]
·:	Therefore [23]

7.2 Propositional Logic

$\neg a$	Logical negation of a [36]
$a \wedge b$	Conjunction (logical AND) operator
	between a and $b[36]$
$a \lor b$	Disjunction (logical OR) operator be-
	tween a and $b[36]$
$a \oplus b$	Exclusive OR (logical XOR) operator
	between a and $b[36]$
$a \rightarrow b$	Implication (or conditional) state-
	ment[36]
$a \leftrightarrow b$	Bi-implication (or biconditional)
	statement, i.e., $(a \rightarrow b) \land (b \rightarrow a)$
	[36]

$a \equiv b, a \iff b, a \Leftrightarrow b$	Logical equivalence, i.e., $a \leftrightarrow b$ is a
	tautology[36]

7.3 Operations

a	Absolute value of a
log	Base-10 logarithm or decimal loga-
	rithm
ln	Natual logarithm
$Re\{x\}$	Real part of x
$\overline{\operatorname{Im}\left\{ x\right\} }$	Imaginary part of x
۲٠	Phase (complex argument)
$x \mod y$	Remainder, i.e., $x - y \lfloor x/y \rfloor$, for $y \neq 0$
x div y	Quotient [36]
$x \equiv y \pmod{m}$	Congruent, i.e., $m \setminus (x - y)$ [36]
frac(x)	Fractional part, i.e., $x \mod 1$ [23]
$a \setminus b, a \mid b$	b is a positive integer multiple of a ,
	i.e., $\exists n \in \mathbb{Z}_{++} \mid b = na \ [23, 36]$
$a \not\setminus b, a \not\mid b$	b is not a positive integer multiple of
	$a, \text{ i.e., } \not\equiv n \in \mathbb{Z}_{++} \mid b = na \ [23, 36]$
[·]	Ceiling operation [23]
[.]	Floor operation [23]

8 Vector Calculus

$\nabla f[38], \operatorname{grad} f[35]$	Vector differential operator (Nabla symbol), i.e., ∇f is the gradient of
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	the scalar-valued function f , i.e., f :
	$\mathbb{R}^n o \mathbb{R}$
t,(u,v)	Parametric variables commonly used,
	t for one variable, (u, v) for two vari-
	ables[38]
$l(x, y, z)$ [35], $\mathbf{r}(x, y, z)$ [38], $x\hat{\mathbf{i}} + y\hat{\mathbf{j}} + z\hat{\mathbf{k}}$	Vector position, i.e., (x, y, z) .
$\overline{\mathbf{l}(t)}$	Vector position parametrized by t ,
	i.e., $(x(t), y(t), z(t))$ [35, 38]
l'(t), dl/dt	First derivative of $l(t)$, i.e., the
	tangent vector of the curve
	(x(t), y(t), z(t)) [38]
$\mathbf{u}(t)[29] \ \mathbf{T}(t)[38], \ dl(t)[35]$	Tangent unit vector of $\mathbf{l}(t)$, i.e.,
	$\mathbf{u}(t) = \mathbf{l}'(t)/ \mathbf{l}'(t) $

$\mathbf{n}(t), \left(\frac{y'(t)}{ \mathbf{l}'(t) }, -\frac{x'(t)}{ \mathbf{l}'(t) }\right)$	Normal vector of $\mathbf{l}(t)$, i.e.,
(1- (-7))	$\mathbf{n}(t) \perp \mathbf{T}(t)[38]$
C	Contour that traveled by $l(t)$, for $a \le t \le b$ [38]
L, L(C)	Total length of the contour C
	(which can be defined the vector
	1, parametrized by t), i.e., $L_C =$
	$\int_a^b \mathbf{l}'(t) \mathrm{d}t [38]$
s(t)	Length of the arc, which can be de-
	fined by the vector l and t , that is, $s(t) = \int_a^t \mathbf{l}'(u) \mathrm{d}u \ (s(b) = L)[38]$
ds	Differential operator of the length of
	the contour C , i.e., $ds = \mathbf{l}'(t) dt$ [38]
$\int_C f(1) \mathrm{d}s, \int_a^b f(1(t)) 1'(t) \mathrm{d}t$	Line integral of the function $f: \mathbb{R}^n \to$
	\mathbb{R} along the contour C . In the context
	of integrals in the complex plane, it
a [9r]	is also called "contour integral"
θ [35]	Angle between the contour C and the vector field \mathbf{F}
$\int_C \mathbf{F} \cdot d\mathbf{l}, \ \int_a^b \mathbf{F}(\mathbf{l}(t)) \cdot \mathbf{l}'(t) dt \ [8, 38],$	Line integral of vector field F along
$\int_C \mathbf{F} \cdot \mathbf{u} ds, \int_C \mathbf{F} \cos \theta ds [35]$	the contour C
$\frac{\int_{C} \mathbf{F} \cdot \mathbf{u} \mathrm{d}s, \int_{C} \mathbf{F} \cos \theta \mathrm{d}s [35]}{\int_{C} \mathbf{F} \cdot \mathrm{d}\mathbf{u} [35]}$	In the field of electromagnetics, it is
	common to apply the line integral be-
	tween the vector field F and the unit
	vector $\mathbf{u}(t)$. Therefore, this line inte-
ch ch	gral may appear as well
$\int_{\mathbf{a}}^{\mathbf{b}} \mathbf{F}, \int_{\mathbf{a}}^{\mathbf{b}} \mathbf{F} \cdot d\mathbf{l}$	Alternative notation to the line inte-
	gral, where the parametric variable t
	goes from a to b , making r goes from $\mathbf{l}(a) = \mathbf{a}$ to $\mathbf{l}(b) = \mathbf{b}$ [8]
\oint_C , \oint_C	Line integral along the closed contour
JC/ JC	C. The arrow indicates the contour
	integral orientation, which is counter-
	clockwise, by default. In the context
	of integrals in the complex plane, it is
- CC	also called "closed contour integral".
\oint_S	Surface integral over the closed sur-
1(face S
l(u, v)	Vector position
	(x(u,v),y(u,v),z(u,v)) parametrized
$-$ l _{ι}	$\frac{\text{by }(u,v)}{(\partial x/\partial u,\partial y/\partial u,\partial z/\partial u)}$
$\frac{1_{u}}{1_{v}}$	$\frac{(\partial x/\partial u, \partial y/\partial u, \partial z/\partial u)}{(\partial x/\partial v, \partial y/\partial v, \partial z/\partial v)}$
<u>-v</u>	(0.7,0,0,7,0,7,0,7,0,7,0,7,0,7,0,7,0,7,0,

-dA	Differential operator of a 2D area
uA	(denoted by D or R) in the \mathbb{R}^2 do-
	main. This differential operator can
	be solved in different ways (rectangu-
	lar, polar, cylindric, etc) [38]
D,R	Integration domain in which dA is
	integrated, i.e., $\iint_D f dA$. R is pre-
	ferred when the integration domain
	is a rectangle, while D is used when
	it has nonrectangular shape [38]
S	Smooth surface $S \subset \mathbb{R}^3$, i.e., a 2D
	area in a 3D space
dS , $ \mathbf{l}_u \times \mathbf{l}_v dA$	Differential operator of a 2D area in
710	a 3D domain (an surface). Note that
	$dS = \mathbf{l}_u \times \mathbf{l}_v dA$ should be accompa-
	nied with the change of the integra-
	tion interval(from S to D)
$A(S), \iint_S dS, \iint_D \mathbf{l}_u \times \mathbf{l}_v dA$	Area of the surface S parametrized by
$M(S)$, MS as, MD $ \mathbf{u}_{u} \times \mathbf{r}_{v} $ and	(u, v), in which dA is the area defined
	in the D domain (which is form by
-117	the <i>u</i> -by- <i>v</i> graph)
$\mathrm{d}V$	Differential operator of a shape vol-
	ume (denoted by E) in \mathbb{R}^3 domain,
	i.e., $\iiint_E dV = V$
E	Integration domain in which dV is in-
	tegrated, i.e., $\iiint_E f dV$ [38]
$V, \iint_D f \mathrm{d}A, \iiint_E f \mathrm{d}V$	Volume of the function f over the re-
	gions D (in the case of double inte-
	grals) or E (in the case of triple inte-
	grals)
$\frac{\iint_{S} f \mathrm{d}S, \iint_{D} f \mathbf{l}_{u} \times \mathbf{l}_{v} \mathrm{d}A}{\mathbf{n}(u, v), \frac{\mathbf{l}_{u}(u, v) \times \mathbf{l}_{v}(u, v)}{ \mathbf{l}_{u}(u, v) \times \mathbf{l}_{v}(u, v) }}$	Surface integral over S
$\mathbf{n}(u,v), \frac{\mathbf{l}_u(u,v) \times \mathbf{l}_v(u,v)}{ \mathbf{l}_u(u,v) \times \mathbf{l}_v(u,v) }$	Normal vector of of the smooth sur-
$ u(u,v)\wedge v(u,v) $	face S
$\iint_{S} \mathbf{F} \cdot \mathbf{n} \mathrm{d}S , \iint_{S} \mathbf{F} \cdot \mathrm{d}\mathbf{S} ,$	Flux integral of vector field \mathbf{F} through
$\iint_{\mathcal{D}} \mathbf{F} \cdot (\mathbf{l}_{u} \times \mathbf{l}_{v}) \mathrm{d}A$	the smooth surface S ($\mathbf{n} dS \triangleq d\mathbf{S}$)
$ \iint_{D} \mathbf{F} \cdot (\mathbf{l}_{u} \times \mathbf{l}_{v}) dA \iint_{S} \mathbf{F} \cdot \mathbf{n} dS, \iint_{S} \mathbf{F} \cdot d\mathbf{S}, $	Flux integral of vector field F through
$\iint_D \mathbf{F} \cdot (\mathbf{l}_u \times \mathbf{l}_v) \mathrm{d}A$	the smooth and closed surface S
$JJD = (-u \cdot -v) \cdots$	$(\mathbf{n} \mathrm{d} \mathbf{S} \triangleq \mathbf{d} \mathbf{S})$
$\nabla \times \mathbf{F}$, curl \mathbf{F}	$\frac{\text{Curl (rotacional) of the vector field } \mathbf{F}}{\text{Curl (rotacional) of the vector field } \mathbf{F}}$
$\nabla \cdot \mathbf{F}$, div \mathbf{F}	Divercence of the vector field F
$\frac{\mathbf{v} \cdot \mathbf{r}, \text{div } \mathbf{r}}{\nabla^2 f, \nabla \cdot (\nabla f), \Delta f,}$	
$\partial^2 f / \partial x^2 + \partial^2 f / \partial y^2 + \partial^2 f / \partial z^2$	
$\sigma_{J}/\sigma x + \sigma_{J}/\sigma y^{-} + \sigma_{J}/\sigma z^{-}$	formed on a scalar-valued function $f \in \mathbb{R}^n$
	$f: \mathbb{R}^n \to \mathbb{R}$

$\nabla^2 \mathbf{F}, \nabla \times \nabla \times \mathbf{F} - \nabla (\nabla \cdot \mathbf{F}), \Delta \mathbf{F},$	Vector Laplacian operator (per-
$(\partial^2 \mathbf{F}/\partial x^2, \partial^2 \mathbf{F}/\partial y^2, \partial^2 \mathbf{F}/\partial z^2)$	formed on a vector field, i.e., a
	vector-valued function, $\mathbf{F}: \mathbb{R}^n \to$
	\mathbb{R}^n). ∇^2 denotes the scalar (vector)
	Laplacian if the function is scalar-
	valued (vector-valued). The notation
	Δ must be avoided as it is overused
	in many contexts

$9\quad Electromagnetic\ waves$

Φ	Electric flux (scalar) (in V m)	
H	Magnetic field vector (in A/m)	
В	Magnetic flux density vector (in	
	$Wb/m^2 = T$	
$\Phi[14]$	Magnetic flux	
$q_{\mathrm{f}},q_{\mathrm{free}},Q_{\mathrm{free}}[18]$	Free electric charge (in C)	
$q_{\rm b}, q_{\rm bound}, Q_{\rm bound}[18]$	Bound electric charge (in C)	
$q, q_{\mathrm{f}} + q_{\mathrm{b}}$	Electric charge (in C)	
$\rho_{\rm f}[1], \rho_{\rm free}$ [18]	Free electric charge density	
$\rho_{\rm b}[1], \rho_{\rm bound}$ [18]	Electric charge density	
$\rho, \rho_{\rm f} + \rho_{\rm b}$	Electric charge density (it can be	
	in C/m^3 , C/m^2 or C/m depending	
	whether it is a volume, surface, or	
	line shapes)	
f[35], F[2]	Electrostatic force (Coulomb force),	
	$(\text{in kg m/s}^2).$	
ε	Electric permittivity (in F/m). If the	
	medium is isotropic, it is a scalar. If	
	it is anisotropic, it is a tensor. [35]	
\mathcal{E}_r	Relative electric permittivity or di-	
	electric constant (in F/m) [35]	
$oldsymbol{arepsilon}_0$	Electric permittivity in vacuum,	
	$8.854 \times 10^{-12} \mathrm{F/m}$ [35]	
E	Electric field vector (in V/m)	
σ	Electric conductivity (in S/m)	
J	Electric current density vector (in	
	A/m^2)	
$\mathbf{J}_m[14]$	Magnetization current density vector	
	$(in A/m^2)$	

Electric flux density, electric dis-
placement, or electric induction vec-
tor (in C/m^2)
Electric potential energy
Electric potential (in voltage, V).
However, keep in mind that there is
a subtle difference between both def-
initions [4]
Electric flux (in V m)
Electric flux (D -field flux)
Electric polarization of the material
$(in C/m^2)$
Electric susceptibility (for linear and
isotropic materials)
Magnetic permeability
Magnetic permeability in vacuum

10 Generic mathematical symbols

	Q.E.D.
<u> </u>	Equal by definition
:=, ←	Assignment [36]
≠	Not equal
∞	Infinity
j	$\sqrt{-1}$

11 Abbreviations

PS: Only names of methods and algorithms, technical abbreviations, and mathematical functions are considered.

wrt. With respe	ect to
st. Subject to	
iff. If and only	if
EVD Eigenvalue	decomposition, or eigen-
decomposi	tion [31]
DNN Deep Neur	al Network
NN Nearest Ne	eighbor
AI Artificial I	ntelligence
SVD Singular va	alue decomposition
CP CANDECO	OMP/PARAFAC
SGD Stochastic	gradient descent

SVM	Support vector machine
BPNN	Backpropagation neural network [27]
RBF	Radial basis function

References

- [1] URL: https://en.wikipedia.org/wiki/Electric_displacement_field#Definition.
- [2] URL: https://en.wikipedia.org/wiki/Coulomb%27s_law.
- [3] URL: https://en.wikipedia.org/wiki/Electric_potential.
- [4] URL: https://physics.stackexchange.com/a/300937/368410.
- [5] Libavius (https://math.stackexchange.com/users/1020990/libavius). Which is the correct vector calculus notation for the Hessian? Mathematics Stack Exchange. URL:https://math.stackexchange.com/q/4560326 (version: 2023-02-15). eprint: https://math.stackexchange.com/q/4560326. URL: https://math.stackexchange.com/q/4560326.
- [6] maple (https://math.stackexchange.com/users/51601/maple). Does the symbol ∇² has the same meaning in Laplace Equation and Hessian Matrix? Mathematics Stack Exchange. URL:https://math.stackexchange.com/q/1353761 (version: 2022-07-29). eprint: https://math.stackexchange.com/q/1353761. URL: https://math.stackexchange.com/q/1353761.
- [7] Rubem Pacelli (https://math.stackexchange.com/users/817590/rubem-pacelli). Ambiguity over the notation ∇²: vector Laplacian operator (Vector Calculus) vs. second directional derivative (Matrix Calculus). Mathematics Stack Exchange. URL:https://math.stackexchange.com/q/4693212 (version: 2023-05-05). eprint: https://math.stackexchange.com/q/4693212. URL: https://math.stackexchange.com/q/4693212.
- [8] TM Apostol. Calculus, 2nd Edn., Vol. 2. 1967.
- [9] Christopher M Bishop and Nasser M Nasrabadi. Pattern Recognition and Machine Learning. Vol. 4. 4. Springer, 2006.
- [10] Stephen Boyd, Stephen P. Boyd, and Lieven Vandenberghe. Convex Optimization. Cambridge university press, 2004.
- [11] Robert Grover Brown and Patrick YC Hwang. "Introduction to Random Signals and Applied Kalman Filtering: With MATLAB Exercises and Solutions". In: Introduction to random signals and applied Kalman filtering: with MATLAB exercises and solutions (1997).
- [12] Charles Casimiro. Lecture notes in Statistical Signal Processing. 2019.
- [13] Rama Chellappa and Sergios Theodoridis. Signal Processing Theory and Machine Learning. Academic Press, 2014. ISBN: 0-12-396502-0.

- [14] David Keun Cheng. Field and Wave Electromagnetics. Pearson Education India, 1989.
- [15] Jon Dattorro. Convex Optimization & Euclidean Distance Geometry. Lulu. com, 2010. ISBN: 0-615-19368-4.
- [16] Paulo SR Diniz. Adaptive Filtering: Algorithms and Practical Implementation. Nowell, MA: Kluwer Academic Publishers, 2002.
- [17] Paulo SR Diniz, Eduardo AB Da Silva, and Sergio L Netto. Digital Signal Processing: System Analysis and Design. Cambridge University Press, 2010. ISBN: 1-139-49157-1.
- [18] Example Wikipedia Page. URL: https://en.wikipedia.org/wiki/ Gauss%27s_law#Equation_involving_the_D_field.
- [19] Example Wikipedia Page. URL: https://en.wikipedia.org/wiki/Flux# Electric_flux.
- [20] Andrea Goldsmith. Wireless Communications. Cambridge university press, 2005. ISBN: 0-521-83716-2.
- [21] Gene H Golub and Charles F Van Loan. *Matrix Computations*. JHU press, 2013. ISBN: 1-4214-0859-7.
- [22] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. Illustrated edição. Cambridge, Massachusetts: The MIT Press, Nov. 18, 2016. ISBN: 978-0-262-03561-3.
- [23] Ronald L Graham et al. "Concrete Mathematics: A Foundation for Computer Science". In: *Computers in Physics* 3.5 (1989), pp. 106–107. ISSN: 0894-1866.
- [24] Simon Haykin. Neural Networks and Learning Machines, 3/E. Pearson Education India, 2009. ISBN: 93-325-8625-X.
- [25] Simon S Haykin. *Adaptive Filter Theory*. Pearson Education India, 2002. ISBN: 81-317-0869-1.
- [26] Vinay K Ingle and John G Proakis. *Digital Signal Processing Using MAT-LAB*. Cole Publishing Company, 2000.
- [27] Yu Jiao, John J Hall, and Yu T Morton. "Automatic Equatorial GPS Amplitude Scintillation Detection Using a Machine Learning Algorithm". In: *IEEE Transactions on Aerospace and Electronic Systems* 53.1 (2017), pp. 405–418. ISSN: 0018-9251.
- [28] Basil Kouvaritakis and Mark Cannon. "Model Predictive Control". In: Switzerland: Springer International Publishing 38 (2016).
- [29] Erwin Kreyszig, K Stroud, and G Stephenson. *Advanced Engineering Mathematics*. Vol. 9. John Wiley & Sons, Inc. 9 th edition, 2006 Page 2 of 6 Teaching methods ..., 2008.
- [30] Alberto Leon-Garcia. Probability, Statistics, and Random Processes for Electrical Engineering. 3rd ed. edição. Upper Saddle River, NJ: Prentice Hall, 2007. ISBN: 978-0-13-147122-1.

- [31] Josef Nossek. Adaptive and Array Signal Processing. 2015.
- [32] Alan V. Oppenheim and Ronald W. Schafer. Discrete-Time Signal Processing: International Edition. 3^a edição. Upper Saddle River Munich: Pearson, Nov. 12, 2009. ISBN: 978-0-13-206709-6.
- [33] Kaare Brandt Petersen and Michael Syskind Pedersen. "The Matrix Cookbook". In: *Technical University of Denmark* 7.15 (2008), p. 510.
- [34] John Proakis and Masoud Salehi. *Digital Communications*. 5th ed. edição. Boston: Mc Graw Hill, Jan. 1, 2007. ISBN: 978-0-07-295716-7.
- [35] Simon Ramo, John R Whinnery, and Theodore Van Duzer. Fields and Waves in Communication Electronics. John Wiley & Sons, 1994. ISBN: 81-265-1525-2.
- [36] Kenneth H Rosen. "Discrete Mathematics and Its Applications (7Th Editio)". In: William C Brown Pub (2011).
- [37] Shayle R Searle and Andre I Khuri. *Matrix Algebra Useful for Statistics*. John Wiley & Sons, 2017. ISBN: 1-118-93514-4.
- [38] James Stewart. Calculus. Cengage Learning, 2011. ISBN: 1-133-17069-2.
- [39] Gilbert Strang et al. *Introduction to Linear Algebra*. Vol. 3. Wellesley-Cambridge Press Wellesley, MA, 1993.
- [40] Sergios Theodoridis. Machine Learning: A Bayesian and Optimization Perspective. 2nd ed. Academic Pr, 2020. ISBN: 978-0-12-818803-3.
- [41] Harry L Van Trees. Optimum Array Processing: Part IV of Detection, Estimation, and Modulation Theory. John Wiley & Sons, 2002. ISBN: 0-471-09390-4.