

Demo ticket

Session

ID: demoZSQ3V6-Z7E
Time limit: 120 min.

Status: closed

Created on: 2014-03-23 04:22 UTC
Started on: 2014-03-23 04:22 UTC
Finished on: 2014-03-23 04:29 UTC

Tasks in test

1 |  MinAbsSumOfTwo

Task score

100%

Test score

100%

100 out of 100 points

HARD

1. MinAbsSumOfTwo

Find the minimal absolute value of a sum of two elements.

score: 100 of 100



Task description

Let A be a non-empty zero-indexed array consisting of N integers. The *abs_sum_of_two* for a pair of indices (P, Q) is the absolute value $|A[P] + A[Q]|$, for $0 \leq P \leq Q < N$. For example, the following array A:

```
A[0] = 1
A[1] = 4
A[2] = -3
```

has pairs of indices (0, 0), (0, 1), (0, 2), (1, 1), (1, 2), (2, 2).

The *abs_sum_of_two* for the pair (0, 0) is $A[0] + A[0] = |1 + 1| = 2$.

The *abs_sum_of_two* for the pair (0, 1) is $A[0] + A[1] = |1 + 4| = 5$.

The *abs_sum_of_two* for the pair (0, 2) is $A[0] + A[2] = |1 + (-3)| = 2$.

The *abs_sum_of_two* for the pair (1, 1) is $A[1] + A[1] = |4 + 4| = 8$.

The *abs_sum_of_two* for the pair (1, 2) is $A[1] + A[2] = |4 + (-3)| = 1$.

The *abs_sum_of_two* for the pair (2, 2) is $A[2] + A[2] = |(-3) + (-3)| = 6$.

Write a function:

```
def solution(A)
```

that, given a non-empty zero-indexed array A consisting of N integers, returns the minimal *abs_sum_of_two* for any pair of indices in this array.

For example, given the following array A:

```
A[0] = 1
A[1] = 4
A[2] = -3
```

the function should return 1, as explained above.

Given array A:

```
A[0] = -8
A[1] = 4
A[2] = 5
A[3] = -10
A[4] = 3
```

the function should return $|(-8) + 5| = 3$.

Solution

Programming language used: Python

Total time used: 7 minutes

Effective time used: 7 minutes

Notes: correct functionality and scalability

Task timeline



04:22:37

04:29:13

Code: 04:29:13 UTC, py, final, score: 100.00

```
01. def solution(A):
02.     A.sort()
03.     N = len(A)
04.
05.     i = 0
06.     j = N-1
07.     min_abs = 1000000000 * 2
08.
09.     while i <= j:
10.         s = A[j] + A[i]
11.         min_abs = min(min_abs, abs(s))
12.         if s > 0:
13.             j -= 1
14.         elif s < 0:
15.             i += 1
16.         else:
17.             break
18.
19.     return min_abs
```

Analysis

Assume that:

- N is an integer within the range [1..100,000];
- each element of array A is an integer within the range [−1,000,000,000..1,000,000,000].

Complexity:

- expected worst-case time complexity is $O(N \cdot \log(N))$;
- expected worst-case space complexity is $O(1)$, beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Detected time complexity: $O(N \cdot \log(N))$		
test	time	result
example1 first example	0.050 s.	OK
example2 second example	0.050 s.	OK
extreme_single sequences of 1 elements	0.050 s.	OK
extreme_double sequences of 2 elements	0.050 s.	OK
positive_small only positive numbers	0.050 s.	OK
negative_small only negative numbers	0.050 s.	OK
random_small random sequence, length = ~1000	0.050 s.	OK
random_medium random sequence, length = ~10,000	0.070 s.	OK
arithmetic_medium arithmetic sequence, length = ~10,000	0.130 s.	OK
random_large random sequence, length = ~100,000	0.280 s.	OK
extreme_large sequence of MAX_INT, length = ~100,000	0.280 s.	OK
arithmetic_large arithmetic sequence, length = ~100,000	0.340 s.	OK
constant_distance constant distance between all elements, length = 100,000	0.330 s.	OK

Training center