

Demo ticket

Session

ID: demoNTZZPT-YXC
Time limit: 120 min.

Status: closed

Created on: 2014-03-20 16:08 UTC
Started on: 2014-03-20 16:08 UTC
Finished on: 2014-03-20 16:13 UTC

Tasks in test

1 |  CountNonDivisible

Task score

100%

Test score

100%

100 out of 100 points

MEDIUM

1. CountNonDivisible

Calculate the number of elements of an array that are not divisors of each element.

score: 100 of 100



Task description

You are given a non-empty zero-indexed array A consisting of N integers.

For each number $A[i]$ such that $0 \leq i < N$, we want to count the number of elements of the array that are not the divisors of $A[i]$. We say that these elements are non-divisors.

For example, consider integer $N = 5$ and array A such that:

```
A[0] = 3
A[1] = 1
A[2] = 2
A[3] = 3
A[4] = 6
```

For the following elements:

- $A[0] = 3$, the non-divisors are: 2, 6,
- $A[1] = 1$, the non-divisors are: 3, 2, 3, 6,
- $A[2] = 2$, the non-divisors are: 3, 3, 6,
- $A[3] = 3$, the non-divisors are: 2, 6,
- $A[4] = 6$, there aren't any non-divisors.

Write a function:

```
def solution(A)
```

that, given a non-empty zero-indexed array A consisting of N integers, returns a sequence of integers representing the numbers of non-divisors.

The sequence should be returned as:

- a structure Results (in C), or
- a vector of integers (in C++), or
- a record Results (in Pascal), or
- an array of integers (in any other programming language).

For example, given:

```
A[0] = 3
A[1] = 1
```

Solution

Programming language used: Python

Total time used: 6 minutes

Effective time used: 6 minutes

Notes: correct functionality and scalability

Task timeline



16:08:35

16:13:52

Code: 16:13:52 UTC, py, final, score: 100.00

```
01. def solution(A):
02.     nums = {}
03.     for a in A:
04.         if a in nums:
05.             nums[a] += 1
06.         else:
07.             nums[a] = 1
08.
09.     N = len(A)
10.     D = [0] * (2 * N + 1)
11.     for n in nums.keys():
12.         i = n
13.         while i <= 2 * N:
14.             D[i] += nums[n]
15.             i += n
16.
17.     ret = [0] * N
18.     for i, a in enumerate(A):
19.         ret[i] = N - D[a]
20.
21.     return ret
22.
```

3/20/2014

Test results - Codility

A[2] = 2
A[3] = 3
A[4] = 6

the function should return [2, 4, 3, 2, 0], as explained above.
Assume that:

- N is an integer within the range [1..50,000];
- each element of array A is an integer within the range [1..2 * N].

Complexity:

- expected worst-case time complexity is O(N*log(N));
- expected worst-case space complexity is O(N), beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Analysis

Detected time complexity:
O(N * log(N))

test	time	result
example example test	0.050 s.	OK
extreme_simple extreme simple	0.050 s.	OK
double two elements	0.050 s.	OK
simple simple tests	0.050 s.	OK
primes prime numbers	0.050 s.	OK
small_random small, random numbers, length = 100	0.050 s.	OK
medium_random medium, random numbers length = 5,000	0.080 s.	OK
large_range 1, 2, ..., N, length = ~20,000	0.140 s.	OK
large_random large, random numbers, length = ~30,000	0.180 s.	OK
large_extreme large, all the same values, length = 50,000	0.230 s.	OK

Training center

© 2009–2014 Codility Ltd., registered in England and Wales (No. 7048726). VAT ID GB981191408. Registered office: 107 Cheapside, London EC2V 6DN

<https://codility.com/demo/results/demoNTZZPT-YXC/>

2/2