

Demo ticket

Session


ID: demoW7M67S-ARJ
Time limit: 120 min.

Status: closed

Created on: 2014-03-15 03:37 UTC
Started on: 2014-03-15 03:38 UTC
Finished on: 2014-03-15 03:49 UTC

Tasks in test

Task score



MEDIUM

1. Triangle

Determine whether a triangle can be built from a given set of edges.

score: 100 of 100



Task description

A zero-indexed array A consisting of N integers is given. A triplet (P, Q, R) is *triangular* if $0 \leq P < Q < R < N$ and:

- $A[P] + A[Q] > A[R]$,
- $A[Q] + A[R] > A[P]$,
- $A[R] + A[P] > A[Q]$.

For example, consider array A such that:

$A[0] = 10$ $A[1] = 2$ $A[2] = 5$
 $A[3] = 1$ $A[4] = 8$ $A[5] = 20$

Triplet $(0, 2, 4)$ is triangular.
Write a function:

```
def solution(A)
```

that, given a zero-indexed array A consisting of N integers, returns 1 if there exists a triangular triplet for this array and returns 0 otherwise.
For example, given array A such that:

$A[0] = 10$ $A[1] = 2$ $A[2] = 5$
 $A[3] = 1$ $A[4] = 8$ $A[5] = 20$

the function should return 1, as explained above. Given array A such that:

$A[0] = 10$ $A[1] = 50$ $A[2] = 5$
 $A[3] = 1$

the function should return 0.
Assume that:

- N is an integer within the range $[0..1,000,000]$;
- each element of array A is an integer within the range $[-2,147,483,648..2,147,483,647]$.

Complexity:

- expected worst-case time complexity is $O(N \cdot \log(N))$;
- expected worst-case space complexity is $O(N)$, beyond

Solution

Programming language used: Python

Total time used: 12 minutes

Effective time used: 12 minutes

Notes: correct functionality and scalability

Task timeline



03:38:13

03:49:59

Code: 03:49:59 UTC, py, final, score: 100.00

```
01. def solution(A):
02.     # write your code in Python 2.6
03.     A.sort()
04.     size = len(A)
05.     for i in xrange(size-2):
06.         if A[i] <= 0:
07.             continue
08.         if A[i] + A[i+1] > A[i+2]:
09.             return 1
10.     return 0
11.
```

Analysis

Detected time complexity:
 $O(N \cdot \log(N))$

test	time	result
example		

input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Codility

example example, positive answer, length=6	0.050 s.	OK
example1 example, negative answer, length=4	0.050 s.	OK
example2 example, positive answer	0.050 s.	OK
example_grouped example, answer is zero	0.050 s.	OK
extreme_empty empty sequence + [5,3,3]	0.050 s.	OK
extreme_single 1-element sequence + [5,3,3]	0.050 s.	OK
extreme_two_elems 2-element sequence + [5,3,3]	0.050 s.	OK
extreme_negative1 three equal negative numbers	0.050 s.	OK
extreme_arith_overflow1 overflow test, 3 MAXINTs + [5,3,3]	0.050 s.	OK
extreme_arith_overflow2 overflow test, 10 and 2 MININTs + [5,3,3]	0.050 s.	OK
extreme_arith_overflow3 overflow test, 0 and 2 MAXINTs + [5,3,3]	0.050 s.	OK
medium1 chaotic sequence of values from [0..100K], length=30 + [1,5,10]	0.050 s.	OK
medium2 chaotic sequence of values from [0..1K], length=50 + [1,5,10]	0.050 s.	OK
medium3 chaotic sequence of values from [0..1K], length=100 + [1,5,10]	0.050 s.	OK
large1 chaotic sequence with values from [0..100K], length=10K + [1,5,10]	0.050 s.	OK
large2 1 followed by an ascending sequence of ~50K elements from [0..100K], length=~50K + [1,5,10]	0.050 s.	OK
large_random chaotic sequence of values from [0..1M], length=100K + [1,5,10]	0.050 s.	OK
large_negative chaotic sequence of negative values from [-1M..-1], length=100K + [1,5,10]	0.050 s.	OK
large_negative2 chaotic sequence of negative values from [-10..-1], length=100K + [5,3,3]	0.050 s.	OK
large_negative3 sequence of -1 value, length=100K + [5,3,3]	0.050 s.	OK

Training center