

Demo ticket

Session


ID: demoEBRF39-QZF
Time limit: 120 min.

Status: closed

Created on: 2014-03-17 18:44 UTC
Started on: 2014-03-17 18:45 UTC
Finished on: 2014-03-17 18:45 UTC

Tasks in test

Task score



MEDIUM

1. MinAvgTwoSlice

Find the minimal average of any slice containing at least two elements.

score: 100 of 100



Task description

A non-empty zero-indexed array A consisting of N integers is given. A pair of integers (P, Q) , such that $0 \leq P < Q < N$, is called a *slice* of array A (notice that the slice contains at least two elements). The *average* of a slice (P, Q) is the sum of $A[P] + A[P + 1] + \dots + A[Q]$ divided by the length of the slice. To be precise, the average equals $(A[P] + A[P + 1] + \dots + A[Q]) / (Q - P + 1)$.
For example, array A such that:

```
A[0] = 4
A[1] = 2
A[2] = 2
A[3] = 5
A[4] = 1
A[5] = 5
A[6] = 8
```

contains the following example slices:

- slice (1, 2), whose average is $(2 + 2) / 2 = 2$;
- slice (3, 4), whose average is $(5 + 1) / 2 = 3$;
- slice (1, 4), whose average is $(2 + 2 + 5 + 1) / 4 = 2.5$.

The goal is to find the starting position of a slice whose average is minimal.

Write a function:

```
def solution(A)
```

that, given a non-empty zero-indexed array A consisting of N integers, returns the starting position of the slice with the minimal average. If there is more than one slice with a minimal average, you should return the smallest starting position of such a slice.

For example, given array A such that:

```
A[0] = 4
A[1] = 2
A[2] = 2
A[3] = 5
A[4] = 1
A[5] = 5
```

Solution

Programming language used: Python

Total time used: 1 minutes

Effective time used: 1 minutes

Notes: correct functionality and scalability

Task timeline



Code: 18:45:40 UTC, py, final, score: 100.00

```
01. def solution(A):
02.     N = len(A)
03.     avg = [0] * (N-1)
04.     last = N - 1
05.     for i in xrange(N-2, -1, -1):
06.         avg[i] = (A[i] + A[i+1]) / 2.0
07.         if i < N-2:
08.             x = 1.0 * (A[i] + avg[i+1] * (last - i))
09.             x /= (last - i + 1)
10.             if x < avg[i]:
11.                 avg[i] = x
12.             else:
13.                 last = i + 1
14.
15.     min_avg = sys.maxint
16.     min_index = -1
17.     for i in xrange(N-1):
18.         if avg[i] < min_avg:
19.             min_avg = avg[i]
20.             min_index = i
21.     return min_index
```

A[6] = 8

the function should return 1, as explained above.
Assume that:

- N is an integer within the range [2..100,000];
- each element of array A is an integer within the range [-10,000..10,000].

Complexity:

- expected worst-case time complexity is O(N);
- expected worst-case space complexity is O(N), beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Analysis



Detected time complexity:
O(N)

test	time	result
example example test	0.050 s.	OK
double_quadruple two or four elements	0.050 s.	OK
simple1 simple test, the best slice has length 3	0.050 s.	OK
simple2 simple test, the best slice has length 3	0.050 s.	OK
small_random random, length = 100	0.050 s.	OK
medium_range increasing, decreasing (legth = ~100) and small functional	0.050 s.	OK
medium_random random, N = ~700	0.050 s.	OK
large_ones numbers from -1 to 1, N = ~100,000	0.280 s.	OK
large_random random, N = ~100,000	0.350 s.	OK
extreme_values all maximal values, N = ~100,000	0.340 s.	OK
large_sequence many seqeneces, N = ~100,000	0.250 s.	OK

Training center