

Software Engineering using Formal Methods

Introduction to PROMELA

Ina Schaefer

Institute for Software Systems Engineering
TU Braunschweig, Germany

Slides by Wolfgang Ahrendt, Richard Bubel, Reiner Hähnle
(Chalmers University of Technology, Gothenburg, Sweden)



Towards Model Checking


System Model

Promela Program

```
byte n = 0;  
active proctype P() {  
    n = 1;  
}  
active proctype Q() {  
    n = 2;  
}
```

System Property

P, Q are never in their
critical section at the same time



What is PROMELA?

PROMELA is an acronym

Process meta-language

PROMELA is a language for modeling modeling concurrent concurrent systems

- multi-threaded
- synchronisation and message passing
- few control structures, pure (no side-effects) expressions
- data structures with finite and fixed bound

What is PROMELA **Not**?

PROMELA is **not** a programming language

Very small language, not intended to program real systems
(we will master most of it in today's lecture!)

- No pointers
- No methods/procedures
- No libraries
- No GUI, no standard input
- No floating point types
- Fair scheduling policy (during verification)
- No data encapsulation
- Non-deterministic

A First PROMELA Program

```
active proctype P() {  
    printf("Hello_world\n")  
}
```

Command Line Execution

Simulating (i.e., interpreting) a PROMELA program

```
> spin hello.pml  
Hello world
```

First observations

- keyword **proctype** declares process named P
- C-like command and expression syntax
- C-like (simplified) formatted print

Arithmetic Data Types

```
active proctype P() {  
    int val = 123;  
    int rev;  
    rev = (val % 10) * 100 + /* % is modulo */  
          ((val / 10) % 10) * 10 + (val / 100);  
    printf("val_=%d,_rev_=%d\n", val, rev)  
}
```

Observations

- Data types `byte`, `short`, `int`, `unsigned` with operations `+`, `-`, `*`, `/`, `%`
- All declarations implicitly at beginning of process
(avoid to have them anywhere else!)
- Expressions computed as `int`, then converted to container type
- Arithmetic variables implicitly initialized to 0
- No floats, no side effects, C/Java-style comments
- No string variables (only in print statements)

Booleans

```
bit   b1 = 0;  
bool  b2 = true;
```

Observations

- `bit` is actually small numeric type containing 0,1 (unlike C, JAVA)
- `bool`, `true`, `false` syntactic sugar for `bit`, 1, 0

Enumerations

```
mtype = { red, yellow, green };  
mtype light = green;  
printf("the light is %e\n", light)
```

Observations

- literals represented as non-0 byte: at most 255
- `mtype` stands for `message type` (first used for message names)
- There is at most one `mtype` per program

Control Statements

Sequence	using ; as separator; C/JAVA-like rules
Guarded Command	
— Selection	non-deterministic choice of an alternative
— Repetition	loop until break (or forever)
Goto	jump to a label

Guarded Commands: Selection

```
active proctype P() {  
    byte a = 5, b = 5;  
    byte max, branch;  
    if  
        :: a >= b -> max = a; branch = 1  
        :: a <= b -> max = b; branch = 2  
    fi  
}
```

Observations

- Guards may “**overlap**” (more than one can be true at the same time)
- Any alternative whose guard is true is **randomly** selected
- When no guard true: process **blocks** until one becomes true

Guarded Commands: Selection Cont'd

```
active proctype P() {  
  bool p = ...;  
  if  
    :: p      -> ...  
    :: true -> ...  
  fi  
}
```

Second alternative can be selected **anytime**, regardless of whether *p* is true

```
active proctype P() {  
  bool p = ...;  
  if  
    :: p      -> ...  
    :: else -> ...  
  fi  
}
```

Second alternative can be selected **only if *p* is false**

So far, all our programs terminate: we need **loops**

Guarded Statement Syntax

```
:: guard-statement -> command
```

Observations

- symbol `->` is overloaded in PROMELA
- first statement after `::` used as guard
 - ▶ `:: guard` is admissible (empty command)
 - ▶ Can use `;` instead of `->` (avoid!)

Guarded Commands: Repetition

```
active proctype P() { /* computes gcd */  
  int a = 15, b = 20;  
  do  
    :: a > b -> a = a - b  
    :: b > a -> b = b - a  
    :: a == b -> break  
  od  
}
```

Observations

- Any alternative whose guard is true is **randomly** selected
- Only way to exit loop is via **break** or **goto**
- When no guard true: loop **blocks** until one becomes true

Counting Loops

Counting loops such as for-loops as usual in imperative programming languages are realized with `break` after the termination condition:

```
#define N 10 /* C-style preprocessing */
active proctype P() {
    int sum = 0; byte i = 1;
    do
        :: i > N -> break /* test */
        :: else -> sum = sum + i; i++ /* body, increase */
    od
}
```

Observations

- Don't forget `else`, otherwise strange behaviour

Arrays

```
#define N 5
active proctype P() {
    byte a[N];
    a[0] = 0; a[1] = 10; a[2] = 20; a[3] = 30; a[4] = 40;
    byte sum = 0, i = 0;
    do
        :: i > N-1 -> break
        :: else      -> sum = sum + a[i]; i++
    od;
}
```

Observations

- Arrays start with 0 as in JAVA and C
- Arrays are scalar types: $a \neq b$ always different arrays
- Array bounds are constant and cannot be changed
- Only one-dimensional arrays (there is an (ugly) workaround)

Record Types

```
typedef DATE {  
    byte day, month, year;  
}  
  
active proctype P() {  
    DATE D;  
    D.day = 1; D.month = 7; D.year = 62  
}
```

Observations

- may include previously declared record types, but **no** self-references
- Can be used to realize multi-dimensional arrays:

```
typedef VECTOR {  
    int vector[10]  
};  
  
VECTOR matrix[5]; /* base type array in record */  
matrix[3].vector[6] = 17;
```


Jumps

```
#define N 10
active proctype P() {
    int sum = 0; byte i = 1;
    do
        :: i > N -> goto exitloop;
        :: else -> sum = sum + i; i++
    od;
exitloop:
    printf("End of loop")
}
```

Observations

- Jumps allowed only within a process
- Labels must be unique for a process
- Can't place labels in front of guards (inside alternative ok)
- Easy to write messy code with goto

Inlining Code

PROMELA has no method or procedure calls

```
typedef DATE {  
    byte day, month, year;  
}  
  
inline setDate(D, DD, MM, YY) {  
    D.day = DD; D.month = MM; D.year = YY  
}  
  
active proctype P() {  
    DATE d;  
    setDate(d,1,7,62)  
}
```

The inline construct

- macro-like abbreviation mechanism for code that occurs multiply
- creates new local variables for parameters, but no new scope
 - ▶ avoid to declare variables in **inline** — they are visible

Non-Deterministic Programs

Deterministic PROMELA programs are trivial

Assume PROMELA program with **one process** and **no overlapping guards**

- All variables are (implicitly or explicitly) initialized
- No user input possible
- Each state is either blocking or has exactly one successor state

Such a program has exactly one possible computation!

Non-trivial PROMELA programs are non-deterministic!

Possible sources of non-determinism

1. Non-deterministic choice of alternatives with overlapping guards
2. Scheduling of concurrent processes

Non-Deterministic Generation of Values

```
byte range;  
if  
  :: range = 1  
  :: range = 2  
  :: range = 3  
  :: range = 4  
fi
```

Observations

- assignment statement used as guard
 - ▶ assignment statement always succeeds (guard is true)
 - ▶ side effect of guard is desired effect of this alternative
 - ▶ could also write `:: true -> range = 1`, etc.
- selects non-deterministically a value in $\{1, 2, 3, 4\}$ for range

Non-Deterministic Generation of Values Cont'd

Generation of values from explicit list impractical for large range

```
#define LOW 0
#define HIGH 9
byte range = LOW;
do
  :: range < HIGH -> range++
  :: break
od
```

Observations

- Increase of `range` and loop exit selected with equal chance
- Chance of generating n in random simulation is $2^{-(n+1)}$
 - ▶ Obtain no representative test cases from random simulation!
 - ▶ Ok for verification, because all computations are generated

Sources of Non-Determinism

1. Non-deterministic choice of alternatives with overlapping guards
2. Scheduling of concurrent processes

Concurrent Processes

```
active proctype P() {  
    printf("Process_P, statement_1\n");  
    printf("Process_P, statement_2\n");  
}
```

```
active proctype Q() {  
    printf("Process_Q, statement_1\n");  
    printf("Process_Q, statement_2\n");  
}
```

Observations

- Can declare more than one process (need unique identifier)
- At most 255 processes

Execution of Concurrent Processes

Command Line Execution

Random simulation of two processes

```
> spin interleave.pml
```

Observations

- Scheduling of concurrent processes on one processor
- Scheduler selects process randomly where next statement executed
- Many different computations are possible: non-determinism
- Use `-p` and `-g` options to see more execution details

Sets of Processes

```
active [2] proctype P() {  
    printf("Process %d, statement 1\n", _pid);  
    printf("Process %d, statement 2\n", _pid)  
}
```

Observations

- Can declare set of identical processes
- Current process identified with reserved variable `_pid`
- Each process can have its own local variables

Command Line Execution


Random simulation of set of two processes

```
> spin interleave_set.pml
```

PROMELA Computations

```
1 active [2] proctype P() {  
2   byte n;  
3   n = 1;  
4   n = 2  
5 }
```

One possible computation of this program



Notation

- Program pointer (line #) for each process in upper compartment
- Value of all variables in lower compartment

Computations are either infinite or terminating or blocking

Admissible Computations: Interleaving

Definition (Interleaving of independent computations)

Assume n independent processes P_1, \dots, P_n and process i has computation $c^i = (s_0^i, s_1^i, s_2^i, \dots)$.

The computation (s_0, s_1, s_2, \dots) is an **interleaving** of c^1, \dots, c^n iff for all $s_j = s_{j'}^i$ and $s_k = s_{k'}^i$, with $j < k$ it is the case that $j' < k'$.

The interleaved state sequence
respects the execution order of each process


Observations

- Semantics of concurrent PROMELA program are all its interleavings
- Called **interleaving semantics** of concurrent programs
- Not universal: in JAVA certain **reorderings** allowed

Interleaving Cont'd

Can represent possible interleavings in a DAG

```
1 active [2] proctype P() {  
2   byte n;  
3   n = 1;  
4   n = 2  
5 }
```



Atomicity

At which granularity of execution can interleaving occur?

Definition (Atomicity)

An expression or statement of a process that is executed entirely without the possibility of interleaving is called **atomic**.

Atomicity in PROMELA

- Assignments, jumps, skip, and expressions are **atomic**
 - ▶ In particular, conditional expressions are atomic:
(p -> q : r), C-style syntax, brackets required
- Guarded commands are **not atomic**

Atomicity Cont'd

```
int a,b,c;
active proctype P() {
    a = 1; b = 1; c = 1;
    if
        :: a != 0 -> c = b / a
        :: else -> c = b
    fi
}
active proctype Q() {
    a = 0
}
```

Command Line Execution

Interleaving into selection statement forced by interactive simulation

```
> spin -p -g -i zero.pml
```

Atomicity Cont'd

How to prevent interleaving?

1. Consider to use expression instead of selection statement:

```
c = (a != 0 -> (b / a): b)
```


2. Put code inside scope of **atomic**:

```
active proctype P() {  
    a = 1; b = 1; c = 1;  
    atomic {  
        if  
            :: a != 0 -> c = b / a  
            :: else -> c = b  
        fi  
    }  
}
```

Usage Scenario of PROMELA

1. **Model** the **essential** features of a system in PROMELA
 - ▶ **abstract** away from complex (numerical) computations
 - make usage of **non-deterministic** choice of outcome
 - ▶ replace unbounded data structures with **finite** approximations
 - ▶ assume **fair** process scheduler
2. **Select properties** that the PROMELA model must satisfy
 - ▶ **Generic Properties** (discussed in later lectures)
 - Mutual exclusion for access to critical resources
 - Absence of deadlock
 - Absence of starvation
 - ▶ **System-specific properties**
 - Event sequences (e.g., system responsiveness)

Formalisation with PROMELA **Abstraction**



Usage Scenario of PROMELA Cont'd

1. **Model** the **essential** features of a system in PROMELA
 - ▶ **abstract** away from complex (numerical) computations
 - make usage of **non-deterministic** choice of outcome
 - ▶ replace unbounded datastructures with **finite** approximations
 - ▶ assume **fair** process scheduler
2. **Select properties** that the PROMELA model must satisfy
 - ▶ Mutual exclusion for access to critical resources
 - ▶ Absence of deadlock
 - ▶ Absence of starvation
 - ▶ Event sequences (e.g., system responsiveness)
3. **Verify** that all possible runs of PROMELA model **satisfy** properties
 - ▶ Typically, need many **iterations** to get model and properties right
 - ▶ Failed verification attempts provide feedback via **counter examples**


Verification: Work Flow (Simplified)

PROMELA Program

```
byte n = 0;  
active proctype P() {  
  n = 1  
}  
active proctype Q() {  
  n = 2  
}
```

Properties

$[(\neg \text{csp} \parallel \neg \text{csq})]$



Literature for this Lecture

Ben-Ari Chapter 1, Sections 3.1–3.3, 3.5, 4.6, Chapter 6

Spin Reference card

jspin User manual, file `doc/jspin-user.pdf` in distribution