


# **GURU NANAK DEV ENGINEERING COLLEGE , LUDHIANA**



## **DATA BASE MANAGEMENT SYSTEM PRACTICAL FILE**

**SUBMITTED BY: -  
TARANJEET SINGH**


**1805996**

**D3 CSE(E3)**

- 1. Create all tables of company database specifying primary and foreign key for each table as per the schema.**
- 2. Insert at least 4 tuples in each table**

**Figure 5.7**

Referential integrity constraints displayed on the COMPANY relational database schema.



```
CREATE TABLE employees
```

```
( first_name VARCHAR(50) , middle_name VARCHAR(50) , last_name VARCHAR(50) NOT NULL, ssn
int PRIMARY KEY ,
```

```
b_date DATE , address varchar(10) , gender varchar(10) , salary INT , super_ssn int , dno int
```

```
);
```

```
INSERT INTO `employees`(`first_name`, `middle_name`, `last_name`, `ssn`, `b_date`, `address`,
`gender`, `salary`, `super_ssn`, `dno`)
```

```
VALUES ("Taran" , "Jeet" ,"Singh", 0011, "2001-02-27" ,"Abohar", "Male", 45000, 1122 , 01)
```

```
INSERT INTO `employees`(`first_name`, `middle_name`, `last_name`, `ssn`, `b_date`, `address`,
`gender`, `salary`, `super_ssn`, `dno`)
```

```
VALUES ("Avneet" , NULL ,"Singh", 0022, "2000-10-02" ,"Kapurthala", "Male", 35000, 1122 , 02)
```

```
INSERT INTO `employees`(`first_name`, `middle_name`, `last_name`, `ssn`, `b_date`, `address`,
`gender`, `salary`, `super_ssn`, `dno`)
```

```
VALUES ("Amrit" , "pal" , "Singh", 0033, "2000-04-21" , "Dehradun", "Male", 55000, 2233 , 03
```

```
INSERT INTO `employees`(`first_name`, `middle_name`, `last_name`, `ssn`, `b_date`, `address`,
`gender`, `salary`, `super_ssn`, `dno`)
```

```
VALUES ("Atul" , NULL , "Singh", 0044, "2000-11-24" , "Delhi", "Male", 55000, 2233 , 04)
```

Result Grid										
Filter Rows:										
Edit:										
Export/Import:										
Wrap Cell Content:										
	first_name	middle_name	last_name	ssn	b_date	address	gender	salary	super_ssn	dno
▶	Taran	Jeet	Singh	11	2001-02-27	Abohar	Male	45000	1122	1
	Avneet	NULL	Singh	22	2000-10-02	Kapurthala	Male	35000	1122	2
	Amrit	pal	Singh	33	2000-04-21	Dehradun	Male	55000	2233	3
	Atul	NULL	Singh	44	2000-11-24	Delhi	Male	55000	2233	4
✱	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL

```
CREATE TABLE department
```

```
( dname VARCHAR(50) , dnumber int PRIMARY KEY ,
```

```
mgr_ssn_date DATE , mgr_ssn int , FOREIGN KEY(mgr_ssn) REFERENCES employees(SSN))
```

```
INSERT INTO `department`(`dname`, `dnumber`, `Mgr_ssn_date`, `mgr_ssn`)
```

```
VALUES ("Management",01,"2020-03-31",0011)
```

```
INSERT INTO `department`(`dname`, `dnumber`, `Mgr_ssn_date`, `mgr_ssn`)
```

```
VALUES ("Research",02,"2020-05-11",0022)
```

```
INSERT INTO `department`(`dname`, `dnumber`, `Mgr_ssn_date`, `mgr_ssn`)
```

```
VALUES ("CSE",03,"2020-08-18",0033)
```

```
INSERT INTO `department`(`dname`, `dnumber`, `Mgr_ssn_date`, `mgr_ssn`)
```

```
VALUES ("Electronics",04,"2020-05-08",0044)
```

Result Grid				
Filter Rows:				
	dname	dnumber	mgr_ssn_date	mgr_ssn
▶	Management	1	2020-03-31	11
	Research	2	2020-05-11	22
	CSE	3	2020-08-18	33
	Electronics	4	2020-05-08	44
*	NULL	NULL	NULL	NULL

```
CREATE TABLE dept_location
```

```
( dnumber int , dlocation varchar(10) , PRIMARY key(dnumber , dlocation), FOREIGN KEY(dnumber)
REFERENCES Department(dnumber))
```

```
INSERT INTO `dept_location`(`dnumber`, `dlocation`) VALUES (01,"Chandigarh")
```

```
INSERT INTO `dept_location`(`dnumber`, `dlocation`) VALUES (02,"Mohali")
```

```
INSERT INTO `dept_location`(`dnumber`, `dlocation`) VALUES (03,"Delhi")
```

```
INSERT INTO `dept_location`(`dnumber`, `dlocation`) VALUES (04,"Ludhiana")
```

Result Grid		
Filter Rows:		
	dnumber	dlocation
▶	1	Chandigarh
	2	Mohali
	3	Delhi
	4	Ludhiana
*	NULL	NULL

```
CREATE TABLE project
```

```
( pname VARCHAR(50) , pnumber int PRIMARY key, plocation varchar(10) , dnum int , FOREIGN
KEY(Dnum)REFERENCES Department(Dnumber)
```

```
);
```

```
INSERT INTO `project`(`pname`, `pnumber`, `plocation`, `dnum`)
```

```
VALUES ("Weapon",1,"chandigarh",01)
```

```
INSERT INTO `project`(`pname`, `pnumber`, `plocation`, `dnum`)
VALUES ("Web development",2,"chandigarh",02)
```

```
INSERT INTO `project`(`pname`, `pnumber`, `plocation`, `dnum`)
VALUES ("App development",3,"Delhi",03)
```

```
INSERT INTO `project`(`pname`, `pnumber`, `plocation`, `dnum`)
VALUES ("Artificial intelligence",4,"Ludhiana",04)
```

Result Grid				
Filter Rows:				
Edit:				
	pname	pnumber	plocation	dnum
▶	Weapon	1	chandigarh	1
	Web development	2	chandigarh	2
	App development	3	Delhi	3
	Artificial intelligence	4	Ludhiana	4
✱	NULL	NULL	NULL	NULL

```
CREATE TABLE workson
```

```
( essn int , pno int ,
```

```
hours int , PRIMARY KEY(Essn,pno) , FOREIGN KEY(Essn) REFERENCES employees(SSN), FOREIGN
KEY(pno)REFERENCES Project(Pnumber)
```

```
);
```

```
INSERT INTO `workson`(`essn`, `pno`, `hours`) VALUES (0011,1,10)
```

```
INSERT INTO `workson`(`essn`, `pno`, `hours`) VALUES (0022,2,12)
```

```
INSERT INTO `workson`(`essn`, `pno`, `hours`) VALUES (0033,3,08)
```

```
INSERT INTO `workson`(`essn`, `pno`, `hours`) VALUES (0044,4,10)
```

Result Grid			
	essn	pno	hours
▶	11	1	10
	22	2	12
	33	3	8
	44	4	10
✱	NULL	NULL	NULL

CREATE TABLE dependent

( essn int , dependent\_name varchar(20), gender varchar(10) ,

bdate date , relationship varchar(10) , PRIMARY KEY(Essn,dependent\_name),FOREIGN KEY(Essn)  
REFERENCES employees(SSN)

);

INSERT INTO `dependent`(`essn`,`dependent\_name`,`gender`,`bdate`,`relationship`)  
VALUES (0011,"ABC","Male","2000-01-22","R1")

INSERT INTO `dependent`(`essn`,`dependent\_name`,`gender`,`bdate`,`relationship`)  
VALUES (0022,"XYZ","Male","2000-07-12","R2")

INSERT INTO `dependent`(`essn`,`dependent\_name`,`gender`,`bdate`,`relationship`)  
VALUES (0033,"PQR","Male","1999-05-19","R3")

INSERT INTO `dependent`(`essn`,`dependent\_name`,`gender`,`bdate`,`relationship`)  
VALUES (0044,"IJK","Male","1998-12-04","R4")

Result Grid					
	essn	dependent_name	gender	bdate	relationship
▶	11	ABC	Male	2000-01-22	R1
	22	XYZ	Male	2000-07-12	R2
	33	PQR	Male	1999-05-19	R3
	44	IJK	Male	1998-12-04	R4
✱	NULL	NULL	NULL	NULL	NULL

### **3. Delete entries of employees who are born after 20 November, 1990**

```
DELETE FROM employees WHERE b_date>"1990-11-20";
```

[illegible]

**4. Alter table employee, ADD COLUMN Job VARCHAR(12);**

```
ALTER TABLE employees Add Job varchar(12);
```

[illegible]

**5. Use update command to modify the value of address in employee table for any one of the inserted tuple.**


```
UPDATE employees SET address ="ludhiana" where ssn=0011
```

[illegible]

## **6. Rename the dependent table to Employee\_dependent table.**

alter table dependent rename to Employee\_dependent

select \* from employee\_dependent




The screenshot shows a 'Result Grid' interface with a table containing 6 columns: 'essn', 'dependent\_name', 'gender', 'bdate', and 'relationship'. There are 5 rows of data. The first four rows have values, and the fifth row contains 'NULL' for all columns. The interface includes a 'Filter Rows' search bar and an 'Edit' button.

	essn	dependent_name	gender	bdate	relationship
▶	11	ABC	Male	2000-01-22	R 1
	22	XYZ	Male	2000-07-12	R 2
	33	PQR	Male	1999-05-19	R 3
	44	IJK	Male	1998-12-04	R 4
*	NULL	NULL	NULL	NULL	NULL

## **7. Retrieve the name and address of all employees who work for the 'Research' department.**

Select first\_name, last\_name, Address from employees ,department where dname="Research";




The screenshot shows a 'Result Grid' interface with a table containing 4 columns: 'first\_name', 'last\_name', and 'Address'. There are 4 rows of data. The first column is empty. The interface includes a 'Filter Rows' search bar.

	first_name	last_name	Address
▶	Taran	Singh	ludhiana
	Avneet	Singh	Kapurthala
	Amrit	Singh	Dehradun
	Atul	Singh	Delhi

## **8.Retrieve the SSN values for all employees.**

select Ssn from employees



The screenshot shows a 'Result Grid' interface with a table containing 2 columns: an empty column and 'Ssn'. There are 4 rows of data. The first column contains a right-pointing triangle icon. The interface includes a 'Filter Rows' search bar.

	Ssn
▶	11
	22
	33
	44



**9. For every project located in 'Stafford', list the project number, the controlling department number, and the department manager's last name, address, and birthdate.**

UPDATE Project SET plocation="STAFFORD" WHERE pnumber=1

Result Grid				
Filter Rows: <input type="text"/>				
Edit:				
	pname	pnumber	plocation	dnum
▶	Weapon	1	STAFFORD	1
	Web development	2	chandigarh	2
	App development	3	Delhi	3
	Artificial intelligence	4	Ludhiana	4
*	NULL	NULL	NULL	NULL

**10. For each employee, retrieve the employee's name, and the name of his or her immediate supervisor**

select first\_name , dependent\_name from employees, employee\_dependent where ssn=essn

Result Grid		
Filter Rows: <input type="text"/>		
	first_name	dependent_name
▶	Taran	ABC
	Avneet	XYZ
	Amrit	PQR
	Atul	IJK

**11. Retrieve the distinct values of salaries for all employees.**

SELECT DISTINCT salary FROM employees

Result Grid	
salary	
▶	45000
	35000
	55000

## 12. Retrieve the name of each employee who has a dependent with the same first name as the employee.


Select First\_name FROM employees,employee\_dependent WHERE  
employees.Ssn=employee\_dependent.essn AND  
employees.first\_name=employee\_dependent.dependent\_name;



First_name
------------

## 13.Retrieve the names of employees who have no dependents


select \* from employees where super\_ssn=NULL



	first_name	middle_name	last_name	ssn	b_date	address	gender	salary	super_ssn	dno	Job
*	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL

## 14. select name of employees having second highest salary


SELECT first\_name,middle\_name,last\_name, MAX(sALary) FROM employees WHERE salary <(SELECT  
MAX(salAry) FROM employees);



	first_name	middle_name	last_name	MAX(sALary)
▶	Taran	Jeet	Singh	45000

15. Retrive the name and address of all employees who either work in the research dept or in the comp. dept

SELECT first\_name,middle\_name,last\_name, address from employees where dno=(SELECT dnumber FROM Department WHERE dname="RESEARCH") or dno=(SELECT dnumber FROM Department WHERE dname="CSE")



The screenshot shows a 'Result Grid' with a toolbar at the top containing 'Filter Rows:', 'Export:', and 'Wrap Cell Content:'. The grid has four columns: first\_name, middle\_name, last\_name, and address. It contains two rows of data.

	first_name	middle_name	last_name	address
▶	Avneet	NULL	Singh	Kapurthala
	Amrit	pal	Singh	Dehradun

16. Retreive name of each employye who works on all project controlled by dept 4

SELECT first\_name,middle\_name,last\_name, address from employees where dno=(SELECT dnum FROM Project where dnum=4)




The screenshot shows a 'Result Grid' with a toolbar at the top containing 'Filter Rows:', 'Export:', and 'Wrap Cell Content:'. The grid has four columns: first\_name, middle\_name, last\_name, and address. It contains one row of data.

	first_name	middle_name	last_name	address
▶	Atul	NULL	Singh	Delhi

17. Retrieve the ssn of all emp who work on prjct no 1 , 2 or 3

SELECT ssn FROM employees where dno=(SELECT dnum FROM Project where pnumber=1) OR dno=(SELECT dnum FROM Project where pnumber=2) OR dno=(SELECT dnum FROM Project where pnumber=3)



The screenshot shows a 'Result Grid' with a toolbar at the top containing 'Filter Rows:'. The grid has one column: ssn. It contains four rows of data, with the last row being NULL.

	ssn
▶	11
	22
	33
*	NULL

### 18. Retrieve name of all emp who do not have supervisor


SELECT first\_name, middle\_name, last\_name FROM employees WHERE super\_ssn is NULL;



The screenshot shows a database interface with a 'Result Grid' tab. The grid has three columns: first\_name, middle\_name, and last\_name. The grid is currently empty, and the 'Filter Rows' field is empty. The 'Export' button is visible, and the 'Wrap Cell Content' option is checked.

### 19. Find max min avg salary among emp who work for research dept

SELECT MAX(E.salary) as maxsal, MIN(E.salary) AS minsal, AVG(salary) AS avgsal FROM employees E  
inner join Department D on D.mgr\_ssn=E.ssn WHERE D.Dname="RESEARCH" group by D.mgr\_ssn




The screenshot shows a database interface with a 'Result Grid' tab. The grid has three columns: maxsal, minsal, and avgsal. The first row of data shows values 35000, 35000, and 35000.0000. The 'Filter Rows' field is empty. The 'Export' button is visible, and the 'Wrap Cell Content' option is checked.

### 20. For each dept retrieve deptno. the no. of emp in dept along with avg salary

SELECT Dno, COUNT (\*), avg(Salary)

FROM employees


GROUP BY Dno;



The screenshot shows a database interface with a 'Result Grid' tab. The grid has three columns: Dno, COUNT(\*), and avg(Salary). The first row of data shows values 1, 1, and 45000.0000. The second row shows 2, 1, and 35000.0000. The third row shows 3, 1, and 55000.0000. The fourth row shows 4, 1, and 55000.0000. The 'Filter Rows' field is empty. The 'Export' button is visible, and the 'Wrap Cell Content' option is checked.

21. For each project ret proj no. proj name and no. of emp who work on that project

SELECT pnumber, pname, COUNT (pnumber) from Project GROUP by pname



	pnumber	pname	COUNT(pnumber)
▶	1	Weapon	1
	2	Web development	1
	3	App development	1
	4	Artificial intelligence	1

22. For each proj. on which more than 2 emp work ret. proj no. proj name and no. of emp wrkn on that project

SELECT pnumber, pname, COUNT (\*) FROM Project, Workson WHERE pnumber = pno GROUP BY pnumber, pname HAVING COUNT (\*) > 2;



	pnumber	pname	COUNT(*)
--	---------	-------	----------