

SOEN331: Introduction to Formal Methods for Software Engineering

Assignment 4 on algebraic specifications

Tarek Ait Hamouda (40044119), Abhijit Gupta (40066502),
Ethel Narra Pangan (40061530)

March 29, 2019

Spec: Location;

Sort: Location;

Imports:String, Point

Description: A location contains a description

Operations:

newLocation: $\text{String} \times \text{Point} \rightarrow \text{Location}$;

setDescription: $\text{String} \times \text{Location} \rightarrow \text{Location}$;

getDescription : $\text{Location} \rightarrow \text{String}$;

setPoint : $\text{Point} \times \text{Location} \rightarrow \text{Location}$;

getPoint : $\text{Location} \rightarrow \text{Point}$;

Variables:

newDesc, d: String; newPoint, p: Point;

Axioms:

[A1] $\text{getDescription}(\text{newLocation}(d, p)) = d$;

[A2] $\text{getDescription}(\text{setDescription}(\text{newDesc}, \text{newLocation}(d, p))) = \text{newDesc}$;

[A3] $\text{getDescription}(\text{setPoint}(\text{newPoint}, \text{newLocation}(d, p))) = d$;

[A4] $\text{getPoint}(\text{newLocation}(d, p)) = p$;

[A5] $\text{getPoint}(\text{setPoint}(\text{newPoint}, \text{newLocation}(\text{d}, \text{p}))) = \text{newPoint};$
 [A6] $\text{getPoint}(\text{setDescription}(\text{newDesc}, \text{newLocation}(\text{d}, \text{p}))) = \text{p};$
 [A7] $\text{setDescription}(\text{newDesc}, \text{newLocation}(\text{d}, \text{p})) = \text{newLocation}(\text{newDesc}, \text{p});$
 [A8] $\text{setDescription}(\text{getDescription}(\text{newLocation}(\text{d}, \text{p})), \text{newLocation}(\text{d}, \text{p})) = \text{newLocation}(\text{d}, \text{p});$
 [A9] $\text{setPoint}(\text{newPoint}, \text{newLocation}(\text{d}, \text{p})) = \text{newLocation}(\text{d}, \text{newPoint});$
 [A10] $\text{setPoint}(\text{getPoint}(\text{newLocation}(\text{d}, \text{p})), \text{newLocation}(\text{d}, \text{p})) = \text{newLocation}(\text{d}, \text{p});$

Spec: $\text{Map}(\text{Location});$

Sort: $\text{Map};$

Imports: $\text{String}, \text{Point}, \text{Boolean}, \text{Location};$

Description: A map contains locations

Operations:

$\text{newmap} \rightarrow \text{Map};$
 $\text{addlocation}: \text{Map} \times \text{Location} \rightarrow \text{Map};$
 $\text{deletelocation} : \text{Map} \times \text{String} \rightarrow \text{Map};$
 $\text{containsdescription} : \text{Map} \times \text{String} \rightarrow \text{Boolean};$
 $\text{containspoint} : \text{Map} \times \text{Point} \rightarrow \text{Boolean};$
 $\text{findlocation} : \text{Map} \times \text{String} \rightarrow \text{Point};$
 $\text{isempty} : \text{Map} \rightarrow \text{Boolean};$
 $\text{clear} : \text{Map} \rightarrow \text{Map};$

Variables:

$\text{d}: \text{String}; \text{p}: \text{Point}; \text{loc}: \text{Location}; \text{map}: \text{Map}$

Axioms:

[A1] $\text{isempty}(\text{newmap}) = \text{true};$
 [A2] $\text{isempty}(\text{clear}(\text{map})) = \text{true};$
 [A3]
 [A4]
 [A5]
 [A6]

[A7]

[A8] findlocation(newmap) = undefined;

[A9] deletelocation(newmap) = undefined;