

BEYOND IMAGINATION
THROUGH INNOVATION

INDUCODE
TECHNOLOGIES

50H MODEL MOTOR GENERATOR SET

60-50 Hz
FREQUENCY CONVERTER


FEATURES

- Precise 50 Hz output frequency
- Common frame design
- Low audible noise
- Easy to operate
- Exceptional MTBF
- Minimal maintenance required

DESCRIPTION

50H Model motor generator sets consist of an Induction or, a synchronous motor and a synchronous generator mounted on a common shaft. These units deliver an output frequency of precisely 50 Hz from no-load to full-load. 50H Model motor generator sets are rated for continuous duty and they provide a clean source of 50 Hz power isolated from switching transients, voltage fluctuations and power line noise. They have high overload capability and are most commonly utilized in military applications where a rugged and reliable 60-50 Hz frequency converter is required. Alternatively, they are also utilized in American manufacturing facilities to provide a source of precise 50 Hz power for large-scale operations. They are dependable in harsh environments and are ideally suited for applications where continuous run time is a necessity.

50H Model motor generator sets are designed to be installed inside where a 75-80 dBA noise level is acceptable. As an option, 50H Model motor generator sets can be mounted in a weather-resistant enclosure, a sound-reduced enclosure, a cargo container or a trailer. Each 50H Model motor generator set is equipped with a standard control system that is either wall-mounted or free standing. The components in the control system perform the functions necessary to operate, monitor and protect the system.



* Picture may not represent Actual Product

SPECIFICATIONS

Motor

- Induction or Brushless synchronous
- Continuous duty, Class F insulation, open drip-proof
- Selection of 60 Hz, 3-phase input voltages to include: 208V, 230V or 460V

Generator

- Brushless synchronous
- Continuous duty, Class F insulation, open drip-proof
- Selection of 50 Hz output voltages to include: 120/208V, 220/380V or 277/480V, 3-phase
- Rated at 0.8 power factor to insure proper handling of inductive loads

Mechanical Construction

- Motor and generator mounted on rigid steel base
- Flexible coupling drive system
- Complete OSHA coupling guard
- Forklift or pallet jack provisions

Standard Control Systems

Each motor generator set is equipped with a separate wall-mounted or floor-standing control panel. The standard package includes the following components:

Motor Controls

- Motor starter with adjustable overload
- Start/Stop push buttons with terminal strip for remote start/stop
- Control power transformer with fusing
- Variable transformer for power factor control, with protective relay for motor out-of-step and field failure protection
- Analog meter package to include ammeter and run time meter
- Pilot lights to indicate "Motor Run" and "60 Hz Line Energized"

Generator Controls

- Analog meter package to include voltmeter, ammeter and frequency meter
- Voltmeter and ammeter phase selector switches (3-phase systems)
- Voltage regulator, $\pm 1\%$ regulation accuracy, with automatic buildup and rheostat for control of regulated voltage
- Output circuit breaker, molded case, to protect generator against short circuit or prolonged overload
- Pilot light to indicate "50 Hz Load On"
- Over voltage protection package to include output circuit breaker shunt trip

50H MODEL MOTOR GENERATOR SET

PERFORMANCE CHARACTERISTICS

- **Voltage regulation :** $\pm 1\%$ from no-load to full-load at rated power factor
- **Voltage steady state stability:** $\pm 0.5\%$ from no-load to full-load at rated power factor
- **Voltage adjustment range :** $\pm 10\%$ in stepless increments of nominal output voltage
- **Frequency regulation :** Precise 50 Hz output from no-load to full-load
- **Voltage transient :** When a full-load at rated power factor is applied or released, the resultant instantaneous droop or overshoot
- **Voltage recovery time :** After a full-load is applied or released, the output voltage will return to the regulation band within 500 milliseconds
- **Harmonic distortion:** Less than 3% max. total distortion factor and less than 2.5% max. single phase when measured line-to-line
- **Ambient operating conditions:** Temperature at 40°C , relative humidity at 95% (higher temperature rating for outdoor use available upon request)
- **Duty cycle:** Motor generator set and controls are rated for continuous duty

MOTOR GENERATOR OPTIONS

- Weather-resistant, NEMA 3R enclosure
- Oversized generator to support motorstarting transients
- Thermal bearing and winding protection
- Input disconnect or circuit breaker
- Input phase protection relay
- Generator reconnection switch to allow selection of multiple output voltages
- Digital meter package
- Remote meter package with start/stop controls

50H Model - Three Phase Output Ratings

Model	Generator Rating at 0.8 PF		Output Current at 120/208V	Output Current at 220/380V	Motor Rating	Motor Starting Method
50H-203	25 KVA	20 KW	69 A	38 A	30 HP	Wye-delta or VFD
50H-253	31.3 KVA	25 KW	87 A	48 A	40 HP	Wye-delta or VFD
50H-303	37.5 KVA	30 KW	104 A	57 A	50 HP	Wye-delta or VFD
50H-403	50 KVA	40 KW	139 A	76 A	60 HP	Wye-delta or VFD
50H-503	62.5 KVA	50 KW	174 A	95 A	75 HP	Wye-delta or VFD
50H-603	75 KVA	60 KW	208 A	114 A	100 HP	Wye-delta or VFD
50H-803	93.8 KVA	75 KW	261 A	143 A	125 HP	Wye-delta or VFD
50H-1003	125 KVA	100 KW	347 A	190 A	150 HP	Wye-delta or VFD
50H-1253	156 KVA	125 KW	434 A	238 A	200 HP	Wye-delta or VFD
50H-1503	188 KVA	150 KW	521 A	285 A	250 HP	Wye-delta or VFD
50H-1753	219 KVA	175 KW	608 A	333 A	300 HP	Wye-delta or VFD
50H-2003	250 KVA	200 KW	695 A	380 A	300 HP	Wye-delta or VFD
50H-2503	313 KVA	250 KW	868 A	475 A	400 HP	Wye-delta or VFD
50H-3003	375 KVA	300 KW	1042 A	570 A	500 HP	Wye-delta or VFD
50H-3503	438 KVA	350 KW	1216 A	666 A	550 HP	Wye-delta or VFD
50H-4003	500 KVA	400 KW	1390 A	761 A	600 HP	Wye-delta or VFD
50H-4503	563 KVA	450 KW	1563 A	856 A	700 HP	Wye-delta or VFD
50H-5003	625 KVA	500 KW	1737 A	951 A	750 HP	Wye-delta or VFD
50H-5503	688 KVA	550 KW	1911 A	1046 A	850 HP	Wye-delta or VFD
50H-6003	750 KVA	600 KW	2084 A	1141 A	1000 HP	Wye-delta or VFD
50H-6503	813 KVA	650 KW	2258 A	1236 A	1000 HP	Wye-delta or VFD
50H-7003	875 KVA	700 KW	2432 A	1331 A	1100 HP	Wye-delta or VFD
50H-7503	938 KVA	750 KW	2605 A	1426 A	1250 HP	Wye-delta or VFD
50H-8003	1000 KVA	800 KW	2779 A	1521 A	1250 HP	Wye-delta or VFD
50H-9003	1125 KVA	900 KW	3126 A	1711 A	1350 HP	Wye-delta or VFD
50H-10003	1250 KVA	1000 KW	3474 A	1901 A	1500 HP	Wye-delta or VFD
50H-11003	1375 KVA	1100 KW	3821 A	2092 A	1650 HP	Wye-delta or VFD
50H-12003	1500 KVA	1200 KW	4169 A	2282 A	1800 HP	Wye-delta or VFD

* We reserve the right to change any rating/specification without notice