Task Tracker — installation on your own server

Installer file task-tracker-onprem-1.2.0.run · works without any internet · Ubuntu 22.04 / 24.04

1 What you need

	Minimum	Recommended
Processor	2 cores (x86_64 or ARM64)	4 cores
Memory	4 GB	8 GB
Disk	20 GB free	50 GB SSD
System	Ubuntu 22.04 or 24.04, access with sudo	
Network	ports 80 and 443 free; fixed LAN IP recommended	

Docker is installed automatically (offline from the package). Data never leaves the server — no cloud, no access from outside.

2 Installation step by step (no internet)

1 Copy and check the file

Plug in the USB stick, copy `task-tracker-onprem-1.2.0.run` (and `.sha256`) to the server; the check must report "OK":

```
cp /media/$USER/USB/task-tracker-onprem-1.2.0.run* ~/ && cd ~
sha256sum -c task-tracker-onprem-1.2.0.run.sha256
```

2 Start the installation

One command, then four questions — Enter keeps the suggestion: **name** of the interface, **logo** (optional, path to PNG/JPG/WEBP/SVG), **language** (`ar`, `de`, `en`), **address** (host name optional, IP is detected).

```
sudo bash task-tracker-onprem-1.2.0.run
```

3 Wait (3–5 minutes)

At the end the installer shows the **address, user name, invite link** and the **path + fingerprint of the certificate**. Everything is also in `/opt/task-tracker/ACCESS.txt` (root only): `sudo cat /opt/task-tracker/ACCESS.txt`

4 Import the certificate — once per device

The server issues its own HTTPS certificates. For browsers to trust it, import `/opt/task-tracker/ca/task-tracker-root-ca.crt` (or download `http://<server-IP>/ca.crt`) and compare the fingerprint:

Windows	Double-click the file → Install Certificate → Local Machine → "Place all certificates in the following store" → Trusted Root Certification Authorities.
Android	Settings → Security → Encryption & credentials → Install a certificate → CA certificate.
iPhone/iPad	Open the download link in Safari → Settings → install the profile; then General → About → Certificate Trust Settings → switch on.

5 Open the invite link

Open the link in the browser and choose a password — done, you are logged in as superuser. The link works **once only** and for 72 hours. Expired? `sudo /opt/task-tracker/invite.sh` creates a new one.

Without questions: `sudo bash task-tracker-onprem-1.2.0.run -- --app-name "My Team" --locale en --yes`. With internet and your own domain (online package): `sudo ./install.sh --tls domain --domain tasks.example.com`.

3 Name, logo, language

Name	Question 1 of the installation. Change it later: `APP_NAME=…` in `/opt/task-tracker/.env`, then `sudo ./update.sh --restart`. Empty = default name per language.
Logo, colours	Logo: question 2 (max. 2 MB). Later in the app as superuser: **Settings** → **Branding**. Included in backups.
Language	Question 3 — language of the login page and of the superuser. Every user can switch their own language.

Run all commands in the folder `/opt/task-tracker`: `cd /opt/task-tracker`

4 Backup

automatic	every night at **03:30**, the last 14 are kept in `/var/backups/task-tracker`
`sudo ./backup.sh`	make a backup now
`sudo ./backup.sh --to /media/$USER/USB`	write the backup straight to a USB stick

Copy a backup to USB regularly — a backup on the same server does not help if the server fails. Backups are not encrypted and contain every password: keep them safe.

5 Restore

`sudo ./restore.sh`	list the available backups
`sudo ./restore.sh --from latest --yes`	restore the newest backup
`sudo ./restore.sh --from /media/$USER/USB/20261031-033000 --yes`	restore a backup from a USB stick

The current state is saved automatically first (`pre-restore-…`) — a wrong restore can be undone.

6 Update and rollback

`sudo bash task-tracker-onprem-<new>.run`	new version: detects the installation and offers the update
`sudo ./update.sh --rollback`	undo the last update
`sudo ./update.sh --restart`	restart only (e.g. after editing `.env`)

Every update backs up everything first. If the new version does not start cleanly, the old one runs again automatically.

7 If something does not work

Certificate warning	Certificate not imported on that device yet (step 4) — or an address was opened other than the one given at installation.
Site not reachable	`sudo docker compose ps` — all three services "running", app "healthy". Log: `sudo docker compose logs -f app`
Link expired / password forgotten	`sudo ./invite.sh` (for other users: `--user NAME`)
"Checksum MISMATCH"	The `.run` file is damaged — copy it again.

Support: TOF Solution · Tarek@tarekfatal.com · Terms of use: `NUTZUNGSHINWEISE.md` (in the package and in `/opt/task-tracker`)