```php
<?php
if (isset($_POST["submit"])) {
   $students = (int)$_POST["students"];
   $slicesStudent = (int)$_POST["slicesStudent"];
   $slicePizza = (int)$_POST["slicesPizza"];
   $totalNeeded = $students * $slicesStudent;
   $totalPizza = ceil($totalNeeded / $slicePizza);
   $leftover = ($totalPizza * $slicePizza) - $totalNeeded;
   $wasted = (1050 / $slicePizza) * $leftover;
   echo "<table border = '1'>";
   echo "<tr><th>Total Pizzas:</th><th>Leftover Slices:</th><th>Wasted Mondey(BDT):</th></tr>";
   echo "<tr> <td>$totalPizza</td><td>$leftover</td><td>$wasted</td></tr>";
   echo "</table>";    } ?>
```

PHP extra

```php
$a = (float) $_POST['a'];
$diff = abs($total - $target);
$n = (int) ceil($required / $capacity);
$percent = ($part / $whole) * 100;
round($x, 2)
min($ct1, $ct2, $ct3);
for ($i=0; $i<5; $i++) { }
```

JS

```js
for (let i = 0; i < 5; i++) {
  console.log(i); // Outputs: 0, 1, 2, 3, 4
}
let password = "MyPassword123!"; const specialChars = "!@#$%^&*";
 let score = 0;
for (const char of password) {
if (specialChars.includes(char)) { score += 25; break; // Stop looping once we find the first special character } }
let avgSp = (sumSpO2 / sp02s.length ).toFixed(2)
parseFloat(document.getElementById('heart_rate').value)
Number(document.getElementById("x").value);
document.getElementById("out").innerHTML =
      "Total: " + total +
      "<br>Average: " + avg.toFixed(2) +
      "<br>Count: " + count +
      "<br>" + msg;
Math.abs(HeartRate - 80)

// Find whichever radio button in the 'gender' group is currently checked
let selectedGender = document.querySelector('input[name="gender"]:checked');
if (selectedGender) {
   let genderValue = selectedGender.value; // Gets "Male" or "Female"
   console.log(genderValue);
} else {
   console.log("No option selected");
}

==========
   <form method="POST" action="">
      <label>Number of Students:</label>
      <input type="text" name="students">
      <br><br>
   </form>
```

```
// radio button
   <form method="POST" action="">
   Gender:
   <input type="radio" name="gender" value="Male"> Male
   <input type="radio" name="gender" value="Female"> Female
   <button type="submit" name="submit">Submit</button>
</form>
// select
<form method="POST" action="">
   Select City:
   <select name="city">
      <option value="Dhaka">Dhaka</option>
      <option value="Chittagong">Chittagong</option>
      <option value="Sylhet">Sylhet</option>
   </select>
   <button type="submit" name="submit">Submit</button>
</form>
```

Db connection

```php
$conn = new mysqli("localhost", "root", "", "tourism", 3306);
if ($conn->connect_error) {
   die("Connection failed: " . $conn->connect_error);
}
 $sql1 = "SELECT SpotName, Region, Rating
From tourist_spot
WHERE Rating > 4.5 OR SpotName LIKE '%Beach%'
ORDER BY Rating DESC";
 $res = $conn->query($sql1);
   while($row = $res->fetch_assoc()){
      echo $row["SpotName"]." " ;
      echo $row["Region"]." ";
      echo $row["Rating"]. "<br>";
   }
```

```
UPDATE tourist_spot
SET Rating = Rating + 0.2,
   EntryFee = EntryFee * 1.1
WHERE Rating >= 4.0 AND Rating <= 4.5
```

```
AND EntryFee > 0;


SELECT Category, SUM(VisitorsPerYear) AS
TotalVisitors
FROM tourist_spot
GROUP BY Category;
SELECT Category, COUNT(*) AS TotalSpots,
    AVG(Rating) AS AvgRating
FROM tourist_spot
GROUP BY Category
HAVING AVG(Rating) > 4.4
ORDER BY AVG(Rating) DESC;


SELECT Category,
    COUNT(*) AS TotalSpots,
    AVG(Rating) AS AvgRating,
    SUM(VisitorsPerYear) AS TotalVisitors
FROM tourist_spot
GROUP BY Category
HAVING AVG(Rating) > 4.4
ORDER BY AvgRating DESC;


SELECT Region, SUM(EntryFee *
VisitorsPerYear) AS Revenue
FROM tourist_spot
GROUP BY Region
HAVING SUM(EntryFee * VisitorsPerYear) >
1000000
ORDER BY Revenue DESC;
```

```
SELECT Category, COUNT(*) AS SpotCount,
AVG(Rating) AS AvgRating,
SUM(VisitorsPerYear) AS TotalVisitors
FROM tourist_spot GROUP BY Category
HAVING AVG(Rating) > 4.4 ORDER BY
AvgRating DESC;
UPDATE tourist_spot SET Rating = Rating +
0.2, EntryFee = EntryFee * 1.10 WHERE
Rating BETWEEN 4.0 AND 4.5 AND
EntryFee > 0;
```

Join

```
SELECT p.ProductName, p.CategoryName,
    CASE
        WHEN p.Revenue > cat_avg.avg_rev
THEN 'Top Seller'
        ELSE 'Regular Seller'
    END AS SellerStatus
FROM sales_data p
JOIN (
  SELECT CategoryID, AVG(Revenue) AS
avg_rev
  FROM sales_data
  GROUP BY CategoryID
) cat_avg ON p.CategoryID =
cat_avg.CategoryID;


SELECT p.ProductName, p.CategoryName,
    IF(p.Revenue > cat_avg.avg_rev, 'Top
Seller', 'Regular Seller') AS SellerStatus
FROM sales_data p
JOIN (
  SELECT CategoryID, AVG(Revenue) AS
avg_rev
  FROM sales_data
  GROUP BY CategoryID
) cat_avg ON p.CategoryID =
cat_avg.CategoryID;
```