OWNER: PURPLE MOSS 1005 CC
N.NEL. 082-458-6941

OWNER: SILVER 44 CC
N.NEL. 082-458-6941

ERF: 19

ERF: 22

BOUNDARY LINE 34 750mm

Retaining Wall Note:
Reinforced retaining wall with 4mm Torch on Bitumen waterproofing with 'KAYTECH/GEOFAB FLOWNET & MASONITE BOARD' to protect against backfilling. All retaining walls to Eng. details with agricultural drain to Eng. details.

4.5m BUILDING LINE RELAXED TO
BUILDING LINE 2 000mm

RETAINING WALL TO ENG. DETAILS

PAVING NOTES:
Paving
222 x 106 x 73 mm paving bricks on well compacted basis to Eng. details

STORM WATER NOTE: direction of slope

ENTRANCE RAMP DOWN

100mmØ soil pipe to 1:60 fall or 1:80. To municipal connection.

TO MUN. CONN. PIT

ROOF OVERHANG

RETAINING WALL TO ENG. DETAILS

Geo Pipe to Eng. details and spec. To muni. storm water connection pit.

STORMWATER NOTE:
100Ø stormwater pipe at a fall of 1:60 min all to eng. details and specs.

line of beam below @ 106 120

roof fall

ROOF NOTE:
SAFLOK SAF 700
0,53mm Colorbond G550 or similar approved roof sheeting from SAFINTRA on 2m purlin spacing all to engineers detail.

500 X 500 box gutter flashing and counter flashing as per eng. details and spec.

direction of fall

min 340mm parapet wall

F.B.O

rwdp

GRASS

5000 x 2500 parking bays to be demarcated by painting

MOUNTABLE KERB

BOUNDARY LINE 14 200mm

4.5m BUILDING LINE RELAXED TO
BUILDING LINE 2 000mm

BOUNDARY LINE 30 470mm

OPEN BALCONY
tiled

2000

PROPOSED NEW OFFICE ON ERF: 21 (993m²)

BUILDING LINE 5000mm

BOUNDARY LINE 18 000mm

BOUNDARY LINE 8 600mm

BOUNDARY LINE 8 550mm

BOUNDARY LINE 8 690mm

755

PRIVATE ROAD

ERF: 20

PRIVATE ROAD

SITE PLAN
SCALE 1:100

AREA SCHEDULE		FAR SCHEDULE
AREA SCHEDULE		TOTAL AREA = 1212 m²
GROUND FLOOR AREA	371 m²	EXCLUSIONS - BASEMENT = 490 m²
1st FLOOR AREA	347 m²	- STAIR WELL = 16 m²
TOTAL FLOOR AREA	718 m²	- LOBBYS, CORRIDORS = 11 m²
BASEMENT	490 m²	TOTAL FAR = 695 m²
TOTAL AREA	1208 m²	

SCHEDULE OF RIGHTS		
PROPERTY DESCRIPTION:	BEDFORDVIEW P.T.N.:21 ERF: 1577	
Zoning:	Residential -	
Erf size:	993 m²	
Parking:	Permissible	Actual
Office Area.....	2 per 100m²	2 per 100m²
Factory Area....	----------	----------
Visitors	13 Bays	13 Bays
Residential	----------	----------
Covered bays....	14 Bays	14 Bays
Total parking required.....	27 Bays	27 Bays
Density :	----------	----------
FAR (floor area ratio):	(0.7) 695.10 m²	0.7
Height (storeys):	2 Storey	2 Storey
Coverage (%):	(35%) 347.55 m²	(29%) 342 m²
Building line:	5m from road & 2m form other.	5m from main road 2m other boundarys
Building Area (FAR):	695.10 m²	695 m²
Building coverage (sqm):	347.55 m²	342 m²
Notes:		

SANITARY REGULATIONS			
OCCUPANCY :G1 (OFFICES)			
PERMITTED		ACTUAL	
POPULATION : 1 PERSON PER 15m ²		POPULATION : 1 PERSON PER 15m ²	
30-60 PEOPLE		44.8 PEOPLE (673m ²)	
MALE	WC-2	MALE	WC-4
	WHB-3		WHB-4
	URANALS-3		URANALS-4
FEMALE	WC-5	FEMALE	WC-5
	WHB-2		WHB-4

PARKING SCHEDULE	
CLASSIFICATION : GENERAL OFFICES	
PERMITTED	ACTUAL
4 SPACES PER 100m ²	
OFFICE AREA = 695m ²	32 BAYS PROVIDED

695m² / 100² X 4 Bays = 27,8 Bays

FIRE PROTECTION SYMBOL LEGEND :			
	FIRE HOSE REEL (30m LENGTH)	fire ext.	FIRE EXTINGUISHER (9 kg DCP - DRY CHEMICAL POWDER)
fire ext.	FIRE EXTINGUISHER (4.5 kg DCP - DRY CHEMICAL POWDER)		
fire hyd.	FIRE HYDRANT (100mm STORZ COUPLING - WOODLANDS TYPE) (SEE SITE PLAN FOR POSITIONS OF HYDRANTS)		
S - VENT	AUTOMATIC MECHANICAL SMOKE VENT SIZE TO COMPLY WITH ANY AND ALL FIRE REGULATIONS FROM SABS		

FIRE PROTECTION QUANTITIES LEGEND :					
UNIT TYPE:	UNIT AMOUNTS:	FIRST FLOOR PLAN	GROUND FLOOR PLAN	BASEMENT	TOTAL PROVIDED
	AMOUNT PROVIDED:	1 off	3 off	1 off	5 off
fire ext.	AMOUNT PROVIDED:	0 off	0 off	0 off	0 off
fire ext.	AMOUNT PROVIDED:	2 off	2 off	2 off	6 off
fire hyd.	AMOUNT PROVIDED:	0 off	0 off	0 off	0 off

DEPARTMENT OF THE CITY CIVIL ENGINEER
23 JAN 2007
23/01/2007

The approval of this plan does not override the conditions of any restriction which may be applicable on this erf or the exemption from the liability to ensure that the building be designed, erected, completed and used in accordance with the provisions of Act 103 of 1977.

The building may be used or occupied without a certificate of Occupancy being issued by this Municipality.

The design and erection of all structural work, including roof trusses and wooden floors must be certified by a professional Structural Engineer.

This plan is only valid for one year from the date of approval.

Insight
ARCHITECTURAL DESIGNS

98 RONALD ROAD
LINBRO PARK
SANDTON
2145

Tel: (+2711) 608 1813

PROJECT :
PROPOSED NEW OFFICE ON ERF: 21 / 1577 BEDFORDVIEW EXT 328

DRAWING :
SITE PLAN

DATE : **20/06/2006**

DRAWN BY :

ISSUED : **P. VERVERIS**

PROJ. NO. : **001-BVO-04082005**

DRWG. NO. : **300806 BVO-003**

REVISIONS :

REV.	DESCRIPTION	DATE.
	○	01
	○	02
	○	03
	○	04
	○	05

CLIENTS SIGNATURE :

DATE :

ENGINEERS SIGNATURE :

DATE : N.740379

NOTES :

All work to be carried out in strict accordance with the ARCHITECTS instructions.

Top of foundations to be a minimum of 300mm below N.G.L. Vertical DPC to all changes in level's.

Reinforced concrete slab to ENGINEER'S details and specifications.

Waterproofing by specialists.
S.A.B.S. approved bitumen based waterproofing laid with required upturns, onto min. 25mm thick screed.
Acrylic based waterproofing to parapet walls & upriser.

All plumbing and drainage installation of sanitary fittings to comply with N.B.R. S.A.B.S. 0400-1990 part P and all relevant local authority by-laws, regulations and requirments.

I.B.'s and R.E.'s to all bends, junctions and changes in direction of soil and waste pipe's.

R.E.'s to all runs exceeding 24m in length.

100Ø GSP. minimum fall 1:60.
100Ø GSP. maximum fall 1:5.

Soil pipes under building's to be encassed in 300mm concrete all round.

All waste fittings to be fitted with re-seal traps.

Staircase specifications to comply with S.A.B.S. 0400-1990 part M.
Balustrades to be minimum 1000mm high.
Balustrades to be minimum 100mm apart.
Risers to be maximum 200mm high.
Treads to be minimum 250mm wide.

THIS DRAWING IS COPYRIGHT.
This is an AUTO CAD generated drawing.
Drawing must not be scaled.
Figured dimensions only may be used.
Dimensions should be verified on site and any discrepancies reported to the ARCHITECTS immediately.