

WEEK-1:

Program 1:

```
GNU nano 8.7.1
#include <stdio.h>
int main(){
printf("Welcome to operating system\n");
return 0;
}
```

Output:

```
userhasini@DESKTOP-QDSCC4:~/oslab$ nano hello.c
userhasini@DESKTOP-QDSCC4:~/oslab$ gcc hello.c -o hello
userhasini@DESKTOP-QDSCC4:~/oslab$ ./hello
Welcome to operating system
```

Program 2:

```
GNU nano 8.7.1
#include <stdio.h>
int main(){
printf("Enter Your name:");
scanf("%s",name);
printf("Welcome &s\n",name);
return 0;
}
```

Output:

```
userhasini@DESKTOP-QDSCC4:~/oslab$ nano readusername.c
userhasini@DESKTOP-QDSCC4:~/oslab$ gcc readusername.c -o readusername
userhasini@DESKTOP-QDSCC4:~/oslab$ ./readusername
Enter your name: hasini
Welcome hasini
userhasini@DESKTOP-QDSCC4:~/oslab$ |
```

Program 3:

```
GNU nano 8.7.1
#include <stdio.h>
#include<unistd.h>
int main(){
fork();
printf("Hello \n");
return 0;
}
```

Output:

```
userhasini@DESKTOP-QDSCC4:~$ nano display.c
userhasini@DESKTOP-QDSCC4:~$ gcc display.c -o display
userhasini@DESKTOP-QDSCC4:~$ ./display
Hello
Hello
```