

→ MLflow.

Classifier → loan app prediction 1/0

✓ → Logistic (✓) → Acc 70.1%

✓ → Logistic (✓) → Acc 72.1%

✓ → RF (✓✓) → Acc 78.1%
max_depth 10

✓ → RF (max_depth = 20) → Acc 82.1% ✓✓

✓ → RF (n_estimators = 100) → Acc 79.1%

model	Hypen	Acc
LR	penal: L1	1
LR	penal: L2	1
RF	max. dep 10	1
RF	20	1
RF	n. est. = 100	1

→ model.py
 → model-1.py
 → model-2.py
 → model-3.py

MLflow = Git + Excel sheet
for models

→ Open source platform
for managing end-to-end
ML lifecycle.

log
the
metric
&
hyperparameter

- ① Track code + data
- ② Track hyperparameters like max_depth
- ③ Track metrics like accuracy
- ④ Save models
- ⑤ Deploy using MLflow.

Collected data




EDA



OHE, LE



Missing values



Outlier detection



Build diff model



Evaluate ML model



Deploy ML model



→ Experiment - name

↳ Run 1

↳ Run 2

↳ Run 3

↳

← mlflow . set - experiment (-)

← mlflow . set - tag ()

- ✓
 - Parameter like max_depth
 - ↳ mlflow.log_param
 - Metrics like Acc
 - ↳ mlflow.log_metric
 - Artifacts → Store model, png
 - ↳ mlflow.log_artifact

→ Break until 22:25 PM

→ MLflow deployment


↳ Model deployment means

to turn the trained
model into API endpoint

that can accept input & provide


response.

POST



wandb

MLflow



[]