



Linux-Foundation

Exam Questions CKAD

Certified Kubernetes Application Developer (CKAD) Program

About ExamBible

[Your Partner of IT Exam](#)

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

Exhibit:



Context

Developers occasionally need to submit pods that run periodically. Task

Follow the steps below to create a pod that will start at a predetermined time and]which runs to completion

only once each time it is started:


- Create a YAML formatted Kubernetes manifest /opt/KDPD00301/periodic.yaml that runs the following shell command: date in a single busybox container. The command should run every minute and must complete within 22 seconds or be terminated by Kubernetes. The Cronjob name and container name should both be hello
- Create the resource in the above manifest and verify that the job executes successfully at least once

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution:



ReadmeWeb Terminal

THE **LINUX** FOUNDATION

```
student@node-1:~$ kubectl create cronjob hello --image=busybox --schedule "* * * * *" --dry-run=client -o yaml > /opt/KDPD00301/periodic.yaml
error: unable to match a printer suitable for the output format "yaml", allowed formats are: go-template, go-template-file, json, jsonpath, jsonpath-as-json, jsonpath-file, name, template, templatefile, yaml
student@node-1:~$ kubectl create cronjob hello --image=busybox --schedule "* * * * *" --dry-run=client -o yaml > /opt/KDPD00301/periodic.yaml
student@node-1:~$ vim /opt/KDPD00301/periodic.yaml
student@node-1:~$ kubectl create -f /opt/KDPD00301/periodic.yaml
cronjob.batch/hello created
student@node-1:~$ kubectl get cronjob
NAME      SCHEDULE      SUSPEND  ACTIVE  LAST SCHEDULE  AGE
hello     */1 * * * *   False    0       <none>         6s
student@node-1:~$
```

NEW QUESTION 2

Exhibit:

Set configuration context:

[student@node-1] \$ | kubectl config use-context nk8s

Task
You have rolled out a new pod to your infrastructure and now you need to allow it to communicate with the web and storage pods but nothing else. Given the running pod kdsn00201 -newpod edit it to use a network policy that will allow it to send and receive traffic only to and from the web and storage pods.

All work on this item should be conducted in the kdsn00201 namespace.

All required NetworkPolicy resources are already created and ready for use as appropriate. You should not create, modify or delete any network policies whilst completing this item.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Suggest the Solution.

NEW QUESTION 3

Exhibit:



Context

You have been tasked with scaling an existing deployment for availability, and creating a service to expose the deployment within your infrastructure. Task Start with the deployment named kdsn00101-deployment which has already been deployed to the namespace kdsn00101 . Edit it to:

- Add the func=webFrontEndkey/value label to the pod template metadata to identify the pod for the service definition
- Have 4 replicas

Next, create ana deploy in namespace kdsn00l01 a service that accomplishes the following:

- Exposes the service on TCP port 8080
- is mapped to me pods defined by the specification of kdsn00l01-deployment
- Is of type NodePort
- Has a name of cherry


- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution:

```
student@node-1:~$ kubectl edit deployment kdsn00101-deployment -n kdsn00101
```



Readme

Web Terminal


THE **LINUX** FOUNDATION

```
uid: 8d3ace00-7761-4189-ba10-fbc676c311bf
spec:
  progressDeadlineSeconds: 600
  replicas: 4
  revisionHistoryLimit: 10
  selector:
    matchLabels:
      app: nginx
  strategy:
    rollingUpdate:
      maxSurge: 25%
      maxUnavailable: 25%
    type: RollingUpdate
  template:
    metadata:
      creationTimestamp: null
      labels:
        app: nginx
        func: webFrontEnd
    spec:
      containers:
      - image: nginx:latest
        imagePullPolicy: Always
        name: nginx
        ports:
        - containerPort: 80

student@node-1:~$ kubectl edit deployment kdsn00101-deployment -n kdsn00101
deployment.apps/kdsn00101-deployment edited
student@node-1:~$ kubectl get deployment kdsn00101-deployment -n kdsn00101
NAME                READY   UP-TO-DATE   AVAILABLE   AGE
kdsn00101-deployment 4/4      4             4           7h17m
student@node-1:~$ kubectl expose deployment kdsn00101-deployment -n kdsn00101 --type NodePort --
port 8080 --name cherry
service/cherry exposed
```

NEW QUESTION 4

Exhibit:



Context

As a Kubernetes application developer you will often find yourself needing to update a running application. Task
Please complete the following:

- Update theappdeployment in the kdpd00202 namespace with a maxSurge of5% and a maxUnavailable of2%
- Perform a rolling update of the web1 deployment, changing the lfccncf/ngmx image version to 1.13
- Roll back theappdeployment to the previous version

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution:

Readme

Web Terminal

THE **LINUX** FOUNDATION

```
student@node-1:~$ kubectl edit deployment app -n kdpd00202
```


Readme

Web Terminal

THE **LINUX** FOUNDATION

```
uid: 1dfa2527-5c61-46a9-8dd3-e24643d3ce14
spec:
  progressDeadlineSeconds: 600
  replicas: 10
  revisionHistoryLimit: 10
  selector:
    matchLabels:
      app: nginx
  strategy:
    rollingUpdate:
      maxSurge: 5%
      maxUnavailable: 2
    type: RollingUpdate
  template:
    metadata:
      creationTimestamp: null
      labels:
        app: nginx
    spec:
      containers:
      - image: lfocncf/nginx:1.13
        imagePullPolicy: IfNotPresent
        name: nginx
        ports:
        - containerPort: 80
          protocol: TCP
:wq!
```

Readme

Web Terminal

THE **LINUX** FOUNDATION

```
student@node-1:~$ kubectl edit deployment app -n kdpd00202
deployment.apps/app edited
student@node-1:~$ kubectl rollout status deployment app -n kdpd00202
Waiting for deployment "app" rollout to finish: 6 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 7 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 7 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 7 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 8 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 8 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 8 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 8 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 9 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 9 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 9 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 1 old replicas are pending termination...
Waiting for deployment "app" rollout to finish: 8 of 10 updated replicas are available...
Waiting for deployment "app" rollout to finish: 9 of 10 updated replicas are available...
deployment "app" successfully rolled out
student@node-1:~$ kubectl rollout undo deployment app -n kdpd00202
deployment.apps/app rolled back
student@node-1:~$ kubectl rollout status deployment app -n kdpd00202
student@node-1:~$ kubectl rollout status deployment app -n kdpd00202
Waiting for deployment "app" rollout to finish: 6 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 6 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 6 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 6 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 7 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 7 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 9 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 9 out of 10 new replicas have been updated...
Waiting for deployment "app" rollout to finish: 1 old replicas are pending termination...
Waiting for deployment "app" rollout to finish: 1 old replicas are pending termination...
Waiting for deployment "app" rollout to finish: 1 old replicas are pending termination...
Waiting for deployment "app" rollout to finish: 8 of 10 updated replicas are available...
Waiting for deployment "app" rollout to finish: 9 of 10 updated replicas are available...
deployment "app" successfully rolled out
student@node-1:~$
```

NEW QUESTION 10

.....

Relate Links

100% Pass Your CKAD Exam with ExamBible Prep Materials

<https://www.exambible.com/CKAD-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>