



# Antiamuny Code Library

tarjen



# 目录

第零章 .....	1
赛前准备 .....	2
测样例脚本(python 版) .....	2
对拍(cpp 版本) .....	3
对拍(bat 版本) .....	3
杂项 .....	4
Rand .....	4
Time .....	4
子集枚举 .....	4
高维前缀和 .....	4
三分 .....	4
Bitset .....	5
Bitset 手写 .....	5
Lcslen(n2/w) .....	6
wqs 二分 .....	7
判断异或方程组是否有解 .....	8
可以判断不同或相同的并查集 .....	9
Int128 .....	9
树哈希 .....	10
求 s 所有前缀对于 t 的所有子串的最长公共子序列长度 .....	11
线性基 .....	12
维护多个二维向量能够表示的范围 .....	15
字符串 .....	16
AC 自动机 .....	16
Dequehash .....	17
Exkmp .....	18
Hash .....	20
Kmp .....	20
Manacher .....	21
倍增 SA .....	22
后缀自动机 SAM .....	24
回文自动机 PAM .....	25
最小表示 .....	26
Runs .....	26
图论 .....	29
Johnson 全源最短路 .....	29
Kosaraju .....	29
K 短路 .....	30
Maxflow 只算值版本 .....	33
Maxflow 网络流最大流 .....	34
Tarjan 缩点 .....	35
二分图匹配 .....	35
二分图最优匹配 .....	36
二分图染色 .....	37
圆方树 .....	38
基环树 .....	39
带权并查集 dsu .....	41

带花树 .....	41
带负环最小费用最大流 .....	43
支配树 .....	45
最小环 .....	46
最小费用最大流 .....	46
欧拉回路 .....	47
三四元环计数 .....	48
数据结构 .....	50
SegmentSet .....	50
SegmentTree .....	51
三维偏序 cdq .....	53
主席树 .....	55
二维树状数组 .....	58
动态开点线段树 .....	59
可持久化 01trie .....	60
最近公共祖先 LCA .....	61
Lca(o1) .....	62
点分治 .....	63
珂朵莉树 .....	64
笛卡尔树 .....	65
线段树区间加区间历史最小值 .....	66
莫队 .....	67
虚树 .....	68
LCT 维护联通性 .....	70
树链剖分 .....	72
数学 .....	76
组合数 .....	76
BSGS 指数方程余数问题(求 $a^x \equiv b \pmod p$ ) .....	76
EXGCD .....	78
FFT .....	78
FWT .....	79
莫比乌斯反演 .....	81
NTT .....	81
任意模数 NTT .....	84
Pollard_Rho .....	86
扩展中国剩余定理 .....	87
拉格朗日插值 .....	88
拉格朗日插值没有模数 .....	89
杜教筛 .....	89
线性筛质数 .....	90
线性递推 .....	90
辛普森积分 .....	92
高斯消元(模意义) .....	92
高斯消元(浮点数) .....	93
计算几何 .....	94
开头 .....	94
点与向量 .....	94
极角排序 .....	94

直线 .....	95
线段 .....	95
多边形 .....	96
凸多边形 .....	97
圆 .....	99
判断多条线段是否有交点 .....	103
半平面交 .....	104
圆面积并 .....	105
多边形面积并 .....	106
点集形成的最小最大三角形 .....	107
点集的凸包 .....	108
给定三点求圆心 .....	109

## 第零章

- 安装 typst:

- Linux, macOS, WSL

```
curl -fsSL https://typst.community/typst-install/install.sh | sh
```

- Windows

```
irm https://typst.community/typst-install/install.ps1 | iex
```

- 安装 VSCode 插件 tinymist:

- 打开 VSCode
- 搜索 tinymist 安装插件

## 赛前准备

### 测样例脚本(python 版)

```
1 import os
2 import sys
3 import zipfile
4 # linux 下去掉.exe 和 加./
5 c = sys.argv[1]
6 code = c.capitalize()
7 os.system(f'g++ {c}.cpp -O2 -Wall -o {c}.exe')
8 try:
9     x = zipfile.Zipfile(f'samples-{code}.zip')
10    x.extractall(f'samples-{code}')
11 except:
12     pass
13
14 for i in range(1,10000):
15     if not os.path.isfile(f'samples-{code}/{i}.ans'):
16         break
17     print(f'Test {i}')
18     os.system(f'{c}.exe < samples-{code}/{i}.in > samples-{code}/{i}.out')
19     out = open(f'samples-{code}/{i}.out').read().replace('\r\n', '\n')
20     ans = open(f'samples-{code}/{i}.ans').read().replace('\r\n', '\n')
21     if(out != ans):
22         print(f'WA {i}')
23     else:
24         print(f'AC {i}')
```

### 对拍(cpp 版本)

```
1  int t=10000,j=0;
2  while(t)
3  {
4      cout<<"test:"<<++j<<"\n";
5      t--;
6      system("testin.exe > data.txt");
7      system("abiao Cheng.exe < data.txt > biaoda.txt");
8      system("nedtest.exe < data.txt > aatest.txt");
9      if(system("fc aatest.txt biaoda.txt")){
10         cout<<"error"<<"\n";
11         break;
12     }
13 }
14 if(t==0) cout<<"no error"<<endl;
15 //system("pause");
16 return 0;
```

### 对拍(bat 版本)

```
1 @echo off
2 setlocal enabledelayedexpansion
3
4 set T=0
5 :loop
6 if %T% gtr 100000 (
7     echo "Finished"
8     exit /b
9 )
10 set /a T+=1
11 echo T=!T!
12 testin.exe > data.txt
13 abiao Cheng.exe < data.txt > biaoda.txt
14 nedtest.exe < data.txt > aatest.txt
15
16 fc aatest.txt biaoda.txt
17 if errorlevel 1 (
18     echo "WA"
19     exit /b
20 )
21
22 goto loop
```



## 杂项

### Rand

```
1 mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
2 int myRand(int B) {
3     return (unsigned long long)rng() % B;
4 }
```

### Time

```
1 struct gettime{
2     clock_t star,ends;
3     gettime(){
4         star = clock();
5     }
6     ~gettime(){
7         ends = clock();
8         cout <<"Running Time : "<<(double)(ends - star)/ CLOCKS_PER_SEC << endl;
9     }
10 } tim;
11 int main()
12 {
13     tim.begin();
14     tim.end();
15     return 0;
16 }
17 }
```

### 子集枚举

```
1 for(int i=0;i<(1<<n);i++){
2     for(int j=i;j;j=(j-1)&i){
3
4     }
5 }
```

### 高维前缀和

```
1 for(int j = 0; j < n; j++)
2     for(int i = 0; i < 1 << n; i++)
3         if(i >> j & 1) f[i] += f[i ^ (1 << j)];
```

### 三分

```
1 double f(double x){
2     //something
3 }
4 const double eps=1e-8;
5 double sanfen(double l, double r){
6     double mid,midr,ans;
7     while (fabs(r-l)>eps) {
8         mid=(l+r)/2;
9         midr=(mid+r)/2;
10        if(f(mid) < f(midr)) l=mid; else r=midr;    //求最大值
11    }
12    ans=f(l);
13    return ans;
14 }
```

## Bitset

```
1 template<int LEN>void solve(){
2     sz=a.size();
3     if (LEN<=b.size()){
4         solve<min(N,LEN+10)>();
5         return;
6     }
7     using Bitset=bitset<LEN>;
8     Bitset is[sz+5];
9     for(int i=0;i<sz;i++)for(int j=0;j<b.size();j++){
10         auto&[x,l,r]=a[i];
11         auto&[y,L,R]=b[j];
12         if(l<=y&&y<=r&&L<=x&&x<=R)is[i][j]=1;
13     }
14     ll rs=0;
15     for(int i=0,x;i<sz;i++)for(int j=i+1;j<sz;j++){
16         x=(is[i]&is[j]).count();
17         rs+=x*(x-1)/2;
18     }
19     cout<<rs<<'\n';
20 }
```

## Bitset 手写

```
1 const int N=3000;
2 typedef unsigned long long ull;
3
4 int lim=N/64+3;
5 struct Bitset{
6     ull v[N/64+5];
7     void init(){
8         memset(v,0,sizeof(v));
9         return;
10    }
11    void add(int x){
12        v[x>>6]|=(1ull<<(x&63));
13        return;
14    }
15    void shiftl(){
16        int lst=0;
17        for(int i=0;i<=lim;i++){
18            int cur=v[i]>>63;
19            v[i]<=1;v[i]|=lst;
20            lst=cur;
21        }
22        return;
23    }
24    int count(){
25        int res=0;
26        for(int i=0;i<=lim;i++) res+=__builtin_popcountll(v[i]);
27        return res;
28    }
29    Bitset operator|(const Bitset &x)const{
30        Bitset res;
31        for(int i=0;i<=lim;i++) res.v[i]=v[i]|x.v[i];
32        return res;
33    }
```

```

34 Bitset operator&(const Bitset &x) const{
35     Bitset res;
36     for(int i=0;i<=lim;i++) res.v[i]=v[i]&x.v[i];
37     return res;
38 }
39 Bitset operator^(const Bitset &x) const{
40     Bitset res;
41     for(int i=0;i<=lim;i++) res.v[i]=v[i]^x.v[i];
42     return res;
43 }
44 Bitset operator-(const Bitset &x) const{
45     Bitset res; ull lst=0;
46     for(int i=0;i<=lim;i++){
47         ull cur=(v[i]<x.v[i]+lst);
48         res.v[i]=v[i]-x.v[i]-lst;
49         lst=cur;
50     }
51     return res;
52 }
53 }

```

### Lcslen(n2/w)

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int N=3010;
4  typedef unsigned long long ull;
5  const int lim=N/64+3;
6  struct Bitset{
7      ull v[N/64+5];
8      void init(){
9          memset(v,0,sizeof(v));
10         return;
11     }
12     void add(int x){
13         v[x>>6]|=(1ull<<(x&63));
14         return;
15     }
16     void shiftl(){
17         int lst=0;
18         for(int i=0;i<=lim;i++){
19             int cur=v[i]>>63;
20             v[i]<=1;v[i]|=lst;
21             lst=cur;
22         }
23         return;
24     }
25     int count(){
26         int res=0;
27         for(int i=0;i<=lim;i++) res+=__builtin_popcountll(v[i]);
28         return res;
29     }
30     Bitset operator|(const Bitset &x) const{
31         Bitset res;
32         for(int i=0;i<=lim;i++) res.v[i]=v[i]|x.v[i];
33         return res;
34     }

```

```

35 Bitset operator&(const Bitset &x)const{
36     Bitset res;
37     for(int i=0;i<=lim;i++) res.v[i]=v[i]&x.v[i];
38     return res;
39 }
40 Bitset operator^(const Bitset &x)const{
41     Bitset res;
42     for(int i=0;i<=lim;i++) res.v[i]=v[i]^x.v[i];
43     return res;
44 }
45 Bitset operator-(const Bitset &x)const{
46     Bitset res;ull lst=0;
47     for(int i=0;i<=lim;i++){
48         ull cur=(v[i]<x.v[i]+lst);
49         res.v[i]=v[i]-x.v[i]-lst;
50         lst=cur;
51     }
52     return res;
53 }
54 }ch[26],f,g;
55 auto getans = [&](int mid){
56     int ll=mid,l2=n-mid;
57     f.init();g.init();
58     for(int i=0;i<26;i++){
59         ch[i].init();
60     }
61     for(int i=mid+1;i<=n;i++)ch[s[i]-'a'].add(i);
62     for(int i=1;i<=mid;i++){
63         g=f|ch[s[i]-'a'];
64         f.shiftl();
65         f.add(1);
66         f=g-f;
67         f=f^g;f=f&g;
68     }
69     return f.count();
70 };

```

## wqs 二分

```

1 // 这里是 上凸 取 min
2 // 上凸取 max 二分的时候改变一下 mid 的变化方向
3 // 下凸取 min 改变 mid 算贡献的符号
4 //min max 指的是求的是最大值 还是最小值
5 int solve(int mid){
6     k=mid;
7     function<void(int,int)> dfs = [&](int x,int h){
8         info dp2[3];memset(dp2,0,sizeof(dp2));
9         for(auto [it,w]:ve[x])if(it!=h){
10             dfs(it,x);
11             gmax(dp2[0],dp[x][0]+dp[it][0]);
12             gmax(dp2[2],dp[x][0]+dp[it][1]);
13             gmax(dp2[2],dp[x][2]+dp[it][0]);
14             dp[x][0]=dp2[0];
15             dp[x][1]=dp2[1];
16             dp[x][2]=dp2[2];
17         }
18         dp[x][0]=dp2[2];

```

```

19     dp[x][1]=dp2[0]+info{a[x]+k,1};
20 };
21 dfs(1,0);
22 return dp[1][0].second;
23 }
24 signed main()
25 {
26     int l=-sum-1000000000000ll,r=sum+1000000000000ll;
27     int ans=1e18;
28     while(l<=r){
29         int mid=(l+r)/2ll;
30         if(solve(mid)>=m){
31             ans=dp[1][0].first-m*mid;
32             r=mid-1;
33         }
34         else l=mid+1;
35     }
36     if(ans!=(int)1e18)cout<<ans<<"\n";
37     else cout<<"Impossible\n";
38     return 0;
39 }

```

### 判断异或方程组是否有解

```

1  const int maxn=1e2+5;
2  //每个方程组一定是  $x_1^{i_1}x_2^{i_2}x_3^{i_3}\dots=1/0$  的形式
3  bitset<maxn>b[maxn]; //1 表示这个方程组存在  $x_i$  比如  $x_3^{i_3}x_5^{i_5}=1$  就应该是 3 和 5 的地方上是 1
4  //b[n+1]存方程右边等于 0/1
5  int sum[maxn];
6  bool check(int x)
7  {
8      for(int i=1;i<=n;i++)if(b[x][i])return true;
9      return !b[x][n+1];
10 }
11 bool solve()
12 {
13     for(int i=1,p=1;i<=n;i++,p++)
14     {
15         if(!b[p][i])
16         {
17             int pos=0;
18             for(int j=p+1; j<=n; j++)
19                 if(b[j][i])
20                 {
21                     pos=j;
22                     break;
23                 }
24             if(pos)swap(b[p],b[pos]);
25         }
26         int flag=b[p][i];
27         for(int j=p+1; j<=n; j++) if(b[j][i]) b[j]^=b[p],flag=1;
28         if(!flag) p--;
29     }
30     for(int i=1; i<=n; i++) if(!check(i)) return false;
31     return true;
32 }

```

可以判断不同或相同的并查集

```
1 int f[maxn];
2 int getf(int x){
3     if(x<0)return -getf(-x);
4     if(x==f[x])return x;
5     else return f[x]=getf(f[x]);
6 }
7 bool merge(int x,int y){//如果是 x!=y 将 y 取反 (x>0 y>0)
8     x=getf(x),y=getf(y);
9     if(x==-y)return false;
10    if(x==y)return true;
11    if(x<0)f[-x]=-y;
12    else f[x]=y;
13    return true;
14 }
```

## Int128

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 inline __int128 read()
4 {
5     __int128 x=0,f=1;
6     char ch=getchar();
7     while(ch<'0' || ch>'9')
8     {
9         if(ch=='-')
10             f=-1;
11         ch=getchar();
12     }
13     while(ch>='0'&&ch<='9')
14     {
15         x=x*10+ch-'0';
16         ch=getchar();
17     }
18     return x*f;
19 }
20 inline void write(__int128 x)
21 {
22     if(x<0)
23     {
24         putchar('-');
25         x=-x;
26     }
27     if(x>9)
28         write(x/10);
29     putchar(x%10+'0');
30 }
31
32 istream& operator >> (istream& in, __int128& num) {
33     string s;in>>s;
34     num=0;
35     for(auto it:s)num=num*10+it-'0';
36     return in;
37 }
38
39 ostream& operator << (ostream& out, __int128 num) {
```

```

40     string s;
41     do{
42         s.push_back(char(num%10+'0'));
43         num/=10;
44     }while(num>0);
45     reverse(s.begin(),s.end());
46     out<<s;
47     return out;
48 }

```

## 树哈希

```

1  #include <cctype>
2  #include <chrono>
3  #include <cstdio>
4  #include <random>
5  #include <set>
6  #include <vector>
7
8  typedef unsigned long long ull;
9
10 const ull mask = std::chrono::steady_clock::now().time_since_epoch().count();
11
12 ull h(ull x) {
13     return x * x * x * 1237123 + 19260817;
14 }
15 ull f(ull x) {
16     ull cur = h(x & ((1 << 31) - 1)) + h(x >> 31);
17     return cur;
18 }
19 ull shift(ull x) {
20     x ^= mask;
21     x ^= x << 13;
22     x ^= x >> 7;
23     x ^= x << 17;
24     x ^= mask;
25     return x;
26 }
27
28 const int N = 1e6 + 10;
29
30 int n;
31 ull hash[N];
32 std::vector<int> edge[N];
33 std::set<ull> trees;
34
35 void getHash(int x, int p) {
36     hash[x] = 1;
37     for (int i : edge[x]) {
38         if (i == p) {
39             continue;
40         }
41         getHash(i, x);
42         hash[x] += shift(hash[i]);
43     }
44     trees.insert(hash[x]);
45 }

```

```

46
47 int main() {
48     scanf("%d", &n);
49     for (int i = 1; i < n; i++) {
50         int u, v;
51         scanf("%d%d", &u, &v);
52         edge[u].push_back(v);
53         edge[v].push_back(u);
54     }
55     getHash(1, 0);
56     printf("%lu", trees.size());
57 }
58

```

求  $s$  所有前缀对于  $t$  的所有子串的最长公共子序列长度

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  struct PairLCS {
4      vector<vector<int>> ih, iv;
5      int n = 0, m = 0;
6      PairLCS(string s, string t) : n(s.size()), m(t.size()) {
7          ih = iv = vector<vector<int>>(n + 1, vector<int>(m + 1));
8          iota(ih[0].begin(), ih[0].end(), 0);
9          for (int i = 1; i <= n; i++) {
10             for (int j = 1; j <= m; j++) {
11                 if (s[i - 1] == t[j - 1]) {
12                     ih[i][j] = iv[i][j - 1];
13                     iv[i][j] = ih[i - 1][j];
14                 } else {
15                     ih[i][j] = std::max(ih[i - 1][j], iv[i][j - 1]);
16                     iv[i][j] = std::min(ih[i - 1][j], iv[i][j - 1]);
17                 }
18             }
19         }
20     }
21     int query(int a, int b, int c) const {
22         int res = 0;
23         for (int i = b + 1; i <= c; i++) res += ih[a][i] <= b;
24         return res;
25     } // s[0,a) t[b,c)
26 };
27
28
29
30 int cas;
31
32 void solution() {
33     int q;
34     std::string s, t;
35     std::cin >> q >> s >> t;
36
37     // int n = s.size(), m = t.size();
38     PairLCS solver(s, t);
39
40     for (int _ = 0; _ < q; _++) {
41         int a, b, c;

```



```

42     std::cin >> a >> b >> c;
43     std::cout << solver.query(a, b, c) << '\n';
44 }
45 }
46
47
48 int main() {
49     ios::sync_with_stdio(false);
50     cin.tie(0);
51     int T = 1;
52     // std::cin >> T;
53     for (cas = 1; cas <= T; cas++) solution();
54
55     return 0;
56 }

```

## 线性基

```

1  struct LinearBasis
2  {
3      static const int maxbase = 35;
4      bool flag = false;
5      ll a[maxbase + 1];
6      int tot;
7      LinearBasis()
8      {
9          memset(a, 0, sizeof a);
10         tot=0;
11     }
12     LinearBasis(ll *x, int n)
13     {
14         LinearBasis();
15         build(x, n);
16     }
17     void build(ll *x, int n)
18     {
19         for(int i = 1; i <= n; ++i)
20             insert(x[i]);
21     }
22     void clear()
23     {
24         memset(a, 0, sizeof a);
25     }
26     bool insert(ll t)
27     {
28         //暴力插入一个数，维护的是一个上三角型的线性基矩阵，时间复杂度低，当待插入元素能插入时，返
回 true
29         for(int i = maxbase; i >= 0; --i)
30         {
31             if(t & (1ll << i))
32             {
33                 if(!a[i])
34                 {
35                     a[i] = t; //这里表示插入成功
36                     break;
37                 }
38                 t ^= a[i];

```

```

39     }
40 }
41 if(t == 0)flag = true;
42 return t;
43 }
44 bool query(ll t)
45 {
46     // 询问 t 是否可以被当前线性基表示, 不插入
47     if(t > queryMax())return false;
48     if(t == 0)return true;
49     for(int i = maxbase; i >= 0; --i)
50     {
51         if(t & (1ll << i))
52         {
53             if(!a[i])
54             {
55                 return false;
56             }
57             t ^= a[i];
58         }
59     }
60     return true;
61 }
62 void Insert(ll t)
63 {
64     // 插入一个线性基, 利用高斯消元法维护一个对角矩阵
65     for(int i = maxbase; i >= 0; --i)
66     {
67         if(t >> i & 1)
68         {
69             if(a[i])t ^= a[i];
70             else
71             {
72                 a[i] = t;
73                 for(int j = i - 1; j >= 0; --j)if(a[j] && (a[i] >> j & 1))a[i]
74                 ^= a[j];
75                 for(int j = i + 1; j <= maxbase; ++j)if(a[j] >> i & 1)a[j] ^= a[i];
76                 break;
77             }
78         }
79     }
80 LinearBasis merge(const LinearBasis &l1, const LinearBasis &l2)
81 {
82     // 得到两个线性基的并
83     LinearBasis ret = l1;
84     for(int i = maxbase; i >= 0; --i)
85         if(l2.a[i])
86             ret.insert(l2.a[i]);
87     return ret;
88 }
89 LinearBasis intersection(const LinearBasis &l1, const LinearBasis &l2)
90 {
91     // 得到两个线性基的交
92     LinearBasis all, ret, full;
93     ret.clear();

```

```

94     for(int i = maxbase; i >= 0; --i)
95     {
96         all.a[i] = l1.a[i];
97         full.a[i] = l1 << i;
98     }
99     for(int i = maxbase; i >= 0; --i)
100    {
101        if(l2.a[i])
102        {
103            ll v = l2.a[i], k = 0;
104            bool flag = true;
105            for(int j = maxbase; j >= 0; --j)
106            {
107                if(v & (1ll << j))
108                {
109                    if(all.a[j])
110                    {
111                        v ^= all.a[j];
112                        k ^= full.a[j];
113                    }
114                    else
115                    {
116                        // l2's basis is not in l1's;
117                        flag = false;
118                        all.a[j] = v;
119                        full.a[j] = k;
120                        break;
121                    }
122                }
123            }
124            if(flag)
125            {
126                ll v = 0; // get intersection by k;
127                for(int j = maxbase; j >= 0; --j)
128                {
129                    if(k & (1ll << j))
130                    {
131                        v ^= l1.a[j];
132                    }
133                }
134                ret.insert(v);
135            }
136        }
137    }
138    return ret;
139 }
140 // 询问最大值
141 ll queryMax()
142 {
143     ll ret = 0;
144     for(int i = maxbase; i >= 0; --i)
145         if((ret ^ a[i]) > ret)
146             ret ^= a[i];
147     return ret;
148 }
149 ll queryMin()

```

```

150     {
151         for(int i = 0; i <= maxbase; ++i)
152             if(a[i])
153                 return a[i];
154         return 0;
155     }
156 ll Kth_Max(ll k)
157 {
158     ll res=0;
159     for(int i=62;i>=0;i--)
160         if (k&(1LL<<i)) res^=a[i];
161     return res;
162 }
163 };
164

```

维护多个二维向量能够表示的范围

```

1  int gcd(int x,int y){
2      if(y==0)return x;
3      else return gcd(y,x%y);
4  }
5  struct vec{
6      int a00,a01,a11;
7      void clear(){
8          a00=a01=a11=0;
9      }
10 void insert(int x,int y){
11     while(x!=0){
12         int t=a00/x;
13         a00-=x*t;
14         a01-=y*t;
15         swap(a00,x);
16         swap(a01,y);
17     }
18     a11=gcd(a11,abs(y));
19     if(a11!=0)a01%=a11;
20 }
21 bool query(int x,int y){
22     if(x!=0){
23         if(a00==0||x%a00!=0)return false;
24         int t=x/a00;
25         y-=a01*t;
26     }
27     if(y==0){
28         return true;
29     }
30     else return a11!=0&& y%a11==0;
31 }
32 };

```

## 字符串

### AC 自动机

```
1  #include <bits/stdc++.h>
2  using namespace std;
3  const int maxn=1e6+10;
4  int n;
5  char c[maxn];
6  struct AC{
7      int trie[maxn][26],tot;
8      int e[maxn],fail[maxn],old[maxn];
9      void init(){
10         memset(trie,0,sizeof(trie));
11         memset(e,0,sizeof(e));
12         memset(fail,0,sizeof(fail));
13         memset(old,0,sizeof(old));
14         tot=0;
15     }
16     void insert(char *t){
17         int x=0;
18         for(int i=1;t[i];i++){
19             if(!trie[x][t[i]-'a']){
20                 trie[x][t[i]-'a']=++tot;
21             }
22             x=trie[x][t[i]-'a'];
23         }
24         e[x]++;
25     }
26     queue<int> qu;
27     void build(){
28         for(int i=0;i<26;i++){
29             if(trie[0][i])qu.push(trie[0][i]);
30         }
31         while(!qu.empty()){
32             int x=qu.front();
33             qu.pop();
34             for(int i=0;i<26;i++){
35                 if(trie[x][i]){
36                     fail[trie[x][i]]=trie[fail[x]][i];
37                     qu.push(trie[x][i]);
38                 }
39                 else trie[x][i]=trie[fail[x]][i];
40             }
41             old[trie[x][i]]=e[fail[trie[x][i]]] ? fail[trie[x][i]] : old[fail[trie[x]
42             [i]]];
43         }
44     }
45     int query(char *t){//这里是统计有多少模板串出现在了文本串之中，所以统计到了就要变成-1
46         int x=0,res=0;
47         for(int i=1;t[i];i++){
48             x=trie[x][t[i]-'a'];
49             for(int j=x;j&&e[j]!=-1;j=old[j]){
50                 res+=e[j];
51                 e[j]=-1;
52             }
53         }
54     }
```

```

53         return res;
54     }
55 };
56 AC ac;
57 int main()
58 {
59     scanf("%d",&n);
60     for(int i=1;i<=n;i++){
61         scanf("%s",c+1);
62         ac.insert(c);
63     }
64     ac.build();
65     scanf("%s",c+1);
66
67     cout<<ac.query(c)<<endl;
68     return 0;
69 }

```

## Dequehash

```

1  /*
2  严格 0base, 不用管任何函数里面的东西, 用就可以了, 不要越界
3  pair<int,int> first 表示哈希 sum, second 表示当前位置的值
4  */
5  #define int long long
6  #define sz(a) ((int)((a).size()))
7  const int maxn=3e5+10;
8  const int mod=1e9+7,base=1331;
9  int fpow(int n, int k, int p = mod) {int r = 1; for (; k; k >>= 1) {if (k & 1) r = r
* n % p; n = n * n % p;} return r;}
10 void add(int& a, int val, int p = mod) {if ((a = (a + val)) >= p) a -= p;}
11 void sub(int& a, int val, int p = mod) {if ((a = (a - val)) < 0) a += p;}
12 int mul(int a, int b, int p = mod) {return (int) a * b % p;}
13 int inv(int a, int p = mod) {return fpow(a, p - 2, p);}
14 int p[maxn],ip[maxn];
15 void init()
16 {
17     p[0] = 1; for(int i=1;i<maxn;i++) p[i] = mul(p[i - 1], base, mod);
18     for(int i=0;i<maxn;i++) ip[i] = inv(p[i], mod);
19 }
20 struct extendable_sequence {
21     deque<pair<int,int>> dq;
22     int pow_offset;
23
24     extendable_sequence() {
25         pow_offset = 0;
26         dq.push_back(make_pair(0, 0));
27     }
28
29     int size() {
30         return sz(dq) - 1;
31     }
32
33     pair<int,int>& operator [] (int i) {
34         return dq[i+1];
35     }
36

```

```

37 void add_back(vector<int> vals) {
38     int t = dq.back().first;
39     for(int i=0;i<sz(vals);i++) {
40         add(t, mul(vals[i], mul(p[sz(dq) - 1], ip[pow_offset], mod), mod), mod);
41         dq.push_back(make_pair(t, vals[i]));
42     }
43 }
44
45 void add_front(vector<int> vals) {
46     pow_offset += sz(vals);
47     int t = dq.front().first;
48     for(int i=sz(vals)-1;i>=0;i--) {
49         dq.front().second = vals[i];
50         sub(t, mul(vals[i], mul(p[i], ip[pow_offset], mod), mod), mod);
51         dq.push_front(make_pair(t, 0));
52     }
53 }
54
55 int calc(int l, int r) {
56     l++, r++;
57     if (l > r) return 0;
58     int res = dq[r].first;
59     sub(res, dq[l - 1].first, mod);
60     res = mul(res, ip[l - 1], mod);
61     res = mul(res, p[pow_offset], mod);
62     return res;
63 }
64 };
65 //返回(x+y)[l 到 r]的哈希值
66 int calc(extendable_sequence& x, extendable_sequence& y, int l, int r) {
67     int res = x.calc(l, min(r, sz(x) - 1));
68     add(res, mul(y.calc(max(0ll, l - sz(x)), r - sz(x)), p[sz(x)], mod), mod);
69     return res;
70 }
71 //返回(x+y)[i]单个元素的值
72 int calc(extendable_sequence& x, extendable_sequence& y, int i) {
73     if (i < sz(x)) {
74         return x[i].second;
75     }
76     if (i - sz(x) < sz(y)) {
77         return y[i - sz(x)].second;
78     }
79     return -1;
80 }

```

## Exkmp

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int maxn = 1e6 + 1e3;
4 struct EXKMP
5 { // S里找T
6
7     char S[maxn], T[maxn];
8     int next[maxn], extend[maxn];
9     void Get_Next()
10    {

```

```

11     int lenT = strlen(T + 1), p = 1, pos;
12     next[1] = lenT; // 对于 next[1] 要特殊考虑
13     while (p + 1 <= lenT && T[p] == T[p + 1])
14         ++p;
15     next[pos = 2] = p - 1; // next[2] 是为了初始化
16
17     for (int i = 3; i <= lenT; i++)
18     { // 注意此时 k + 1 = i
19         int len = next[i - pos + 1];
20         if (len + i < p + 1)
21             next[i] = len; // 对应上面第一种情况
22         else
23         {
24             int j = max(p - i + 1, 0); // 找到前面对于 子串 最靠后已经匹配的位置
25             while (i + j <= lenT && T[j + 1] == T[i + j])
26                 ++j; // 第二种需要暴力匹配
27             p = i + (next[pos = i] = j) - 1; // 记得更新 p, pos
28         }
29     }
30 }
31 void ExKMP()
32 {
33     int lenS = strlen(S + 1), lenT = strlen(T + 1), p = 1, pos;
34     Get_Next();
35     while (p <= lenT && S[p] == T[p])
36         ++p;
37     p = extend[pos = 1] = p - 1; // 初始化 extend[1]
38
39     for (int i = 2; i <= lenS; i++)
40     {
41         int len = next[i - pos + 1];
42         if (len + i < p + 1)
43             extend[i] = len;
44         else
45         {
46             int j = max(p - i + 1, 0);
47             while (i + j <= lenS && j <= lenT && T[j + 1] == S[i + j])
48                 ++j;
49             p = i + (extend[pos = i] = j) - 1;
50         }
51     } // 和上面基本一模一样啦
52 }
53 } sol;
54 int main()
55 {
56     scanf("%s", sol.S + 1);
57     scanf("%s", sol.T + 1);
58
59     sol.ExKMP();
60     int len = strlen(sol.S + 1);
61     for (int i = 1; i <= len; i++)
62         printf("%d%c", sol.extend[i], i == len ? '\n' : ' ');
63
64     return 0;
65 }

```



## Hash

```
1  const int N=1e6+10;
2  typedef long long ll;
3  const ll p1=31,p2=131;
4  const ll mod1=1e9+7,mod2=1e9+9;
5  typedef pair<ll,ll> hs;
6  const hs p = make_pair(p1,p2);
7  hs &operator+=(hs &a, hs b) {
8      a.first=(a.first+b.first)%mod1;
9      a.second=(a.second+b.second)%mod2;
10     return a;
11 }
12 hs operator+(hs a, hs b) { return a += b; }
13 hs &operator-=(hs &a, hs b) {
14     a.first=(a.first-b.first+mod1)%mod1;
15     a.second=(a.second-b.second+mod2)%mod2;
16     return a;
17 }
18 hs operator-(hs a, hs b) { return a -= b; }
19 hs &operator*=(hs &a, hs b) {
20     a.first=(a.first*b.first)%mod1;
21     a.second=(a.second*b.second)%mod2;
22     return a;
23 }
24 hs operator*(hs a, hs b) { return a *= b; }
25 struct Hash{
26     int n;
27     vector<hs>has1,has2,Pow;
28     void Hash_init(string &s){
29         n=(int)s.size();
30         Pow.resize(n+2);
31         has1.resize(n+2);
32         has2.resize(n+2);
33         Pow[0]=make_pair(1ll,1ll);
34         for(int i=1;i<=n;i++)Pow[i]=Pow[i-1]*p;
35         for(int i=1;i<=n;i++)has1[i]=has1[i-1]*p+hs{s[i-1]-'a'+1,s[i-1]-'a'+1};
36         for(int i=n;i>=1;i--)has2[i]=has2[i+1]*p+hs{s[i-1]-'a'+1,s[i-1]-'a'+1};
37     }
38     hs get1(int l,int r){
39         return has1[r]-has1[l-1]*Pow[r-l+1];
40     }
41     hs get2(int l,int r){
42         return has2[l]-has2[r+1]*Pow[r-l+1];
43     }
44 };
```

## Kmp

```
1  #include <bits/stdc++.h>
2  using namespace std;
3  const int maxn=1e6+10;
4  struct KMP{//lbase
5      int len1,n,nxt[maxn];//nxt 表示以 i 为结尾的前缀与后缀相同的长度
6      char s1[maxn],s2[maxn];
7      void build()
8      {
9          n=strlen(s+1);
```

```

10     nxt[1]=0;
11     int x=2,now=1;//x 是 s2 当前搜索到的位置, now 是前缀位置
12     while(x<=n){
13         if(s[x]==s[now]){
14             nxt[x]=now;
15             now++;
16             x++;
17         }
18         else{
19             if(now>1){
20                 now=nxt[now-1]+1;
21             }
22             else{
23                 nxt[x]=0;
24                 now=1;
25                 x++;
26             }
27         }
28     }
29 }
30 void find(){//s1 lbase
31     int now=1,tar=1;
32     len1=strlen(s1+1);
33     while(tar<=len1){
34         if(s1[tar]==s[now]){
35             tar++;
36             now++;
37         }
38         else{
39             if(now>1){
40                 now=nxt[now-1]+1;
41             }
42             else tar++;
43         }
44         if(now==n+1){
45             printf("%d\n",tar-now+1);
46         }
47     }
48 }
49 };
50 KMP sol;
51 int main()
52 {
53     scanf("%s%s",sol.s1+1,sol.s+1);
54     sol.build();
55     sol.find();
56     for(int i=1;i<=sol.n;i++)cout<<sol.nxt[i]<<" ";
57     return 0;
58 }

```

## Manacher

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int maxn = 1.1e7 + 5;
4 struct ST{
5     char s[maxn * 2], str[maxn * 2];

```

```

6  int Len[maxn * 2], len;
7  void getstr() { // 重定义字符串
8      int k = 0;
9      len = strlen(s);
10     str[k++] = '@'; // 开头加个特殊字符防止越界
11     for (int i = 0; i < len; i++) {
12         str[k++] = '#';
13         str[k++] = s[i];
14     }
15     str[k++] = '#';
16     len = k;
17     str[k] = 0; // 字符串尾设置为 0, 防止越界
18 }
19 int manacher() {
20     int mx = 0, id; // mx 为最右边, id 为中心点
21     int maxx = 0;
22     for (int i = 1; i < len; i++) {
23         if (mx > i) Len[i] = min(mx - i, Len[2 * id - i]); // 判断当前点有没有超过 mx
24         else Len[i] = 1; // 超过了就让他等于 1, 之后再进行检查
25         while (str[i + Len[i]] == str[i - Len[i]]) Len[i]++; // 判断当前点是不是最长回文子串,
不断的向右扩展
26         if (Len[i] + i > mx) { // 更新 mx
27             mx = Len[i] + i;
28             id = i; // 更新中间点
29             maxx = max(maxx, Len[i]); // 最长回文子串长度
30         }
31     }
32     return (maxx - 1);
33 }
34 void writ(){
35     printf("%s\n", str);
36     for(int i=0; i<len; i++){
37         cout<<Len[i]<<" ";
38     }
39     cout<<"\n";
40 }
41 };
42 ST s1, s2;
43 int main() {
44     scanf("%s", s1.s);
45     s1.getstr();
46     printf("%d\n", s1.manacher());
47     return 0;
48 }

```

## 倍增 SA

```

1  #include<bits/stdc++.h>
2  using namespace std;
3  const int N = 1e6 + 10; // 2*strlen
4  struct Suffix{
5      int ht[N], rk[N], sa[N], y[N], c[N];
6      int n, m;
7      char s[N];
8      int st[20][N];
9      void init(){

```

```

10     n=strlen(s+1);
11     m=300;
12     for(int i=0;i<=m;i++) c[i]=0;
13     for(int i=0;i<=2*n;i++) y[i]=0;
14     for(int i=1;i<=n;i++) c[rk[i]]=s[i]++;
15     for(int i=1;i<=m;i++) c[i]+=c[i-1];
16     for(int i=n;i>=1;i--) sa[c[rk[i]]--]=i;
17     for(int k=1;k<=n;k<=1){
18         int p=0;
19         for(int i=n-k+1;i<=n;i++) y[++p]=i;
20         for(int i=1;i<=n;i++){
21             if(sa[i]>k){
22                 y[++p]=sa[i]-k;
23             }
24         }
25         for(int i=0;i<=m;i++) c[i]=0;
26         for(int i=1;i<=n;i++) c[rk[i]]++;
27         for(int i=1;i<=m;i++) c[i]+=c[i-1];
28         for(int i=n;i>=1;i--) sa[c[rk[y[i]]]--]=y[i];
29         for(int i=0;i<=n;i++) swap(rk[i],y[i]);
30         rk[sa[1]]=p=1;
31         for(int i=2;i<=n;i++){
32             rk[sa[i]]=(y[sa[i]] == y[sa[i-1]] && y[sa[i]+k] == y[sa[i-1]+k] ? p : ++p);
33         }
34         if(p>=n) break;
35         m=p;
36     }
37     for(int i=1,k=0;i<=n;i++){
38         if(k)k--;
39         int j=sa[rk[i]-1];
40         while(s[i+k] == s[j+k])k++;
41         ht[rk[i]] = k;
42     }
43     for(int i=1;i<=n;i++)st[0][i]=ht[i];
44     for(int j=1;j<20;j++){
45         for(int i=1;i+(1<<j)-1<=n;i++)st[j][i]=min(st[j-1][i],st[j-1]
[i+(1<<(j-1))]);
46     }
47 }
48 int get(int l,int r){
49     int g=__lg(r-l+1);
50     return min(st[g][l],st[g][r-(1<<g)+1]);
51 }
52 int lcp(int x,int y){
53     x=rk[x],y=rk[y];
54     if(x==y)return n-x+1;
55     if(x>y)swap(x,y);
56     return get(x+1,y);
57 }
58 int query(int l1,int r1,int l2,int r2){
59     int len=lcp(l1,l2);
60     len=min({len,r1-l1+1,r2-l2+1});
61     if(len==min(r1-l1+1,r2-l2+1)){
62         if(r1-l1>r2-l2)return 1;
63         if(r1-l1<r2-l2)return -1;
64         if(r1-l1==r2-l2)return 0;

```

```

65     }
66     char p=s[l1+len],q=s[l2+len];
67     if(p>q)return 1;
68     if(p==q)return 0;
69     return -1;
70 }
71 void writ()
72 {
73     printf("%s\n",s+1);
74     for(int i=1;i<=n;i++)cout<<sa[i]<<" ";cout<<"\n";
75     for(int i=1;i<=n;i++)cout<<ht[i]<<" ";cout<<"\n";
76     for(int i=1;i<=n;i++)cout<<rk[i]<<" ";cout<<"\n";
77 }
78
79 };
80 Suffix suf;

```

## 后缀自动机 SAM

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int N=2e6;
4  struct SAM {
5      struct Node {
6          int tr[26];
7          int len, fa;
8          Node() { memset(tr, 0, sizeof(tr)); len = fa = 0; }
9      }ep[N << 1];
10     int last, tot, n;
11     char base;
12     vector<int> edg[N << 1];
13     int siz[N << 1];
14     void init(int _n) {
15         last = tot = 1;
16         base = 'a';
17         for (int i = 0; i <= 2 * _n; i++) {
18             ep[i] = Node();
19             edg[i].clear();
20             siz[i] = 0;
21         }
22     }
23     void insert(char x) {
24         int c = x - base;
25         int p = last;
26         int np = last = ++tot;
27         siz[np] = 1;
28         ep[np].len = ep[p].len + 1;
29         for (; p && !ep[p].tr[c]; p = ep[p].fa)
30             ep[p].tr[c] = np;
31         if (!p) ep[np].fa = 1;
32         else {
33             int q = ep[p].tr[c];
34             if (ep[q].len == ep[p].len + 1) ep[np].fa = q;
35             else {
36                 int nq = ++tot;
37                 ep[nq] = ep[q];
38                 ep[nq].len = ep[p].len + 1;

```

```

39         ep[q].fa = ep[np].fa = nq;
40         for (; p && ep[p].tr[c] == q; p = ep[p].fa)
41             ep[p].tr[c] = nq;
42     }
43 }
44 }
45 void construct() {
46     for (int i = 2; i <= tot; i++) {
47         edg[ep[i].fa].push_back(i);
48     }
49 }
50 void dfs(int u) {
51     for (auto v : edg[u]) {
52         dfs(v);
53         siz[u] += siz[v];
54     }
55 }
56 void build(string& s) {
57     n = s.size();
58     init(n);
59     for (int i = 0; i < n; i++) {
60         insert(s[i]);
61     }
62     construct();
63     dfs(1);
64 }
65 } sam;
66 }
67

```

## 回文自动机 PAM

```

1  #include<bits/stdc++.h>
2  using namespace std;
3  const int N=2e6+10;
4  struct PAM_Trie
5  {
6      int ch[26];
7      int fail,len,num;
8  };
9  struct PAM
10 {
11     PAM_Trie b[N];
12     int n,length,last,cnt;
13     char s[N];
14     PAM()
15     {
16         b[0].len = 0; b[1].len = -1;
17         b[0].fail = 1; b[1].fail = 0;
18         last = 0;
19         cnt = 1;
20     }
21     int get_fail(int x)
22     {
23         while(s[n-b[x].len-1]!=s[n])
24         {
25             x=b[x].fail;

```

```

26     }
27     return x;
28 }
29 void insert()
30 {
31     int p=get_fail(last);
32     if(!b[p].ch[s[n]-'a'])
33     {
34         b[++cnt].len=b[p].len+2;
35         int tmp=get_fail(b[p].fail);
36         b[cnt].fail=b[tmp].ch[s[n]-'a'];
37         b[cnt].num=b[b[cnt].fail].num+1;
38         b[p].ch[s[n]-'a']=cnt;
39     }
40     last=b[p].ch[s[n]-'a'];
41     cout<<last<<"\n";
42     //如果要统计出现次数 f[last]++;
43 }
44 void init()
45 {
46     length=strlen(s+1);
47     for(n=1;n<=length;n++)
48     {
49         insert();
50     }
51 }
52 }pa;
53 int main()
54 {
55     scanf("%s",pa.s+1);
56     pa.init();
57     return 0;
58 }

```

### 最小表示

```

1 int getMin(string s) {
2     int i = 0, j = 1, k = 0;
3     int len = s.length();
4     while(i<len && j<len && k<len) {
5         int tmp = s[(i + k) % len] - s[(j + k) % len];
6         if(tmp==0) k++;
7         else {
8             if(tmp>0) i += k + 1;
9             else j += k + 1;
10            if(i==j) j++;
11            k = 0;
12        }
13    }
14    return min(i, j);
15 }

```

### Runs

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 typedef long long ll;
4 struct Runs {

```

```

5     int l, r, p;
6 };
7 namespace RunsGetter {
8     const int N = 2e5 + 5;
9     using namespace std;
10    struct StrHash{
11        ll p[N],h[N];int mod,buf;
12        StrHash (int _buf,int _mod){buf=_buf;mod=_mod;}
13        void Init(char *s,int n)
14        {
15            p[0]=1;
16            for (int i=1;i<=n;i++){
17                p[i]=p[i-1]*buf%mod;
18                h[i]=(h[i-1]*buf+s[i] - 'a'+1)%mod;
19            }
20        }
21        bool tl(int u,int v,int len){
22            return (h[u]-h[v]+(h[v-len]-h[u-len])*p[len])%mod==0;
23        }
24        bool tr(int u,int v,int len){
25            return (h[u+len-1]-h[v+len-1]+(h[v-1]-h[u-1])*p[len])%mod==0;
26        }
27        int get(int l,int r){
28            return (h[r]+(mod-h[l-1])*p[r-l+1])%mod;
29        }
30    }h1(10,1000000007),h2(13,1000000009);
31    int n;char s[N];
32    int extl(int u,int v){
33        if (s[u]!=s[v])return 0;
34        int l=1,r=min(u,v),mid;
35        while(l<r){
36            mid=(l+r+1)>>1;
37            if (h1.tl(u,v,mid)&&h2.tl(u,v,mid))l=mid;
38            else r=mid-1;
39        }return l;
40    }
41    int extr(int u,int v)
42    {
43        if (s[u]!=s[v])return 0;
44        int l=1,r=n-max(u,v)+1,mid;
45        while(l<r){
46            mid=(l+r+1)>>1;
47            if (h1.tr(u,v,mid)&&h2.tr(u,v,mid))l=mid;
48            else r=mid-1;
49        }
50        return l;
51    }
52    Runs b[N*20];
53    bool cmpR(const Runs &A, const Runs &B)
54    {return A.l==B.l ? (A.r==B.r ? A.p<B.p : A.r<B.r) : A.l<B.l;}
55    int tot;
56    int chk(int u,int v)
57    {
58        int tl=extl(u,v),tr=extr(u,v);
59        if (tl+tr>=v-u+1){
60            b[++tot]=(Runs){u-tl+1,v+tr-1,v-u};

```



```

61         return v+tr-1;
62     }
63     return 0;
64 }
65 vector<Runs> getRuns(int n0, char* t0)
66 {
67     n=n0;
68     for(int i=1;i<=n0;i++)s[i]=t0[i];
69     h1.Init(s,n);h2.Init(s,n);
70     for (int p=1;p<=n;p++)
71         for (int k=p,mx=0;k+p<=n;k+=p)
72             if (mx<k)
73                 mx=max(mx,chk(k,k+p)-p);
74     sort(b+1,b+tot+1,cmpR);
75     int m=0;
76     for (int i=1;i<=tot;i++)
77         if (b[i].l!=b[i-1].l||b[i].r!=b[i-1].r)
78             b[++m]=b[i];
79     tot=m;
80     vector<Runs> e;
81     for(int i=1;i<=m;i++)e.push_back(b[i]);
82     return e;
83 }
84 }

```

## 图论

### Johnson 全源最短路

```
1 struct graph {
2     vector<vector<pair<int, ll>>> e;
3     graph(int n) : e(n + 1) {}
4     void adde(int u, int v, ll w) { e[u].push_back({v, w}); }
5     vector<ll> h;
6     // initialize h(u), return false if there exists a negative cycle
7     bool init() {
8         int n = e.size();
9         h.assign(n, 0);
10        queue<int> que;
11        for (int u = 1; u < n; u++) que.push(u);
12        vector<int> vis(n, 0), cnt(n, n + 1);
13        while (que.size()) {
14            auto u = que.front();
15            que.pop();
16            vis[u] = false;
17            if (!cnt[u]--) return false; // exists a negative cycle
18            for (auto &[v, w] : e[u])
19                if (h[v] > h[u] + w) {
20                    h[v] = h[u] + w;
21                    if (!vis[v]) que.push(v), vis[v] = 1;
22                }
23        }
24        return true;
25    }
26    // single source shortest path from given sink based on h(u)
27    vector<ll> query(int s) {
28        int n = e.size();
29        vector<ll> dis(n, inf);
30        priority_queue<pair<ll, int>, vector<pair<ll, int>>,
31            greater<pair<ll, int>>>
32            que;
33        que.push({dis[s] = 0, s});
34        while (que.size()) {
35            auto [du, u] = que.top();
36            que.pop();
37            if (dis[u] < du) continue;
38            for (auto [v, w] : e[u]) {
39                auto dv = du + w + h[u] - h[v];
40                if (dis[v] > dv) que.push({dis[v] = dv, v});
41            }
42        }
43        for (int i = 0; i < n; i++) dis[i] += h[i] - h[s];
44        return dis;
45    }
46 };
```

### Kosaraju

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 const int maxn = 100010;
4 vector<int> ve[maxn], ve2[maxn];
5 vector<int> sta; // 存第一次 dfs1() 的结果，即标记点的先后顺序，优先级小的点先进
```

```

6  int vis[maxn];    // vis[i]标记第一次 dfs1()点 i 是否访问过
7  int col[maxn];   // col[i]标记点 i 属于第几个强连通分量, 同时记录 dfs2()过程中点 i 是否访问过
8  int cnt;        // cnt 表示强连通分量的个数
9  void dfs1(int x){
10     vis[x] = 1;
11     for(auto it:ve[x])if(!vis[it])
12         dfs1(it);
13     sta.push_back(x); //记录点的先后顺序, 按照拓扑排序, 优先级大的放在 S 的后面
14 }
15
16 void dfs2(int x){
17     if(col[x])    return;
18     col[x] = cnt;
19     for(auto it:ve[x])if(!col[it])
20         dfs2(it);
21 }
22 void Kosaraju(int n) {
23     cnt = 0;
24     sta.clear();
25     memset(vis,0,sizeof(vis));
26     memset(col,0,sizeof(col));
27     for(int i=1; i<=n; i++) //搜索所有点
28         dfs1(i);
29     for(int i=n-1; i>=0; i--){
30         if(!col[sta[i]]){
31             cnt++;
32             dfs2(sta[i]);
33         }
34     }
35 }
36

```

## K 短路

```

1  //复杂度 nlogn +mlogm+klogk
2  #include <bits/stdc++.h>
3  #include <queue>
4
5  template <class T, class U>
6  inline bool smin(T &x, const U &y) {
7      return y < x ? x = y, 1 : 0;
8  }
9  template <class T, class U>
10 inline bool smax(T &x, const U &y) {
11     return x < y ? x = y, 1 : 0;
12 }
13
14 using LL = long long;
15 using PII = std::pair<int, int>;
16
17 constexpr int N(2.5e5 + 5);
18
19 using T = LL;
20 struct Edge {
21     int x, y; T z;
22 };
23 struct Heap {

```

```

24     struct Node {
25         int ls, rs, h, v;
26         T w;
27     } t[N * 40];
28     int cnt;
29     int newNode(int v, T w) {
30         t[++cnt] = {0, 0, 1, v, w};
31         return cnt;
32     }
33     int merge(int x, int y) {
34         if (!x) return y;
35         if (!y) return x;
36         if (t[x].w > t[y].w) std::swap(x, y);
37         t[++cnt] = t[x], x = cnt;
38         t[x].rs = merge(t[x].rs, y);
39         if (t[t[x].ls].h < t[t[x].rs].h) std::swap(t[x].ls, t[x].rs);
40         t[x].h = t[t[x].rs].h + 1;
41         return x;
42     }
43 } h;
44
45
46 std::vector<T> kShortestPath(int n, int k, int s, int t, const std::vector<Edge> &e) {
47     int m = e.size();
48     std::vector<int> deg(n + 1), g(m);
49     for (auto &[x, y, z] : e) deg[y]++;
50     for (int i = 1; i <= n; i++) deg[i] += deg[i - 1];
51     for (int i = 0; i < m; i++) g[--deg[e[i].y]] = i;
52
53     std::vector<T> d(n, -1);
54     std::vector<int> fa(n, -1), p;
55
56     using Q = std::pair<T, int>;
57     std::priority_queue<Q, std::vector<Q>, std::greater<Q>> q;
58
59     {
60         p.reserve(n);
61         d[t] = 0, q.push({0, t});
62
63         std::vector<bool> vis(n);
64         while (!q.empty()) {
65             int x = q.top().second;
66             q.pop();
67             if (vis[x]) continue;
68             vis[x] = true;
69             p.push_back(x);
70             for (int i = deg[x]; i < deg[x + 1]; i++) {
71                 auto &[y, _, z] = e[g[i]];
72                 if (d[y] == -1 || d[y] > d[x] + z) {
73                     d[y] = d[x] + z, fa[y] = g[i];
74                     q.push({d[y], y});
75                 }
76             }
77         }
78     }
79 }

```

```

80     if (d[s] == -1) std::vector<T>(k, -1);
81     std::vector<int> heap(n);
82     h.cnt = 0;
83     for (int i = 0; i < m; i++) {
84         auto &[x, y, z] = e[i];
85         if (d[x] != -1 && d[y] != -1 && fa[x] != i) {
86             heap[x] = h.merge(heap[x], h.newNode(y, d[y] + z - d[x]));
87         }
88     }
89
90     for (int x : p) {
91         if (x != t) heap[x] = h.merge(heap[x], heap[e[fa[x]].y]);
92     }
93
94     if (heap[s]) q.push({d[s] + h.t[heap[s]].w, heap[s]});
95     std::vector<T> res = {d[s]};
96
97     for (int i = 1; i < k && !q.empty(); i++) {
98         auto [w, o] = q.top();
99         q.pop();
100
101         res.push_back(w);
102
103         int j = h.t[o].v;
104         if (heap[j]) q.push({w + h.t[heap[j]].w, heap[j]});
105         for (auto s : {h.t[o].ls, h.t[o].rs}) {
106             if (s) q.push({w + h.t[s].w - h.t[o].w, s});
107         }
108     }
109     res.resize(k, -1);
110     return res;
111 }
112
113 int a[N];
114 void solve() {
115     int n, k;
116     std::cin >> n >> k;
117
118     std::vector<Edge> e;
119     for (int i = 1; i <= n; i++) {
120         std::cin >> a[i];
121     }
122     e.push_back({0, 1, a[1]});
123     for (int i = 2; i <= n; i++) {
124         if (i - 3 > 0) e.push_back({i - 3, i, a[i]});
125         e.push_back({i - 2, i, a[i]});
126         e.push_back({i - 1, i, a[i]});
127     }
128     if (n - 1 >= 1) e.push_back({n - 1, n + 1, 0});
129     e.push_back({n, n + 1, 0});
130
131     auto res = kShortestPath(n + 2, k, 0, n + 1, e);
132
133     for (auto x : res) std::cout << x << "\n";
134 }
135

```

```

136 int main() {
137     // freopen("t.in", "r", stdin);
138
139     std::ios::sync_with_stdio(false);
140     std::cin.tie(nullptr);
141
142     int t = 1;
143
144     // std::cin >> t;
145
146     while (t--) {
147         solve();
148     }
149     return 0;
150 }

```

### Maxflow 只算值版本

```

1 struct dinic{
2     struct E{
3         int to, cap, inv;
4     };
5     vector<E> g[N];
6     int dis[N], now[N];
7     void addedge(int u, int v, int w){
8         g[u].push_back({v, w, (int)g[v].size()});
9         g[v].push_back({u, 0, (int)g[u].size()-1});
10    }
11    void bfs(int st){
12        queue<int> q;
13        memset(dis, 0, sizeof dis);
14        q.push(st); dis[st]=1;
15        while(q.size()){
16            int u=q.front(); q.pop();
17            for(auto &[v, w, inv]:g[u]){
18                if(w&&!dis[v]){
19                    dis[v]=dis[u]+1;
20                    q.push(v);
21                }
22            }
23        }
24    }
25    int dfs(int u, int t, int flow){
26        if(u==t) return flow;
27        for(int &i=now[u], sz=g[u].size(), d; i<sz; i++){
28            auto &[v, w, inv]=g[u][i];
29            if(w&&dis[v]>dis[u]){
30                d=dfs(v, t, min(flow, w));
31                if(d>0){
32                    w-=d;
33                    g[v][inv].cap+=d;
34                    return d;
35                }
36            }
37        }
38        return 0;
39    }

```

```

40     int maxflow(int st,int ed){
41         for(int flow=0,res;;){
42             bfs(st);
43             if(!dis[ed])return flow;
44             memset(now,0,sizeof now);
45             while((res=dfs(st,ed,inf))>0){
46                 flow+=res;
47             }
48         }
49     }
50 };

```

## Maxflow 网络流最大流

```

1 // 用 givest 定源点汇点
2 // addedge 一次加了正反两条边
3 // init 慎用
4 // S 必须是 0
5 // 输出方案注意是 head 开头
6 #include <bits/stdc++.h>
7 using namespace std;
8 const int N=2510,M=2510*10;
9 class Maxflow{
10 private:
11     int nedge=1,p[2*M],nex[2*M],head[N],c[2*M],cur[2*M];
12     int dist[2*N];
13     int S,T;
14     void Addedge(int a,int b,int v){
15         p[++nedge]=b;nex[nedge]=head[a];head[a]=nedge;
16         c[nedge]=v;
17     }
18     bool bfs(){
19         queue<int>q;
20         for(int i=S;i<=T;i++)dist[i]=-1;
21         dist[S]=0;q.push(S);
22         while(!q.empty()){
23             int now=q.front();q.pop();
24             for(int k=head[now];k;k=nex[k])if(dist[p[k]]==-1&&c[k]>0){
25                 dist[p[k]]=dist[now]+1;
26                 q.push(p[k]);
27             }
28         }
29         return dist[T]>-1;
30     }
31     int dfs(int x,int low){
32         if(x==T)return low;
33         if(low==0)return 0;
34         int used=0;
35         for(int &k=cur[x];k;k=nex[k])if(dist[p[k]]==dist[x]+1&&c[k]>0){
36             int a=dfs(p[k],min(c[k],low-used));
37             c[k]-=a;c[k^1]+=a;used+=a;
38             if(low==used)break;
39         }
40         if(used==0)dist[x]=-1;
41         return used;
42     }
43 public:

```

```

44 void init(int s,int t){
45     for(int i=S;i<=T;i++)head[i]=0;
46     S=s,T=t;
47     nedge=1;
48 }
49 void addedge(int a,int b,int v){
50     Addedge(a,b,v);
51     Addedge(b,a,0);
52 }
53 int dinic(){
54     int flow=0;
55     while(bfs()){
56         for(int i=S;i<=T;i++)cur[i]=head[i];
57         flow+=dfs(S,1e9);
58     }
59     return flow;
60 }
61 };

```

## Tarjan 缩点

```

1 stack<int>s;
2 vector<int>ve[maxn];
3 int col[maxn],num,dfn[maxn],low[maxn],dfstime;
4 void tarjan(int u)
5 {
6     s.push(u);
7     dfn[u]=low[u]=++dfstime;
8     for(auto v:ve[u])
9     {
10         if(!dfn[v])
11         {
12             tarjan(v);
13             low[u]=min(low[u],low[v]);
14         }
15         else if(!col[v]) low[u]=min(low[u],dfn[v]);
16     }
17     if(dfn[u]==low[u])
18     {
19         col[u]=++num;
20         while(s.top()!=u)
21         {
22             col[s.top()]=num;
23             s.pop();
24         }
25         s.pop();
26     }
27 }

```

## 二分图匹配

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 int const N = 1510 * 4, M = 75010;
4 int e[M], ne[M], h[N], idx;
5 int n, m, k, match[N], backup[N], st[N];
6 void add(int a, int b) {
7     e[idx] = b, ne[idx] = h[a], h[a] = idx++;

```



```

8 }
9 int find(int x) {
10     for (int i = h[x]; ~i; i = ne[i]) {
11         int j = e[i];
12         if (!st[j]) {
13             st[j] = 1;
14             if (!match[j] || find(match[j])) {
15                 match[j] = x;
16                 return 1;
17             }
18         }
19     }
20     return 0;
21 }
22 int main() {
23     cin >> n >> m >> k;
24     memset(h, -1, sizeof h);
25     for (int i = 1, a, b; i <= k; ++i) {
26         scanf("%d%d", &a, &b);
27         add(a, b + n);
28     }
29     int maxMatch = 0;
30     for (int i = 1; i <= n; ++i) {
31         memset(st, 0, sizeof st);
32         if (find(i)) maxMatch++;
33     }
34     cout<<maxMatch<<endl;
35     return 0;
36 }
37

```

## 二分图最优匹配

```

1 #include<bits/stdc++.h>
2 using namespace std;
3 const int maxn=110;
4 int n, m;
5 int a[maxn][maxn];
6 int lx[maxn], ly[maxn], link[maxn];
7 bool vx[maxn], vy[maxn];
8 int dfs(int x)
9 {
10     if(x==-1)return 0;
11     vx[x] = 1;
12     for (int i = 1; i <= n; i++)
13     {
14         if (!vy[i] && lx[x] + ly[i] == a[x][i])
15         {
16             vy[i] = 1;
17             if (link[i] == -1 || dfs(link[i]))
18             {
19                 link[i] = x;
20                 return 1;
21             }
22         }
23     }
24     return 0;
25 }

```

```

25 }
26 bool deal()
27 {
28     memset(ly, 0, sizeof(ly));
29     memset(lx, 0xf7, sizeof(lx));
30     memset(link, -1, sizeof(link));
31     for (int i = 1; i <= n; i++)
32     {
33         for (int j = 1; j <= n; j++)
34             lx[i] = max(lx[i], a[i][j]);
35     }
36     for(int i = 1; i <= n; i++)
37     {
38         while(1)
39         {
40             memset(vx, 0, sizeof(vx));
41             memset(vy, 0, sizeof(vy));
42             if (dfs(i)) break;
43             int delta = 0x7f7f7f7f;
44             for (int j= 1; j <= n; j++)
45             {
46                 if (vx[j] == 1)
47                     for(int k = 1; k <= n; k++)
48                         if (vy[k] == 0) delta = min(delta, lx[j]+ ly[k]- a[j][k]);
49             }
50             if (delta == 0x7f7f7f7f) return 0;
51             for (int j= 1; j <= n; j++)
52                 if (vx[j] == 1) lx[j] -= delta;
53             for(int k = 1; k <= n; k++)
54                 if (vy[k] == 1) ly[k] += delta;
55         }
56     }
57     return 1;
58 }
59 int main()
60 {
61     if (deal() == 1) {
62         int ans = 0;
63         for(int i = 1; i <= n; i++)
64         {
65             ans += a[link[i]][i];
66         }
67         cout << ans << '\n'; //取最小就把所有边权取负再跑
68     }
69     return 0;
70 }

```

## 二分图染色

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int maxn=1010;
4 int n,m;
5 vector<int>ve[maxn];
6 int col[maxn][maxn],ans[maxn*2];
7 void dfs(int x,int y,int c1,int c2)
8 {

```

```

9     if(col[y][c1]){
10         dfs(y,col[y][c1],c2,c1);
11         col[x][c1]=y;
12         col[y][c1]=x;
13     }
14     else {
15         col[x][c1]=y;
16         col[y][c1]=x;
17         col[y][c2]=0;
18     }
19 }
20 map<pair<int,int>,int>ma;
21 int main()
22 {
23     ios::sync_with_stdio(false);
24     cin.tie(0);
25     cin>>n>>m;
26     int anss=0;
27     for(int i=1;i<=m;i++){
28         int x,y;
29         cin>>x>>y;
30         ve[x].push_back(y);
31         ma[{x,y}]=i;
32         int c1=1,c2=1;
33         while(col[x][c1])c1++;
34         while(col[y][c2])c2++;
35         anss=max({c1,c2,anss});
36         if(c1>c2){
37             swap(x,y);swap(c1,c2);
38         }
39         if(c1==c2){
40             col[x][c1]=y;
41             col[y][c1]=x;
42         }
43         else{
44             dfs(x,y,c1,c2);
45         }
46     }
47     cout<<anss<<"\n";
48     for(int i=1;i<=n;i++){
49         for(int j=1;j<=anss;j++)if(col[i][j])ans[ma[{i,col[i][j]}]]=j;
50     }
51     for(int i=1;i<=m;i++)cout<<ans[i]<<"\n";
52     return 0;
53 }

```

## 圆方树

```

1     vector<vector<int>> e1(n);
2     int cnt = n;
3
4     int now = 0;
5     vector<int> dfn(n, -1), low(n);
6     vector<int> stk;
7     function<void(int)> tarjan = [&](int u) {
8         stk.push_back(u);
9         dfn[u] = low[u] = now++;

```

```

10     for (auto v : ve[u]) {
11         if (dfn[v] == -1) {
12             tarjan(v);
13             low[u] = min(low[u], low[v]);
14             if (low[v] == dfn[u]) {
15                 e1.push_back({});
16                 int x;
17                 do {
18                     x = stk.back();
19                     stk.pop_back();
20                     e1[cnt].push_back(x);
21                 } while (x != v);
22                 e1[u].push_back(cnt);
23                 ++cnt;
24             }
25         } else {
26             low[u] = min(low[u], dfn[v]);
27         }
28     }
29 };
30 tarjan(0);

```

## 基环树

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int maxn=2e5+10;
4  /*
5  1 init
6  2 addedge
7  3 Get
8  */
9  struct Graph{
10     vector<int>ve[maxn];
11     int base[maxn],id[maxn];
12     bool Incircle[maxn];
13     vector<int> Circle;
14     int len=0;
15     int dep[maxn],f[21][maxn];
16     int n;
17     void init(int _n){
18         n=_n;
19         for(int i=1;i<=n;i++){
20             for(int j=0;j<21;j++)f[j][i]=0;
21             ve[i].clear();
22             Incircle[i]=false;
23             id[i]=-1;
24             base[i]=i;
25             Circle.clear();
26             len=0;
27             dep[i]=0;
28         }
29     }
30     void addedge(int x,int y){
31         ve[x].push_back(y);
32         ve[y].push_back(x);
33     }

```

```

34 void dfs(int x,int fa)
35 {
36     base[x]=base[fa];
37     dep[x]=dep[fa]+1;
38     for(int i=0;i<=19;i++)
39         f[i+1][x]=f[i][f[i][x]];
40     for(auto it:ve[x])
41     {
42         if(it==fa) continue;
43         f[0][it]=x;
44         dfs(it,x);
45     }
46 }
47 void Get(){
48     vector<int> sta;
49     vector<bool> vis(n+1,false);
50     function<bool(int,int)> dfs2 = [&](int x,int h){
51         vis[x]=true;
52         sta.push_back(x);
53         for(auto it:ve[x])if(it!=h){
54             if(vis[it]){
55                 Circle.push_back(it);
56                 while(!sta.empty()&&sta.back()!=it){
57                     Circle.push_back(sta.back());
58                     sta.pop_back();
59                 }
60                 return true;
61             }
62             else{
63                 if(dfs2(it,x))return true;
64             }
65         }
66         sta.pop_back();
67         return false;
68     };
69     dfs2(1,0);
70     len=(int)Circle.size();
71     for(auto it:Circle)Incircle[it]=true;
72     for(auto it:Circle){
73         for(auto it2:ve[it])if(!Incircle[it2]){
74             f[0][it2]=it;
75             dfs(it2,it);
76         }
77     }
78     for(int i=0;i<len;i++)id[Circle[i]]=i;
79 }
80 int lca(int x,int y)
81 {
82     if(dep[x]<dep[y]) swap(x,y);
83     for(int i=20;i>=0;i--)
84     {
85         if(dep[f[i][x]]>=dep[y]) x=f[i][x];
86         if(x==y) return x;
87     }
88     for(int i=20;i>=0;i--)
89         if(f[i][x]!=f[i][y])

```

```

90         x=f[i][x],y=f[i][y];
91     return f[0][x];
92 }
93 int dis(int x,int y){
94     if(base[x]==base[y]){
95         int l=lca(x,y);
96         return dep[x]+dep[y]-2*dep[l];
97     }
98     else{
99         int g=(id[base[x]]-id[base[y]]+len)%len;
100        return dep[x]+dep[y]+min(g,len-g);
101    }
102 }
103 };
104 Graph g;

```

### 带权并查集 dsu

```

1  const int maxn=1e5+10;
2  int f[maxn],dis[maxn];
3  int getf(int x){
4      if(x==f[x])return x;
5      int z=getf(f[x]);
6      dis[x]+=dis[f[x]];
7      return f[x]=z;
8  }
9  void unit(int i,int j,int len){
10     int x=getf(i),y=getf(j);
11     f[x]=y;
12     //在赋值之前因为 x 是头节点所以 dis 一定等于 0
13     dis[x]=dis[j]-dis[i]+len;
14 }

```

### 带花树

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  struct blossom { // 0base
4      int n, vis_t;
5      vector<vector<int>> E;
6      vector<int> match, label, org, vis, parent;
7      queue<int> Q;
8      blossom(int _n) {
9          n = _n;
10         E = vector<vector<int>>(n, vector<int>());
11         match.assign(n, -1);
12         label.resize(n);
13         org.resize(n);
14         iota(org.begin(), org.end(), 0);
15         parent.assign(n, -1);
16         vis.assign(n, 0);
17         vis_t = 0;
18     }
19     void addEdge(int u, int v) {
20         E[u].emplace_back(v);
21         E[v].emplace_back(u);
22     }
23     auto lca(int v, int u) {

```

```

24     vis_t++;
25     while (true) {
26         if (v != -1) {
27             if (vis[v] == vis_t) {
28                 return v;
29             }
30             vis[v] = vis_t;
31             if (match[v] == -1) {
32                 v = -1;
33             } else {
34                 v = org[parent[match[v]]];
35             }
36         }
37         swap(v, u);
38     }
39 }
40 void agument(int v) {
41     while (v != -1) {
42         auto pv = parent[v];
43         auto nxt = match[pv];
44         match[v] = pv;
45         match[pv] = v;
46         v = nxt;
47     }
48 }
49 void flower(int v, int u, int a) {
50     while (org[v] != a) {
51         parent[v] = u;
52         u = match[v];
53         if (label[u] == 1) {
54             label[u] = 0;
55             Q.emplace(u);
56         }
57         org[v] = org[u] = a;
58         v = parent[u];
59     }
60 }
61 auto bfs(int root) {
62     fill(label.begin(), label.end(), -1);
63     iota(org.begin(), org.end(), 0);
64     while (!Q.empty()) {
65         Q.pop();
66     }
67     Q.emplace(root);
68     label[root] = 0;
69     while (!Q.empty()) {
70         auto u = Q.front();
71         Q.pop();
72         for (auto v : E[u]) {
73             if (label[v] == -1) {
74                 label[v] = 1;
75                 parent[v] = u;
76                 if (match[v] == -1) {
77                     agument(v);
78                     return true;
79                 }

```

```

80         label[match[v]] = 0;
81         Q.push(match[v]);
82         continue;
83     } else if (label[v] == 0 && org[v] != org[u]) {
84         auto a = lca(org[u], org[v]);
85         flower(v, u, a);
86         flower(u, v, a);
87     }
88 }
89 }
90 return false;
91 }
92 void solve() {
93     for (int i = 0; i < n; ++i) {
94         if (match[i] == -1) {
95             bfs(i);
96         }
97     }
98 }
99 };
100 int main()
101 {
102     blossom G(n);
103     for (int i = 0; i < n; ++i) {
104         for (int j = i + 1; j < n; ++j) {
105             auto [xi, yi] = stone[i];
106             auto [xj, yj] = stone[j];
107             if (abs(xi - xj) + abs(yi - yj) <= L) {
108                 G.addEdge(i, j);
109             }
110         }
111     }
112     G.solve();
113     int num = 0;
114     for (int i = 0; i < n; ++i) {
115         if (G.match[i] != -1) {
116             num++;
117         }
118     }
119 }

```

### 带负环最小费用最大流

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int N = 200 + 5, M = 2e4 + N;
4  struct flow {
5      int cnt = 1, hd[N], nxt[M << 1], to[M << 1], limit[M << 1], cst[M << 1];
6      void add(int u, int v, int w, int c) {
7          nxt[++cnt] = hd[u], hd[u] = cnt, to[cnt] = v, limit[cnt] = w, cst[cnt] = c;
8          nxt[++cnt] = hd[v], hd[v] = cnt, to[cnt] = u, limit[cnt] = 0, cst[cnt] = -c;
9      }
10     int fl[N], fr[N], dis[N], in[N];
11     pair<int, int> mincost(int s, int t) {
12         int flow = 0, cost = 0;
13         while (1) {
14             queue<int> q;

```



```

15     memset(dis, 0x3f, sizeof(dis));
16     q.push(s), fl[s] = 1e9, dis[s] = 0;
17     while (!q.empty()) {
18         int t = q.front();
19         q.pop(), in[t] = 0;
20         for (int i = hd[t]; i; i = nxt[i]) {
21             int it = to[i], d = dis[t] + cst[i];
22             if (limit[i] && d < dis[it]) {
23                 dis[it] = d, fl[it] = min(fl[t], limit[i]), fr[it] = i;
24                 if (!in[it]) in[it] = 1, q.push(it);
25             }
26         }
27     }
28     if (dis[t] > 1e9) return make_pair(flow, cost);
29     flow += fl[t], cost += dis[t] * fl[t];
30     for (int u = t; u != s; u = to[fr[u] ^ 1])
31         limit[fr[u]] -= fl[t], limit[fr[u] ^ 1] += fl[t];
32 }
33 }
34 };
35 struct bounded_flow {
36     int e, u[M], v[M], lo[M], hi[M], cst[M];
37     void add(int _u, int _v, int w, int c) {
38         if (c < 0) {
39             u[++e] = _u, v[e] = _v, lo[e] = w, hi[e] = w, cst[e] = c;
40             u[++e] = _v, v[e] = _u, lo[e] = 0, hi[e] = w, cst[e] = -c;
41         } else
42             u[++e] = _u, v[e] = _v, lo[e] = 0, hi[e] = w, cst[e] = c;
43     }
44     flow g;
45     pair<int, int> mincost(int n, int s, int t, int ss, int tt) {
46         static int w[N];
47         memset(w, 0, sizeof(w));
48         int flow = 0, cost = 0, tot = 0;
49         for (int i = 1; i <= e; i++) {
50             w[u[i]] -= lo[i], w[v[i]] += lo[i];
51             cost += lo[i] * cst[i];
52             g.add(u[i], v[i], hi[i] - lo[i], cst[i]);
53         }
54         for (int i = 1; i <= n; i++)
55             if (w[i] > 0)
56                 g.add(ss, i, w[i], 0), tot += w[i];
57             else if (w[i] < 0)
58                 g.add(i, tt, -w[i], 0);
59         g.add(t, s, 1e9, 0);
60         pair<int, int> res = g.mincost(ss, tt);
61         cost += res.second;
62         flow += g.limit[g.hd[s]];
63         g.hd[s] = g.nxt[g.hd[s]], g.hd[t] = g.nxt[g.hd[t]];
64         res = g.mincost(s, t);
65         return make_pair(flow + res.first, cost + res.second);
66     }
67 } f;
68 int n, m, s, t;
69 int main() {
70     cin >> n >> m >> s >> t;

```

```

71     for (int i = 1; i <= m; i++) {
72         int u, v, w, c;
73         cin >> u >> v >> w >> c, f.add(u, v, w, c);
74     }
75     pair<int, int> res = f.mincost(n, s, t, 0, n + 1);
76     cout << res.first << " " << res.second << endl;
77     return 0;
78 }
79

```

## 支配树

```

1  /*
2  lbase
3  注意 up 是数组需要外界导入
4  使用的时候直接 dtree::即可
5  */
6  namespace dtree{
7      const int MAXN = 200020;
8      vector<int> E[MAXN], RE[MAXN], rdom[MAXN];
9
10     int S[MAXN], RS[MAXN], cs;
11     int par[MAXN], val[MAXN], sdom[MAXN], rp[MAXN], dom[MAXN];
12
13     void clear(int n) {
14         cs = 0;
15         for(int i=0;i<=n;i++) {
16             par[i] = val[i] = sdom[i] = rp[i] = dom[i] = S[i] = RS[i] = 0;
17             E[i].clear(); RE[i].clear(); rdom[i].clear();
18         }
19     }
20     void add_edge(int x, int y) { E[x].push_back(y); }
21     void Union(int x, int y) { par[x] = y; }
22     int Find(int x, int c = 0) {
23         if(par[x] == x) return c ? -1 : x;
24         int p = Find(par[x], 1);
25         if(p == -1) return c ? par[x] : val[x];
26         if(sdom[val[x]] > sdom[val[par[x]]]) val[x] = val[par[x]];
27         par[x] = p;
28         return c ? p : val[x];
29     }
30     void dfs(int x) {
31         RS[ S[x] = ++cs ] = x;
32         par[cs] = sdom[cs] = val[cs] = cs;
33         for(int e : E[x]) {
34             if(S[e] == 0) dfs(e), rp[S[e]] = S[x];
35             RE[S[e]].push_back(S[x]);
36         }
37     }
38     int solve(int s, int *up) { //s 是起点
39         dfs(s);
40         for(int i=cs;i;i--) {
41             for(int e : RE[i]) sdom[i] = min(sdom[i], sdom[Find(e)]);
42             if(i > 1) rdom[sdom[i]].push_back(i);
43             for(int e : rdom[i]) {
44                 int p = Find(e);
45                 if(sdom[p] == i) dom[e] = i;

```

```

46     else dom[e] = p;
47 }
48 if(i > 1) Union(i, rp[i]);
49 }
50 for(int i=2;i<=cs;i++) if(sdom[i] != dom[i]) dom[i] = dom[dom[i]];
51 for(int i=2;i<=cs;i++) up[RS[i]] = RS[dom[i]];
52 return cs;
53 }
54 }

```

### 最小环

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int maxn=1e2+10;
4  const int inf=2e7+10;
5  int a[maxn][maxn],b[maxn][maxn];
6  int main()
7  {
8      int n;cin>>n;
9      int m;cin>>m;
10     for(int i=1;i<=n;i++){
11         for(int j=1;j<=n;j++){
12             a[i][j]=b[i][j]=inf;
13             a[i][i]=b[i][i]=0;
14         }
15     }
16     while(m--){
17         int x,y;cin>>x>>y;
18         int w;cin>>w;
19         a[x][y]=min(a[x][y],w);
20         a[y][x]=min(a[y][x],w);
21         b[x][y]=min(b[x][y],w);
22         b[y][x]=min(b[y][x],w);
23     }
24     int ans=inf;
25     for(int i=1;i<=n;i++){
26         for(int j=1;j<i;j++){
27             for(int k=j+1;k<i;k++){
28                 ans=min(ans,a[i][j]+a[i][k]+b[j][k]);
29             }
30         }
31     }
32     for(int j=1;j<=n;j++){
33         for(int k=1;k<=n;k++){
34             b[j][k]=min(b[j][i]+b[i][k],b[j][k]);
35         }
36     }
37     if(ans==inf)cout<<"No solution.";
38     else cout<<ans;
39 }

```

### 最小费用最大流

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int N=1e4,M=1e6;
4  struct SSP {
5      int cnt = 1, hd[N], nxt[M << 1], to[M << 1], limit[M << 1], cst[M << 1];
6      void init(){
7          memset(hd,0,sizeof(hd));
8          cnt=1;

```

```

9     }
10    // w limit c cost
11    void add(int u, int v, int w, int c) {
12        nxt[++cnt] = hd[u], hd[u] = cnt, to[cnt] = v, limit[cnt] = w, cst[cnt] = c;
13        nxt[++cnt] = hd[v], hd[v] = cnt, to[cnt] = u, limit[cnt] = 0, cst[cnt] = -c;
14    }
15
16    int fr[N], fl[N], in[N], dis[N];
17
18    pair<int, int> min_cost(int s, int t) {
19        int flow = 0, cost = 0;
20        while (true) { // SPFA
21            queue<int> q;
22            memset(dis, 0x3f, sizeof(dis));
23            memset(in, 0, sizeof(in));
24            fl[s] = 1e9, dis[s] = 0, q.push(s);
25            while (!q.empty()) {
26                int cur = q.front();
27                q.pop(), in[cur] = 0;
28                for (int i = hd[cur]; i; i = nxt[i]) {
29                    int it = to[i], d = dis[cur] + cst[i];
30                    if (limit[i] && d < dis[it]) {
31                        fl[it] = min(limit[i], fl[cur]), fr[it] = i, dis[it] = d;
32                        if (!in[it]) in[it] = 1, q.push(it);
33                    }
34                }
35            }
36            if (dis[t] > 1e9) return {flow, cost}; //改成>0 就是可行流
37            flow += fl[t], cost += dis[t] * fl[t];
38            for (int u = t; u != s; u = to[fr[u] ^ 1]) limit[fr[u]] -= fl[t],
limit[fr[u] ^ 1] += fl[t];
39        }
40    }
41 } Sol;

```

## 欧拉回路

```

1  #include<bits/stdc++.h>
2  using namespace std;
3  const int M=2333,N=666;
4  struct edge
5  {
6      int nxt,to;
7  }e[M<<1];
8  int head[N],tot=1;
9  int cut[M<<1];
10 void add(int u,int v)
11 {
12     e[++tot]=(edge){head[u],v},head[u]=tot;
13     e[++tot]=(edge){head[v],u},head[v]=tot;
14 }
15 vector<int> st;
16 void dfs(int u)//欧拉回路
17 {
18     for(int i=head[u];i!=0;i=e[i].nxt)
19     {
20         if(cut[i]) continue;

```

```

21     int v=e[i].to;
22     cut[i]=cut[i^1]=1;
23     dfs(v);
24 }
25 st.push(u);
26 }
27 int main()
28 {
29
30
31     return 0;
32 }
33

```

### 三四元环计数

```

1  #include<bits/stdc++.h>
2  using namespace std;
3  const int mod=1e9+7;
4  void add(int &x,int y){
5      if((x+=y)>=mod)x-=mod;
6  }
7  void solve(){
8      int ans3=0,ans4=0;
9      int n,m;cin>>n>>m;
10     vector<pair<int,int>> edges(m);
11     vector<int>d(n+1),flg(n+1),id(n+1),rk(n+1),c(n+1);
12     vector<vector<int>> ve(n+1),f(n+1),g(n+1);
13     for(int i=0;i<m;i++){
14         int u,v;cin>>u>>v;
15         edges[i]=make_pair(u,v);
16         ve[u].push_back(v);
17         ve[v].push_back(u);
18     }
19     for(int i=1;i<=n;i++)
20         d[id[i]=i]=(int)ve[i].size();
21     for(auto [u,v]:edges){
22         if(d[u]>d[v]||(d[u]==d[v]&&u>v))g[u].push_back(v);
23         else g[v].push_back(u);
24     }
25     sort(id.begin()+1,id.end(),[&](int x,int y){
26         return d[x]<d[y];
27     });
28     for(int i=1;i<=n;i++)rk[id[i]]=i;
29     for(int u=1;u<=n;u++)for(auto v:ve[u])
30         if(rk[v]>rk[u])f[u].push_back(v);
31     for(int u=1,C=0;u<=n;u++){
32         for(auto v:ve[u])for(auto w:f[v])if(rk[w]>rk[u])add(ans4,c[w]),++c[w];
33         for(auto v:ve[u])for(auto w:f[v])if(rk[w]>rk[u])c[w]=0;
34         ++C;
35         for(auto v:g[u])flg[v]=C;
36         for(auto v:g[u])
37             for(auto w:g[v])add(ans3,(flg[w]==C));
38     }
39     cout<<ans3<<" "<<ans4<<endl;
40 }
41 /*

```

```
42 5 7
43 1 2
44 2 3
45 4 2
46 5 1
47 1 4
48 3 5
49 3 1
50
51 ans3=3 ans4=2
52 */
```

## 数据结构

### SegmentSet

```
1  /*
2  every pair of pair<int,int> will not intersect
3  if i is true then it will be in the set
4  */
5  struct SegmentSet{
6      set<pair<int,int>>s;
7      void write(){
8          for(auto [x,y]:s)cout<<x<<"/"<<y<<" ";cout<<"\n";
9      }
10     //make l...r to be true
11     void insert(int l,int r)
12     {
13         int L=l,R=r;
14         auto it=s.lower_bound(make_pair(L,(int)-2e9));
15         while(it!=s.end()&&it->first<=R+1){
16             R=max(it->second,R);
17             it=s.erase(it);
18         }
19         if(it!=s.begin()){
20             it--;
21             if(it->second+1>=L){
22                 L=min(L,it->first);
23                 R=max(R,it->second);
24                 s.erase(it);
25             }
26         }
27         s.insert(make_pair(L,R));
28     }
29     // if l...r all true return false
30     bool query_no_full(int l,int r){
31         auto it=s.lower_bound(make_pair(l,(int)-2e9));
32         if(it!=s.end()){
33             if(l==it->first&&r<=it->second)return false;
34         }
35         if(it!=s.begin()){
36             it--;
37             if(it->second>=r)return false;
38         }
39         return true;
40     }
41     //make l...r to be false
42     void del(int l,int r){
43         auto it=s.lower_bound(make_pair(l,(int)-2e9));
44         while(it!=s.end()&&it->first<=r){
45             if(it->second<=r){
46                 it=s.erase(it);continue;
47             }
48             int R=it->second;
49             s.erase(it);
50             s.insert(make_pair(r+1,R));
51             break;
52         }
53         it=s.lower_bound(make_pair(l,(int)-2e9));
```

```

54     if(it!=s.begin()){
55         it--;
56         int L=it->first,R=it->second;
57         if(R>=l){
58             s.erase(it);
59             if(L<=l-1)s.insert(make_pair(L,l-1));
60             if(R>=r+1)s.insert(make_pair(r+1,R));
61         }
62     }
63 }
64 // if l...r all false return false
65 bool query_at_least_one(int l,int r){
66     auto it=s.lower_bound(make_pair(l,(int)-2e9));
67     if(it!=s.end()){
68         if(it->first<=r)return true;
69     }
70     if(it!=s.begin()){
71         it--;
72         if(it->second>=l)return true;
73     }
74     return false;
75 }
76 };

```

## SegmentTree

```

1  //??????????? ???????>=?sum??????
2  #include <bits/stdc++.h>
3  using namespace std;
4  const int maxn=1e6+10;
5  struct Node{
6      int l,r,res,tag;
7  };
8  struct SegmentTree{
9      Node a[maxn*4];
10     void tag_init(int i){
11         a[i].tag=0;
12     }
13     void tag_union(int fa,int i){
14         a[i].tag+=a[fa].tag;
15     }
16     void tag_cal(int i){
17         a[i].res+=a[i].tag*(a[i].r-a[i].l+1);
18     }
19     void pushdown(int i){
20         tag_cal(i);
21         if(a[i].l!=a[i].r){
22             tag_union(i,i*2);
23             tag_union(i,i*2+1);
24         }
25         tag_init(i);
26     }
27     void pushup(int i){
28         if(a[i].l==a[i].r)return;
29         pushdown(i*2);
30         pushdown(i*2+1);
31         a[i].res=a[i*2].res+a[i*2+1].res;

```



```

32     }
33     void build(int i,int l,int r){
34         a[i].l=l,a[i].r=r;tag_init(i);
35         if(l>=r)return;
36         int mid=(l+r)/2;
37         build(i*2,l,mid);
38         build(i*2+1,mid+1,r);
39     }
40     void update(int i,int l,int r,int w){
41         pushdown(i);
42         if(a[i].r<l||a[i].l>r||l>r)return;
43         if(a[i].l>=l&&a[i].r<=r){
44             a[i].tag=w;
45             return;
46         }
47         update(i*2,l,r,w);
48         update(i*2+1,l,r,w);
49         pushup(i);
50     }
51     int query(int i,int l,int r){
52         pushdown(i);
53         if(a[i].r<l||a[i].l>r||l>r)return 0;
54         if(a[i].l>=l&&a[i].r<=r){
55             return a[i].res;
56         }
57         return query(i*2,l,r)+query(i*2+1,l,r);
58     }
59     int min_right(int qL, int& nowsum,int querysum, int i) {//???????>=sum???
60         pushdown(i);
61         if (a[i].r < qL)return -1;
62         if (qL <= a[i].l) {
63             int ss = nowsum+a[i].res;
64             if (ss<querysum) {
65                 nowsum = ss;
66                 return -1;
67             }
68             if (a[i].l == a[i].r)return a[i].l;
69         }
70         int pos = min_right(qL, nowsum,querysum,i*2);
71         if (pos != -1)return pos;
72         return min_right(qL, nowsum,querysum,2*i+1);
73     }
74     int max_left(int qR,int &nowsum,int querysum,int i){//???????>=sum???
75         pushdown(i);
76         if(a[i].l > qR)return -1;
77         if(qR>=a[i].r){
78             int ss=nowsum+a[i].res;
79             if(ss<querysum){
80                 nowsum=ss;
81                 return -1;
82             }
83             if(a[i].l==a[i].r)return a[i].r;
84         }
85         int pos=max_left(qR,nowsum,querysum,i*2+1);
86         if(pos!=-1)return pos;
87         return max_left(qR,nowsum,querysum,i*2);

```

```

88     }
89 };
90 SegmentTree tri;
91 int main()
92 {
93     ios::sync_with_stdio(false);
94     cin.tie(0);
95     int n,q;cin>>n>>q;
96     tri.build(1,1,n);
97     for(int i=1;i<=n;i++){
98         int x;cin>>x;tri.update(1,i,i,x);
99     }
100     while(q--){
101         int ops;cin>>ops;
102         if(ops==1){
103             int l,r,x;cin>>l>>r>>x;
104             tri.update(1,l,r,x);
105         }
106         if(ops==2){
107             int l,r;cin>>l>>r;
108             cout<<tri.query(1,l,r)<<"\n";
109         }
110         if(ops==3){
111             int x,sum;cin>>x>>sum;
112             int nowsum=0;
113             cout<<tri.min_right(x,nowsum,sum,1)<<"\n";
114         }
115         if(ops==4){
116             int x,sum;cin>>x>>sum;
117             int nowsum=0;
118             cout<<tri.max_left(x,nowsum,sum,1)<<"\n";
119         }
120     }
121 }
122

```

### 三维偏序 **cdq**

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int maxn=4e5+10;
4  struct Treearray{
5      int c[maxn],n;
6      void set_n(int _n){
7          n=_n;
8          for(int i=1;i<=n;i++)c[i]=0;
9      }
10     int lowbit(int x){
11         return x&(-x);
12     }
13     void update(int i,int k){    //在 i 位置加上 k
14         while(i <= n){
15             c[i] += k;
16             i += lowbit(i);
17         }
18     }
19     int getsum(int i){          //求 A[1 - i]的和

```

```

20     int res = 0;
21     while(i > 0){
22         res += c[i];
23         i -= lowbit(i);
24     }
25     return res;
26 }
27 };
28 Treearray tri;
29 int a[maxn],b[maxn],c[maxn];
30 int n,k;
31 int ans[maxn],id[maxn],cnt[maxn],t[maxn];
32 void subdiv(int l,int r){
33     if(l==r)return;
34     int mid=(l+r)/2;
35     subdiv(l,mid);
36     subdiv(mid+1,r);
37     sort(id+l,id+mid+1,[](int x,int y){
38         if(b[x]==b[y])return c[x]<c[y];
39         return b[x]<b[y];
40     });
41     sort(id+mid+1,id+r+1,[](int x,int y){
42         if(b[x]==b[y])return c[x]<c[y];
43         return b[x]<b[y];
44     });
45
46     // for(int i=l;i<=r;i++)cout<<id[i]<<" \n"[i==r];
47     assert(tri.getsum(tri.n)==0);
48     for(int i=l,j=mid+1;i<=mid||j<=r;){
49         if(j!=r+1&&(i==mid+1||b[id[i]]>b[id[j]])){
50             // cout<<"id="<<id[j]<<" +"<<tri.getsum(c[id[j]])<<"\n";
51             ans[id[j]]+=tri.getsum(c[id[j]]);
52             j++;
53         }
54         else{
55             tri.update(c[id[i]],t[id[i]]);
56             i++;
57         }
58     }
59     for(int i=l;i<=mid;i++)tri.update(c[id[i]],-t[id[i]]);
60 }
61 int main()
62 {
63     ios::sync_with_stdio(false);
64     cin.tie(0);
65     cin>>n>>k;
66     tri.set_n(200000);
67     vector<tuple<int,int,int>> v(n);
68     for(int i=0;i<n;i++){
69         int x,y,z;cin>>x>>y>>z;v[i]=make_tuple(x,y,z);
70     }
71     sort(v.begin(),v.end());
72     int g=0;
73     for(int i=0;i<n;i++){
74         int j=i;
75         while(j+1<n&&v[i]==v[j+1])j++;

```

```

76     g++;
77     a[g]=get<0>(v[i]);
78     b[g]=get<1>(v[i]);
79     c[g]=get<2>(v[i]);
80     t[g]=j-i+1;
81     i=j;
82     // cout<<"g="<<g<<" "<<a[g]<<" "<<b[g]<<" "<<c[g]<<"\n";
83 }
84 for(int i=1;i<=g;i++)id[i]=i;
85 subdiv(1,g);
86 for(int i=1;i<=g;i++){
87     cnt[ans[i]+t[i]-1]+=t[i];
88     // cout<<"i="<<i<<" ans="<<ans[i]<<"\n";
89 }
90 for(int i=0;i<n;i++)cout<<cnt[i]<<"\n";
91 return 0;
92 }
93

```

## 主席树

```

1 //注意 Sum 和 cnt 的区别
2 #include <bits/stdc++.h>
3 using namespace std;
4 const int maxn = 1e5; // 数据范围
5 int n, m;
6 struct Persistent_SegmentTree
7 {
8     int sum[(maxn << 5) + 10], root[maxn + 10], lch[(maxn << 5) + 10],
9         rch[(maxn << 5) + 10], cnt[(maxn<<5)+10];
10    int tot = 0;
11    void init()
12    {
13        tot = 0;
14    }
15    int a[maxn + 10];
16    void update(int &rot, int pr, int L, int R, int k)
17    { // 插入操作
18        rot = ++tot;
19        lch[rot] = lch[pr];
20        rch[rot] = rch[pr];
21        sum[rot] = sum[pr] + k;
22        cnt[rot] = cnt[pr] + 1;
23        if (L == R)
24            return;
25        int mid = (L + R) >> 1;
26        if (k <= mid)
27            update(lch[rot], lch[pr], L, mid, k);
28        else
29            update(rch[rot], rch[pr], mid + 1, R, k);
30    }
31    int getcnt(int s, int t, int L, int R, int l, int r) // s,t 为 root[l],root[r]的根
    节点 中所有大小在[l,r]之间数字出现次数
32    {
33        if (l <= L && R <= r)
34            return cnt[t] - cnt[s];
35        int res = 0;

```

```

36     int mid = (L + R) >> 1;
37     if (l <= mid)
38         res += getcnt(lch[s], lch[t], L, mid, l, r);
39     if (r > mid)
40         res += getcnt(rch[s], rch[t], mid + 1, R, l, r);
41     return res;
42 }
43
44 int getsum(int s, int t, int L, int R, int l, int r) // s,t为 root[l],root[r]的根
    节点 中所有大小在 [l,r] 之间数字的和
45 {
46     if (l <= L && R <= r)
47         return sum[t] - sum[s];
48     int res = 0;
49     int mid = (L + R) >> 1;
50     if (l <= mid)
51         res += getsum(lch[s], lch[t], L, mid, l, r);
52     if (r > mid)
53         res += getsum(rch[s], rch[t], mid + 1, R, l, r);
54     return res;
55 }
56 int get_Kth_min_Sum(int s,int t,int l,int r,int k,int &nowsum,int &ans){//return
    第 k 小的值
57     int ss = nowsum+cnt[t]-cnt[s];
58     if (ss<k) {
59         nowsum = ss;
60         ans+=sum[t]-sum[s];
61         return -1;
62     }
63     if (l == r){
64         ans+=(k-nowsum)*l;
65         return l;
66     }
67     int mid=(l+r)/2;
68     int pos = get_Kth_min_Sum(lch[s],lch[t],l,mid,k,nowsum,ans);
69     if (pos != -1)return pos;
70     return get_Kth_min_Sum(rch[s],rch[t],mid+1,r,k,nowsum,ans);
71 }
72 int get_Kth_max_Sum(int s,int t,int l,int r,int k,int &nowsum,int &ans){//return
    第 k 大的值
73     int ss = nowsum+cnt[t]-cnt[s];
74     if (ss<k) {
75         nowsum = ss;
76         ans+=sum[t]-sum[s];
77         return -1;
78     }
79     if (l == r){
80         ans+=(k-nowsum)*l;
81         return l;
82     }
83     int mid=(l+r)/2;
84     int pos = get_Kth_max_Sum(rch[s],rch[t],mid+1,r,k,nowsum,ans);
85     if (pos != -1)return pos;
86     return get_Kth_max_Sum(lch[s],lch[t],l,mid,k,nowsum,ans);
87 }
88 int get_upper(int s,int t,int l,int r,int x){//第一个大于等于 x 的数

```

```

89     if (r < x) return -1;
90     if (x <= l) {
91         int ss = cnt[t]-cnt[s];
92         if (ss==0) {
93             return -1;
94         }
95         if (l == r) return l;
96     }
97     int mid=(l+r)/2;
98     int pos = get_upper(lch[s],lch[t],l,mid,x);
99     if (pos != -1) return pos;
100    return get_upper(rch[s],rch[t],mid+1,r,x);
101 }
102 int get_lower(int s,int t,int l,int r,int x){//第一个小于等于 x 的数
103     if(l > x) return -1;
104     if(x>=r){
105         int ss=cnt[t]-cnt[s];
106         if(ss==0){
107             return -1;
108         }
109         if(l==r) return r;
110     }
111     int mid=(l+r)/2;
112     int pos=get_lower(rch[s],rch[t],mid+1,r,x);
113     if(pos!=-1) return pos;
114     return get_lower(lch[s],lch[t],l,mid,x);
115 }
116 };
117 Persistent_SegmentTree tri;
118 int main()
119 {
120     int n,q;
121     cin >> n >> q;
122
123     for (int i = 1; i <= n; i++)
124     {
125         int x;
126         cin >> x;
127         tri.update(tri.root[i], tri.root[i - 1], 1, n, x);
128         assert(1<=x&&x<=n);
129     }
130     while (q--)
131     {
132         int ops;cin>>ops;
133         int l,r,k,L,R;
134         if(ops==1){
135             cin>>l>>r>>L>>R;
136             cout<<tri.getsum(tri.root[l-1],tri.root[r],1,n,L,R)<<"\n";
137         }
138         if(ops==2){// get kth max no output -1
139             cin>>l>>r>>k;
140             int nowsum=0,ans=0;
141             cout<<tri.get_Kth_max_Sum(tri.root[l-1],tri.root[r],1,n,k,nowsum,ans)<<"\n";
142         }
143         if(ops==3){// get kth max sum siz<k return allsum
144             cin>>l>>r>>k;

```

```

145         int nowsum=0,ans=0;
146         tri.get_Kth_max_Sum(tri.root[l-1],tri.root[r],1,n,k,nowsum,ans);
147         cout<<ans<<"\n";
148     }
149     if(ops==4){// get kth min no output -1
150         cin>>l>>r>>k;
151         int nowsum=0,ans=0;
152         cout<<tri.get_Kth_min_Sum(tri.root[l-1],tri.root[r],1,n,k,nowsum,ans)<<"\n";
153     }
154     if(ops==5){// get kth min sum siz<k return allsum
155         cin>>l>>r>>k;
156         int nowsum=0,ans=0;
157         tri.get_Kth_min_Sum(tri.root[l-1],tri.root[r],1,n,k,nowsum,ans);
158         cout<<ans<<"\n";
159     }
160     if(ops==6){// get the min element >= k no return -1
161         cin>>l>>r>>k;
162         cout<<tri.get_upper(tri.root[l-1],tri.root[r],1,n,k)<<"\n";
163     }
164     if(ops==7){// get the max element <= k no return -1
165         cin>>l>>r>>k;
166         cout<<tri.get_lower(tri.root[l-1],tri.root[r],1,n,k)<<"\n";
167     }
168 }
169 }

```

## 二维树状数组

```

1  const int maxn=1010;
2  struct treearray{
3      int mkp1[maxn][maxn],mkp2[maxn][maxn],mkp3[maxn][maxn],mkp4[maxn][maxn];
4      inline int lowbit(int x)
5      {
6          return x&(-x);
7      }
8      inline void Update(int x,int y,int k)
9      {
10         for(int i=x;i<=n;i+=lowbit(i))
11         {
12             for(int j=y;j<=m;j+=lowbit(j))
13             {
14                 mkp1[i][j]+=k;
15                 mkp2[i][j]+=k*x;
16                 mkp3[i][j]+=k*y;
17                 mkp4[i][j]+=k*x*y;
18             }
19         }
20     }
21     inline void update(int a,int b,int x,int y,int k)
22     {
23         Update(a,b,k);
24         Update(a,y+1,-k);
25         Update(x+1,b,-k);
26         Update(x+1,y+1,k);
27     }
28     inline int Query(int x,int y)
29     {

```

```

30     int ans=0;
31     for(int i=x;i>=1;i-=lowbit(i))
32     {
33         for(int j=y;j>=1;j-=lowbit(j))
34         {
35             ans+=(x+1)*(y+1)*mkp1[i][j]
36             -(y+1)*mkp2[i][j]-(x+1)*mkp3[i][j]+mkp4[i][j];
37         }
38     }
39     return ans;
40 }
41 inline int query(int a,int b,int x,int y)
42 {
43     return Query(x,y)+Query(a-1,b-1)-Query(x,b-1)-Query(a-1,y);
44 }
45 };
46 treearray tri;
47 int main()
48 {
49
50 }
51

```

## 动态开点线段树

```

1 // root 表示整棵线段树的根结点; cnt 表示当前结点个数
2 const int maxn=1e5+10;
3 int n, cnt, root;
4 int sum[maxn*20], ls[maxn*20], rs[maxn*20];
5
6 // 用法: update(root, 1, n, x, f); 其中 x 为待修改节点的编号
7 void update(int& p, int L, int R, int x, int f) { // 引用传参
8     if (!p) p = ++cnt; // 当结点为空时, 创建一个新的结点
9     if (L == R) {
10         sum[p] += f;
11         return;
12     }
13     int m = L + ((R - L) >> 1);
14     if (x <= m)
15         update(ls[p], L, m, x, f);
16     else
17         update(rs[p], m + 1, R, x, f);
18     sum[p] = sum[ls[p]] + sum[rs[p]]; // pushup
19 }
20 // 用法: query(root, 1, n, l, r);
21 int query(int p, int L, int R, int l, int r) {
22     if (!p) return 0; // 如果结点为空, 返回 0
23     if (L >= l && R <= r) return sum[p];
24     int m = L + ((R - L) >> 1), ans = 0;
25     if (l <= m) ans += query(ls[p], L, m, l, r);
26     if (r > m) ans += query(rs[p], m + 1, R, l, r);
27     return ans;
28 }
29 int merge(int a, int b, int l, int r) {
30     if (!a) return b;
31     if (!b) return a;
32     if (l == r) {

```



```

33     sum[a]+=sum[b];
34     return a;
35 }
36 int mid = (l + r) >> 1;
37 ls[a] = merge(ls[a], ls[b], l, mid);
38 rs[a] = merge(rs[a], rs[b], mid + 1, r);
39 sum[a]=sum[ls[a]]+sum[rs[a]];
40 return a;
41 }
42 void split(int &p, int &q, int L, int R, int l, int r) { //p 原树 q 新树
43     if (R < l || r < L) return;
44     if (!p) return;
45     if (l <= L && R <= r) {
46         q = p;
47         p = 0;
48         return;
49     }
50     if (!q) q = ++cnt;
51     int m = L + R >> 1;
52     if (l <= m) split(ls[p], ls[q], L, m, l, r);
53     if (m < r) split(rs[p], rs[q], m + 1, R, l, r);
54     sum[p]=sum[ls[p]]+sum[rs[p]];
55     sum[q]=sum[ls[q]]+sum[rs[q]];
56 }
57 int query1(int& Sum,int Up, int rt, int l, int r) { //min_x of f(x)+x>Up
58     // cout<<"Sum="<<Sum<<" Up="<<Up<<" rt="<<rt<<" l="<<l<<" r="<<r<<"\n";
59     if(!rt){
60         if(r+Sum<=Up)return -1;
61         else return r-(r+Sum-Up)+1;
62     }
63     if (true) {
64         int ss = Sum+sum[rt];
65         if (ss+r<=Up) {
66             Sum = ss;
67             return -1;
68         }
69         if (l == r)return l;
70     }
71     int mid = (l + r) / 2;
72     int pos = query1(Sum,Up,ls[rt], l, mid);
73     if (pos != -1)return pos;
74     return query1(Sum,Up,rs[rt], mid + 1, r);
75 }

```

## 可持久化 01trie

```

1  const int maxn=1e5+10;
2  struct Persistent_Trie
3  {
4      int ch[maxn][2],tot,sum[maxn];
5      void clear()
6      {
7          tot=0;
8          return;
9      }
10     void cpy(int from,int to)
11     {

```

```

12     ch[to][0]=ch[from][0];
13     ch[to][1]=ch[from][1];
14     sum[to]=sum[from];
15     return;
16 }
17 void insert(int &root,int old,int num,int nowbit)
18 {
19     root=++tot;
20     cpy(old,root);
21     sum[root]++;
22     if(nowbit==1) return;
23     if(num&(1<<nowbit))
24     {
25         insert(ch[root][1],ch[root][1],num,nowbit-1);
26     }
27     else
28     {
29         insert(ch[root][0],ch[root][0],num,nowbit-1);
30     }
31 }
32 int query(int s,int t,int x)
33 {
34     int ans=0;
35     for(int i=30;i>=0;--i)
36     {
37         if(sum[ch[t][!(x&(1<<i))]]-sum[ch[s][!(x&(1<<i))]])
38         {
39             t=ch[t][!(x&(1<<i))];
40             s=ch[s][!(x&(1<<i))];
41             ans|=(1<<i);
42         }
43         else
44         {
45             t=ch[t][!(x&(1<<i))];
46             s=ch[s][!(x&(1<<i))];
47         }
48     }
49     return ans;
50 }
51 };

```

## 最近公共祖先 LCA

```

1  const int maxn=1e5+10;
2  vector<int>ve[maxn];
3  int dep[maxn],f[21][maxn];
4  void dfs(int x,int fa)
5  {
6      dep[x]=dep[fa]+1;
7      for(int i=0;i<=19;i++)
8          f[i+1][x]=f[i][f[i][x]];
9      for(auto it:ve[x])
10     {
11         if(it==fa) continue;
12         f[0][it]=x;
13         dfs(it,x);
14     }

```

```

15 }
16 int lca(int x,int y)
17 {
18     if(dep[x]<dep[y]) swap(x,y);
19     for(int i=20;i>=0;i--)
20     {
21         if(dep[f[i][x]]>=dep[y]) x=f[i][x];
22         if(x==y) return x;
23     }
24     for(int i=20;i>=0;i--)
25         if(f[i][x]!=f[i][y])
26             x=f[i][x],y=f[i][y];
27     return f[0][x];
28 }

```

### Lca(o1)

```

1 #define int long long
2 const int maxn=1e5+10;//注意开两倍大小的空间 在 dp 上
3 vector<pair<int,int>>ve[maxn];
4 int dep[maxn];
5 pair<int,int>dp[21][maxn*3];
6 int red[maxn],d[maxn];
7 int Dep[maxn];
8 int dfn[maxn];
9 void dfs(int x,int fa,int l,int dis)
10 {
11     if(red[x])dis=0;
12     d[x]=dis;
13     dep[x]=dep[fa]+1;
14     Dep[x]=Dep[fa]+l;
15     for(auto [it,len]:ve[x])
16     {
17         if(it==fa) continue;
18         dfs(it,x,len,dis+len);
19     }
20 }
21 vector<int> sp;
22 void dfs2(int u, int fa)
23 {
24
25     dfn[u] = sp.size();
26     sp.push_back(u);
27     for (auto& e : ve[u])if(e.first!=fa)
28     {
29         int& v = e.first;
30         dfs2(v, u);
31         sp.push_back(u);
32     }
33 }
34 void initrmq()
35 {
36     int n = sp.size();
37     for (int i = 0; i < n; i++) dp[0][i] = {dfn[sp[i]], sp[i]};
38     for (int i = 1; (1 << i) <= n; i++)
39         for (int j = 0; j + (1 << i) - 1 < n; j++)
40             dp[i][j] = min(dp[i - 1][j], dp[i - 1][j + (1 << (i - 1))]);

```

```

41 }
42 int lca(int u, int v)
43 {
44     int l = dfn[u], r = dfn[v];
45     if (l > r) swap(l, r);
46     int k = __lg(r-l+1);
47     return min(dp[k][l], dp[k][r - (1 << k) + 1]).second;
48 }

```

## 点分治

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int maxn = 100010;
4  const int inf = 2e9;
5  int n, siz[maxn], dist[maxn], vis[maxn], maxx[maxn];
6  vector<pair<int, int>> ve[maxn];
7
8  void add_edge(int x, int y, int z)
9  {
10     ve[x].emplace_back(y, z);
11 }
12
13 void calcsiz(int x, int fa, int sum, int &rt)
14 {
15     siz[x] = 1;
16     maxx[x] = 0;
17     for (auto &[to, len] : ve[x])
18         if (to != fa && !vis[to])
19             {
20                 calcsiz(to, x, sum, rt);
21                 maxx[x] = max(maxx[x], siz[to]);
22                 siz[x] += siz[to];
23             }
24     maxx[x] = max(maxx[x], sum - siz[x]);
25     if (maxx[x] < maxx[rt])
26         rt = x;
27 }
28
29
30 void calcdist(int x, int fa)
31 {
32     for (auto &[to, len] : ve[x])
33         if (to != fa && !vis[to])
34             {
35                 dist[to] = dist[x] + len, calcdist(to, x);
36             }
37 }
38 void dfs(int x, int fa)
39 {
40     vis[x] = true;
41     for (auto &[to, len] : ve[x])
42         if (to != fa && !vis[to])
43             {
44                 dist[to] = len;
45                 calcdist(to, x);
46             }
47 }

```

```

47
48
49     for (auto &[to, len] : ve[x])
50         if (to != fa && !vis[to])
51             {
52                 int sum = siz[to];
53                 int rt = 0;
54                 calcsiz(to, x, sum, rt);
55                 calcsiz(rt, -1, sum, rt);
56                 dfs(rt, x);
57             }
58     }
59
60 int main()
61 {
62     ios::sync_with_stdio(false);
63     cin.tie(0);
64     cin >> n ;
65     for (int i = 1; i < n; i++)
66     {
67         int a, b,c;
68         cin >> a >> b>>c, add_edge(a, b, c), add_edge(b, a, c);
69     }
70     int rt = 0;
71     maxx[rt] = inf;
72     int sum = n;
73     calcsiz(1, -1, sum, rt);
74     calcsiz(rt, -1, sum, rt);
75     dfs(rt, -1);
76     return 0;
77 }
78

```

## 珂朵莉树

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  struct SegmentMap{
4      map<int,int> ma;
5      int sum=0;
6      int n;
7      SegmentMap(int _n=0){
8          n=_n;
9          ma[1]=0;
10         ma[n+1]=-1;
11     }
12     void del(int l,int r,int x){//减去当前 (l,r,x) 的贡献
13         sum-=(r-l+1)*x;
14     }
15     void add(int l,int r,int x){//加上当前 (l,r,x) 的贡献
16         sum+=(r-l+1)*x;
17     }
18     void split(int x){
19         auto t=prev(ma.upper_bound(x))->second;
20         ma[x]=t;
21     }
22     void update(int l,int r,auto&& T){

```

```

23     split(l);split(r+1);
24     auto it=prev(ma.upper_bound(l));
25     int pr=-1;
26     while(it->first<=r){
27         int nowl=it->first,nowr=next(it)->first-1;
28         int x=it->second;
29         del(nowl,nowr,x);
30         add(nowl,nowr,T(x));
31         if(l!=nowl&&pr==T(x))it=ma.erase(it);
32         else {
33             it->second=T(x);
34             it=next(it);
35         }
36         pr=T(x);
37     }
38     if(it->first!=n+1&&it->second==pr)ma.erase(it);
39     if(l!=1){
40         it=ma.lower_bound(l);
41         if(prev(it)->second==it->second)ma.erase(it);
42     }
43 }
44 };
45 int main()
46 {
47     ios::sync_with_stdio(false);
48     cin.tie(0);
49     int n,q;cin>>n>>q;
50     SegmentMap sol(n);
51     while(q--){
52         int op;cin>>op;
53         if(op==1){
54             int l,r;cin>>l>>r;
55             sol.update(l,r,[](int x){
56                 return (int)sqrt(x);
57             });
58         }
59         else{
60             int l,r,x;cin>>l>>r>>x;
61             sol.update(l,r,[x](int y){
62                 return x;
63             });
64         }
65         cout<<sol.sum<<"\n";
66     }
67 }

```

## 笛卡尔树

```

1  const int maxn=2e5+10;
2  vector<int> ve[maxn];
3  int a[maxn];
4  int n;
5  int build(){
6      int top=0;
7      vector<int> Stack(n+1,0);
8      for(int i=0;i<=n;i++){
9          ve[i].clear();

```

```

10     ve[i].resize(2,-1);
11 }
12 Stack[++top]=1;
13 for(int i=2;i<=n;i++){
14     while(top&&a[Stack[top]]>=a[i])top--;
15     if(!top)ve[i][0]=Stack[top+1];
16     else ve[i][0]=ve[Stack[top]][1],ve[Stack[top]][1]=i;
17     Stack[++top]=i;
18 }
19 return Stack[1];
20 }

```

### 线段树区间加区间历史最小值

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  #define int long long
4  const int maxn=1e6+10;
5  const int inf =2e9;
6  struct Node{
7      int l,r,res,tag,tag2,res2;
8  };
9  struct SegmentTree{
10     Node a[maxn*4];
11     void tag_init(int i){
12         a[i].tag=a[i].tag2=0;
13     }
14     void tag_union(int fa,int i){
15         if(a[fa].tag2<0)a[i].tag2=min(a[i].tag2,a[i].tag+a[fa].tag2);
16         a[i].tag+=a[fa].tag;
17     }
18     void tag_cal(int i){
19         if(a[i].tag2<0)a[i].res2=min(a[i].res2,a[i].res+a[i].tag2);
20         a[i].res+=a[i].tag;
21     }
22     void pushdown(int i){
23         tag_cal(i);
24         if(a[i].l!=a[i].r){
25             tag_union(i,i*2);
26             tag_union(i,i*2+1);
27         }
28         tag_init(i);
29     }
30     void pushup(int i){
31         if(a[i].l==a[i].r)return;
32         pushdown(i*2);
33         pushdown(i*2+1);
34         a[i].res=min(a[i*2].res,a[i*2+1].res);
35         a[i].res2=min(a[i*2].res2,a[i*2+1].res2);
36     }
37     void build(int i,int l,int r){
38         a[i].l=l,a[i].r=r;tag_init(i);
39         if(l>=r)return;
40         int mid=(l+r)/2;
41         build(i*2,l,mid);
42         build(i*2+1,mid+1,r);
43     }

```

```

44 void update(int i,int l,int r,int w){
45     if(a[i].r<l||a[i].l>r||l>r)return;
46     pushdown(i);
47     if(a[i].l>=l&&a[i].r<=r){
48         a[i].tag+=w;
49         a[i].tag2=min(a[i].tag2,a[i].tag);
50         return;
51     }
52     update(i*2,l,r,w);
53     update(i*2+1,l,r,w);
54     pushup(i);
55 }
56 int query(int i,int l,int r){
57     pushdown(i);
58     if(a[i].r<l||a[i].l>r||l>r)return inf;
59     if(a[i].l>=l&&a[i].r<=r){
60         return a[i].res2;
61     }
62     return min(query(i*2,l,r),query(i*2+1,l,r));
63 }
64 };
65 SegmentTree tri;
66 signed main()
67 {
68     int n,m;
69     cin>>n>>m;
70     tri.build(1,1,n);
71     for(int i=1;i<=m;i++){
72         int ops;cin>>ops;
73         if(ops==1){
74             int l,r,x;cin>>l>>r>>x;
75             tri.update(1,l,r,x);
76         }
77         else{
78             int l,r;cin>>l>>r;
79             cout<<tri.query(1,l,r)<<"\n";
80         }
81     }
82     return 0;
83 }

```

莫队

```

1 #include<bits/stdc++.h>
2 using namespace std;
3 const int N=1e6+5;
4 int n,m,a[N],block,ans[N],now,cnt[N];
5 struct node
6 {
7     int l,r,i;
8     friend bool operator<(const node a,const node b)
9     {
10         if((a.l/block)==(b.l/block)) return ((a.l/block%2)?a.r>b.r:a.r<b.r);
11         else return a.l<b.l;
12     }
13 }q[N];
14 void add(int x)

```



```

15 {
16 }
17 void del(int x)
18 {
19 }
20 int main()
21 {
22     block=max(1,n/sqrt(m));
23     sort(q+1,q+1+m);
24     int l=1,r=0;
25     for(int i=1;i<=m;i++)
26     {
27         while(l<q[i].l) del(l++);
28         while(l>q[i].l) add(--l);
29         while(r<q[i].r) add(++r);
30         while(r>q[i].r) del(r--);
31         ans[q[i].i]=now;
32     }
33     for(int i=1;i<=m;i++)
34         printf("%d\n",ans[i]);
35     return 0;
36 }
37

```

## 虚树

```

1 //带边权的虚树
2 //ve2 是虚树,ve 是原树
3 //注意使用时 mlen 的意义需要修改 getlen 和 dfs 预处理的时候都要修改
4 //用的时候就 addintoxs(x) 丢进去,每次 init 就全部删除
5 //add 是加原边,ADD 不用管它
6 //solve 里面是必备的几步,不能去除
7 #include <bits/stdc++.h>
8 using namespace std;
9 #define int long long
10 const int maxn=1e5+10;
11 const int inf =1e18;
12 int n,m;
13 struct XS{
14     struct kkk{
15         int to,len;
16     };
17     int dep[maxn],f[maxn][21],id[maxn];
18     int mlen[maxn][21],ans[maxn][21];
19     int state[maxn];
20     int sum[maxn],all;
21     vector<kkk> ve[maxn],ve2[maxn];
22     int now;//统计 dfs 序
23     void dfs(int u,int fa)
24     {
25         id[u]=now++;
26         dep[u]=dep[fa]+1;
27         for(int i=0;i<=19;i++){
28             f[u][i+1]=f[f[u][i]][i];
29             mlen[u][i+1]=mlen[f[u][i]][i]+mlen[u][i];
30         }
31         for(auto v:ve[u])

```

```

32     {
33         if(v.to==fa) continue;
34         f[v.to][0]=u;
35         mlen[v.to][0]=v.len;
36         dfs(v.to,u);
37     }
38 }
39 int lca(int x,int y)
40 {
41     if(dep[x]<dep[y]) swap(x,y);
42     for(int i=20;i>=0;i--)
43     {
44         if(dep[f[x][i]]>=dep[y]) x=f[x][i];
45         if(x==y) return x;
46     }
47     for(int i=20;i>=0;i--)
48         if(f[x][i]!=f[y][i])
49             x=f[x][i],y=f[y][i];
50     return f[x][0];
51 }
52 int getlen(int x,int y)
53 {
54     if(x==y) return 0;
55     if(dep[x]<dep[y]) swap(x,y);
56     int res=0;
57     for(int i=20;i>=0;i--){
58         if(dep[f[x][i]]>=dep[y]){
59             res=res+mlen[x][i];
60             x=f[x][i];
61         }
62         if(x==y) return res;
63     }
64     return inf;
65 }
66 void add(int x,int y,int len){//加边
67     ve[x].push_back({y,len});
68     ve[y].push_back({x,len});
69 }
70 void ADD(int x,int y,int len){//虚树加边
71     ve2[x].push_back({y,len});
72     ve2[y].push_back({x,len});
73 }
74 vector<int> vis;//b vis 这两个用来初始化
75 bool b[maxn];
76 vector<int> v1;//用来表示加入虚树的点
77 int sta[maxn];
78 void init(){//删除虚树
79     {
80         for(auto it:vis){
81             ve2[it].clear();
82             b[it]=false;
83             sum[it]=0;
84         }
85         vis.clear();
86         v1.clear();
87     }

```

```

88     void makexs()
89     {
90         sort(v1.begin(),v1.end(),[&](int x,int y){
91             return id[x]<id[y];
92         });
93         sta[0]=0;
94         int top=1;
95         sta[top]=1;
96         vis.push_back(1);
97         for(auto it:v1){
98             int l=lca(it,sta[top]);
99             if(l!=sta[top]){
100                 while(id[l]<id[sta[top-1]]){
101                     int w=getlen(sta[top],sta[top-1]);
102                     ADD(sta[top-1],sta[top],w);
103                     vis.push_back(sta[top--]);
104                 }
105                 if(id[l]>id[sta[top-1]]){
106                     int w=getlen(sta[top],l);
107                     ADD(l,sta[top],w);
108                     vis.push_back(sta[top]);
109                     sta[top]=l;
110                 }
111                 else {
112                     int w=getlen(sta[top],sta[top-1]);
113                     ADD(sta[top],sta[top-1],w);
114                     vis.push_back(sta[top--]);
115                 }
116             }
117             sta[++top]=it;
118         }
119         for(int i=1;i<top;i++){
120             int w=getlen(sta[i],sta[i+1]);
121             ADD(sta[i],sta[i+1],w);
122             vis.push_back(sta[i+1]);
123         }
124     }
125     void addintoxs(int x){
126         if(x==1)return;
127         v1.push_back(x);
128         b[x]=true;
129     }
130     void solve(){
131         now=0;
132         dfs(1,0);
133         for(int i=1;i<=n;i++){
134             makexs();
135             init();
136         }
137     }
138 };
139 XS xs;

```

## LCT 维护联通性

```

1  #include <bits/stdc++.h>
2  using namespace std;

```

```

3  const int maxn = 10010;
4
5  struct LCT {
6      int ch[maxn][2], fa[maxn], tag[maxn];
7
8      void clear(int x) { ch[x][0] = ch[x][1] = fa[x] = tag[x] = 0; }
9
10     int getch(int x) { return ch[fa[x]][1] == x; }
11
12     int isroot(int x) { return ch[fa[x]][0] != x && ch[fa[x]][1] != x; }
13
14     void pushdown(int x) {
15         if (tag[x]) {
16             if (ch[x][0]) swap(ch[ch[x][0]][0], ch[ch[x][0]][1]), tag[ch[x][0]] ^= 1;
17             if (ch[x][1]) swap(ch[ch[x][1]][0], ch[ch[x][1]][1]), tag[ch[x][1]] ^= 1;
18             tag[x] = 0;
19         }
20     }
21
22     void update(int x) {
23         if (!isroot(x)) update(fa[x]);
24         pushdown(x);
25     }
26
27     void rotate(int x) {
28         int y = fa[x], z = fa[y], chx = getch(x), chy = getch(y);
29         fa[x] = z;
30         if (!isroot(y)) ch[z][chy] = x;
31         ch[y][chx] = ch[x][chx ^ 1];
32         fa[ch[x][chx ^ 1]] = y;
33         ch[x][chx ^ 1] = y;
34         fa[y] = x;
35     }
36
37     void splay(int x) {
38         update(x);
39         for (int f = fa[x]; f = fa[x], !isroot(x); rotate(x))
40             if (!isroot(f)) rotate(getch(x) == getch(f) ? f : x);
41     }
42
43     void access(int x) {
44         for (int f = 0; x; f = x, x = fa[x]) splay(x), ch[x][1] = f;
45     }
46
47     void makeroot(int x) {
48         access(x);
49         splay(x);
50         swap(ch[x][0], ch[x][1]);
51         tag[x] ^= 1;
52     }
53
54     int find(int x) {
55         access(x);
56         splay(x);
57         while (ch[x][0]) x = ch[x][0];
58         splay(x);

```

```

59         return x;
60     }
61     /*-----*/
62     bool query(int x,int y){//查询是否为同一颗树
63         return find(x)==find(y);
64     }
65     void addedge(int x,int y){
66         if (find(x) != find(y)) makeroot(x), fa[x] = y;
67     }
68     void deledge(int x,int y){
69         makeroot(x);
70         access(y);
71         splay(y);
72         if (ch[y][0] == x && !ch[x][1]) ch[y][0] = fa[x] = 0;
73     }
74 } st;
75
76 int n, q, x, y;
77 char op[maxn];
78
79 int main() {
80     scanf("%d%d", &n, &q);
81     while (q--) {
82         scanf("%s%d%d", op, &x, &y);
83         if (op[0] == 'Q') {
84             if (st.query(x,y))
85                 printf("Yes\n");
86             else
87                 printf("No\n");
88         }
89         if (op[0] == 'C')st.addedge(x,y);
90         if (op[0] == 'D')st.deledge(x,y);
91     }
92     return 0;
93 }

```

## 树链剖分

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  typedef long long ll;
4  const int maxn=1e5+10;
5  int mod;
6  void add(int &x,int y){if((x+=y)>=mod)x-=mod;}
7  struct Node{
8      int l,r,res,tag;
9  };
10 struct SegmentTree{
11     Node a[maxn*4];
12     void tag_init(int i){
13         a[i].tag=0;
14     }
15     void tag_union(int fa,int i){
16         add(a[i].tag,a[fa].tag);
17     }
18     void tag_cal(int i){
19         add(a[i].res,(ll)a[i].tag*(a[i].r-a[i].l+1)%mod);

```

```

20     }
21     void pushdown(int i){
22         tag_cal(i);
23         if(a[i].l!=a[i].r){
24             tag_union(i,i*2);
25             tag_union(i,i*2+1);
26         }
27         tag_init(i);
28     }
29     void pushup(int i){
30         if(a[i].l==a[i].r) return;
31         pushdown(i*2);
32         pushdown(i*2+1);
33         a[i].res=(a[i*2].res+a[i*2+1].res)%mod;
34     }
35     void build(int i,int l,int r){
36         a[i].l=l,a[i].r=r;tag_init(i);a[i].res=0;
37         if(l==r) return;
38         int mid=(l+r)/2;
39         build(i*2,l,mid);
40         build(i*2+1,mid+1,r);
41     }
42     void update(int i,int l,int r,int w){
43         pushdown(i);
44         if(a[i].r<l||a[i].l>r||l>r) return;
45         if(a[i].l>=l&&a[i].r<=r){
46             a[i].tag=w;
47             return;
48         }
49         update(i*2,l,r,w);
50         update(i*2+1,l,r,w);
51         pushup(i);
52     }
53     int query(int i,int l,int r){
54         pushdown(i);
55         if(a[i].r<l||a[i].l>r||l>r) return 0;
56         if(a[i].l>=l&&a[i].r<=r){
57             return a[i].res;
58         }
59         return (query(i*2,l,r)+query(i*2+1,l,r))%mod;
60     }
61 };
62 SegmentTree tri;
63 vector<int> ve[maxn];
64 int L[maxn],R[maxn],tot,root=1;
65 int siz[maxn],top[maxn],dep[maxn],fa[maxn],dfn[maxn];
66 void dfs_sz(int x,int h){
67     if(x!=root)ve[x].erase(find(ve[x].begin(),ve[x].end(),h));
68     siz[x] = 1;
69     dep[x]=dep[h]+1;
70     fa[x]=h;
71     for(auto &it:ve[x]) {
72         dfs_sz(it,x);
73         siz[x] += siz[it];
74         if(siz[it] > siz[ve[x][0]]) {
75             swap(it, ve[x][0]);

```

```

76     }
77 }
78 }
79 void dfs_hld(int x) {
80     L[x] =++tot;
81     dfn[tot]=x;
82     for(auto it: ve[x]) {
83         top[it] = (it == ve[x][0] ? top[x] : it);
84         dfs_hld(it);
85     }
86     R[x] =tot;
87 }
88 void chain_add(int x, int y, int w) { // chain add w
89     while(top[x] != top[y]) {
90         if(dep[top[x]] < dep[top[y]]) swap(x, y);
91         tri.update(1, L[top[x]], L[x], w);
92         x = fa[top[x]];
93     }
94     if(L[x] > L[y]) swap(x, y);
95     tri.update(1, L[x], L[y], w);
96 }
97 int chain_sum(int x, int y) { // query the length of chain
98     int sum=0;
99     while(top[x] != top[y]) {
100         if(dep[top[x]] < dep[top[y]]) swap(x, y);
101         add(sum,tri.query(1, L[top[x]], L[x]));
102         x = fa[top[x]];
103     }
104     if(L[x] > L[y]) swap(x, y);
105     add(sum,tri.query(1, L[x], L[y]));
106     return sum;
107 }
108 int main()
109 {
110     ios::sync_with_stdio(false);
111     cin.tie(0);
112     int n,q;cin>>n>>q>>root>>mod;
113     vector<int> a(n+1);
114     for(int i=1;i<=n;i++)cin>>a[i],a[i]%=mod;
115     for(int i=1;i<n;i++){
116         int x,y;cin>>x>>y;
117         ve[x].push_back(y);
118         ve[y].push_back(x);
119     }
120     top[root]=root;
121     tri.build(1,1,n);dfs_sz(root,0);dfs_hld(root);
122     for(int i=1;i<=n;i++){
123         tri.update(1,L[i],L[i],a[i]);
124     }
125     while(q--){
126         int op;cin>>op;
127         if(op==1){
128             int x,y,w;cin>>x>>y>>w;
129             chain_add(x,y,w);
130         }
131         if(op==2){

```

```

132         int x,y;cin>>x>>y;
133         cout<<chain_sum(x,y)<<"\n";
134     }
135     if(op==3){//update the subtree of root x +=y
136         int x,y;cin>>x>>y;
137         tri.update(1,L[x],R[x],y);
138     }
139     if(op==4){
140         int x;cin>>x;
141         cout<<tri.query(1,L[x],R[x])<<"\n";
142     }
143 }
144
145 }

```



# 数学

## 组合数

```
1  #include <bits/stdc++.h>
2  using namespace std;
3  #define int long long
4  const int maxn=100010;
5  const int mod=1e9+7;
6  int ksm(int x,int k){
7      int res=1;
8      while(k){
9          if(k&1) res=res*x%mod;
10         x=x*x%mod;
11         k/=2;
12     }
13     return res;
14 }
15 int ny(int x){
16     return ksm(x,mod-2);
17 }
18 void add(int &x,int y){
19     if((x+=y)>=mod)x-=mod;
20 }
21 void del(int &x,int y){
22     if((x-=y)<0)x+=mod;
23 }
24 int inv[maxn],fac[maxn];
25 int C(int n,int m){return n==0?1:fac[n]*inv[n-m]%mod*inv[m]%mod;}
26 int A(int n,int m){return n==0?1:fac[n]*inv[n-m]%mod;}
27 void init(){
28     inv[0]=fac[0]=1;
29     inv[1]=1;
30     for(int i=1;i<maxn;i++){
31         fac[i]=fac[i-1]*i%mod;
32     }
33     inv[1]=1;
34     for(int i=2;i<maxn;i++){
35         inv[i]=(int)(mod-mod/i)*inv[mod%i]%mod;
36     }
37     inv[0]=1;
38     for(int i=1;i<maxn;i++){
39         inv[i]=inv[i-1]*inv[i]%mod;
40     }
41 }
42 signed main()
43 {
44     init();
45     if(mod==(int)(1e9+7))assert(C(2000,1000)==72475738);
46     if(mod==998244353)assert(C(2000,1000)==472799582);
47 }
```

## BSGS 指数方程余数问题(求 $a^x=b\%p$ )

```
1  #include <cstdio>
2  #include <cstring>
3  #include <cmath>
4  #include <algorithm>
```

```

5  #include <unordered_map>
6
7  using namespace std;
8
9  typedef long long LL;
10
11 const int INF = 0x3f3f3f3f;
12
13 int a, b, p;
14 unordered_map<int, int> hs;
15
16 int exgcd(int a, int b, int &x, int &y) {
17     if (!b) {
18         x = 1, y = 0;
19         return a;
20     }
21     int d = exgcd(b, a % b, y, x);
22     y -= a / b * x;
23     return d;
24 }
25
26 int BSGS(int a, int b, int p) {
27     if (1 % p == b % p) return 0;
28     int k = sqrt(p) + 1;
29     hs.clear();
30     for (int y = 0, r = b % p; y < k; y++) {
31         hs[r] = y;
32         r = (LL)r * a % p;
33     }
34     int ak = 1;
35     for (int i = 1; i <= k; i++) ak = (LL)ak * a % p;
36     for (int x = 1, l = ak; x <= k; x++) {
37         if (hs.count(l)) return k * x - hs[l];
38         l = (LL)l * ak % p;
39     }
40     return -INF;
41 }
42
43 int exBSGS(int a, int b, int p) {
44     b = (b % p + p) % p;
45     if (1 % p == b % p) return 0;
46     int x, y;
47     int d = exgcd(a, p, x, y);
48     if (d > 1) {
49         if (b % d) return -INF;
50         exgcd(a / d, p / d, x, y);
51         return exBSGS(a, (LL)b / d * x % (p / d), p / d) + 1;
52     }
53     return BSGS(a, b, p);
54 }
55
56 int main() {
57     while (~scanf("%d%d%d", &a, &p, &b), a || b || p) {
58         int res = exBSGS(a, b, p);
59         if (res < 0) puts("No Solution");
60         else printf("%d\n", res);

```

```

61     }
62     return 0;
63 }

```

## EXGCD

```

1  int exgcd(int a, int b, int &x, int &y){/* ax+by=gcd(a,b)  !(a==0&&b==0)
2      if(b==0){
3          x=1;
4          y=0;
5          return a;
6      }
7      int d=exgcd(b,a%b,x,y);
8      int t=x;
9      x=y;
10     y=t-(a/b)*y;
11     return d;
12 }

```

## FFT

```

1  //当 vector 用就可以了
2  #include <bits/stdc++.h>
3  #define fp(i, a, b) for (int i = (a), i##_ = (b) + 1; i < i##_; ++i)
4  #define fd(i, a, b) for (int i = (a), i##_ = (b) - 1; i > i##_; --i)
5  using namespace std;
6  using ll = int64_t;
7  using db = double;
8  /*-----*/
9  struct cp {
10     db x, y;
11     cp(db real = 0, db imag = 0) : x(real), y(imag){};
12     cp operator+(cp b) const { return {x + b.x, y + b.y}; }
13     cp operator-(cp b) const { return {x - b.x, y - b.y}; }
14     cp operator*(cp b) const { return {x * b.x - y * b.y, x * b.y + y * b.x}; }
15 };
16 using vcp = vector<cp>;
17 using Poly = vector<int>;
18 namespace FFT {
19     const db pi = acos(-1);
20     vcp Omega(int L) {
21         vcp w(L); w[1] = 1;
22         for (int i = 2; i < L; i <= 1) {
23             auto w0 = w.begin() + i / 2, w1 = w.begin() + i;
24             cp wn(cos(pi / i), sin(pi / i));
25             for (int j = 0; j < i; j += 2)
26                 w1[j] = w0[j >> 1], w1[j + 1] = w1[j] * wn;
27         }
28         return w;
29     }
30     auto W = Omega(1 << 21); // NOLINT
31     void DIF(cp *a, int n) {
32         cp x, y;
33         for (int k = n >> 1; k >= 1)
34             for (int i = 0; i < n; i += k << 1)
35                 for (int j = 0; j < k; ++j)
36                     x = a[i + j], y = a[i + j + k],
37                     a[i + j + k] = (a[i + j] - y) * W[k + j], a[i + j] = x + y;

```

```

38     }
39     void IDIT(cp *a, int n) {
40         cp x, y;
41         for (int k = 1; k < n; k <= 1)
42             for (int i = 0; i < n; i += k < 1)
43                 for (int j = 0; j < k; ++j)
44                     x = a[i + j], y = a[i + j + k] * W[k + j],
45                     a[i + j + k] = x - y, a[i + j] = x + y;
46         const db Inv = 1. / n;
47         fp(i, 0, n - 1) a[i].x *= Inv, a[i].y *= Inv;
48         reverse(a + 1, a + n);
49     }
50 }
51
52 namespace Polynomial {
53     // basic operator
54     void DFT(vcp &a) { FFT::DIF(a.data(), a.size()); }
55     void IDFT(vcp &a) { FFT::IDIT(a.data(), a.size()); }
56     int norm(int n) { return 1 << (__lg(n - 1) + 1); }
57
58     // Poly mul
59     vcp &dot(vcp &a, vcp &b) { fp(i, 0, a.size() - 1) a[i] = a[i] * b[i]; return a; }
60     Poly operator+(Poly a, Poly b) {
61         int maxlen = max(a.size(), b.size());
62         Poly ans(maxlen + 1);
63         a.resize(maxlen + 1), b.resize(maxlen + 1);
64         for (int i = 0; i < maxlen; i++)
65             ans[i] = a[i] + b[i];
66         return ans;
67     }
68     Poly operator*(ll k, Poly a) {
69         Poly ans;
70         for(auto i:a)
71             ans.push_back(k * i);
72         return ans;
73     }
74     Poly operator*(Poly a, Poly b) {
75         int n = a.size() + b.size() - 1;
76         vcp c(norm(n));
77         fp(i, 0, a.size() - 1) c[i].x = a[i];
78         fp(i, 0, b.size() - 1) c[i].y = b[i];
79         DFT(c), dot(c, c), IDFT(c), a.resize(n);
80         fp(i, 0, n - 1) a[i] = int(c[i].y * .5 + .5);
81         return a;
82     }
83 }
84 /*-----*/
85 using namespace Polynomial;

```

## FWT

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int mod = 998244353;
4 void add(int &x, int y) {
5     if ((x += y) >= mod) x -= mod;
6 }

```

```

7 void del(int &x, int y) {
8     if ((x -= y) < 0) x += mod;
9 }
10 void fwtor(int a[], int m, int opt) //(1,-1)
11 {
12     for (int len = 2; len <= m; len <= 1)
13         for (int p = len >> 1, i = 0; i < m; i += len)
14             for (int j = i; j < i + p; j++)
15                 if (opt > 0)
16                     add(a[j + p], a[j]);
17                 else
18                     del(a[j + p], a[j]);
19 }
20 void fwtand(int a[], int m, int opt) //(1,-1)
21 {
22     for (int len = 2; len <= m; len <= 1)
23         for (int p = len >> 1, i = 0; i < m; i += len)
24             for (int j = i; j < i + p; j++)
25                 if (opt > 0)
26                     add(a[j], a[j + p]);
27                 else
28                     del(a[j], a[j + p]);
29 }
30 void fwtxor(int a[], int m, int opt) //(1,1/2)
31 {
32     for (int len = 2; len <= m; len <= 1)
33         for (int p = len >> 1, i = 0; i < m; i += len)
34             for (int j = i; j < i + p; j++) {
35                 add(a[j], a[j + p]);
36                 a[j + p] = (a[j] - 2ll * a[j + p] % mod + mod) % mod;
37                 a[j] = 1ll * a[j] * opt % mod;
38                 a[j + p] = 1ll * a[j + p] * opt % mod;
39             }
40 }
41 int a[1 << 17], b[1 << 17], c[1 << 17];
42 void mul(int a[], int b[], int c[], int m) {
43     for (int i = 0; i < m; i++) c[i] = 1ll * a[i] * b[i] % mod;
44 }
45 void print(int a[], int m) {
46     for (int i = 0; i < m; i++) cout << a[i] << " \n"[i == m - 1];
47 }
48 int main() {
49     int n;
50     cin >> n;
51     int m = 1 << n;
52     for (int i = 0; i < m; i++) cin >> a[i];
53     for (int i = 0; i < m; i++) cin >> b[i];
54
55     fwtor(a, m, 1), fwtor(b, m, 1), mul(a, b, c, m);
56     fwtor(a, m, -1), fwtor(b, m, -1), fwtor(c, m, -1), print(c, m);
57
58     fwtand(a, m, 1), fwtand(b, m, 1), mul(a, b, c, m);
59     fwtand(a, m, -1), fwtand(b, m, -1), fwtand(c, m, -1), print(c, m);
60
61     fwtxor(a, m, 1), fwtxor(b, m, 1), mul(a, b, c, m);

```

```

62     fwtxor(c, m, (mod + 1) / 2), print(c, m);
63 }

```

## 莫比乌斯反演

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  const int maxn=1e5+10;
4  int pr[maxn],tot,mul[maxn],phi[maxn];
5  bool vis[maxn];
6  void init(int n)
7  {
8      mul[1]=phi[1]=1;
9      for(int i=2;i<=n;i++)
10     {
11         if(!vis[i])
12         {
13             mul[i]=-1;
14             pr[++tot]=i;
15             phi[i]=i-1;
16         }
17         for(int j=1;j<=tot && (long long)pr[j]*i<=n;j++)
18         {
19             int num=pr[j]*i;
20             vis[num]=1;
21             mul[num]=-mul[i];
22             phi[num]=phi[i]*phi[pr[j]];
23             if(i%pr[j]==0)
24             {
25                 phi[num]=pr[j]*phi[i];
26                 mul[num]=0;
27                 break;
28             }
29         }
30     }
31 }

```

## NTT

```

1  #include <bits/stdc++.h>
2
3  #define fp(i, a, b) for (int i = (a), i##_ = (b) + 1; i < i##_; ++i)
4  #define fd(i, a, b) for (int i = (a), i##_ = (b) - 1; i > i##_; --i)
5  #define file(s) freopen(s".in", "r", stdin), freopen(s".out", "w", stdout)
6  using namespace std;
7  const int maxn = 2e5 + 5, P = 998244353;
8  using arr = int[maxn];
9  using ll = int64_t;
10 /*-----*/
11 class Cipolla {
12     int P, I2{};
13     using pll = pair<ll, ll>;
14     #define X first
15     #define Y second
16     ll mul(ll a, ll b) const { return a * b % P; }
17     pll mul(pll a, pll b) const { return {(a.X * b.X + I2 * a.Y % P * b.Y) % P, (a.X
18 * b.Y + a.Y * b.X) % P}; }

```

```

18     template<class T> T POW(T a, int b, T x) { for (; b >= 1, a = mul(a, a)) if
    (b & 1) x = mul(x, a); return x; }
19 public:
20     Cipolla(int p = 0) : P(p) {}
21     pair<int, int> sqrt(int n) {
22         int a = rand(), x;
23         if (!(n % P)) return {0, 0};
24         if (POW(n, (P - 1) >> 1, (int)1) == P - 1) return {-1, -1};
25         while (POW(I2 = ((ll) a * a - n + P) % P, (P - 1) >> 1, (int)1) == 1) a
    = rand();
26         x = (int) POW(pll{a, 1}, (P + 1) >> 1, {1, 0}).X;
27         if (2 * x > P) x = P - x;
28         return {x, P - x};
29     }
30 #undef X
31 #undef Y
32 };
33 /*-----*/
34 #define ADD(a, b) (((a) += (b)) >= P ? (a) -= P : 0) // (a += b) %= P
35 #define SUB(a, b) (((a) -= (b)) < 0 ? (a) += P : 0) // ((a -= b) += P) %= P
36 #define MUL(a, b) ((ll) (a) * (b) % P)
37 //vector<int> getInv(int L) {
38 //    vector<int> inv(L); inv[1] = 1;
39 //    fp(i, 1, L - 1) inv[i] = MUL((P - P / i), inv[P % i]);
40 //    return inv;
41 //}
42 //auto inv = getInv(maxn); // NOLINT
43 int POW(ll a, int b = P - 2, ll x = 1) { for (; b >= 1, a = a * a % P) if (b & 1)
    x = x * a % P; return x; }
44 //int INV(int a) { return a < maxn ? inv[a] : POW(a); }
45 namespace NTT {
46     const int g = 3;
47     vector<int> Omega(int L) {
48         int wn = POW(g, P / L);
49         vector<int> w(L); w[L >> 1] = 1;
50         fp(i, L / 2 + 1, L - 1) w[i] = MUL(w[i - 1], wn);
51         fd(i, L / 2 - 1, 1) w[i] = w[i << 1];
52         return w;
53     }
54     auto W = Omega(1 << 21); // NOLINT
55     void DIF(int *a, int n) {
56         for (int k = n >> 1; k; k >>= 1)
57             for (int i = 0, y; i < n; i += k << 1)
58                 fp(j, 0, k - 1)
59                     y = a[i + j + k], a[i + j + k] = MUL(a[i + j] - y + P, W[k + j]),
    ADD(a[i + j], y);
60     }
61     void IDIT(int *a, int n) {
62         for (int k = 1; k < n; k <= 1)
63             for (int i = 0, x, y; i < n; i += k << 1)
64                 fp(j, 0, k - 1)
65                     x = a[i + j], y = MUL(a[i + j + k], W[k + j]),
66                     a[i + j + k] = x - y < 0 ? x - y + P : x - y, ADD(a[i + j], y);
67         int Inv = P - (P - 1) / n;
68         fp(i, 0, n - 1) a[i] = MUL(a[i], Inv);
69         reverse(a + 1, a + n);

```

```

70     }
71 }
72 namespace Polynomial {
73     using Poly = std::vector<int>;
74
75     // mul/div int
76     Poly &operator*=(Poly &a, int b) { for (auto &x : a) x = MUL(x, b); return a; }
77     Poly operator*(Poly a, int b) { return a *= b; }
78     Poly operator*(int a, Poly b) { return b * a; }
79     Poly &operator/=(Poly &a, int b) { return a *= POW(b); }
80     Poly operator/(Poly a, int b) { return a /= b; }
81
82     // Poly add/sub
83     Poly &operator+=(Poly &a, Poly b) {
84         a.resize(max(a.size(), b.size()));
85         fp(i, 0, b.size() - 1) ADD(a[i], b[i]);
86         return a;
87     }
88     Poly operator+(Poly a, Poly b) { return a += b; }
89     Poly &operator-=(Poly &a, Poly b) {
90         a.resize(max(a.size(), b.size()));
91         fp(i, 0, b.size() - 1) SUB(a[i], b[i]);
92         return a;
93     }
94     Poly operator-(Poly a, Poly b) { return a -= b; }
95
96     // Poly mul
97     void DFT(Poly &a) { NTT::DIF(a.data(), a.size()); }
98     void IDFT(Poly &a) { NTT::IDIT(a.data(), a.size()); }
99     int norm(int n) { return 1 << (32 - __builtin_clz(n - 1)); }
100    void norm(Poly &a) { if (!a.empty()) a.resize(norm(a.size()), 0); }
101    Poly &dot(Poly &a, Poly &b) {
102        fp(i, 0, a.size() - 1) a[i] = MUL(a[i], b[i]);
103        return a;
104    }
105    Poly operator*(Poly a, Poly b) {
106        int n = a.size() + b.size() - 1, L = norm(n);
107        if (a.size() <= 8 || b.size() <= 8) {
108            Poly c(n);
109            fp(i, 0, a.size() - 1) fp(j, 0, b.size() - 1)
110                c[i + j] = (c[i + j] + (ll) a[i] * b[j]) % P;
111            return c;
112        }
113        a.resize(L), b.resize(L);
114        DFT(a), DFT(b), dot(a, b), IDFT(a);
115        return a.resize(n), a;
116    }
117
118    // Poly inv
119    Poly Inv2k(Poly a) { // a.size() = 2^k
120        int n = a.size(), m = n >> 1;
121        if (n == 1) return {POW(a[0])};
122        Poly b = Inv2k(Poly(a.begin(), a.begin() + m)), c = b;
123        b.resize(n), DFT(a), DFT(b), dot(a, b), IDFT(a);
124        fp(i, 0, n - 1) a[i] = i < m ? 0 : P - a[i];
125        DFT(a), dot(a, b), IDFT(a);

```



```

126         return move(c.begin(), c.end(), a.begin()), a;
127     }
128     Poly Inv(Poly a) {
129         int n = a.size();
130         norm(a), a = Inv2k(a);
131         return a.resize(n), a;
132     }
133
134     // Poly div/mod
135     Poly operator/(Poly a, Poly b){
136         int k = a.size() - b.size() + 1;
137         if (k < 0) return {0};
138         reverse(a.begin(), a.end());
139         reverse(b.begin(), b.end());
140         b.resize(k), a = a * Inv(b);
141         a.resize(k), reverse(a.begin(), a.end());
142         return a;
143     }
144     pair<Poly, Poly> operator%(Poly a, const Poly& b) {
145         Poly c = a / b;
146         a -= b * c, a.resize(b.size() - 1);
147         return {c, a};
148     }
149
150     // Poly sqrt
151     Poly Sqrt(Poly a) {
152         int n = a.size(), k = norm(n);
153         Poly b = {(new Cipolla(P))->sqrt(a[0]).first}, c;
154         a.resize(k * 2, 0);
155         for (int L = 2; L <= k; L <= 1) {
156             b.resize(2 * L, 0), c = Poly(a.begin(), a.begin() + L) * Inv(b);
157             fp(i, 0, 2 * L - 1) b[i] = MUL(b[i] + c[i], (P + 1) / 2);
158         }
159         return b.resize(n), b;
160     }
161
162     // Poly calculus
163     void Derivative(Poly &a) {
164         fp(i, 1, a.size() - 1) a[i - 1] = MUL(i, a[i]);
165         a.pop_back();
166     }
167 }

```

## 任意模数 NTT

```

1  const long long mod = 1e18;
2  namespace polynomial {
3      typedef complex<long double> cplx;
4      const long double pi = acos((long double)-1.0);
5      const int len = 15, mask = (1 << len) - 1;
6      struct UnitRoot {
7          static vector<cplx> w;
8          static vector<cplx> get_root(int n) {
9              n = 1 << 32 - __builtin_clz(n);
10             if (n > w.size()) {
11                 w.resize(n);
12                 for (int i = 0; i < n; i++)

```

```

13         w[i] = cplx(cos(2 * i * pi / n), sin(2 * i * pi / n));
14     }
15     int m = w.size() / n;
16     vector<cplx> res(n);
17     for (int i = 0, j = 0; i < n; i++, j += m) res[i] = w[j];
18     return res;
19 }
20 };
21 vector<cplx> UnitRoot::w;
22
23 void fft(vector<cplx> &p, const vector<cplx> &w) {
24     int n = w.size();
25     for (int i = 1, j = 0; i < n - 1; ++i) {
26         int s = n;
27         do {
28             s >>= 1;
29             j ^= s;
30         } while (~j & s);
31         if (i < j) {
32             swap(p[i], p[j]);
33         }
34     }
35     for (int d = 0; (1 << d) < n; ++d) {
36         int m = 1 << d, m2 = m * 2, rm = n >> (d + 1);
37         for (int i = 0; i < n; i += m2) {
38             for (int j = 0; j < m; ++j) {
39                 auto &p1 = p[i + j + m], &p2 = p[i + j];
40                 auto t = w[rm * j] * p1;
41                 p1 = p2 - t;
42                 p2 = p2 + t;
43             }
44         }
45     }
46 }
47 vector<long long> conv(const vector<long long> &a, const vector<long long> &b) {
48     vector<cplx> w = UnitRoot::get_root(a.size() + b.size() - 1);
49     int n = w.size();
50     vector<cplx> A(n), B(n), C(n), D(n);
51     for (int i = 0; i < a.size(); ++i) A[i] = cplx(a[i] >> len, a[i] & mask);
52     for (int i = 0; i < b.size(); ++i) B[i] = cplx(b[i] >> len, b[i] & mask);
53     fft(A, w), fft(B, w);
54     for (int i = 0; i < n; ++i) {
55         int j = (n - i) % n;
56         cplx da = (A[i] - conj(A[j])) * cplx(0, -0.5), db = (A[i] + conj(A[j]))
57 * cplx(0.5, 0), dc = (B[i] - conj(B[j])) * cplx(0, -0.5), dd = (B[i] + conj(B[j])) *
58 cplx(0.5, 0);
59         C[j] = da * dd + da * dc * cplx(0, 1); D[j] = db * dd + db * dc * cplx(0, 1);
60     }
61     fft(C, w), fft(D, w);
62     vector<long long> res(a.size() + b.size() - 1);
63     for (int i = 0; i < res.size(); ++i) {
64         long long da = (long long)(C[i].imag() / n + 0.5) % mod, db = (long long)
65 (C[i].real() / n + 0.5) % mod, dc = (long long)(D[i].imag() / n + 0.5) % mod, dd = (long
66 long)(D[i].real() / n + 0.5) % mod;
67         res[i] = ((dd << (len * 2)) + ((db + dc) << len) + da) % mod;
68     }
69 }

```

```

65         return res;
66     }
67 };
68 using namespace polynomial;

```

## Pollard\_Rho

```

1  typedef long long ll;
2  map<ll, bool>P;
3  mt19937_64 rnd(time(0));
4  namespace Pollard_Rho
5  {
6  #define ldb long double
7  ll mul(ll x, ll y, ll mod)
8  {
9      return ((x * y - (ll)((ldb)x / mod * y) * mod) + mod) % mod;
10 }
11 ll gcd(ll a, ll b)
12 {
13     return (b == 0 ? a : gcd(b, a % b));
14 }
15 ll ksm(ll a, ll b, ll mod)
16 {
17     ll ans = 1; a %= mod;
18     while (b) {if (b & 1)ans = mul(ans, a, mod); b >>= 1; a = mul(a, a, mod);}
19     return ans;
20 }
21 int pr[15] = {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37};
22 bool Miller_Rabin(ll n)
23 {
24     if (n == 2 || n == 3)return 1;
25     if (n % 2 == 0 || n == 1)return 0;
26     ll d = n - 1;
27     int s = 0;
28     while (d % 2 == 0)s ++, d >>= 1;
29     for (int i = 0; i <= 11; i ++)
30     {
31         if (pr[i] >= n)break;
32         ll a = pr[i];
33         ll x = ksm(a, d, n);
34         ll y = 0;
35         for (int j = 0; j <= s - 1; j ++)
36         {
37             y = mul(x, x, n);
38             if (y == 1 && x != 1 && x != (n - 1))return 0;
39             x = y;
40         }
41         if (y != 1)return 0;
42     }
43     return 1;
44 }
45 ll Pollard_Rho(ll n)
46 {
47     ll now, pre, g;
48     while (true)
49     {
50         now = pre = rnd() % (n - 1) + 1;

```

```

51     g = 1;
52     ll c = rnd() % (n - 1) + 1;
53     for (int i = 1, fst = 1 ;; i++)
54     {
55         now = (mul(now, now, n) + c) % n;
56         g = mul(g, abs(now - pre), n);
57         if (now == pre || !g) break;
58         if (!(i & 127) || i == fst)
59         {
60             g = gcd(g, n);
61             if (g > 1) return g;
62             if (i == fst) pre = now, fst <= 1;
63         }
64     }
65 }
66 }
67 void Find(ll n)
68 {
69     if (n == 1) return ;
70     if (Miller_Rabin(n))
71     {
72         P[n] = 1;
73         return ;
74     }
75     ll p = Pollard_Rho(n);
76     int c = 0;
77     while (!(n % p))
78     {
79         n /= p, c++;
80     }
81     Find(p);
82     Find(n);
83 }
84 }
85 void solve(int x, set<int> &s){
86     Pollard_Rho :: Find(x);
87     for (auto [x, _] : P) s.insert(x);
88     P.clear();
89 }

```

## 扩展中国剩余定理

```

1  #define int long long
2  int mul(int a,int b,int mod){//0(1)取模快速乘, 不会爆 long long
3      return (a*b-(int)((long double)a/mod*b)*mod+mod)%mod;
4  }
5  int exgcd(int a, int b, int& x, int& y){
6      if(!b){
7          x = 1, y = 0;
8          return a;
9      }
10     int d = exgcd(b,a%b,y,x);
11     y -= a/b*x;
12     return d;
13 }
14 int solve(int n,vector<int>&mo,vector<int>&res){
15     int a1,m1;

```

```

16     a1=res[0],m1=mo[0];
17     bool ok = 1;
18     for(int i=1;i<n;i++){
19         int a2,m2,k1,k2;
20         m2=mo[i],a2=res[i];
21         int d = exgcd(m1,m2,k1,k2);
22         if((a2-a1)%d) ok = 0;
23         else{
24             k1=mul(k1,(a2-a1)/d,m2/d);//这个地方必须要用取模快速乘
25             a1=a1+k1*m1;
26             m1=abs(m1/d*m2);
27         }
28     }
29     if(ok) return (a1%m1+m1)%m1;
30     else return -1;
31 }

```

### 拉格朗日插值

```

1  #define int long long
2  const int N=1e6+10,mod=998244353;
3  int ksm(int a,int n,int m=mod){int s=1;while(n){if(n&1) s=s*a%m;a=a*a%m;n>>=1;}return s;}
4  int fac[N+5],facinv[N+5],inv[N+5];
5  struct LR{
6      int Inv(int n){return ksm(n,mod-2);}
7      void init(){ //预处理阶乘和阶乘逆元,逆元.
8          fac[0]=inv[0]=inv[1]=1;
9          for(int i=1;i<=N;i++)
10             fac[i]=fac[i-1]*i%mod;
11         facinv[N]=Inv(fac[N]);
12         for(int i=N-1;~i;i--)
13             facinv[i]=facinv[i+1]*(i+1)%mod;
14         for(int i=2;i<N+5;i++)
15             inv[i]=(mod-mod/i)*inv[mod%i]%mod;
16     }
17     int cal(vector<int>&x,vector<int>&y,int k){ //离散点 n 个点[0,n-1] x[i],y[i] 插 f(k)
18         int n=x.size();
19         int s=0;
20         for(int i=0;i<n;i++)if(x[i]==k) return y[i];
21         for(int i=0;i<n;i++){
22             int p=y[i]%mod,q=1;
23             for(int j=0;j<n;j++){
24                 if(i==j) continue;
25                 p=p*((k-x[j])%mod+mod)%mod;
26                 q=q*((x[i]-x[j])%mod+mod)%mod;
27             }
28             s=(s+p*Inv(q)%mod)%mod;
29         }return (s%mod+mod)%mod;
30     }
31     int inpo(vector<int>&f,int x){ //给定 连续 i 属于[0,n] f(i) 拉插 f(x)
32         int n=f.size()-1;
33         if(x>=0&&x<=n) return f[x];
34         int p,s=0;
35         vector<int>pre(n+1),suf(n+1);
36         pre[0]=x-0;
37         for(int i=1;i<=n;i++)pre[i]=pre[i-1]*(x-i)%mod;

```

```

38     suf[n]=x-n;
39     for(int i=n-1;i>=0;i--)suf[i]=suf[i+1]*(x-i)%mod;
40     for(int i=0;i<=n;i++){
41         p=facinv[n-i]%mod*facinv[i]%mod;
42         if(i>0)p=p*pre[i-1]%mod;
43         if(i<n)p=p*suf[i+1]%mod;
44         if((n-i)&1) s=(s-p*f[i]%mod+mod)%mod;
45         else s=(s+p*f[i]%mod)%mod;
46     }
47     return (s%mod+mod)%mod;
48 }
49 }sol;

```

## 拉格朗日插值没有模数

```

1 struct LR{
2     int inter(std::vector<int> vec, int x){
3         int n = vec.size() - 1;
4         int ans = 0;
5         for (int i = 0; i <= n; ++ i){
6             int div = 1;
7             for (int j = 0; j <= n; ++ j){
8                 if (i != j) div *= (i - j);
9             }
10            bool flag = div < 0;
11            div = std::abs(div);
12            int prod = vec[i];
13            for (int j = 0; j <= n; ++ j){
14                if (i == j) continue;
15                int gcd = std::abs(std::__gcd(x - j, div));
16                prod *= (x - j) / gcd;
17                div /= gcd;
18            }
19            ans += flag ? -prod : prod;
20        }
21        return ans;
22    }
}

```

## 杜教筛

```

1 const int maxn=3e6+10;
2 int sumf[maxn];
3 int Sum(int n){// 这是 f * g 的 n 项前缀和
4
5 }
6 int Sumg(int n){// g 的 n 项前缀和
7
8 }
9 map<int,int> f;
10 int F (int n) {
11     if (n <= 3000'000) return sumf[n]; // 预处理出 n 较小时的前缀和
12     if (f.find(n)!=f.end()) return f[n]; // 记忆化, 如果求过这个值, 就不需要再递归一遍了
13     int ans = Sum(n);
14     for (int l = 2, r; l <= n; l = r + 1) // 整除分块
15         r = n / (n / l), ans -= (Sumg(r) - Sumg(l-1)) * F (n / l);
16     // [l,r] 的 F (n / l) 是一样的, 对 g(x) 求个和即可
17     return f[n] = ans / Sumg(1); // 别忘了除上 g(1)
}

```

```
18 }
19
```

## 线性筛质数

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 const int maxn=1e6+10;
4 bool v[maxn];
5 int n,pr;
6 vector<int> p;
7 void init()
8 {
9     v[1]=true;
10    for(int i=2;i<maxn;i++)
11    {
12        if(!v[i])p.push_back(i);
13        for(int j=0;j<p.size()&&i*p[j]<maxn;++j){v[i*p[j]]=true;if(i%p[j]==0)break;}
14    }
15 }
16
```

## 线性递推

```
1 #include<bits/stdc++.h>
2 using namespace std;
3 #define rep(i,a,n) for (int i=a;i<n;i++)
4 #define per(i,a,n) for (int i=n-1;i>=a;i--)
5 #define all(x) (x).begin(),(x).end()
6 #define siz(x) ((int)(x).size())
7 typedef vector<int> VI;
8 typedef long long ll;
9 typedef pair<int,int> PII;
10 const ll mod=1000000007;
11 ll powmod(ll a,ll b) {ll res=1;a%=mod; assert(b>=0); for(;b>=>1)
12     {if(b&1)res=res*a%mod;a=a*a%mod;}return res;}
13 ll n;
14 namespace linear_seq {
15     const int N=10010;
16     ll res[N],base[N],_c[N],_md[N];
17     vector<int> Md;
18     void mul(ll *a,ll *b,int k) {
19         rep(i,0,k+k) _c[i]=0;
20         rep(i,0,k) if (a[i]) rep(j,0,k) _c[i+j]=(_c[i+j]+a[i]*b[j])%mod;
21         for (int i=k+k-1;i>=k;i--) if (_c[i])
22             rep(j,0,siz(Md)) _c[i-k+Md[j]]=(_c[i-k+Md[j]]-_c[i]*_md[Md[j]])%mod;
23         rep(i,0,k) a[i]=_c[i];
24     }
25     int solve(ll n,VI a,VI b) {
26         ll ans=0,pnt=0;
27         int k=siz(a);
28         assert(siz(a)==siz(b));
29         rep(i,0,k) _md[k-1-i]=-a[i];_md[k]=1;
30         Md.clear();
31         rep(i,0,k) if (_md[i]!=0) Md.push_back(i);
32         rep(i,0,k) res[i]=base[i]=0;
33         res[0]=1;
```

```

34     while ((lll<<pnt)<=n) pnt++;
35     for (int p=pnt;p>=0;p--) {
36         mul(res,res,k);
37         if ((n>>p)&1) {
38             for (int i=k-1;i>=0;i--) res[i+1]=res[i];res[0]=0;
39             rep(j,0,siz(Md)) res[Md[j]]=(res[Md[j]]-res[k]*_md[Md[j]])%mod;
40         }
41     }
42     rep(i,0,k) ans=(ans+res[i]*b[i])%mod;
43     if (ans<0) ans+=mod;
44     return ans;
45 }
46 VI BM(VI s) {
47     VI C(1,1),B(1,1);
48     int L=0,m=1,b=1;
49     rep(n,0,siz(s)) {
50         ll d=0;
51         rep(i,0,L+1) d=(d+(ll)C[i]*s[n-i])%mod;
52         if (d==0) ++m;
53         else if (2*L<=n) {
54             VI T=C;
55             ll c=mod-d*powmod(b,mod-2)%mod;
56             while (siz(C)<siz(B)+m) C.push_back(0);
57             rep(i,0,siz(B)) C[i+m]=(C[i+m]+c*B[i])%mod;
58             L=n+1-L; B=T; b=d; m=1;
59         } else {
60             ll c=mod-d*powmod(b,mod-2)%mod;
61             while (siz(C)<siz(B)+m) C.push_back(0);
62             rep(i,0,siz(B)) C[i+m]=(C[i+m]+c*B[i])%mod;
63             ++m;
64         }
65     }
66     return C;
67 }
68 int gao(VI a,ll n) {
69     VI c=BM(a);
70     c.erase(c.begin());
71     rep(i,0,siz(c)) c[i]=(mod-c[i])%mod;
72     return solve(n,c,VI(a.begin(),a.begin()+siz(c)));
73 }
74 };
75
76 int main() {
77     vector<int>v;
78     v.push_back(2);
79     v.push_back(24);
80     v.push_back(96);
81     v.push_back(416);
82     v.push_back(1536);
83     v.push_back(5504);
84     v.push_back(18944);
85     v.push_back(64000);
86     v.push_back(212992);
87     v.push_back(702464);
88     scanf("%lld", &n);
89     printf("%lld\n",1LL * linear_seq::gao(v,n-1) % mod);

```



```
90 }
91
```

### 辛普森积分

```
1 double simpson(double l, double r) {
2     double mid = (l + r) / 2;
3     return (r - l) * (f(l) + 4 * f(mid) + f(r)) / 6; // 辛普森公式
4 }
5
6 double asr(double l, double r, double eps, double ans, int step) { // step 是递归的下限
7     double mid = (l + r) / 2;
8     double fl = simpson(l, mid), fr = simpson(mid, r);
9     if (abs(fl + fr - ans) <= 15 * eps && step < 0)
10         return fl + fr + (fl + fr - ans) / 15; // 足够相似的话就直接返回
11     return asr(l, mid, eps / 2, fl, step - 1) +
12           asr(mid, r, eps / 2, fr, step - 1); // 否则分割成两段递归求解
13 }
14
15 double calc(double l, double r, double eps) {
16     return asr(l, r, eps, simpson(l, r), 12);
17 }
18
```

### 高斯消元(模意义)

```
1 #define int long long
2 const int eps=0;
3 const int maxn=220;
4 const int mod=1e6+3;
5 int ksm(int x,int k){
6     int res=1;
7     while(k){
8         if(k&1)res=res*x%mod;
9         x=x*x%mod;
10        k/=2;
11    }
12    return res;
13 }
14 int ny(int x){
15     return ksm(x,mod-2);
16 }
17 void add(int &x,int y){
18     if((x+=y)>=mod)x-=mod;
19 }
20 void del(int &x,int y){
21     if((x-=y)<0)x+=mod;
22 }
23 int a[maxn][maxn],x[maxn]; // 方程左边的矩阵和方程右边的值, 求解之后 x 存的就是结果
24 int Gauss(int equ,int var){ // equ 方程数 var 未知数个数 return 1 表示有解
25     int i,j,k,col,max_r;
26     for(k=0,col=0;k<equ&&col<var;k++,col++){
27         max_r=k;
28         for(i=k+1;i<equ;i++)
29             if((a[i][col])>(a[max_r][col]))
30                 max_r=i;
31         if((a[max_r][col])==0)return 0;
32         if(k!=max_r){
```

```

33         for(j=col;j<var;j++)
34             swap(a[k][j],a[max_r][j]);
35         swap(x[k],x[max_r]);
36     }
37     x[k]=x[k]*ny(a[k][col])%mod;
38     for(j=col+1;j<var;j++)a[k][j]=a[k][j]*ny(a[k][col])%mod;
39     a[k][col]=1;
40     for(i=0;i<equ;i++)
41         if(i!=k){
42             del(x[i],x[k]*a[i][col]%mod);
43             for(j=col+1;j<var;j++)del(a[i][j],a[k][j]*a[i][col]%mod);
44             a[i][col]=0;
45         }
46     }
47     return 1;
48 }

```

### 高斯消元(浮点数)

```

1  #define lf double
2  //0 base
3  const lf eps=1e-9;
4  const int maxn=220;
5  lf a[maxn][maxn],x[maxn]; //方程左边的矩阵和方程右边的值，求解之后 x 存的就是结果
6  int Gauss(int equ,int var){ //equ 方程数 var 未知数个数 return 1 表示有解
7      int i,j,k,col,max_r;
8      for(k=0,col=0;k<equ&&col<var;k++,col++){
9          max_r=k;
10         for(i=k+1;i<equ;i++)
11             if(fabs(a[i][col])>fabs(a[max_r][col]))
12                 max_r=i;
13         if(fabs(a[max_r][col])<eps) return 0;
14         if(k!=max_r){
15             for(j=col;j<var;j++){
16                 swap(a[k][j],a[max_r][j]);
17                 swap(x[k],x[max_r]);
18             }
19         }
20         x[k]/=a[k][col];
21         for(j=col+1;j<var;j++)a[k][j]/=a[k][col];
22         a[k][col]=1;
23         for(i=0;i<equ;i++){
24             if(i!=k){
25                 x[i]-=x[k]*a[i][col];
26                 for(j=col+1;j<var;j++)a[i][j]-=a[k][j]*a[i][col];
27                 a[i][col]=0;
28             }
29         }
30     }
31     return 1;
32 }

```

# 计算几何

## 开头

```
1 #include <bits/stdc++.h>
2 using namespace std;
3
4 using point_t=long double; //全局数据类型, 可修改为 long long 等
5
6 constexpr point_t eps=1e-8;
7 constexpr long double PI=3.14159265358979323841;
8
```

## 点与向量

```
1 // 点与向量
2 template<typename T> struct point
3 {
4     T x,y;
5
6     bool operator==(const point &a) const {return (abs(x-a.x)<=eps && abs(y-a.y)<=eps);}
7     bool operator<(const point &a) const {if (abs(x-a.x)<=eps) return y<a.y-eps;
8     return x<a.x-eps;}
9     bool operator>(const point &a) const {return !(*this<a || *this==a);}
10    point operator+(const point &a) const {return {x+a.x,y+a.y};}
11    point operator-(const point &a) const {return {x-a.x,y-a.y};}
12    point operator-() const {return {-x,-y};}
13    point operator*(const T k) const {return {k*x,k*y};}
14    point operator/(const T k) const {return {x/k,y/k};}
15    T operator*(const point &a) const {return x*a.x+y*a.y;} // 点积
16    T operator^(const point &a) const {return x*a.y-y*a.x;} // 叉积, 注意优先级
17    int toleft(const point &a) const {const auto t=(*this)^a; return (t>eps)-(t<-eps);} // to-left 测试
18    T len2() const {return (*this)*(*this);} // 向量长度的平方
19    T dis2(const point &a) const {return (a-(*this)).len2();} // 两点距离的平方
20
21    // 涉及浮点数
22    long double len() const {return sqrtl(len2());} // 向量长度
23    long double dis(const point &a) const {return sqrtl(dis2(a));} // 两点距离
24    long double ang(const point &a) const {return acosl(max(-1.0l,min(1.0l,((*this)*a)/(len()*a.len()))));} // 向量夹角
25    point rot(const long double rad) const {return {x*cos(rad)-y*sin(rad),x*sin(rad)+y*cos(rad)};} // 逆时针旋转 (给定角度)
26    point rot(const long double cosr,const long double sinr) const {return {x*cosr-y*sinr,x*sinr+y*cosr};} // 逆时针旋转 (给定角度的正弦与余弦)
27 };
28 using Point=point<point_t>;
```

## 极角排序

```
1 // 极角排序
2 struct argcmp
3 {
4     bool operator()(const Point &a,const Point &b) const
5     {
6         const auto quad=[](const Point &a)
```

```

7      {
8          if (a.y<-eps) return 1;
9          if (a.y>eps) return 4;
10         if (a.x<-eps) return 5;
11         if (a.x>eps) return 3;
12         return 2;
13     };
14     const int qa=quad(a),qb=quad(b);
15     if (qa!=qb) return qa<qb;
16     const auto t=a^b;
17     // if (abs(t)<=eps) return a*a<b*b-eps; // 不同长度的向量需要分开
18     return t>eps;
19 }
20 };

```

## 直线

```

1 // 直线
2 template<typename T> struct line
3 {
4     point<T> p,v; // p 为直线上一点, v 为方向向量
5
6     bool operator==(const line &a) const {return v.toleft(a.v)==0 && v.toleft(p-
    a.p)==0;}
7     int toleft(const point<T> &a) const {return v.toleft(a-p);} // to-left 测试
8     bool operator<(const line &a) const // 半平面交算法定义的排序
9     {
10         if (abs(v^a.v)<=eps && v*a.v>=-eps) return toleft(a.p)==-1;
11         return argcmp()(v,a.v);
12     }
13
14     // 涉及浮点数
15     point<T> inter(const line &a) const {return p+v*((a.v^(p-a.p))/(v^a.v));} // 直
    线交点
16     long double dis(const point<T> &a) const {return abs(v^(a-p))/v.len();} // 点到
    直线距离
17     point<T> proj(const point<T> &a) const {return p+v*((v*(a-p))/(v*v));} // 点在直
    线上的投影
18 };
19
20 using Line=line<point_t>;

```

## 线段

```

1 // 线段
2 template<typename T> struct segment
3 {
4     point<T> a,b;
5
6     bool operator<(const segment &s) const {return make_pair(a,b)<make_pair(s.a,s.b);}
7
8     // 判定性函数建议在整数域使用
9
10    // 判断点是否在线段上
11    // -1 点在线段端点 | 0 点不在线段上 | 1 点严格在线段上
12    int is_on(const point<T> &p) const
13    {

```

```

14     if (p==a || p==b) return -1;
15     return (p-a).topleft(p-b)==0 && (p-a)*(p-b)<-eps;
16 }
17
18 // 判断线段直线是否相交
19 // -1 直线经过线段端点 | 0 线段和直线不相交 | 1 线段和直线严格相交
20 int is_inter(const line<T> &l) const
21 {
22     if (l.topleft(a)==0 || l.topleft(b)==0) return -1;
23     return l.topleft(a)!=l.topleft(b);
24 }
25
26 // 判断两线段是否相交
27 // -1 在某一线段端点处相交 | 0 两线段不相交 | 1 两线段严格相交
28 int is_inter(const segment<T> &s) const
29 {
30     if (is_on(s.a) || is_on(s.b) || s.is_on(a) || s.is_on(b)) return -1;
31     const line<T> l{a,b-a},ls{s.a,s.b-s.a};
32     return l.topleft(s.a)*l.topleft(s.b)==-1 && ls.topleft(a)*ls.topleft(b)==-1;
33 }
34
35 // 点到线段距离
36 long double dis(const point<T> &p) const
37 {
38     if ((p-a)*(b-a)<-eps || (p-b)*(a-b)<-eps) return min(p.dis(a),p.dis(b));
39     const line<T> l{a,b-a};
40     return l.dis(p);
41 }
42
43 // 两线段间距离
44 long double dis(const segment<T> &s) const
45 {
46     if (is_inter(s)) return 0;
47     return min({dis(s.a),dis(s.b),s.dis(a),s.dis(b)});
48 }
49 };
50
51 using Segment=segment<point_t>;

```

## 多边形

```

1 // 多边形
2 template<typename T> struct polygon
3 {
4     vector<point<T>> p; // 以逆时针顺序存储
5
6     size_t nxt(const size_t i) const {return i==p.size()-1?0:i+1;}
7     size_t pre(const size_t i) const {return i==0?p.size()-1:i-1;}
8
9     // 回转数
10    // 返回值第一项表示点是否在多边形边上
11    // 对于狭义多边形, 回转数为 0 表示点在多边形外, 否则点在多边形内
12    pair<bool,int> winding(const point<T> &a) const
13    {
14        int cnt=0;
15        for (size_t i=0;i<p.size();i++)

```

```

16     {
17         const point<T> u=p[i],v=p[nxt(i)];
18         if (abs((a-u)^(a-v))<=eps && (a-u)*(a-v)<=eps) return {true,0};
19         if (abs(u.y-v.y)<=eps) continue;
20         const Line uv={u,v-u};
21         if (u.y<v.y-eps && uv.toleft(a)<=0) continue;
22         if (u.y>v.y+eps && uv.toleft(a)>=0) continue;
23         if (u.y<a.y-eps && v.y>=a.y-eps) cnt++;
24         if (u.y>=a.y-eps && v.y<a.y-eps) cnt--;
25     }
26     return {false,cnt};
27 }
28
29 // 多边形面积的两倍
30 // 可用于判断点的存储顺序是顺时针或逆时针
31 T area() const
32 {
33     T sum=0;
34     for (size_t i=0;i<p.size();i++) sum+=p[i]^p[nxt(i)];
35     return sum;
36 }
37
38 // 多边形的周长
39 long double circ() const
40 {
41     long double sum=0;
42     for (size_t i=0;i<p.size();i++) sum+=p[i].dis(p[nxt(i)]);
43     return sum;
44 }
45 };
46
47 using Polygon=polygon<point_t>;

```

## 凸多边形

```

1 //凸多边形
2 template<typename T> struct convex: polygon<T>
3 {
4     // 闵可夫斯基和
5     convex operator+(const convex &c) const
6     {
7         const auto &p=this->p;
8         vector<Segment> e1(p.size()),e2(c.p.size()),edge(p.size()+c.p.size());
9         vector<point<T>> res; res.reserve(p.size()+c.p.size());
10        const auto cmp=[](const Segment &u,const Segment &v) {return argcmp()(u.b-
11        u.a,v.b-v.a);};
12        for (size_t i=0;i<p.size();i++) e1[i]={p[i],p[this->nxt(i)]};
13        for (size_t i=0;i<c.p.size();i++) e2[i]={c.p[i],c.p[c.nxt(i)]};
14        rotate(e1.begin(),min_element(e1.begin(),e1.end(),cmp),e1.end());
15        rotate(e2.begin(),min_element(e2.begin(),e2.end(),cmp),e2.end());
16        merge(e1.begin(),e1.end(),e2.begin(),e2.end(),edge.begin(),cmp);
17        const auto check=[](const vector<point<T>> &res,const point<T> &u)
18        {
19            const auto back1=res.back(),back2=*prev(res.end(),2);
20            return (back1-back2).toleft(u-back1)==0 && (back1-back2)*(u-back1)>=-eps;
21        };
22        auto u=e1[0].a+e2[0].a;

```

```

22     for (const auto &v:edge)
23     {
24         while (res.size()>1 && check(res,u)) res.pop_back();
25         res.push_back(u);
26         u=u+v.b-v.a;
27     }
28     if (res.size()>1 && check(res,res[0])) res.pop_back();
29     return {res};
30 }
31
32 // 旋转卡壳
33 // func 为更新答案的函数, 可以根据题目调整位置
34 template<typename F> void rotcaliper(const F &func) const
35 {
36     const auto &p=this->p;
37     const auto area=[](const point<T> &u,const point<T> &v,const point<T> &w)
{return (w-u)^(w-v)};};
38     for (size_t i=0,j=1;i<p.size();i++)
39     {
40         const auto nxti=this->nxt(i);
41         func(p[i],p[nxti],p[j]);
42         while (area(p[this->nxt(j)],p[i],p[nxti])>=area(p[j],p[i],p[nxti]))
43         {
44             j=this->nxt(j);
45             func(p[i],p[nxti],p[j]);
46         }
47     }
48 }
49
50 // 凸多边形的直径的平方
51 T diameter2() const
52 {
53     const auto &p=this->p;
54     if (p.size()==1) return 0;
55     if (p.size()==2) return p[0].dis2(p[1]);
56     T ans=0;
57     auto func=[&](const point<T> &u,const point<T> &v,const point<T> &w)
{return max({ans,w.dis2(u),w.dis2(v)});};
58     rotcaliper(func);
59     return ans;
60 }
61
62 // 判断点是否在凸多边形内
63 // 复杂度 O(logn)
64 // -1 点在多边形边上 | 0 点在多边形外 | 1 点在多边形内
65 int is_in(const point<T> &a) const
66 {
67     const auto &p=this->p;
68     if (p.size()==1) return a==p[0]?-1:0;
69     if (p.size()==2) return segment<T>{p[0],p[1]}.is_on(a)?-1:0;
70     if (a==p[0]) return -1;
71     if ((p[1]-p[0]).toleft(a-p[0])==-1 || (p.back()-p[0]).toleft(a-p[0])==1)
return 0;
72     const auto cmp=[&](const Point &u,const Point &v){return (u-p[0]).toleft(v-
p[0])==1;};
73     const size_t i=lower_bound(p.begin()+1,p.end(),a,cmp)-p.begin();

```

```

74     if (i==1) return segment<T>{p[0],p[i]}.is_on(a)?-1:0;
75     if (i==p.size()-1 && segment<T>{p[0],p[i]}.is_on(a)) return -1;
76     if (segment<T>{p[i-1],p[i]}.is_on(a)) return -1;
77     return (p[i]-p[i-1]).toleft(a-p[i-1])>0;
78 }
79
80 // 凸多边形关于某一方向的极点
81 // 复杂度 O(logn)
82 // 参考资料: https://codeforces.com/blog/entry/48868
83 template<typename F> size_t extreme(const F &dir) const
84 {
85     const auto &p=this->p;
86     const auto check=[&](const size_t i){return dir(p[i]).toleft(p[this->nxt(i)]-
p[i])>=0;};
87     const auto dir0=dir(p[0]); const auto check0=check(0);
88     if (!check0 && check(p.size()-1)) return 0;
89     const auto cmp=[&](const Point &v)
90     {
91         const size_t vi=&v-p.data();
92         if (vi==0) return 1;
93         const auto checkv=check(vi);
94         const auto t=dir0.toleft(v-p[0]);
95         if (vi==1 && checkv==check0 && t==0) return 1;
96         return checkv^(checkv==check0 && t==0);
97     };
98     return partition_point(p.begin(),p.end(),cmp)-p.begin();
99 }
100
101 // 过凸多边形外一点求凸多边形的切线, 返回切点下标
102 // 复杂度 O(logn)
103 // 必须保证点在多边形外
104 pair<size_t,size_t> tangent(const point<T> &a) const
105 {
106     const size_t i=extreme([&](const point<T> &u){return u-a;});
107     const size_t j=extreme([&](const point<T> &u){return a-u;});
108     return {i,j};
109 }
110
111 // 求平行于给定直线的凸多边形的切线, 返回切点下标
112 // 复杂度 O(logn)
113 pair<size_t,size_t> tangent(const line<T> &a) const
114 {
115     const size_t i=extreme([&](...){return a.v;});
116     const size_t j=extreme([&](...){return -a.v;});
117     return {i,j};
118 }
119 };
120
121 using Convex=convex<point_t>;

```

## 圆

```

1 // 圆
2 struct Circle
3 {
4     Point c;
5     long double r;

```



```

6
7     bool operator==(const Circle &a) const {return c==a.c && abs(r-a.r)<=eps;}
8     long double circ() const {return 2*PI*r;} // 周长
9     long double area() const {return PI*r*r;} // 面积
10
11     // 点与圆的关系
12     // -1 圆上 | 0 圆外 | 1 圆内
13     int is_in(const Point &p) const {const long double d=p.dis(c); return abs(d-
14     r)<=eps?-1:d<r-eps;}
15
16     // 直线与圆关系
17     // 0 相离 | 1 相切 | 2 相交
18     int relation(const Line &l) const
19     {
20         const long double d=l.dis(c);
21         if (d>r+eps) return 0;
22         if (abs(d-r)<=eps) return 1;
23         return 2;
24     }
25
26     // 圆与圆关系
27     // -1 相同 | 0 相离 | 1 外切 | 2 相交 | 3 内切 | 4 内含
28     int relation(const Circle &a) const
29     {
30         if (*this==a) return -1;
31         const long double d=c.dis(a.c);
32         if (d>r+a.r+eps) return 0;
33         if (abs(d-r-a.r)<=eps) return 1;
34         if (abs(d-abs(r-a.r))<=eps) return 3;
35         if (d<abs(r-a.r)-eps) return 4;
36         return 2;
37     }
38
39     // 直线与圆的交点
40     vector<Point> inter(const Line &l) const
41     {
42         const long double d=l.dis(c);
43         const Point p=l.proj(c);
44         const int t=relation(l);
45         if (t==0) return vector<Point>();
46         if (t==1) return vector<Point>{p};
47         const long double k=sqrt(r*r-d*d);
48         return vector<Point>{p-(l.v/l.v.len())*k,p+(l.v/l.v.len())*k};
49     }
50
51     // 圆与圆交点
52     vector<Point> inter(const Circle &a) const
53     {
54         const long double d=c.dis(a.c);
55         const int t=relation(a);
56         if (t==-1 || t==0 || t==4) return vector<Point>();
57         Point e=a.c-c; e=e/e.len()*r;
58         if (t==1 || t==3)
59         {
60             if (r*r+d*d-a.r*a.r>=eps) return vector<Point>{c+e};
61             return vector<Point>{c-e};
62         }
63     }

```

```

61     }
62     const long double costh=(r*r+d*d-a.r*a.r)/(2*r*d),sinh=sqrt(1-costh*costh);
63     return vector<Point>{c+e.rot(costh,-sinh),c+e.rot(costh,sinh)};
64 }
65
66 // 圆与圆交面积
67 long double inter_area(const Circle &a) const
68 {
69     const long double d=c.dis(a.c);
70     const int t=relation(a);
71     if (t==-1) return area();
72     if (t<2) return 0;
73     if (t>2) return min(area(),a.area());
74     const long double costh1=(r*r+d*d-a.r*a.r)/(2*r*d),costh2=(a.r*a.r+d*d-r*r)/
(2*a.r*d);
75     const long double sinh1=sqrt(1-costh1*costh1),sinh2=sqrt(1-costh2*costh2);
76     const long double th1=acos(costh1),th2=acos(costh2);
77     return r*r*(th1-costh1*sinh1)+a.r*a.r*(th2-costh2*sinh2);
78 }
79
80 // 过圆外一点圆的切线
81 vector<Line> tangent(const Point &a) const
82 {
83     const int t=is_in(a);
84     if (t==1) return vector<Line>();
85     if (t==-1)
86     {
87         const Point v={-(a-c).y,(a-c).x};
88         return vector<Line>{{a,v}};
89     }
90     Point e=a-c; e=e/e.len()*r;
91     const long double costh=r/c.dis(a),sinh=sqrt(1-costh*costh);
92     const Point t1=c+e.rot(costh,-sinh),t2=c+e.rot(costh,sinh);
93     return vector<Line>{{a,t1-a},{a,t2-a}};
94 }
95
96 // 两圆的公切线
97 vector<Line> tangent(const Circle &a) const
98 {
99     const int t=relation(a);
100     vector<Line> lines;
101     if (t==-1 || t==4) return lines;
102     if (t==1 || t==3)
103     {
104         const Point p=inter(a)[0],v={-(a.c-c).y,(a.c-c).x};
105         lines.push_back({p,v});
106     }
107     const long double d=c.dis(a.c);
108     const Point e=(a.c-c)/(a.c-c).len();
109     if (t<=2)
110     {
111         const long double costh=(r-a.r)/d,sinh=sqrt(1-costh*costh);
112         const Point d1=e.rot(costh,-sinh),d2=e.rot(costh,sinh);
113         const Point u1=c+d1*r,u2=c+d2*r,v1=a.c+d1*a.r,v2=a.c+d2*a.r;
114         lines.push_back({u1,v1-u1}); lines.push_back({u2,v2-u2});
115     }

```

```

116     if (t==0)
117     {
118         const long double costh=(r+a.r)/d,sinth=sqrt(1-costh*costh);
119         const Point d1=e.rot(costh,-sinth),d2=e.rot(costh,sinth);
120         const Point u1=c+d1*r,u2=c+d2*r,v1=a.c-d1*a.r,v2=a.c-d2*a.r;
121         lines.push_back({u1,v1-u1}); lines.push_back({u2,v2-u2});
122     }
123     return lines;
124 }
125
126 // 圆的反演
127 tuple<int,Circle,Line> inverse(const Line &l) const
128 {
129     const Circle null_c={{0.0,0.0},0.0};
130     const Line null_l={{0.0,0.0},{0.0,0.0}};
131     if (l.toleft(c)==0) return {2,null_c,l};
132     const Point v=l.toleft(c)==1?Point{l.v.y,-l.v.x}:Point{-l.v.y,l.v.x};
133     const long double d=r*r/l.dis(c);
134     const Point p=c+v/v.len()*d;
135     return {1,{(c+p)/2,d/2},null_l};
136 }
137
138 tuple<int,Circle,Line> inverse(const Circle &a) const
139 {
140     const Circle null_c={{0.0,0.0},0.0};
141     const Line null_l={{0.0,0.0},{0.0,0.0}};
142     const Point v=a.c-c;
143     if (a.is_in(c)==-1)
144     {
145         const long double d=r*r/(a.r+a.r);
146         const Point p=c+v/v.len()*d;
147         return {2,null_c,{p,{-v.y,v.x}}};
148     }
149     if (c==a.c) return {1,{c,r*r/a.r},null_l};
150     const long double d1=r*r/(c.dis(a.c)-a.r),d2=r*r/(c.dis(a.c)+a.r);
151     const Point p=c+v/v.len()*d1,q=c+v/v.len()*d2;
152     return {1,{(p+q)/2,p.dis(q)/2},null_l};
153 }
154 };
155
156 // 圆与多边形面积交
157 long double area_inter(const Circle &circ,const Polygon &poly)
158 {
159     const auto cal=[](const Circle &circ,const Point &a,const Point &b)
160     {
161         if ((a-circ.c).toleft(b-circ.c)==0) return 0.0l;
162         const auto ina=circ.is_in(a),inb=circ.is_in(b);
163         const Line ab={a,b-a};
164         if (ina && inb) return ((a-circ.c)^(b-circ.c))/2;
165         if (ina && !inb)
166         {
167             const auto t=circ.inter(ab);
168             const Point p=t.size()==1?t[0]:t[1];
169             const long double ans=((a-circ.c)^(p-circ.c))/2;
170             const long double th=(p-circ.c).ang(b-circ.c);
171             const long double d=circ.r*circ.r*th/2;

```

```

172         if ((a-circ.c).topleft(b-circ.c)==1) return ans+d;
173         return ans-d;
174     }
175     if (!ina && inb)
176     {
177         const Point p=circ.inter(ab)[0];
178         const long double ans=((p-circ.c)^(b-circ.c))/2;
179         const long double th=(a-circ.c).ang(p-circ.c);
180         const long double d=circ.r*circ.r*th/2;
181         if ((a-circ.c).topleft(b-circ.c)==1) return ans+d;
182         return ans-d;
183     }
184     const auto p=circ.inter(ab);
185     if (p.size()==2 && Segment{a,b}.dis(circ.c)<=circ.r+eps)
186     {
187         const long double ans=((p[0]-circ.c)^(p[1]-circ.c))/2;
188         const long double th1=(a-circ.c).ang(p[0]-circ.c),th2=(b-circ.c).ang(p[1]-
circ.c);
189         const long double d1=circ.r*circ.r*th1/2,d2=circ.r*circ.r*th2/2;
190         if ((a-circ.c).topleft(b-circ.c)==1) return ans+d1+d2;
191         return ans-d1-d2;
192     }
193     const long double th=(a-circ.c).ang(b-circ.c);
194     if ((a-circ.c).topleft(b-circ.c)==1) return circ.r*circ.r*th/2;
195     return -circ.r*circ.r*th/2;
196 };
197
198 long double ans=0;
199 for (size_t i=0;i<poly.p.size();i++)
200 {
201     const Point a=poly.p[i],b=poly.p[poly.nxt(i)];
202     ans+=cal(circ,a,b);
203 }
204 return ans;
205 }

```

## 判断多条线段是否有交点

```

1 // 判断多条线段是否有交点
2 // 扫描线, 复杂度  $O(n\log n)$ 
3 bool segs_inter(const vector<Segment> &segs)
4 {
5     if (segs.empty()) return false;
6     using seq_t=tuple<point_t,int,Segment>;
7     const auto seqcmp=[](const seq_t &u, const seq_t &v)
8     {
9         const auto [u0,u1,u2]=u;
10        const auto [v0,v1,v2]=v;
11        if (abs(u0-v0)<=eps) return make_pair(u1,u2)<make_pair(v1,v2);
12        return u0<v0-eps;
13    };
14    vector<seq_t> seq;
15    for (auto seg:segs)
16    {
17        if (seg.a.x>seg.b.x+eps) swap(seg.a,seg.b);
18        seq.push_back({seg.a.x,0,seg});
19        seq.push_back({seg.b.x,1,seg});

```

```

20     }
21     sort(seq.begin(), seq.end(), seqcmp);
22     point_t x_now;
23     auto cmp=[&](const Segment &u, const Segment &v)
24     {
25         if (abs(u.a.x-u.b.x)<=eps || abs(v.a.x-v.b.x)<=eps) return u.a.y<v.a.y-eps;
26         return ((x_now-u.a.x)*(u.b.y-u.a.y)+u.a.y*(u.b.x-u.a.x))*(v.b.x-v.a.x)<((x_now-
v.a.x)*(v.b.y-v.a.y)+v.a.y*(v.b.x-v.a.x))*(u.b.x-u.a.x)-eps;
27     };
28     multiset<Segment, decltype(cmp)> s{cmp};
29     for (const auto [x,o,seg]:seq)
30     {
31         x_now=x;
32         const auto it=s.lower_bound(seg);
33         if (o==0)
34         {
35             if (it!=s.end() && seg.is_inter(*it)) return true;
36             if (it!=s.begin() && seg.is_inter(*prev(it))) return true;
37             s.insert(seg);
38         }
39         else
40         {
41             if (next(it)!=s.end() && it!=s.begin() && (*prev(it)).is_inter(*next(it)))
return true;
42             s.erase(it);
43         }
44     }
45     return false;
46 }

```

## 半平面交

```

1 // 半平面交
2 // 排序增量法, 复杂度 O(nlogn)
3 // 输入与返回值都是用直线表示的半平面集合
4 vector<Line> halfinter(vector<Line> l, const point_t lim=1e9)
5 {
6     const auto check=[](const Line &a,const Line &b,const Line &c){return
a.toleft(b.inter(c))<0;};
7     // 无精度误差的方法, 但注意取值范围会扩大到三次方
8     /*const auto check=[](const Line &a,const Line &b,const Line &c)
9     {
10         const Point p=a.v*(b.v^c.v),q=b.p*(b.v^c.v)+b.v*(c.v^(b.p-c.p))-a.p*(b.v^c.v);
11         return p.toleft(q)<0;
12     };*/
13     l.push_back({{-lim,0},{0,-1}}); l.push_back({{0,-lim},{1,0}});
14     l.push_back({{lim,0},{0,1}}); l.push_back({{0,lim},{-1,0}});
15     sort(l.begin(),l.end());
16     deque<Line> q;
17     for (size_t i=0;i<l.size();i++)
18     {
19         if (i>0 && l[i-1].v.toleft(l[i].v)==0 && l[i-1].v*l[i].v>eps) continue;
20         while (q.size()>1 && check(l[i],q.back(),q[q.size()-2])) q.pop_back();
21         while (q.size()>1 && check(l[i],q[0],q[1])) q.pop_front();
22         if (!q.empty() && q.back().v.toleft(l[i].v)<=0) return vector<Line>();
23         q.push_back(l[i]);
24     }

```

```

25     while (q.size()>1 && check(q[0],q.back(),q[q.size()-2])) q.pop_back();
26     while (q.size()>1 && check(q.back(),q[0],q[1])) q.pop_front();
27     return vector<Line>(q.begin(),q.end());
28 }

```

## 圆面积并

```

1  // 圆面积并
2  // 轮廓积分, 复杂度  $O(n^2 \log n)$ 
3  // ans[i] 表示被至少覆盖了 i+1 次的区域的面积
4  vector<long double> area_union(const vector<Circle> &circs)
5  {
6      const size_t siz=circs.size();
7      using arc_t=tuple<Point,long double,long double,long double>;
8      vector<vector<arc_t>> arcs(siz);
9      const auto eq=[](const arc_t &u,const arc_t &v)
10     {
11         const auto [u1,u2,u3,u4]=u;
12         const auto [v1,v2,v3,v4]=v;
13         return u1==v1 && abs(u2-v2)<=eps && abs(u3-v3)<=eps && abs(u4-v4)<=eps;
14     };
15
16     auto cut_circ=[](const Circle &ci,const size_t i)
17     {
18         vector<pair<long double,int>> evt;
19         evt.push_back({-PI,0}); evt.push_back({PI,0});
20         int init=0;
21         for (size_t j=0;j<circs.size();j++)
22         {
23             if (i==j) continue;
24             const Circle &cj=circs[j];
25             if (ci.r<cj.r-eps && ci.relation(cj)>=3) init++;
26             const auto inters=ci.inter(cj);
27             if (inters.size()==1) evt.push_back({atan2l((inters[0]-ci.c).y,(inters[0]-
ci.c).x),0});
28             if (inters.size()==2)
29             {
30                 const Point dl=inters[0]-ci.c,dr=inters[1]-ci.c;
31                 long double argl=atan2l(dl.y,dl.x),argr=atan2l(dr.y,dr.x);
32                 if (abs(argl+PI)<=eps) argl=PI;
33                 if (abs(argr+PI)<=eps) argr=PI;
34                 if (argl>argr+eps)
35                 {
36                     evt.push_back({argl,1}); evt.push_back({PI,-1});
37                     evt.push_back({-PI,1}); evt.push_back({argr,-1});
38                 }
39                 else
40                 {
41                     evt.push_back({argl,1});
42                     evt.push_back({argr,-1});
43                 }
44             }
45         }
46         sort(evt.begin(),evt.end());
47         int sum=init;
48         for (size_t i=0;i<evt.size();i++)
49         {

```

```

50         sum+=evt[i].second;
51         if (abs(evt[i].first-evt[i+1].first)>eps)
arcs[sum].push_back({ci.c,ci.r,evt[i].first,evt[i+1].first});
52         if (abs(evt[i+1].first-PI)<=eps) break;
53     }
54 };
55
56     const auto oint=[](const arc_t &arc)
57     {
58         const auto [cc,cr,l,r]=arc;
59         if (abs(r-l-PI)<=eps) return 2.0l*PI*cr*cr;
60         return cr*cr*(r-l)+cc.x*cr*(sin(r)-sin(l))-cc.y*cr*(cos(r)-cos(l));
61     };
62
63     for (size_t i=0;i<circs.size();i++)
64     {
65         const auto &ci=circs[i];
66         cut_circ(ci,i);
67     }
68     vector<long double> ans(siz);
69     for (size_t i=0;i<siz;i++)
70     {
71         long double sum=0;
72         sort(arcs[i].begin(),arcs[i].end());
73         int cnt=0;
74         for (size_t j=0;j<arcs[i].size();j++)
75         {
76             if (j>0 && eq(arcs[i][j],arcs[i][j-1])) arcs[i+(++cnt)].push_back(arcs[i]
[j]);
77             else cnt=0,sum+=oint(arcs[i][j]);
78         }
79         ans[i]=sum/2;
80     }
81     return ans;
82 }

```

## 多边形面积并

```

1 // 多边形面积并
2 // 轮廓积分, 复杂度  $O(n^2 \log n)$ ,  $n$  为边数
3 // ans[i] 表示被至少覆盖了  $i+1$  次的区域的面积
4 vector<long double> area_union(const vector<Polygon> &polys)
5 {
6     const size_t siz=polys.size();
7     vector<vector<pair<Point,Point>>> segs(siz);
8     const auto check=[](const Point &u,const Segment &e){return !((u<e.a && u<e.b) ||
(u>e.a && u>e.b));};
9
10    auto cut_edge=[&](const Segment &e,const size_t i)
11    {
12        const Line le{e.a,e.b-e.a};
13        vector<pair<Point,int>> evt;
14        evt.push_back({e.a,0}); evt.push_back({e.b,0});
15        for (size_t j=0;j<polys.size();j++)
16        {
17            if (i==j) continue;
18            const auto &pj=polys[j];

```

```

19     for (size_t k=0;k<pj.p.size();k++)
20     {
21         const Segment s={pj.p[k],pj.p[pj.nxt(k)]};
22         if (le.toleft(s.a)==0 && le.toleft(s.b)==0)
23         {
24             evt.push_back({s.a,0});
25             evt.push_back({s.b,0});
26         }
27         else if (s.is_inter(le))
28         {
29             const Line ls{s.a,s.b-s.a};
30             const Point u=le.inter(ls);
31             if (le.toleft(s.a)<0 && le.toleft(s.b)>=0) evt.push_back({u,-1});
32             else if (le.toleft(s.a)>=0 && le.toleft(s.b)<0) evt.push_back({u,1});
33         }
34     }
35 }
36 sort(evt.begin(),evt.end());
37 if (e.a>e.b) reverse(evt.begin(),evt.end());
38 int sum=0;
39 for (size_t i=0;i<evt.size();i++)
40 {
41     sum+=evt[i].second;
42     const Point u=evt[i].first,v=evt[i+1].first;
43     if (!(u==v) && check(u,e) && check(v,e)) segs[sum].push_back({u,v});
44     if (v==e.b) break;
45 }
46 };
47
48 for (size_t i=0;i<polys.size();i++)
49 {
50     const auto &pi=polys[i];
51     for (size_t k=0;k<pi.p.size();k++)
52     {
53         const Segment ei={pi.p[k],pi.p[pi.nxt(k)]};
54         cut_edge(ei,i);
55     }
56 }
57 vector<long double> ans(siz);
58 for (size_t i=0;i<siz;i++)
59 {
60     long double sum=0;
61     sort(segs[i].begin(),segs[i].end());
62     int cnt=0;
63     for (size_t j=0;j<segs[i].size();j++)
64     {
65         if (j>0 && segs[i][j]==segs[i][j-1]) segs[i+(++cnt)].push_back(segs[i][j]);
66         else cnt=0,sum+=segs[i][j].first^segs[i][j].second;
67     }
68     ans[i]=sum/2;
69 }
70 return ans;
71 }

```

点集形成的最小最大三角形



```

1 // 点集形成的最小最大三角形
2 // 极角序扫描线, 复杂度  $O(n^2 \log n)$ 
3 // 最大三角形问题可以使用凸包与旋转卡壳做到  $O(n^2)$ 
4 pair<point_t, point_t> minmax_triangle(const vector<Point> &vec)
5 {
6     if (vec.size() <= 2) return {0, 0};
7     vector<pair<int, int>> evt;
8     evt.reserve(vec.size() * vec.size());
9     point_t maxans = 0, minans = numeric_limits<point_t>::max();
10    for (size_t i = 0; i < vec.size(); i++)
11    {
12        for (size_t j = 0; j < vec.size(); j++)
13        {
14            if (i == j) continue;
15            if (vec[i] == vec[j]) minans = 0;
16            else evt.push_back({i, j});
17        }
18    }
19    sort(evt.begin(), evt.end(), [&](const pair<int, int> &u, const pair<int, int> &v)
20    {
21        const Point du = vec[u.second] - vec[u.first], dv = vec[v.second] - vec[v.first];
22        return argcmp()({du.y, -du.x}, {dv.y, -dv.x});
23    });
24    vector<size_t> vx(vec.size()), pos(vec.size());
25    for (size_t i = 0; i < vec.size(); i++) vx[i] = i;
26    sort(vx.begin(), vx.end(), [&](int x, int y){return vec[x] < vec[y];});
27    for (size_t i = 0; i < vx.size(); i++) pos[vx[i]] = i;
28    for (auto [u, v]: evt)
29    {
30        const size_t i = pos[u], j = pos[v];
31        const size_t l = min(i, j), r = max(i, j);
32        const Point vecu = vec[u], vecv = vec[v];
33        if (l > 0) minans = min(minans, abs((vec[vx[l-1]] - vecu)^(vec[vx[l-1]] - vecv)));
34        if (r < vx.size() - 1) minans = min(minans, abs((vec[vx[r+1]] - vecu)^(vec[vx[r+1]] -
35        vecv)));
36        maxans = max({maxans, abs((vec[vx[0]] - vecu)^(vec[vx[0]] -
37        vecv)), abs((vec[vx.back()] - vecu)^(vec[vx.back()] - vecv))});
38        if (i < j) swap(vx[i], vx[j]), pos[u] = j, pos[v] = i;
39    }
40    return {minans, maxans};
41 }

```

## 点集的凸包

```

1 // 点集的凸包
2 // Andrew 算法, 复杂度  $O(n \log n)$ 
3 Convex convexhull(vector<Point> p)
4 {
5     vector<Point> st;
6     if (p.empty()) return Convex{st};
7     sort(p.begin(), p.end());
8     const auto check = [&](const vector<Point> &st, const Point &u)
9     {
10        const auto back1 = st.back(), back2 = *prev(st.end(), 2);
11        return (back1 - back2).toleft(u - back1) <= 0;
12    };
13    for (const Point &u: p)

```

```

14     {
15         while (st.size()>1 && check(st,u)) st.pop_back();
16         st.push_back(u);
17     }
18     size_t k=st.size();
19     p.pop_back(); reverse(p.begin(),p.end());
20     for (const Point &u:p)
21     {
22         while (st.size()>k && check(st,u)) st.pop_back();
23         st.push_back(u);
24     }
25     st.pop_back();
26     return Convex{st};
27 }

```

给定三点求圆心

```

1 void cal(Point& a, Point& b, Point& c){ // 圆上三点定圆心
2     double a1=b.x-a.x, b1=b.y-a.y, c1=(a1*a1+b1*b1)/2;
3     double a2=c.x-a.x, b2=c.y-a.y, c2=(a2*a2+b2*b2)/2;
4     double d =a1*b2-a2*b1;
5     X =a.x+(c1*b2-c2*b1)/d;
6     Y =a.y+(a1*c2-a2*c1)/d;
7     r=dis2(a);
8 }
9

```