

Phonemizer: Text to Phones Transcription for Multiple Languages in Python

Mathieu Bernard¹ and Hadrien Titeux¹

¹ LSCP/ENS/CNRS/EHESS/Inria/PSL Research University, Paris, France

DOI: [10.21105/joss.03958](https://doi.org/10.21105/joss.03958)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Daniel S. Katz](#) ↗

Reviewers:

- [@henrykironde](#)
- [@chrisbrickhouse](#)

Submitted: 25 October 2021

Published: 29 November 2021

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Phones are elementary sounds the speech is made of, on which syllables and words are built. The transcription of texts from their orthographic form into a phonetic alphabet is an important requirement in various applications related to speech and language processing, for instance for text to speech systems. Phonemizer is a Python package addressing precisely this issue: it transcribes a text from its orthographic representation into a phonetic one. The package is user-friendly and exposes a single `phonemize` function, also available as a command-line interface. It supports about a hundred different languages and provides end-user functionalities such as punctuation preservation, phones accentuation, tokenization at phone/syllable/word levels, as well as parallel processing of large input texts.

Statement of Need

Whereas the high-level features introduced above are implemented directly by phonemizer, the phonetic transcription itself is delegated to third party backends, wrapped in an homogeneous interface by the package. The default backend used by phonemizer is eSpeak ([Dunn & Vitolins, 2019](#)), a text to speech software built on linguistic expertise and hand written transcription rules. It transcribes text into the International Phonetic Alphabet and supports more than a hundred languages. Using MBROLA voices ([Tits & Vitolins, 2019](#)), available for 35 languages, the eSpeak backend transcribes text in the SAMPA computer readable phonetic alphabet. Festival ([Black et al., 2014](#)) is another text to speech software used as a backend for phonemizer. It is available for American English only, and uses a non standard phoneset for transcription, but this backend is the only one to meet the requirement of some applications by preserving syllable boundaries. The third phonemizer backend is Segments ([Forkel et al., 2019](#)), a Python package providing Unicode Standard tokenization routines and orthography segmentation. It relies on a grapheme to phone mapping to generate the transcription. This backend is mostly usefull for low-resource languages, for which users with linguistic expertise can write their own mappings. Six languages are provided as exemples with phonemizer: Chintang, Cree, Inuktitut, Japanese, Sesotho and Yucatec.

Text to phones transcription is a critical need in different applications related to natural language and speech processing. So far, the phonemizer package has been used in the preprocessing pipeline of various deep learning text to speech systems ([Ideas Engineering, 2021](#); [Mozilla, 2021](#); [Watanabe et al., 2018](#)). It has also been used as a preprocessing step in word segmentation studies regarding the role of speech prosody in segmentability ([Ludusan et al., 2017](#)) and the psychology of child development ([Bernard et al., 2020](#); [Cristia et al., 2019](#)). A phonetic transcription generated by the package was used to evaluate a phone discrimination task for the Zero Speech Challenge 2017 ([Dunbar et al., 2017](#)). Finally, the phonemizer is very suitable to prepare datasets for their use with the Kaldi speech recognition

41 toolkit (Povey et al., 2011), where a phonetic transcription of text is a requirement for various
42 algorithms.

43 Acknowledgements

44 We are thankful to Alex Cristia who initiated this project and to Emmanuel Dupoux for his
45 support and advices. We also thank the phonemizer users for their bug reports and features
46 requests. This work is funded by the European Research Council (ERC-2011-AdG-295810
47 BOOTPHON), the Agence Nationale pour la Recherche (ANR-17-EURE-0017 Frontcog,
48 ANR-10-IDEX-0001-02 PSL, ANR-19-P3IA-0001 PRAIRIE 3IA Institute) and grants from
49 CIFAR (Learning in Machines and Brains), Facebook AI Research (Research Grant), Google
50 (Faculty Research Award), Microsoft Research (Azure Credits and Grant), and Amazon Web
51 Service (AWS Research Credits).

52 References

- 53 Bernard, M., Thiollere, R., Saksida, A., Loukatou, G. R., Larsen, E., Johnson, M., Fibla, L.,
54 Dupoux, E., Daland, R., Cao, X. N., & Alejandrina, C. (2020). WordSeg: Standardizing
55 unsupervised word form segmentation from text. *Behavior Research Methods*, 52(1),
56 264–278.
- 57 Black, A. W., Clark, R., Richmond, K., Yamagishi, J., Oura, K., & King, S. (2014). *The*
58 *festival speech synthesis system* (Version 2.4). CSTR, University of Edinburgh. <https://www.cstr.ed.ac.uk/projects/festival>
- 59
- 60 Cristia, A., Dupoux, E., Ratner, N. B., & Soderstrom, M. (2019). Segmentability differences
61 between child-directed and adult-directed speech: A systematic test with an ecologically
62 valid corpus. *Open Mind*, 3, 13–22.
- 63 Dunbar, E., Cao, X. N., Benjumea, J., Karadayi, J., Bernard, M., Besacier, L., Anguera, X.,
64 & Dupoux, E. (2017). The zero resource speech challenge 2017. *2017 IEEE Automatic*
65 *Speech Recognition and Understanding Workshop (ASRU)*, 323–330.
- 66 Dunn, R. H., & Vitolins, V. (2019). eSpeak NG speech synthesizer. In *GitHub repository*
67 (Version 1.50). GitHub. <https://github.com/espeak-ng/espeak-ng>
- 68 Forkel, R., Moran, S., List, J.-M., Greenhill, S. J., Ashby, L., Gorman, K., & Kaiping, G.
69 (2019). *Cldf/segments: Unicode standard tokenization* (Version v2.1.3). Zenodo. <https://doi.org/10.5281/zenodo.3549784>
- 70
- 71 Ideas Engineering. (2021). Non-autoregressive transformer based neural network for text-to-
72 speech. In *GitHub repository*. GitHub. <https://github.com/as-ideas/TransformerTTS>
- 73 Ludusan, B., Mazuka, R., Bernard, M., Cristia, A., & Dupoux, E. (2017). The role of
74 prosody and speech register in word segmentation: A computational modelling perspective.
75 *Proceedings of the Association for Computational Linguistics*, 178–183.
- 76 Mozilla. (2021). Deep learning for text to speech. In *GitHub repository*. GitHub. <https://github.com/mozilla/TTS>
- 77
- 78 Povey, D., Ghoshal, A., Boulianne, G., Burget, L., Glembek, O., Goel, N., Hannemann, M.,
79 Motlicek, P., Qian, Y., Schwarz, P., Silovsky, J., Stemmer, G., & Vesely, K. (2011). The
80 kaldi speech recognition toolkit. *IEEE 2011 Workshop on Automatic Speech Recognition*
81 *and Understanding*.
- 82 Tits, N., & Vitolins, V. (2019). MBROLA. In *GitHub repository* (Version 3.3). GitHub.
83 <https://github.com/numediart/MBROLA>

- ⁸⁴ Watanabe, S., Hori, T., Karita, S., Hayashi, T., Nishitoba, J., Unno, Y., Enrique Yalta
⁸⁵ Soplin, N., Heymann, J., Wiesner, M., Chen, N., Renduchintala, A., & Ochiai, T. (2018).
⁸⁶ ESPnet: End-to-end speech processing toolkit. *Proceedings of Interspeech*, 2207–2211.
⁸⁷ <https://doi.org/10.21437/Interspeech.2018-1456>

DRAFT