0. **Code:** uppalh8095 Uppal Harsh MakeupTest2.zip

1. RaiseAPolynomialToPowerN/RaiseAPolynomialToPowerN/Program.cs

1. RaiseAPolynomialToPowerN/RaiseAPolynomialToPowerN/Program.cs

```
namespace RaiseAPolynomialToPowerN
{
    internal class Program
    {
        static void Main(string[] args)
        {
            int[] array = {
                5,
                6,
                7,
                8,
                9
            };
            int[] result = RaisePolynomial(array, 3);
            Console.WriteLine(String.Join(", ", result));
        }
        static int[] RaisePolynomial(int[] array, int n)
        {
            if (array == null || array.Length == 0 || n ≤ 0)
            {
                return null;
            }

            int new_array_length = ((array.Length - 1) * n) + 1;
            int[] result = new int[new_array_length];
            int count = new_array_length - 1;

            //Copy the initial array to the result array from the end;
            for (int i = array.Length - 1; i ≥ 0; i--)
            {
                result[count] = array[i];
```

B1

B2

B3

1. **RaiseAPolynomialToPowerN/RaiseAPolynomialToPowerN/Program.cs**

```
            count--;

        }

        int start = count + 1;
        int[] new_arr = new int[new_array_length];
        int temp = 0;
        for (int x = 1; x < n; x++)
        {

            int end = new_array_length - 1;
            for (int num = array.Length - 1; num ≥ 0; num--)
            {
                int multiply = array[num];
                int cnt = new_array_length - 1;
                for (int j = end; j ≥ start; j--)
                {
                    int add_num = result[cnt] * multiply;
                    new_arr[j] = new_arr[j] + add_num;
                    cnt--;
                    temp = j;
                }
                end--;
                start = temp;
                start--;
            }
            start++;
            for (int f = new_array_length - 1; f ≥ 0; f--)
            {
                result[f] = new_arr[f];
            }
```

B6

B4

B5

new_arr[f] = 0; ← initialize back to zero.

after adding this line, your code works!

1. **RaiseAPolynomialToPowerN/RaiseAPolynomialToPowerN/Program.cs**

```
            }



            //Calculate the power n for each el;ement and store it in a new array.
            return new_arr;

        }
    }
}
```