

## PYTHON PARAMETER PASSING & MUTABILITY (IN-DEPTH NOTES)

---

### 1 How Python passes arguments (CORE IDEA)

 Python uses “pass by object reference”

(Some books call it *pass by assignment*)

This means:

- A **reference (address) to the object** is passed to the function
  - What happens next depends on **whether the object is mutable or immutable**
- 

### 2 Mutable vs Immutable Objects

#### Immutable Objects (CANNOT change in place)


- int
- float
- bool
- str
- tuple
- None

 Any “change” creates a **new object**

---

#### Mutable Objects (CAN change in place)

- list
- dict
- set
- custom class objects

 Changes affect the **same object in memory**

---

### 3 What people mean by “Pass by Value” & “Pass by Reference”

 Python does NOT have true pass by value

 Python does NOT have true pass by reference

But to **understand**, we use these terms conceptually.

---

◆ **Pass by Value (conceptual)**

- A **copy** of the value is passed
- Changes inside function **do NOT affect original**

👉 Python behaves like this for **immutable objects**

**Example**

```
def change(x):
```

```
    x = 20
```

```
a = 10
```

```
change(a)
```

```
print(a)
```

**Output**

```
10
```

✓ Original not changed

---

◆ **Pass by Reference (conceptual)**

- A **reference to the same object** is passed
- Changes inside function **affect original**

👉 Python behaves like this for **mutable objects**

**Example**

```
def change(lst):
```

```
    lst.append(4)
```

```
a = [1, 2, 3]
```

```
change(a)
```

```
print(a)
```

**Output**

[1, 2, 3, 4]

✓ Original modified

---

### What ACTUALLY happens (Important!)

#### Example with dictionary & boolean

```
def update_data(d, flag):
```

```
    d["x"] = 100
```

```
    flag = True
```

```
my_dict = {}
```

```
my_flag = None
```

```
update_data(my_dict, my_flag)
```

```
print(my_dict)
```

```
print(my_flag)
```

#### Output

```
{'x': 100}
```

```
None
```

---

#### Memory explanation

##### Dictionary (mutable)

my\_dict —► {}

↑

d (same object)

##### Boolean (immutable)

my\_flag —► None

flag = True (new object, local only)

---

## 5 Rebinding vs Mutation (VERY IMPORTANT)

- ◆ **Mutation** → changes original

```
lst.append(10)
```

```
dict["a"] = 5
```

- ◆ **Rebinding** → creates new object

```
lst = [1, 2]
```

```
x = 100
```

```
flag = True
```

---

### ⚠ Tricky Example

```
def test(lst):
```

```
    lst = [9, 9, 9] # rebinding
```

```
a = [1, 2, 3]
```

```
test(a)
```

```
print(a)
```

### Output

```
[1, 2, 3]
```

✗ No change (rebinding, not mutation)

---

## 6 How to change immutable value outside a function

### ✓ Method 1: Return it (BEST WAY)

```
def change(x):
```

```
    return x + 10
```

```
a = 5
```

```
a = change(a)
```

---

### ✓ Method 2: Wrap inside mutable container

```
def change(flag):  
    flag[0] = True
```

```
f = [None]  
change(f)  
print(f[0])
```

---


### Tuple Question (IMPORTANT)

Given:

```
t = (10, 20, 30, 40)
```

 Is this possible?

```
t += (50)
```

 **NO — ERROR**

Because (50) is **NOT** a tuple

Python thinks it is:

```
50
```

So:

```
t += 50  TypeError
```

---

### Correct Way

```
t += (50,)
```

**Why comma is required?**

- Single-element tuple **must have a comma**

(50,)  tuple

(50)  int

---

### Important: tuple is immutable

```
t += (50,)
```

This does **NOT modify** the tuple.  
It **creates a new tuple and rebinds t**.

---

### **Proof**

```
t = (1, 2)
print(id(t))
```

```
t += (3,)
print(id(t))
```

IDs will be **different**.

---

### **One-Page Summary (WRITE THIS)**

Python passes **object references**

Mutable objects → mutation affects outside

Immutable objects → reassignment does NOT

Tuple cannot be modified, only rebound

(50,) is tuple, 50 is int