# TEST REPORT

**Document ID:** DOC-0000939
**Project:** PRJ-015
**Uploaded on:** 2024-02-08
**Uploaded by:** user177
**Export class:** EAR99

**Report No:** TR-117045
**Laboratory:** Lab South
**Test Date:** 2024-02-08

## Part P-100614 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Tensile strength | 250 - 520 MPa | 503.684 | PASS |
| Hardness | 20 - 60 HRC | 28.208 | PASS |
| Thermal cycle | 50 - 500 cycles | 378.414 | PASS |
| Salt spray | 48 - 500 hours | 468.887 | PASS |

Overall result for P-100614: PASS

## Part P-101412 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Thermal cycle | 50 - 500 cycles | 246.124 | PASS |
| Hardness | 20 - 60 HRC | 19.146 | FAIL |
| Flatness | 0.01 - 0.2 mm | 0.206 | FAIL |
| Salt spray | 48 - 500 hours | 64.734 | PASS |

Overall result for P-101412: FAIL

## Part P-101083 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Tensile strength | 250 - 520 MPa | 270.725 | PASS |
| Thermal cycle | 50 - 500 cycles | 174.129 | PASS |
| Salt spray | 48 - 500 hours | 250.269 | PASS |
| Hardness | 20 - 60 HRC | 58.202 | PASS |

Overall result for P-101083: PASS