# TEST REPORT

**Document ID:** DOC-0002314
**Project:** PRJ-011
**Uploaded on:** 2025-11-11
**Uploaded by:** user138
**Export class:** EAR99

**Report No:** TR-669912
**Laboratory:** Lab South
**Test Date:** 2025-11-11

## Part P-101009 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Dimensional check | 0.05 - 0.5 mm | 0.399 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.095 | PASS |
| Tensile strength | 250 - 520 MPa | 399.587 | PASS |
| Hardness | 20 - 60 HRC | 40.35 | PASS |

Overall result for P-101009: PASS

## Part P-101231 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Hardness | 20 - 60 HRC | 29.398 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.056 | PASS |
| Tensile strength | 250 - 520 MPa | 271.051 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.452 | PASS |

Overall result for P-101231: PASS

## Part P-101011 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Dimensional check | 0.05 - 0.5 mm | 0.105 | PASS |
| Tensile strength | 250 - 520 MPa | 564.535 | FAIL |
| Thermal cycle | 50 - 500 cycles | 246.168 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.174 | PASS |

Overall result for P-101011: FAIL