**EXPORT CONTROLLED - ECCN 3A001**

# TEST REPORT

**Document ID:** DOC-0000306
**Project:** PRJ-005
**Uploaded on:** 2023-03-28
**Uploaded by:** user114
**Export class:** ECCN-3A001

**Report No:** TR-542293
**Laboratory:** Lab North
**Test Date:** 2023-03-28

## Part P-100473 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Dimensional check | 0.05 - 0.5 mm | 0.213 | PASS |
| Hardness | 20 - 60 HRC | 33.038 | PASS |
| Tensile strength | 250 - 520 MPa | 383.925 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.044 | PASS |

Overall result for P-100473: PASS

## Part P-100136 rev C.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Thermal cycle | 50 - 500 cycles | 167.409 | PASS |
| Hardness | 20 - 60 HRC | 29.196 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.214 | FAIL |
| Salt spray | 48 - 500 hours | 98.228 | PASS |

Overall result for P-100136: FAIL

## Part P-100343 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Flatness | 0.01 - 0.2 mm | 0.113 | PASS |
| Salt spray | 48 - 500 hours | 459.891 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.176 | PASS |
| Tensile strength | 250 - 520 MPa | 523.222 | FAIL |

Overall result for P-100343: FAIL