# TEST REPORT

**Document ID:** DOC-0002547
**Project:** PRJ-019
**Uploaded on:** 2026-02-24
**Uploaded by:** user146
**Export class:** EAR99

**Report No:** TR-540678
**Laboratory:** Lab South
**Test Date:** 2026-02-24

## Part P-101690 rev B.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Flatness | 0.01 - 0.2 mm | 0.011 | PASS |
| Thermal cycle | 50 - 500 cycles | 478.611 | PASS |
| Tensile strength | 250 - 520 MPa | 559.915 | FAIL |
| Salt spray | 48 - 500 hours | 399.316 | PASS |

Overall result for P-101690: FAIL

## Part P-103441 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Thermal cycle | 50 - 500 cycles | 101.191 | PASS |
| Tensile strength | 250 - 520 MPa | 509.554 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.428 | PASS |
| Salt spray | 48 - 500 hours | 184.503 | PASS |

Overall result for P-103441: PASS

## Part P-100358 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Salt spray | 48 - 500 hours | 350.043 | PASS |
| Hardness | 20 - 60 HRC | 28.458 | PASS |
| Thermal cycle | 50 - 500 cycles | 179.659 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.132 | PASS |

Overall result for P-100358: PASS