ITAR CONTROLLED - USML CATEGORY XIX

TEST REPORT

Document ID: DOC-0002671
Project: PRJ-017
Uploaded on: 2026-04-22
Uploaded by: user070
Export class: ITAR-USML-XIX

Report No: TR-133899
Laboratory: Lab North
Test Date: 2026-04-22

Part P-102651 rev A.1

Test	Requirement	Measured	Result
Salt spray	48 - 500 hours	193.623	PASS
Dimensional check	0.05 - 0.5 mm	0.343	PASS
Hardness	20 - 60 HRC	64.185	FAIL
Thermal cycle	50 - 500 cycles	367.314	PASS

Overall result for P-102651: FAIL

Part P-104258 rev A.1

Test	Requirement	Measured	Result
Salt spray	48 - 500 hours	257.173	PASS
Hardness	20 - 60 HRC	42.613	PASS
Thermal cycle	50 - 500 cycles	501.031	FAIL
Dimensional check	0.05 - 0.5 mm	0.09	PASS

Overall result for P-104258: FAIL

Part P-100394 rev B.1

Test	Requirement	Measured	Result
Flatness	0.01 - 0.2 mm	0.155	PASS
Thermal cycle	50 - 500 cycles	248.359	PASS
Salt spray	48 - 500 hours	519.868	FAIL
Tensile strength	250 - 520 MPa	440.134	PASS

Overall result for P-100394: FAIL