# TEST REPORT

**Document ID:** DOC-0001518
**Project:** PRJ-002
**Uploaded on:** 2024-10-26
**Uploaded by:** user016
**Export class:** EAR99

**Report No:** TR-556261
**Laboratory:** Lab North
**Test Date:** 2024-10-26

## Part P-101713 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Salt spray | 48 - 500 hours | 387.836 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.39 | PASS |
| Tensile strength | 250 - 520 MPa | 290.767 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.052 | PASS |

Overall result for P-101713: PASS

## Part P-100243 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Tensile strength | 250 - 520 MPa | 483.459 | PASS |
| Thermal cycle | 50 - 500 cycles | 405.321 | PASS |
| Salt spray | 48 - 500 hours | 151.6 | PASS |
| Hardness | 20 - 60 HRC | 23.136 | PASS |

Overall result for P-100243: PASS

## Part P-101482 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Flatness | 0.01 - 0.2 mm | 0.218 | FAIL |
| Tensile strength | 250 - 520 MPa | 485.993 | PASS |
| Thermal cycle | 50 - 500 cycles | 324.819 | PASS |
| Salt spray | 48 - 500 hours | 162.136 | PASS |

Overall result for P-101482: FAIL