# TEST REPORT

**Document ID:** DOC-0001912
**Project:** PRJ-036
**Uploaded on:** 2025-05-07
**Uploaded by:** user087
**Export class:** EAR99

**Report No:** TR-464453
**Laboratory:** Central Test
**Test Date:** 2025-05-07

## Part P-101476 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Tensile strength | 250 - 520 MPa | 450.525 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.499 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.21 | FAIL |
| Salt spray | 48 - 500 hours | 421.714 | PASS |

Overall result for P-101476: FAIL

## Part P-100668 rev C.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Hardness | 20 - 60 HRC | 48.41 | PASS |
| Salt spray | 48 - 500 hours | 215.416 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.463 | PASS |
| Thermal cycle | 50 - 500 cycles | 163.959 | PASS |

Overall result for P-100668: PASS

## Part P-103053 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Flatness | 0.01 - 0.2 mm | 0.13 | PASS |
| Tensile strength | 250 - 520 MPa | 285.369 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.218 | PASS |
| Thermal cycle | 50 - 500 cycles | 418.486 | PASS |

Overall result for P-103053: PASS