# TEST REPORT

**Document ID:** DOC-0000724
**Project:** PRJ-034
**Uploaded on:** 2023-10-16
**Uploaded by:** user085
**Export class:** EAR99

**Report No:** TR-747023
**Laboratory:** Lab South
**Test Date:** 2023-10-16

## Part P-100180 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Flatness | 0.01 - 0.2 mm | 0.139 | PASS |
| Tensile strength | 250 - 520 MPa | 334.613 | PASS |
| Salt spray | 48 - 500 hours | 388.983 | PASS |
| Thermal cycle | 50 - 500 cycles | 515.378 | FAIL |

Overall result for P-100180: FAIL

## Part P-100961 rev A.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Thermal cycle | 50 - 500 cycles | 545.68 | FAIL |
| Flatness | 0.01 - 0.2 mm | 0.093 | PASS |
| Tensile strength | 250 - 520 MPa | 476.193 | PASS |
| Hardness | 20 - 60 HRC | 56.423 | PASS |

Overall result for P-100961: FAIL

## Part P-100158 rev B.1

| Test | Requirement | Measured | Result |
|---|---|---|---|
| Thermal cycle | 50 - 500 cycles | 164.052 | PASS |
| Dimensional check | 0.05 - 0.5 mm | 0.309 | PASS |
| Flatness | 0.01 - 0.2 mm | 0.194 | PASS |
| Hardness | 20 - 60 HRC | 41.941 | PASS |

Overall result for P-100158: PASS