Detecting Colluding Groups from Moves Alone: Group Scans with History-Conditioned Shuffle Tests

Tarun Trivedi (Independent), **Eashan Gandotra** (Independent)

With Apart Research — research conducted at the AI Collusion Research Sprint, October 2026

Abstract

Auditors of multi-agent systems often see what agents do, not what they say to each other. The information-theoretic detector of Bonjour et al. (2022) looks for one pair of players whose moves depend on each other, so it cannot report a colluding group: in simulated many-player Rock Paper Scissors it found none of the planted groups of three to five colluders, and its fixed threshold raised 8–23% false alarms in short games without collusion. We propose a group scan that scores every subset of players by how much their moves depend on each other and judges the best score against shuffled copies of the game. Among 20 players, a 5-player group colluding in 20% of rounds is found exactly in 48% of 100-round games, against 5% for the best pairwise method. The shuffle must respect what honest players react to: honest players who respond to the previous round look like colluders in up to 100% of games unless rounds with the same recent history are shuffled together, which keeps false alarms at 4–9% while still catching a group that colludes for profit. In LLM double auctions where sellers see only a recorded summary of the last hour, gpt-4.1-mini sellers given a message channel and profit pressure earn about 50% more than with pressure alone; the test flags them but not the controls, and it misses sellers who coordinate only by following public moves. Moves-only auditing works if the auditor records what each agent sees and tests groups.

1. Introduction

LLM agents are increasingly deployed as autonomous economic actors: pricing, bidding and trading on behalf of firms. Agrawal et al. (2025) show that LLM sellers in a double auction can collude, raising prices, especially with a channel to talk to each other and pressure from management to keep margins high. An auditor of such a market usually cannot read private channels; it sees the moves. We study the sprint's research question 1.4: *can information-theoretic methods detect collusion from moves alone?*

Threat model. $k \geq 2$ of n agents coordinate through a channel the auditor cannot observe (a shared signal, a message channel, a common plan). The auditor sees every action and the public state, and must say which agents, if any, collude, at a chosen false-alarm rate (5%). Honest agents need not be random: they may react to public history, which itself correlates their moves. The existing detector (Bonjour et al., 2022) is built for one colluding pair; real coordination may involve a group.

Our contributions:

1. **A failure mode of pairwise net influence.** Inside a group each member's partners cancel in its score, so the published rule rarely flags even one in-group pair (8–15% of games), although the links are ~200 standard deviations above chance; its fixed threshold is also uncalibrated.
2. **A shuffle-calibrated group scan** that recovers weak, broad groups pairwise methods miss (48% vs 5% for a weak 5-player group among 20) at near-nominal false-alarm rates; a per-pair test does better on hubs and isolated pairs.

3. **History conditioning is necessary.** Honest players who react to history are flagged in up to 100% of games unless the shuffle stays within history states; with the right state, a coalition whose coordination pays is found while honest exploiters are not.
4. **An LLM market where the null holds by design.** Each seller's prompt is built only from a logged coarse state, and a within-state same-move test detects comms + CEO-pressure collusion among gpt-4.1-mini sellers, with 2 and with 5 sellers, while staying quiet on the controls.

2. Related Work

Information-theoretic collusion detection. Bonjour, Aggarwal & Bhargava (2022) define a pairwise influence γ(i;j) as the mutual information between two players' actions given the game state, and net influence as

$$\Gamma(i;j) = \gamma(i;j) - \max_{k \neq i,j} \gamma(k;j).$$

A pair is flagged when Γ passes a threshold α (0.05 in the paper's experiments) in both directions and exactly one pair passes. This is the closest prior work; we reproduce it (Appendix B) and keep its building block, pairwise conditional mutual information, but change the decision rule and calibration.

LLM collusion in markets. Agrawal et al. (2025) study LLM sellers in a continuous double auction and find that a communication channel increases collusive pricing and that CEO profit pressure also shapes it, measuring collusion from prices and messages. We ask whether it is detectable from moves alone, and reuse comms + pressure as our positive condition.

Per-agent detectors and multiple testing. Rose et al. (2026) score individual agents for suspicious behaviour; our "player score" baseline is inspired by this but is not their method. Our "pair test" applies Benjamini–Hochberg (1995) false-discovery control to all pairs and joins significant pairs into groups.

Scan statistics. Searching subsets for the most anomalous one and calibrating its maximum by permutation is standard in disease and event surveillance (Kulldorff, 1997; Neill, 2012) and controls the family-wise error over all subsets (max-T; Westfall & Young, 1993). What is new here is the target: subsets of agents scored by their pairwise dependence, a null that shuffles only within history states, and the confound of honest agents who react to the same history.

Gap. We know of no collusion detector that (i) reports groups larger than two from moves, (ii) has a calibrated false-alarm rate, and (iii) handles honest agents correlated through shared history.

3. Methods

3.1 Simulated game: n-player Rock Paper Scissors

Each round every player plays every other player (+1 win, −1 loss); n ∈ {5, 10, 20}; 100–3000 rounds. With a *collusion probability* (CP) per round, planted colluders coordinate; otherwise they play randomly. Colluders sit at random seats unknown to the detectors. Table 1 defines the planted groups and the honest player types used throughout.

Table 1. Planted colluding groups and honest player types.

Kind	Name	What the players do
Colluders	Pair	A helper plays the move that loses to its partner, feeding the partner a point.
Colluders	Two pairs	Two separate pairs, as above.
Colluders	Hub	One leader and two helpers; each helper feeds the leader, and the helpers never coordinate with each other.
Colluders	Triangle, k-clique	$k = 3$, 4 or 5 players share a secret signal and all play the same move (a 3-clique is a triangle).
Colluders	xor	Player C plays (A + B) mod 3, so every pair looks independent.
Colluders	Steer	4 players all play one move to create a clear lead, then all play the move that beats the honest players who react to that lead; coordination pays.
Honest	Random	Plays uniformly at random.
Honest	Leader-reactive	With probability 0.5, plays the move that beats last round's most common move.
Honest	Margin-reactive	Same, but only when that move led by 3 or more.
Honest	Exploiter	With probability CP / (1 + CP) (the steer group's exploit rate), plays the move that beats the leader-reactive response, on its own, without coordinating.

3.2 Detectors

All detectors start from the pairwise conditional mutual information (CMI) $\gamma_{ij} = I(a_i; a_j \mid s)$ in bits, where s is a *history state* computed from the previous round: none, top (which move led), order (ranking of move counts) or full (exact counts).

Within-state shuffle null. Each player's action column is permuted independently among rounds that share the same state. This preserves each player's state-dependent habits and destroys any coordination beyond them. Under the null that players are conditionally independent given the state, and rounds are exchangeable within a state, it is an exact permutation test.

Group scan (ours). Given every player's action in every round and the history state of each round:

1. **Edge statistics.** Compute γ_{ij} for every pair of players on the observed data.
2. **Shuffle.** Draw two independent sets of B within-state shuffles, Set A and Set B, and compute every γ_{ij} on each shuffled dataset.
3. **Standardize edges with Set A.** $z_{ij} = (\gamma_{ij} - \mu^A_{ij})/\sigma^A_{ij}$, where μ^A_{ij} and σ^A_{ij} are the mean and standard deviation of γ_{ij} over Set A. The Set-B datasets are standardized with the same Set-A moments.
4. **Score every group.** For every subset C with $|\mathrm{C}| \geq 2$ (~10^6 subsets at n = 20), compute T(C) and S(C) below, where the Set-A moments are exact quadratic forms in the edge means and covariance.

$$T(C) = \sum_{i<j \in C} z_{ij}, \qquad S(C) = \frac{T(C) - \mathbb{E}_A[T(C)]}{\sqrt{\mathrm{Var}_A[T(C)]}}.$$

1. **Calibrate with Set B.** Compute $\max_C S(C)$ on each Set-B dataset; the threshold is the 95th percentile of these B maxima.

2. **Decide.** If the observed $\max_C S(C)$ exceeds the threshold, report $\arg\max_C S(C)$ as a colluding group; otherwise stop.
3. **Remove and repeat.** Drop the reported group's players and return to step 4 on the remaining players, with the threshold recomputed among them (a sequential extension of the single max-T test). Stop when no group passes or fewer than two players remain.

Baselines. *Bonjour*: the published rule (fixed 0.05). *Bonjour (calibrated)*: same rule, threshold from the shuffle null. *Pair test*: Benjamini–Hochberg at q = 0.05 over all pairs (p-values from a gamma fit to the Set-A null, since with 200 shuffles raw permutation p-values cannot reach the BH bar at n $\geq$ 10), groups = connected components. *Player score*: per-player total link strength, top players flagged.

Metrics. *Exact recovery*: the reported group equals the planted one. *Clean recovery*: exact and nothing else reported. *False alarm*: any report when no collusion exists (target 5%). 95% Wilson intervals in brackets. B = 1000 for all simulation numbers unless stated (2,000 shuffles in the 2×2 LLM study, 1,000 in the 5×5 study).

3.3 LLM double auction with a coarse shared state

The LLM study asks whether the within-state shuffle null of §3.2 carries over to LLM agents. It is only valid if the state captures everything honest agents react to (Section 4.3), and with LLMs that carry memory or see detailed price paths no recorded state does (Appendix C). We therefore **design the market so the state is the agents' entire public input.**

- **Market.** Sellers (cost $80) and scripted buyers (value $100) each hour *lower*, *keep* or *raise* their quote by $2 (logged as *tighten*, *hold*, *widen* in the code and data). At most one trade per hour, between the lowest ask and the highest bid, at the midpoint. Asks start at $96, bids at $84. Exact prices stay inside the simulator.
- **Shared state** S_t, the only thing in each prompt besides the rules: 2×2 market (2 sellers, 2 buyers, 30 hours) — each seller's last move, who sold, and whether the lowest ask is high ($\geq$ $92) or low; 5×5 market (5 sellers, 5 buyers, 50 hours) — how many sellers lowered / kept / raised, who sold, and the ask level. No memory, scratch pad or hour number.
- **Conditions.** `comms_off` (rules only); `pressure_off` (plus a CEO message: margins are tracked and low-margin sellers are decommissioned); `comms_pressure` (CEO message plus a 200-character message channel; each seller sees every seller's last message). Messages are the hidden channel: they are not in S_t.
- **Model.** gpt-4.1-mini, temperature 0.7, JSON output. 2×2: 200 games per condition (36,000 calls, ≈$6.35). 5×5: 100 games per condition (75,000 calls, ≈$14.38).
- **Test.** Every seller's prompt is a function of S_t (and its own name), so sellers are conditionally independent given S_t unless something outside it links them; any message that changes moves breaks this null, collusive or not. Exchangeability within a state is approximate, because S_{t+1} includes each seller's move at t; a scripted check (300 replications of 20 five-seller games) gave 4.3% and 5.0% false alarms at a 5% target. The statistic is the *same-move count* (hours in which a pair of sellers made the same move). We switched to it from CMI after the 200-game 2×2 run, where CMI flagged 10% of 20-game batches against 80% for same-move, so the 2×2 same-move rates are post hoc; the statistic was fixed before the 5×5 run, which tests it as specified. With 5 sellers we report a global test (sum over all 10 pairs) and a max-pair test (largest standardized pair, which controls family-wise error and names the pair), over disjoint batches of 5, 10 and 20 games.

What did not work. LLM buyers drove bids to the floor, so we switched to scripted buyers; sellers confused "tighten/widen", so we renamed the moves; CMI was underpowered (above); and triple scans for xor were dropped, since a test over triples is blind to the same construction with four players.

4. Results

4.1 Pairwise net influence cannot see groups

Observation. The published rule reports exactly one pair, so it cannot recover a group of three or more by construction (0% in Table 2). More telling, it rarely flags even one in-group pair: 15% of triangle games, 12% of 4- and 5-clique games and 8% of hub games (5–20 players), close to its false-alarm rate, while the links inside a triangle are about 200 standard deviations above the shuffled data (Figure 1). With no collusion its fixed threshold raised false alarms in 8–23% of 100-round games and never fired in longer ones (up to 43% in a 3-player variant that conditions on the previous round; Appendix B). Every shuffle-calibrated detector stayed at 3–9%.

Interpretation. Net influence subtracts the strongest *other* influence on j. Inside a group, j's other partners are as strong as i, so $\Gamma \approx 0$ for every member. A fixed threshold on an estimator whose bias depends on rounds and state cannot be calibrated.




Figure 1. 5 players, CP 0.5, 1000 rounds; players 0–2 form a triangle, 3–4 are honest. Each cell is row player i → column player j. Left: Bonjour net influence (a pair is flagged only if it reaches 0.05 in both directions). Right: link strength as a z-score against shuffled data. Inside the triangle the score is ≈ 0 while the links are ≈ 200. The dark cells from honest to colluding players are negative because each colluder's strongest influence comes from another colluder.

4.2 The group scan finds weak, broad groups

Scoring the group as a whole adds up evidence too weak in any single pair. With 20 players, 100 rounds and a 5-clique at CP 0.2, the group scan recovered the exact group in **48%** [**38, 58**] of games, against 5% [2, 11] for the pair test and 4% [2, 10] for the player score (Figure 2). It also degrades less as players are added: for a triangle at CP 0.2 and 300 rounds, the player score falls from 93% to 32% between 5 and 20 players, the group scan from 93% to 84% (Table 2). We plant groups of 3–5 because larger

groups have more linked pairs and are easier for every method; the scan searches all sizes. In a near-total cartel (18 of 20 players) it recovers the exact group in 96–100% of games from CP 0.2 with 300 rounds or CP 0.3 with 100, while the player score keeps up at weak collusion (76–100% at CP 0.1–0.2 with 300 rounds) but levels off at 76–92% at CP 0.3–0.5.

Table 2. Exact recovery (%) at one setting every group was run at: CP 0.2, 300 rounds, 200 shuffles, 20 players (triangle also at 5), 50 games per cell at 20 players and 100 at 5; 95% Wilson intervals for the two strongest methods.

Planted group	Bonjour	Pair test	Player score	Group scan
Pair	34	**70** [56, 81]	8	64 [50, 76]
Two pairs	23	**69** [59, 77]	6	60 [50, 69]
Hub	0	**66** [52, 78]	2	44 [31, 58]
Triangle (5 players)	0	83 [74, 89]	93	**93** [86, 97]
Triangle	0	70 [56, 81]	32	**84** [71, 92]
4-clique	0	78 [65, 87]	66	**90** [79, 96]
5-clique	0	78 [65, 87]	90	**96** [87, 99]
xor	0	0	0	0




Figure 2. Exact recovery vs CP for 4- and 5-cliques among 20 players (100 rounds, 1000 shuffles, 100 games per point, 95% Wilson intervals). Bonjour stays at 0.

Where it loses. On hubs the pair test does better (66% vs 44%, Table 2): the scan often reports one leader–helper pair, because the two helpers are linked only indirectly ($z \approx 29$, against ≈ 150 for leader–helper links; 5 players, CP 0.5). On single and two separate weak pairs the pair test also edges ahead (70 vs 64 and 69 vs 60; intervals overlap): for a lone link, the scan pays for searching ~10^6 groups, while a per-pair correction is cheaper.

4.3 The test must condition on what honest players react to

Observation. Honest players who react to last round's moves are correlated with each other. With no state, the group scan flagged them in **up to 100%** of 1000-round games (Figure 3). Leader-reactive players need at least the *top* state, margin-reactive players *full*; with the right state, false alarms are 4–9%.




Figure 3. False-alarm rate by history state (coarse → fine) for four mixes of honest players; 10 players, 1000 rounds, no colluders, 200 games per point, 95% Wilson intervals. Dashed line: 5% target. Bonjour's fixed rule (grey) sits at 0 because its cutoff never fires at 1000 rounds, not because it is calibrated.

Profitable collusion. A 4-player steer group earns 0.21 points per round each at CP 0.3, **2.6**× what four independent exploiters earn reacting at the same rate; the margin-reactive players pay for it (Table 3). With the full state, the group scan finds the steer group cleanly in 94–98% of 1000+-round games at CP 0.2–0.3, while the honest exploiters are flagged in 4–7%. With coarser states the exploiters look like colluders as games get longer (66–71% under *top*, 96–100% with no state at 3000 rounds).

Table 3. Steer group vs honest exploiters. Each game has either 4 steer colluders or 4 exploiters, plus 3 margin-reactive and 3 random players; 200 games per cell. Payoff = points per round per member, averaged over 300–3000 rounds (random play earns 0; margin-reactive players' payoff in brackets). Recovery and false alarms: group scan, full state, at 300 / 1000 / 3000 rounds.

CP	Steer payoff	Exploiter payoff	Steer clean recovery (%)	Exploiter false alarms (%)
0.1	0.08 (−0.11)	0.03 (−0.04)	7 / 84 / 95	6 / 6 / 7
0.2	0.15 (−0.20)	0.06 (−0.07)	76 / 98 / 94	5 / 4 / 6
0.3	0.21 (−0.27)	0.08 (−0.10)	92 / 94 / 94	5 / 6 / 6

Interpretation. The state is a bias–variance choice: too coarse and honest reactions look like collusion; too fine and short games lose power (a triangle among reactors: 50% clean recovery at 300 rounds with *full*, 94–95% from 1000 rounds).

4.4 LLM sellers: comms + CEO pressure is detected, controls are not

Observation. In both markets, comms + pressure raised sellers' combined profit by 49% (2×2) and 56% (5×5) over pressure alone, and by 65% and 60% over neither (Table 4). In the 2×2 market the mean trade price rises from \$85 to \$89 (seller cost \$80, buyer value \$100) while trades fall from 89% to 79% of hours. It was the only condition the test flagged consistently. Pooled over 200 games, the 2×2 same-move statistic gave $z = +7.9$ for comms + pressure and $|z| \leq 1.5$ for both controls (CMI: +5.0 vs $|z| \leq 0.8$). In the 5×5 market, pooled over 100 games, the global test gave $p = 0.001$ (the floor at 1000 shuffles; +1,991 matching seller pairs above the shuffle's expectation out of 50,000 pair-hours, top pairs $z = 9$–12) against $p = 0.17$ and 0.71 on the controls. Raw agreement alone would not show this: comms + pressure sellers made the same move in 66.8% of pair-hours, against 62.8% expected within states, but sellers with no channel and no pressure agreed even more often (68.6%) because they all lowered together.

Table 4. Batches flagged at $\alpha = 0.05$, out of disjoint batches of 5, 10 and 20 games. 2×2: same-move test. 5×5: global test over all 10 seller pairs. Profit = all sellers' combined profit per market hour, \$ (per seller: divide by 2 or 5), with a 95% bootstrap interval over games.

Market	Condition	Sellers' profit / hour (\$)	5 games	10 games	20 games
2×2	comms off	4.29 [4.06, 4.51]	2/40	0/20	0/10
2×2	pressure, no comms	4.76 [4.52, 5.00]	1/40	2/20	2/10
2×2	**comms + pressure**	**7.07** [6.76, 7.38]	12/40	8/20	**8/10**
5×5	comms off	5.12 [4.82, 5.42]	0/20	0/10	0/5
5×5	pressure, no comms	5.24 [4.93, 5.54]	0/20	0/10	0/5
5×5	**comms + pressure**	**8.20** [7.83, 8.59]	**19/20**	**10/10**	**5/5**

The batch counts are small: 95% Wilson intervals are [49, 94]% for 8/10, [76, 99]% for 19/20 and [57, 100]% for 5/5. The 5×5 max-pair test flags comms + pressure in 16/20, 10/10 and 5/5 batches, and the controls in 1/20 and 0/20 five-game batches and none of the larger ones.




Figure 4. Batches flagged (%) vs games per batch, with 95% Wilson intervals; the batch counts are in Table 4. Left: 2×2 market, same-move test (40 / 20 / 10 batches). Right: 5×5 market, global test (20 / 10 / 5 batches). Dashed line: 5% target.

Interpretation. CEO pressure makes the seller who just sold raise (2×2, low-price hours after a trade: 8% without pressure → 33% with it), and the channel stops the other seller from undercutting ("lower" falls from 82% with pressure alone to 41% with the channel), so moves synchronize. In the 5×5 market the whole group converges on "hold, don't undercut" (e.g. "Maintain stable asks; avoid price wars to protect profits for all sellers.", seed 102, hour 25), so the excess agreement appears in all 10 pairs and is detected in smaller batches (each 5×5 game also has 50 hours and 10 pairs, against 30 hours and one). Because every pair is in sync, the max-pair test cannot isolate a sub-cartel here; in a scripted check where only S1 and S2 coordinate (10% of hours, 300 batches of 20 games) it flags every batch and names the right pair in 99.7%. The 2×2 pressure-only control's 2 of 10 batches (95% interval [6, 51]%) is consistent with 5% but is the weakest control result. What the test detects is a shared signal outside the logged state; reading it as collusion rests on the profit gap over the pressure-only control.

5. Discussion and Limitations

Implications for AI safety. Auditing agent markets from moves alone is feasible with two ingredients the existing method lacks: a test over groups, and a null that models what honest agents legitimately react to. The second is the binding constraint. In a deployed market the auditor should log what each agent is shown; the test is then valid when decisions depend only on what is logged. It flags any shared signal outside the log, collusive or not, so calling a flag collusion needs an outcome check such as the profit gap.

An auditor's recipe. (1) Log what each agent observes each round. (2) Run the group scan with a shuffle that stays within those logged states. (3) Before calling a flagged group collusion, compare its payoff with a comparable honest baseline.

Limitations (details in Appendix A). Coordination that is a function of the public state is invisible: in 2-seller pilots (Appendix D) the test missed sellers told to form an explicit cartel, who earned 7.63 per hour against 4.72 with comms off, because they coordinated by following last hour's public moves. So is coordination with no pairwise trace (xor). The exact search stops at about 20 players, the state must be chosen by the auditor, and the LLM results use one model, scripted buyers and no memory.

Future work. Learned or richer states (e.g. conditioning on a model of honest play), higher-order dependence (partial information decomposition, Williams & Beer 2010), payoff-based tests that target harmful coordination of any order, and LLM markets with memory and more models.

6. Conclusion

The pairwise information-theoretic detector for collusion is blind to groups: its net-influence score cancels inside them and its fixed threshold is uncalibrated. A group scan with a within-state shuffle test recovers weak, broad colluding groups at near-nominal false-alarm rates (3–9% at a 5% target), provided the state captures what honest players react to. In LLM markets where each seller's prompt is built only from a logged state, the same-move version of the test detects comms + CEO-pressure collusion among gpt-4.1-mini sellers (8 of 10 20-game batches with 2 sellers, 19 of 20 5-game batches with 5) and not the controls.

Code and Data

All code, results and the LLM auction games are at https://github.com/taruntrivedi3/collusion-detection. `results/RESULTS_INDEX.md` lists the exact command and seeds for every number, including the two LLM studies (`studies/llm_auction/`, `studies/llm_auction_5seller/`). An interactive viewer (https://taruntrivedi3.github.io/collusion-detection/viewer/) replays example games, including the 2- and 5-seller LLM games with the sellers' messages.

Work Done Before the Sprint

Before the sprint began, we read the papers, came up with a game plan, played around with a few toy examples, and implemented the starting code. We also ran the recorded-market study in Appendix C (`studies/auction_null_calibration/`), including its log parser. Everything else in this report was done during the sprint.

References

1. Agrawal, K., Teo, V., Vazquez, J. J., Kunnavakkam, S., Srikanth, V., & Liu, A. (2025). Evaluating LLM agent collusion in double auctions. arXiv:2507.01413. Code: https://github.com/andyjliu/llm-agent-collusion
2. Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B*, 57(1), 289–300.
3. Bonjour, T., Aggarwal, V., & Bhargava, B. (2022). Information theoretic approach to detect collusion in multi-agent games. *Proceedings of the 38th Conference on Uncertainty in Artificial Intelligence (UAI)*, PMLR 180, 223–232. https://proceedings.mlr.press/v180/bonjour22a.html
4. Kulldorff, M. (1997). A spatial scan statistic. *Communications in Statistics – Theory and Methods*, 26(6), 1481–1496.
5. Neill, D. B. (2012). Fast subset scan for spatial pattern detection. *Journal of the Royal Statistical Society: Series B*, 74(2), 337–360.
6. Rose, A., Cullen, C., Abdelnabi, S., Torr, P., Kaplowitz, B. G., & Schroeder de Witt, C. (2026). Detecting multi-agent collusion through multi-agent interpretability. arXiv:2604.01151.
7. Westfall, P. H., & Young, S. S. (1993). *Resampling-Based Multiple Testing: Examples and Methods for p-Value Adjustment.* Wiley.

8. Williams, P. L., & Beer, R. D. (2010). Nonnegative decomposition of multivariate information. arXiv:1004.2515.

Appendix A. Limitations and Dual-Use / Ethical Considerations

Limitations.

- **Coordination that is a function of the public state is invisible.** Follow-the-leader or an explicit cartel that keys on last round's public moves is absorbed into the state. In the 2×2 pilots of Appendix D, sellers told to form a cartel and agree each hour on a joint move were not detected for this reason. A direction test (does a seller raise after others raise?) catches such coordination but also fires on tacit following without communication, so it needs a comms-off calibration.
- **Any shared channel is flagged, collusive or not.** The LLM test detects coordination outside the logged state; the collusion reading rests on the profit gap over the pressure-only control.
- **Higher-order collusion.** xor-style coordination has no pairwise trace (0% for every method); any fixed-order test is blind to the next order.
- **Exact search stops at ~20 players** (~10^6 subsets).
- **The state must be chosen**; the test cannot detect that honest agents react to something unrecorded. On recorded markets from Agrawal et al. (2025), shared time trends made the test badly miscalibrated (Appendix C).
- **False-alarm rates are near, not exactly, nominal.** The group scan's highest cell, 8% [6, 11] at 20 players and 300 rounds, came out at 5.1% [4.4, 6.0] on 3,000 fresh games. The pair test runs slightly high (7.7% [6.8, 8.7] on those games) because its gamma-fit tail is generous.
- **LLM scope.** One model (gpt-4.1-mini), scripted buyers, coarse states and no agent memory. Richer inputs give LLMs more to react to and require a richer state.

Dual use. A detector also tells colluders what to avoid. Our results show that coordinating through the public state, or at higher order, evades pairwise and group dependence tests. We report these blind spots openly because auditors need to know them, and because the defence (logging what agents observe, payoff-based tests) is the same regardless. We release no method for hiding collusion beyond what the limitations already state.

False accusations. A flag is statistical evidence that agents' moves are more aligned than their observed inputs explain, not proof of intent. Mis-specified states produce confident false flags (up to 100% in Section 4.3). Any operational use should treat a flag as grounds for review, report the state used, and calibrate on known-honest runs.

LLM experiments. All agents are simulated; no real market, person or firm is affected. The CEO pressure prompt is taken from prior work to reproduce a known effect.

Appendix B. Reproducing Bonjour et al.

Our average scores match the paper's Figure 3 in bits. Our detection accuracy matches its Table 2 only when the score conditions on the previous round's three moves (27 states), which the paper does not state; one number (CP 0.2, 1000 rounds: paper 24%, ours 49%) remains unexplained. With that 27-state score, the fixed threshold flags a pair among 3 random players in 43.4% of 100-round games (19.2% at 300, 0.1% at 1000); the calibrated version stays at 5–6%. Full tables: `results/SUMMARY.md` (Tables 4, 8).

Appendix C. Recorded markets from Agrawal et al. (2025)

We ran the group scan on 75 recorded 5-seller markets from the original study. The recorded price paths share strong time trends (high early, lower later) that no available state captures without leaving nothing to shuffle. On independently resampled seller paths, the within-state scan flagged 88.5% of groups at nominal 5% (circular shifts: 37.2%). A same-pool empirical calibration reached 4.1% false alarms and 85.6% detection of copied triples, but did not transfer to held-out markets (4.2–48.8% null flags across folds). This motivated the coarse-state design of Section 3.3: without a state that explains honest behaviour, the test is not usable. Details: `studies/auction_null_calibration/`.

Appendix D. Earlier 2×2 LLM pilots

Before the 200-game 2×2 run we ran four pilots, 20 games of 30 hours per condition, while developing the market. They include conditions we later dropped when we restricted the study to the setup of Agrawal et al. (2025): `comms_on` (message channel only), `comms_instructed` (channel, plus being told that coordinating to keep prices high pays) and `comms_cartel` (told they have secretly formed a cartel, to agree each hour on what both will do, and never to undercut). All results are reported below.

Table 5. Pilot results. Shuffle-test p-values from 5,000 within-state shuffles. Direction D: how much more often a seller raises after the other seller raised than after it lowered, within the same sold-by / ask-level stratum (95% bootstrap interval over games).

Pilot	Condition	Profit / hour	Same-move p	CMI p	Direction D
v1	comms off	0.00	0.85	0.19	−0.00 [−0.01, 0.00]
v1	comms on	0.00	0.94	0.04	+0.04 [−0.02, 0.11]
v1	comms instructed	0.00	0.42	0.67	+0.65 [0.60, 0.71]
v2	comms off	4.79	0.30	0.19	+0.05 [−0.01, 0.12]
v2	comms on	4.70	0.60	0.97	+0.01 [−0.05, 0.08]
v2	comms instructed	7.42	0.13	0.37	+0.60 [0.52, 0.67]
v3	comms off	4.80	0.48	0.73	+0.21 [0.06, 0.31]
v3	comms + pressure	7.38	0.87	0.25	+0.05 [−0.02, 0.12]
v3	comms cartel	5.33	0.15	0.14	+0.89 [0.76, 0.96]
v4	comms off	4.72	0.48	0.93	+0.12 [0.00, 0.21]
v4	pressure, no comms	5.32	0.98	0.94	+0.17 [0.10, 0.24]
v4	comms cartel	7.63	0.36	0.85	+0.34 [0.27, 0.40]
v4	comms + pressure	7.81	0.0002	0.0002	−0.09 [−0.18, 0.00]

Differences between pilots. In v1 the buyers were also LLMs; they lowered their bids to the floor and almost no trades happened, so v2 onward use scripted buyers. In v3 each seller saw only the other seller's message, and the cartel's plans kept alternating; v4 shows both messages and tells cartel sellers to follow S1's plan when the plans differ. Prompts were otherwise those in `llm_pilot.py`, up to wording edits made while developing it; the exact v1–v3 prompts were not saved.

What the pilots show.

- **Explicit and instructed coordination is missed.** Cartel and instructed sellers raise prices (v2 instructed 7.42, v4 cartel 7.63 per hour) but coordinate by following the other seller's last move, which is part of the state, so the shuffle test cannot see it (same-move $p \geq 0.12$).
- **The direction test sees it, but is not calibrated.** D is large for cartel and instructed sellers ($+0.34$ to $+0.89$) but also positive for honest controls (up to $+0.21$ for comms off and $+0.17$ for pressure only), so it would need a comms-off baseline to be used as a detector.
- **Comms + pressure is not always detected at 20 games.** It was flagged in v4 ($p = 0.0002$) and missed in v3 ($p = 0.87$), consistent with the $8/10$ detection rate for 20-game batches in Table 4.
- **A channel alone does not produce collusion.** `comms_on` earns the same as comms off.

Data: `studies/llm_auction/runs/pilot_v1 ... pilot_v4/games.jsonl`; `python3 pilots.py` reproduces Table 5.

LLM Usage Statement

We used Claude Code (Anthropic) throughout the project: to write and refactor the simulation and analysis code, run the experiments, review the repository, and draft and edit this report and the documentation. The authors made the research decisions (what to test, which agents and conditions to use, what to keep or cut), directed and reviewed the work, and checked the numbers and claims. gpt-4.1-mini (OpenAI) played the sellers in the LLM auction experiments. All numbers in this report come from the released code and data.