

Send to R — Setup & Test Checklist

Shopping List App · tasar1-ship-it.github.io/shopping · Direction in this checklist: wife sends, Ronald receives. For the reverse, swap every “your” and “her”.

Part A — Confirm the fixed build is deployed (Mac, 1 minute)

In Terminal, run:

```
grep APP_V ~/Downloads/shopping/index.html
```

Pass: shows **APP_V='1751...'** (a long number) — the new build is deployed. Continue to Part B.

Fail: shows **__BUILD__** or “No such file” — the deploy never completed. Restore the repo (paste block in chat), download the design file, run **deploy**, repeat A1.

Part B — **Get both phones onto the new build** (2 minutes)

On each phone, fully close the app: swipe it away in the app switcher (home-screen icon) or close the Safari tab completely.

Reopen tasar1-ship-it.github.io/shopping/

Proof the new build loaded: **Shopping and Completed are empty** (each deploy auto-clears them — expected, not a bug). Template is untouched. If old items are still visible, the phone is on the cached version: close and reopen again.

■ **Never use Settings → Safari → “Clear History and Website Data” to force a refresh. It wipes the device ID and silently breaks the pairing — the #1 way this feature dies.**

Part C — Check cloud connection (both phones, 10 seconds)

Look at the bar under the title: ● **My ID: XXXXXX**

Green dot on both phones → cloud connected. Continue.

Red dot → **Firestore problem**. Go to console.firebase.google.com → Realtime Database → Rules → must be **.read: true, .write: true** → Publish. Then repeat B1–B2.

Part D — Pairing (the codes)

The rule: the **sender's phone stores the receiver's code**. She **sends to you** → her phone stores **your code**.

Your phone: read the 6-letter code in the header (My ID). Write it down exactly. Codes never contain the letters I, L, O or the digits 0, 1 — if you think you see one, you are misreading it.

Her phone: go to the Shopping tab and **add one item first** (e.g. “test”) — the Send buttons only appear when the list has at least one item.

Her phone: tap **“Setup Send to R”** (first time) or the **gear icon** next to the Send button (already set up) → type your code → **Save**.

Verify: her header now shows **Paired: XXXXXX** — it must match your header's My ID letter for letter. If not, repeat D3.

Part E — Live test (30 seconds)

Your phone: app open, on screen, Shopping tab.

Her phone: with 1–2 test items in Shopping, tap “**Send to R (2)**”. Pass: her phone toasts “**2 items sent!**”. Fail (“Send failed”): her dot is red → back to Part C.

Your phone, within ~5 seconds: toast “**2 items received!**” and the items appear in Shopping. Nothing after 10 seconds: press the home button, then reopen the app (this triggers a forced inbox check). Still nothing: fully close and reopen — sent items wait safely in the cloud and are delivered at startup; they are not lost.

Still failing? Screenshot **both** phones' header bars (dot + My ID + Paired) and send them to Claude — the remaining cause is identifiable in one look.

Facts to remember

Items sent while your app is closed are **not lost** — they arrive the next time you open the app. No push notification is possible; it is a web app.

Every **deploy** wipes Shopping + Completed on **both phones** at their next open. Template, pairing, and language always survive.

Sent items **merge** into the receiver's list — nothing on the receiving phone is overwritten. Duplicates are possible if both added the same thing.

Each phone keeps its own lists. Sending **copies** items; it does not sync lists.