Inventories

Ansible Fundamentals

Agenda

- Inventory Basics
- Adding Vars to Hosts

Inventory Basics

Inventory

What is inventory?

- Inventory is a list of machines that can be used on your ansible commands
- Inside inventory you must define groups that allow you to identify your servers on a easy way
- Inventory may be referenced in different ways following this precedence list
  - Command Line **`-i`** Option
  - **`ANSIBLE_INVENTORY`** Environment Variable
  - **`ansible.cfg`** Configuration File:
  - Default Inventory Path: **`/etc/ansible/hosts`**
- Some best practices: [Ansible Best Practices]

Inventory Format

- You may use two formats: INI and YAML

```
mail.example.com

[webservers]
foo.example.com
bar.example.com

[dbservers]
one.example.com
two.example.com
three.example.com
```

INI

```yaml
ungrouped:
  hosts:
    mail.example.com:
webservers:
  hosts:
    foo.example.com:
    bar.example.com:
dbservers:
  hosts:
    one.example.com:
    two.example.com:
    three.example.com:
```

YAML

Default groups

- Even if you do not define any groups in your inventory file, Ansible creates two default groups: **all** and **ungrouped**
- The **all** group contains every host
- The **ungrouped** group contains all hosts that don't have another group aside from **all**
- Every host will always belong to at least 2 groups (all and ungrouped or all and some other group)

Hosts in multiple groups

- You can (and probably will) put each host in more than one group.
- For example a production webserver in a datacenter in Atlanta might be included in groups called **`[prod]`** and **`[atlanta]`** and **`[webservers]`**.
- You can create groups that track:
  - **What** - An application, stack or microservice (for example, database servers, web servers, and so on).
  - **Where** - A datacenter or region, to talk to local DNS, storage, and so on (for example, east, west).
  - **When** - The development stage, to avoid testing on production resources (for example, prod, test).

Hosts in multiple groups

```yaml
ungrouped:
  hosts:
    mail.example.com:
webservers:
  hosts:
    foo.example.com:
    bar.example.com:
dbservers:
  hosts:
    one.example.com:
    two.example.com:
    three.example.com:
east:
  hosts:
    foo.example.com:
    one.example.com:
    two.example.com:
west:
  hosts:
    bar.example.com:
    three.example.com:
prod:
  hosts:
    foo.example.com:
    one.example.com:
    two.example.com:
test:
  hosts:
    bar.example.com:
    three.example.com:
```

Parent/child group relationships

- You can create parent/child relationships among groups
- Parent groups are also known as nested groups or groups of groups
- For example, if all your production hosts are already in groups such as **`atlanta_prod`** and **`denver_prod`**, you can create a production group that includes those smaller groups.
- This approach reduces maintenance because you can add or remove hosts from the parent group by editing the child groups.
- Child groups have a couple of properties to note:
  - Any host that is member of a child group is automatically a member of the parent group.
  - Groups can have multiple parents and children, but not circular relationships.
  - Hosts can also be in multiple groups, but there will only be one instance of a host at runtime. Ansible merges the data from the multiple groups.

Parent/child group relationships

```yaml
ungrouped:
  hosts:
    mail.example.com:
webservers:
  hosts:
    foo.example.com:
    bar.example.com:
dbservers:
  hosts:
    one.example.com:
    two.example.com:
    three.example.com:
east:
  hosts:
    foo.example.com:
    one.example.com:
    two.example.com:
west:
  hosts:
    bar.example.com:
    three.example.com:
prod:
  children:
    east:
test:
  children:
    west:
```

Adding Ranges of Hosts

- If you have a lot of hosts with a similar pattern, you can add them as a range rather than listing each hostname separately:

```
[webservers]
www[01:50].example.com
```

```yaml
webservers:
  hosts:
    www[01:50].example.com:
```

- You can specify a stride (increments between sequence numbers) when defining a numeric range of hosts:

```
[webservers]
www[01:50:2].example.com
```

```yaml
webservers:
  hosts:
    www[01:50:2].example.com:
```

- You can also define alphabetic ranges:

```
[databases]
db-[a:f].example.com
```

Organizing inventory in a directory

- You can consolidate multiple inventory sources in a single director
- Simplest version of this is a directory with multiple files instead of a single inventory file
- The following inventory directory combines an inventory plugin source, a dynamic inventory script, and a file with static hosts:

```
inventory/
  openstack.yml          # configure inventory plugin to get hosts from OpenStack cloud
  dynamic-inventory.py   # add additional hosts with dynamic inventory script
  on-prem                # add static hosts and groups
  parent-groups          # add static hosts and groups
```

Passing multiple inventory sources

- You can target multiple inventory at the same time by giving multiple inventory parameters from the command line

```
$ ansible -i dev.yml -i test.yml host -m ping
```

- Or you can target this inventory directory as follows:

```
$ ansible -i inventory all -m ping
```

Adding Vars to Hosts

Inventory

Adding variables to inventory

- You can store variable values that relate to a specific host or group in inventory
- To start with, you may add variables directly to the hosts and groups in your main inventory file
- However, storing variables in separate host and group variable files is a more robust approach to describing your system policy
- Setting variables in the main inventory file is only a shorthand

Adding variables to inventory

- INI Format with key=value

```
[targets]

localhost               ansible_connection=local
other1.example.com      ansible_connection=ssh        ansible_user=myuser
other2.example.com      ansible_connection=ssh        ansible_user=myotheruser
```

- YAML Format

```yaml
atlanta:
  hosts:
    host1:
      http_port: 80
      maxRequestsPerChild: 808
    host2:
      http_port: 303
      maxRequestsPerChild: 909
```

Inventory Aliases

- You can also define aliases in your inventory using host variables
- INI Format

```
jumper ansible_port=5555 ansible_host=192.0.2.50
```

- YAML Format

```yaml
hosts:
  jumper:
    ansible_port: 5555
    ansible_host: 192.0.2.50
```

Group Variables

- If all hosts in a group share a variable value, you can apply that variable to an entire group at once
- INI Format

```
[atlanta]
host1
host2

[atlanta:vars]
ntp_server=ntp.atlanta.example.com
proxy=proxy.atlanta.example.com
```

YAML Format

```yaml
atlanta:
  hosts:
    host1:
    host2:
  vars:
    ntp_server: ntp.atlanta.example.com
    proxy: proxy.atlanta.example.com
```

Organizing Host and Group Variables

- Directory Structure: Host and group variables should be organized in separate directories named **`host_vars`** and **`group_vars`** respectively, located at the root level of your Ansible project.
- File Naming: Inside the **`host_vars`** directory, create a file for each host named after its hostname. Similarly, inside the **`group_vars`** directory, create a file for each group named after its group name.
- YAML Format: Variables inside these files should be defined in YAML format. Each variable is defined with a name followed by its value.
- Variable Precedence: Variables defined in **`host_vars`** have higher precedence. This means that if a variable is defined both in a host's file in **`host_vars`** and in a group file in **`group_vars`**, the value from the **`host_vars`** file will be used for that host.

Organizing Host and Group Variables: Example

- Let's say you have a group called **`web_servers`** and a host called **`web01.example.com`**.
- **`group_vars/web_servers.yml`**

```
nginx_version: 1.18.0
document_root: /var/www/html
```

- **`host_vars/web01.example.com.yml`**

```
document_root: /var/www/web01
```

Organizing Host and Group Variables: Example

- In this example, all hosts in the **`web_servers`** group will have the **`nginx_version`** variable set to **`1.18.0`**.
- However, while the **`document_root`** for most hosts in the group will be **`/var/www/html`**, for the **`web01.example.com host`**, it will be **`/var/www/web01`** due to the higher precedence of the **`host_vars`** definition.

Best practices for Ansible project Folders

- On Ansible Best Practices you may find two approaches

```
production
staging

group_vars/
   group1.yml
   group2.yml
host_vars/
   hostname1.yml
   hostname2.yml
```

```
inventories/
   production/
      hosts
      group_vars/
         group1.yml
         group2.yml
      host_vars/
         hostname1.yml
         hostname2.yml

   staging/
      hosts
      group_vars/
         group1.yml
         group2.yml
      host_vars/
         stagehost1.yml
         stagehost2.yml
```

Review Complex Inventory

Inventories