logentries BY RAPID7 | cb-restaurant-service | Log Sets / Aggregated Logs | Help | gorkem_tasci@...

Search

Logs | Log Sets | Reset

Favorites (0)

You have no favorites yet

Mark important log sets by hovering over a log set and choosing "Add to favorites"

3 Log sets (5 Logs Selected) Add log set

- [x] DemoSet (1)
- [x] Heroku (1)
- [x] Internal Logs (3)

```
)0:00 app web.1 - - /\\ / ___'_ __ _ _(_)_ __ __ _ \ \ \ \ Heroku/Syslog drain
):00 app web.1 - - ( ( )\___ | '_ | '_| | '_ \/ _` | \ \ \ \ Heroku/Syslog drain
)0:00 app web.1 - - \\/ ___)| |_)| | | | | || (_| | ) ) ) ) Heroku/Syslog drain
)0:00 app web.1 - - ' |____| .__|_| |_|_| |_\__, | / / / / Heroku/Syslog drain
)0:00 app web.1 - - =========|_|==============|___/=/_/_/_/ Heroku/Syslog drain
)0:00 app web.1 - - :: Spring Boot :: (v2.3.1.RELEASE) Heroku/Syslog drain
):00 app web.1 - - Heroku/Syslog drain
)0:00 app web.1 - - 16:46:16.235 [main] INFO c.t.r.RestaurantServiceApplication - Starting RestaurantServiceApplication v0.0.1-SNAPSHOT on 0db3
)0:00 app web.1 - - 16:46:16.242 [main] INFO c.t.r.RestaurantServiceApplication - The following profiles are active: heroku Heroku/Syslog drain
)0:00 app web.1 - - 16:46:18.627 [main] INFO o.s.d.r.c.RepositoryConfigurationDelegate - Bootstrapping Spring Data R2DBC repositories in DEFAUL
):00 app web.1 - - 16:46:19.084 [main] INFO o.s.d.r.c.RepositoryConfigurationDelegate - Finished Spring Data repository scanning in 446ms. Four
)0:00 heroku web.1 - - State changed from starting to up Heroku/Syslog drain
)0:00 app web.1 - - 16:46:23.771 [main] INFO o.s.b.w.e.netty.NettyWebServer - Netty started on port(s): 46534 Heroku/Syslog drain
)0:00 app web.1 - - 16:46:23.796 [main] INFO c.t.r.RestaurantServiceApplication - Started RestaurantServiceApplication in 10.128 seconds (JVM r
)0:00 heroku router - - at=info method=GET path="/foods/933a5c3c-abd9-47b9-901e-a907a69f9202" host=cb-restaurant-service.herokuapp.com request_
)0:00 app web.1 - - 16:46:26.364 [reactor-tcp-epoll-1] DEBUG o.s.d.r.core.DefaultDatabaseClient - Executing SQL statement [SELECT food.* FROM f
"ipaddress": "159.146.41.23", "event": "weblogon", "user": "1988273" } Internal Logs/Web Access Log
):00 heroku router - - at=info method=GET path="/swagger-ui.html" host=cb-restaurant-service.herokuapp.com request_id=89fd5aaa-8b23-4187-8eda-6
)0:00 heroku router - - at=info method=GET path="/webjars/swagger-ui/index.html?configUrl=/api-docs/swagger-config" host=cb-restaurant-service.
00 heroku router - - at=info method=GET path="/webjars/swagger-ui/swagger-ui.css" host=cb-restaurant-service.herokuapp.com request_id=fada5eec
)0:00 heroku router - - at=info method=GET path="/webjars/swagger-ui/swagger-ui-bundle.js" host=cb-restaurant-service.herokuapp.com request_id=
)0:00 heroku router - - at=info method=GET path="/webjars/swagger-ui/swagger-ui-standalone-preset.js" host=cb-restaurant-service.herokuapp.com
)0:00 heroku router - - at=info method=GET path="/api-docs/swagger-config" host=cb-restaurant-service.herokuapp.com request_id=3c6467e2-11c8-4e
)0:00 heroku router - - at=info method=GET path="/api-docs/swagger-config" host=cb-restaurant-service.herokuapp.com request_id=c80dc964-cc6c-44
):00 app web.1 - - 16:53:33.437 [reactor-http-epoll-7] INFO o.s.api.AbstractOpenApiResource - Init duration for springdoc-openapi is: 2752 ms H
)0:00 heroku router - - at=info method=GET path="/api-docs" host=cb-restaurant-service.herokuapp.com request_id=3a2a3c14-7b00-4beb-96bd-fe7a040
)0:00 heroku router - - at=info method=GET path="/api-docs" host=cb-restaurant-service.herokuapp.com request_id=d0458bcf-9614-47fa-9297-bcf6264
```