## Introduction

BiS Valves offer an extensive range of excess flow valve products, in cartridge, manifold mounted and ported installation formats.

## Excess Flow Valves

Their primary function is to shut a line down in the event of breakage or rupture of a downstream pipe or hose, or any other application where excessive flow must be avoided.

# Excess Flow

## Overview

### Selecting the Correct Product

Selection guide for excess flow valves

| | Page | Suitable for liquids | Suitable for gases | 1/4" – 3/8" BSP / NPT ports | 1/2" – 1" BSP/NPT ports | > 1" BSP/ NPT ports | Medium pressure ports | Cartridge installation | Manifold mount installation | Venting check valve | Thermal relief function |
|---|---|---|---|---|---|---|---|---|---|---|---|
| R25 | ? | | | | | | | | | | |
| R37 | ? | | | | | | | | | | |
| R50 | ? | | | | | | | | | | |
| R75 | ? | | | | | | | | | | |
| R100 | ? | | | | | | | | | | |
| R150 | ? | | | | | | | | | | |
| ER25 | ? | | | | | | | | | | |
| ER37 | ? | | | | | | | | | | |

Important – This is a guide to selecting products that may be suitable. The valve data sheet and application notes must be thoroughly reviewed prior to final selection. Please contact us if the options you require are not shown