
NR25 -20K

CHECK VALVE


1/4" UP TO 1,379 BAR 20,000 PSI




The NR25-20K is a 1/4" nominal bore check valve. It will allow flow in one direction, and blocks flow in the opposite direction. It may also be referred to as a non-return valve.

The valve uses sealed poppet technology to give virtually zero leakage with liquids and gases.

- Check or Non-Return valve
- Super duplex and stainless steel construction
- Sealed poppet design
- Virtually zero leakage
- Can be used subsea
- Suitable for liquid or gas
- Suitable for use with air, nitrogen, sweet natural gas, mineral oils, water glycols, water and sea water
- Suitable for many other media, contact us for advice
- NACE MR01-75 compliant version available
- High cracking pressure variants available, contact us for details
- Various seal options available
- Various porting options available



Specifications

BASIC MODEL NUMBER	NR25-20K
SYMBOL	
MAX WORKING PRESSURE (LIQUID)	1,379 bar (20,000 psi)
MAX WORKING PRESSURE (GAS)	690 bar (10,000 psi)
CV (FLOW CAPACITY)	0.2 - 0.65 See Product Selector opposite
FLUID	Liquids and Gases See materials section
TEMPERATURE RANGE	See Product Selector opposite and Technical Data section
NOMINAL SIZE	1/4"
CRACKING PRESSURE	0.1 - 0.3 bar (2 - 5 psi)
WEIGHT	0.6 kg (1.3 lb)

Specifications may change without notice


Materials

Externally Exposed Parts: Super duplex.
Internally Wetted Parts: Super duplex and 316 stainless steel with 302 stainless steel spring and PEEK. The spring is inconel for SWD and NACE variants.

The standard valve is designed for use with air, nitrogen, sweet natural gas, mineral oil, water glycols and plain water, and may also be used with a wide variety of media compatible with the materials of construction.

⚠ The standard valve has Viton® seals. Further seal options are available via the Product Selector. Compatibility with the working fluid at the operating temperature must be considered.


Typical Performance



Typical performance based on water

Installation Diagram





Product Selector

NR25 - 44AE - NBR - SWD - 20K

VALVE TYPE	PORTING OPTIONS	SEAL OPTIONS	VALVE OPTIONS	MAX WORKING PRESSURE
		Leave blank for Viton® seals -10˚C to +160˚C	Leave blank if not required	
NR25	44AE 1/4" OD medium pressure tube port 0.2CV	NBR Nitrile seals -30˚C to +105˚C	SWD Materials compatible with sea water	20K 1,379 bar (20,000 psi) Liquid
	56AE 3/8" OD medium pressure tube port 0.65CV	EP EPDM seals -45˚C to +150˚C	NACE Materials comply with NACE MR01-75	690 bar (10,000 psi) Gas
		KLZ Kalrez® seals -25˚C to +200˚C		
		HNBR Hydrogenated Nitrile seals -20˚C to +150˚C		
Repair and seal kits are available on request For a seal kit add SK at the end of the model code and for a repair kit add RK		Further seal options are available on request		