Introduction

BiS Valves offer an extensive range of relief valve products, in cartridge, manifold mounted and ported installation formats.

Safety Relief Valves

Typically low-pressure, vent-to-atmosphere designs with a pop-open characteristic, from about 0.7 bar. CE marked as Category IV safety accessories under the Pressure Equipment Directive 2014/68/EU.

Relief Valves

Higher-pressure piped-return valves (to 1,379 bar / 20,000 psi) offer proportional or metering-style operation. Cartridge, manifold-mounted and exotic-material options are available via the factory.

Selecting the Correct Product

Selection guide for safety relief valves

	Page	Suitable for liquids	Suitable for gases	1/4" – 3/8" BSP / NPT ports	1/2" – 1" BSP/NPT ports	> 1" BSP/ NPT ports	Medium pressure ports	Cartridge installation	Manifold mount installation	Venting check valve	Thermal relief function
BS25	?										
BS37	?										
BS50	?										
BS75	?										
S25	?										
S37	?										
S50	?										
S75	?										
S100	?										
TS25	?										
TS25C	?										
TS37	?										
TS50	?										
TS75	?										
TS100	?										

Selection guide for relief valves

	Page	Suitable for liquids	Suitable for gases	1/4" – 3/8" BSP / NPT ports	1/2" – 1" BSP/NPT ports	> 1" BSP/ NPT ports	Medium pressure ports	Cartridge installation	Manifold mount installation	Venting check valve	Thermal relief function
SM25UF	?										
RL25	?										
RL25-G	?										
RL25C	?										
RL25C-G	?										
RL25M	?										
RL37	?										
RL37-G	?										
RL50	?										
RL50-G	?										
RL50M	?										
RL75	?										
RL75-G	?										
PRV75C	?										
RL100	?										
RL100-G											
HTS25											
HS25											