
RL25C

RELIEF VALVE

1/4"


UP TO 1,034 BAR 15,000 PSI




The RL25C is a cartridge style relief valve. Designed for emergency relief applications, it may be used to protect systems up to 1,034 bar (15,000 psi).

The valve is a proportional metering style relief valve, and is approved as a safety accessory to category IV of the Pressure Equipment Directive, enabling its use in the most demanding applications.

- Approved to category IV of the Pressure Equipment Directive (2014/68/EU)
- Cartridge style valve, ideal for use in manifolds
- Wire locking and tagging available on request
- Minimal leakage at 90% of set pressure
- Reseat within 20% of set pressure
- Repeatabily within ±5% of set pressure
- Suitable for subsea applications
- Suitable for use with mineral oils and water glycols, with options for water and sea water duty
- Suitable for many other media, contact us for advice
- Various spring ranges available.



Specifications

BASIC MODEL NUMBER	RL25C
SYMBOL	
MAX WORKING PRESSURE	1,034 bar (15,000 psi)
MAX OUTLET PORT PRESSURE	69 bar (1,000 psi) Note: Any outlet port pressure is directly additive to the set pressure
ORIFICE SIZE	Ø3.2mm (Ø0.125")
FLUID	Liquids only See materials section
TEMPERATURE RANGE	See Product Selector opposite and Technical Data section
NOMINAL SIZE	1/4"
WEIGHT	0.5 kg (1.1 lb)

Specifications may change without notice


Materials

Externally Exposed Parts: 316 stainless steel.

Internally Wetted Parts: 316 and 302 stainless steel and acetal. The seat and ball are 440C stainless steel and silicon nitride respectively. The water duty version contains a 17-4 PH stainless steel seat. The sea water duty valve uses only 316 stainless steel, inconel and silicon nitride in wetted areas. Note that use with water above 100°C is not recommended.


⚠ The standard valve has Viton® seals. Further seal options are available via the Product Selector. Compatibility with the working fluid at the operating temperature must be considered.


Typical Performance



Typical performance based on water
Contact us with system details for an application specific calculation

Installation Diagram





NOTE - TOLERANCED DIMENSIONS TO HAVE SURFACE FINISH OF 0.8

CAVITY DETAIL

Product Selector

RL25C - WD - NBR - 1.6K

VALVE TYPE	WORKING FLUID OPTIONS	SEAL OPTIONS	SET PRESSURE RANGE
	Leave blank if none required	Leave blank for Viton® seals -10˚c to +120˚c	
RL25C	WD Water duty	NBR Nitrile seals -30˚C to +105˚C	1.6K 28 - 110 bar (400 - 1,600 psi)
	SWD Sea water duty	KLZ Kalrez® seals -25˚C to +120˚C	4K 69 - 276 bar (1,000 - 4,000 psi)
		HNBR Hydrogenated Nitrile seals -20˚C to +120˚C	9K 207 - 621 bar (3,000 - 9,000 psi)
		Further seal options are available on request	15K 552 - 1,034 bar (8,000 - 15,000 psi)
			Advise us of set pressure if factory pre-setting is required

Repair and seal kits are available on request

For a seal kit add SK at the end of the model code and for a repair kit add RK