
TS75

SAFETY RELIEF VALVE


3/4″ UP TO 40 BAR 580 PSI




The TS75 is a safety relief valve with a threaded exhaust port for piping vented flow away from the valve.
Designed with an elastomeric seat seal, the valve combines excellent leakage performance with a high discharge flow capacity from its pop-open characteristic.

The valve is approved as a safety accessory to category IV of the Pressure Equipment Directive, and is suitable for use in the most demanding liquid or gas applications.

- Approved to category IV of the Pressure Equipment Directive (2014/68/EU)
- Pop-open characteristic for maximum discharge capacity
- Available preset and internally adjustable.
- Available with relieving gear to enable the manual release of pressure
- Wire locking and tagging available on request
- Virtually zero leakage at 90% of set pressure
- Reseat within the greater of 5 psi or 7.5% of set pressure when valve has opened and not popped
- Reseat within 50% of set pressure once popped
- Repeatability within the greater of 2 psi or ±3% of nominal set pressure



Specifications

BASIC MODEL NUMBER	TS75
SYMBOL	
MAX WORKING PRESSURE	40 bar (580 psi)
MAX OUTLET PORT PRESSURE	10 bar (145 psi) Note: Any outlet port pressure is directly additive to the set pressure
ORIFICE SIZE	Ø9.8mm (Ø0.386″)
FLUID	Liquids and Gases See materials section
TEMPERATURE RANGE	See Product Selector opposite and Technical Data section
PORT SIZE	3/4″
WEIGHT	0.4 kg (0.9 lb)

Specifications may change without notice


Materials

Externally Exposed Parts: 316 stainless steel and acetal.
Internally Wetted Parts: 316 and 302 stainless steel, and acetal.

The standard valve is designed for use with air, nitrogen, sweet natural gas, mineral oil, water glycols and plain water, and may also be used with a wide variety of media compatible with the materials of construction. Other material options are available, contact us for advice. Note that use with water above 100°C is not recommended.


⚠ The standard valve has Viton® seals. Further seal options are available via the Product Selector. Compatibility with the working fluid at the operating temperature must be considered.


Typical Performance



Typical performance based on water
Contact us with system details for an application specific calculation

Installation Diagram





RG - RELIEVING GEAR OPTION

Product Selector

TS75 P - RG - NBR - 2B

VALVE TYPE	PORTING OPTIONS	VALVE OPTIONS	SEAL OPTIONS	SET PRESSURE RANGE
		Leave blank if not required	Leave blank for Viton® seals -10˚C to +120˚C	
TS75	P 3/4" BSPP male inlet 3/4" BSPP female exhaust	RG Relieving gear	NBR Nitrile seals -30˚C to +105˚C	2B 0.7 - 2 bar (10 - 29 psi)
	N 3/4" NPT male inlet 3/4" NPT female exhaust	This option is not recommended with the 2B spring option	EP EPDM seals -45˚C to +150˚C	7B 2 - 7 bar (29 - 102 psi)
		⚠ Exposure to high and low fluid temperatures will influence handle temperature. Operator safety must be considered	KLZ Kalrez® seals -25˚C to +200˚C	12B 6 - 12 bar (87 - 174 psi)
			HNBR Hydrogenated Nitrile seals -20˚C to +150˚C	25B 11 - 25 bar (160 - 363 psi)
			Further seal options are available on request	40B 20 - 40 bar (290 - 580 psi)
				Advise us of set pressure if factory pre-setting is required

Repair and seal kits are available on request

For a seal kit add SK at the end of the model code and for a repair kit add RK