



# National University of Computer and Emerging Sciences



## OBJECT-ORIENTED PRORAMMING

Summer 2023

**Pir Sami Ullah Shah**

Lecture # 4 Recursion



**Web**

Images

More ▾

Search tools

About 4,440,000 results (0.19 seconds)

Did you mean: [recursion](#)

[Recursion - Wikipedia, the free encyclopedia](#)

[en.wikipedia.org/wiki/Recursion](https://en.wikipedia.org/wiki/Recursion) ▾

**Recursion** is the process of repeating items in a self-similar way. For instance, when the surfaces of two mirrors are exactly parallel with each other the nested ...

[Recursion \(disambiguation\)](#) - [Recursion \(computer science\)](#) - [Self-similarity](#) - [Tail call](#)

[Recursion \(computer science\) - Wikipedia, the free encyclopedia](#)

[en.wikipedia.org/wiki/Recursion\\_\(computer\\_science\)](https://en.wikipedia.org/wiki/Recursion_(computer_science)) ▾

Recursion in computer science is a method where the solution to a problem ...

[Recursive functions and algorithms](#) - [Recursive data types](#) - [Types of recursion](#)

# Recursive Function

- A function that **calls itself** is called **recursive function**

```
void Message()  
{  
    cout << "This is a recursive function.\n";  
    Message();  
}
```

- What is the problem with the above function?

# Recursion

- The function `message()` is like an **infinite loop** because there is **no code to stop it from repeating**



# Recursive Function – Number of Repetitions

---

- Recursive function must have some algorithm (i.e., logic) to control the number of times it repeats


```
void Message(int times)
{
    if (times > 0) //base case
    {
        cout << "This is a recursive function.\n";
        Message(times - 1);
    }
    return;
}
```

- Modification to Message function
  - Receive an int argument to **control the number of times to call itself**
  - For each recursive call, the parameter controlling the recursion should **move closer to the base case (converge)**


# Recursive Function – Execution (1)

---

- Each time the function is called, a new instance of the **times** parameter is created
  - Suppose program invokes the function as **Message(5)**



In the first call to function, times is set to 5.



When the function calls itself, a new instance of times is created with the value 4.

# Recursive Function – Execution (2)

```
void Message(int times)
{
    if (times > 0)
    {
        cout << "This is a recursive function.\n";
        Message(times - 1);
    }
    return;
}
```

1<sup>st</sup> call of the function  
Value of times: 5

2<sup>nd</sup> call of the function  
Value of times: 4

3<sup>rd</sup> call of the function  
Value of times: 3

4<sup>th</sup> call of the function  
Value of times: 2

5<sup>th</sup> call of the function  
Value of times: 1

6<sup>th</sup> call of the function  
Value of times: 0

- This cycle repeats itself until 0 is passed to the function
- Depth of recursion: 6

# Program Output

---

This is a recursive function.

This is a recursive function.

This is a recursive function.

This is a recursive function.

This is a recursive function.



# What Happens When Called?

---

- Each time a recursive function is called, a new copy of the function runs, with new instances of parameters and local variables being created
- As each copy finishes executing, it returns to the copy of the function that called it
- When the first copy finishes executing, it returns to the part of the program that made the initial call to the function


# Recursive Function – Modification

---



- Statements after the recursive invocation of the function

```
void Message(int times)
{
    cout << "Message called with " << times << " in times.\n";
    if (times > 0) {
        cout << "This is a recursive function.\n";
        Message(times - 1);
    }
    cout << "Message returning with " << times;
    cout << " in times.\n";
}
```

# Recursive Function – Execution (3)



# Recursion



# Recursion

---



**Inception**



**Recursion**

# Recursion


---

- Solving a problem by reducing it to a **smaller version of itself**
- A properly written recursive function must
  - Handle the **base cases**, and
  - **Recursive cases** (convergence to the base case)
- **Failure** to properly handle the base case or converge to the base case may result **in infinite recursion**
- Very Important: **NO LOOPS!!!** (for, while, do-while)

# Recursion

---

- To solve problem recursively

1. Define the base case(s)
  2. Define the recursive case(s)
    - a) Divide the problem into smaller sub-problems
    - b) Solve the sub-problems
    - c) Combine results to get answer
- 


Sub-problems solved as a recursive call to the same function

- Sub-problem must be smaller than the original problem
  - Otherwise recursion never terminates

# Print Numbers in Descending Order

---

```
void printDes(int n) {  
  
    if ( n <= 0 ) //Base condition  
        return;  
  
    cout << n << " "; //Prints number n  
  
    printDes(n-1); //Recursive call  
}
```

print(10) produces  10 9 8 7 6 5 4 3 2 1



# Print Numbers in Ascending Order

---

```
void printAsc(int n) {  
  
    if ( n <= 0 ) //Base condition  
        return;  
  
    printAsc(n-1); //Recursive call  
  
    cout << n << " "; //Prints number n  
}
```

print(10) produces 1 2 3 4 5 6 7 8 9 10

# Example: Sum function (Iterative)

---

```
//Our initial total is zero
```

```
int total = 0;
```

```
//We want the sum from 1 + 2 + ... + 9 + 10
```

```
int n = 10;
```


```
/* The following for loop will calculate the  
summation from 1 - n */
```

```
for ( int i = 1; i <= n; i++ ) {  
    total = total + i;  
}
```

# Example: Sum function (Recursive)

---


```
int sum(int n) {  
    if ( n <= 0 ) //base case  
        return 0;  
    else //recursive call  
        return n + sum(n-1);  
}
```



# Example: Sum Function

---

- $\text{sum}(5) = 5 + 4 + 3 + 2 + 1 = 15$



# Example: Multiply Function

---

- Multiplication is basically just **addition**

$$10 * 5 = 10 + 10 + 10 + 10 + 10 = 50$$

Added 10, 5 times

$$7 * 4 = 7 + 7 + 7 + 7 = 28$$

Added 7, 4 times

Write a recursive function that performs multiplication

# Example: Multiply Function

---

```
int multiply (int n, int times){  
  
    if(times == 0) //base case  
        return 0;  
    else           //recursive case  
        return n + multiply(n,times-1);  
  
}
```

# Example: Factorial Function (1)

---

- A mathematical definition: For a non-negative integer  $n$

$$fac(n) = \begin{cases} 1 & \text{if } n \leq 1 \\ n \times fac(n-1) & \text{otherwise} \end{cases}$$

- Factorial is defined in terms of itself
  - Defined in cases: a base case and a recursive case

```
int fac(int n) {  
    if (n <= 1) {  
        return 1;  
    }  
    else {  
        return n * fac(n - 1);  
    }  
}
```

# Example: Factorial Function (2)

---

- Suppose the factorial function is invoked as `fac(5)`

```
fac(5)
5 * fac(4)
5 * 4 * fac(3)
5 * 4 * 3 * fac(2)
5 * 4 * 3 * 2 * fac(1)
5 * 4 * 3 * 2 * 1
5 * 4 * 3 * 2
5 * 4 * 6
5 * 24
120
```



# Example: Character count

---

```
// Function prototype
int numChars(char, char*, int);

int main()
{
    char array[] = "abcddddef";

    /* Display the number of times the letter 'd'
    appears in the string. */

    cout << "The letter d appears "
    << numChars('d', array, 0) << " times.\n";

    return 0;
}
```

# Example: Character count

```
int numChars(char search, char * str, int index) {  
  
    if (*(str + index) == '\0') { //Base case  
        return 0;  
    }  
  
    else if (*(str + index) == search){ //Recursive case  
        return 1 + numChars(search, str, index+1); }  
  
    else { // Recursive case  
        return 0 + numChars(search, str, index+1);  
    }  
}
```

# Example: Fibonacci Series

---

## Fibonacci series:

0, 1, 1, 2, 3, 5, 8, 13, 21, ...

- Except the **first two numbers**, each term is the sum of the **two preceding terms**

- Recursive solution:

$$\text{fib}(n) = \text{fib}(n - 1) + \text{fib}(n - 2);$$


- Base cases:

$$n == 0, \quad n == 1$$

# Recursion

---

**5<sup>th</sup> Fib.  
Number**



# Recursive Fibonacci Function

---

```
#include <iostream>
using namespace std;

int fib(int n) {
    if (n <= 0)           // base case
        return 0;
    else if (n==1)        // base case
        return 1;
    else
        return fib(n-1) + fib(n-2);
}

int main() {
    int n;
    cin>>n;
    cout<<n<<"th Fibonacci number is: "<<fib(n);
    return 0;
}
```

# Printing Patterns using Recursion

Input : n = 5

Output :

```
* * * * *
* * * *
* * *
* *
*
```

Input : n = 7

Output :

```
* * * * * * *
* * * * *
* * * *
* * *
* *
*
*
```

```
void printCols(int nCols) {
    if (nCols > 0) {
        cout << "* ";
        printCols(nCols - 1);
    }
}

void printRows(int nRows) {
    if (nRows > 0) {
        printCols(nRows);
        cout << endl;
        printRows(nRows - 1);
    }
}

void main()
{
    printRows(7);
}
```

# Printing Patterns using Recursion

```
  #
 # #
# # #
# # # #
# # # # #
```

```
void printSpace(int nSpc) {
    if (nSpc > 0) {
        cout << " ";
        printSpace(nSpc - 1);
    }
}
```

```
void printCols(int nCols) {
    if (nCols > 0) {
        cout << "# ";
        printCols(nCols - 1);
    }
}
```

```
printRows(int total, int n) {
    if (n > 0) {
        printSpace(n);
        printCols(total-(n-1));
        cout << endl;
        printRows(total, n - 1);
    }
}

int main()
{
    printRows(5,5);
    return 0;
}
```

# Stack Overflow (1)

---

- Recursive functions cannot use statically allocated local variables
  - Each instance of the function needs its own copies of local variables
- Most modern languages allocate local variables for functions on the run-time stack
- Calling a recursive function **many times** or **with large arguments** may result in stack overflow

```
$ java Fac 10000
Exception in thread "main" java.lang.StackOverflowError
at Fac.facIter(Fac.java:35)
at Fac.facIter(Fac.java:38)
at Fac.facIter(Fac.java:38)
...
```



# Recursion vs Iteration


---

- Recursive algorithms can also be coded with iterative control structures, but which is best to use?
- There are advantages and disadvantages to each approach
- Recursion disadvantages:
  - **Less efficient** than iterative algorithms.
  - Majority of repetitive programming tasks are best done with loops.
- Recursion advantages:
  - Code clarity
  - Easier to code some algorithms using recursion, e.g. quicksort

# Recursion or Iteration?

---

- If there is **sufficient memory available for recursion**
- **Primarily a design decision.** If a problem is more easily solved with a loop, that should be the approach you take. If recursion results in a better design, that is the choice you should make.



# Any Question So Far?

---

