



Taskflow: A General-purpose Task-parallel Programming System

Dr. Tsung-Wei (TW) Huang

Department of Electrical and Computer Engineering


University of Wisconsin at Madison, Madison, WI

<https://taskflow.github.io/>



Why Parallel Computing?

- Advances performance to a new level previously out of reach




Parallel Programming is Not Easy!

- **You need to deal with A LOT OF technical details**

- Parallelism abstraction (software + hardware)
- Concurrency control
- Synchronization
- Task and data race avoidance
- Dependency constraints
- Scheduling efficiencies (load balancing)
- Programming productivity
- Performance portability
- ...

- **And, don't forget about trade-offs**

- Performance vs Developer's intent





We want a solution that can sit on top to help programmers manage these details as much as possible because programmers care how fast (performance + productivity) they can get things done!



Static Task Graph Programming in Taskflow¹

#include <taskflow/taskflow.hpp> // Live: <https://godbolt.org/z/j8hx3xnnx>

```
int main(){
    tf::Taskflow taskflow;
    tf::Executor executor;
    auto [A, B, C, D] = taskflow.emplace(
        [] () { std::cout << "TaskA\n"; },
        [] () { std::cout << "TaskB\n"; },
        [] () { std::cout << "TaskC\n"; },
        [] () { std::cout << "TaskD\n"; }
    );
    A.precede(B, C);
    D.succeed(B, C);
    executor.run(taskflow).wait();
    return 0;
}
```




Control Taskflow Graph (CTFG) Programming Model

- A key innovation that distinguishes Taskflow from existing libraries


```

auto [init, cond, yes, no] =
taskflow.emplace(
    [] () { },
    [] () { return 0; },
    [] () { std::cout << "yes"; },
    [] () { std::cout << "no"; }
);
cond.succeed(init)
    .precede(yes, no);
    
```



```

auto [init, opt, cond, stop] =
taskflow.emplace(
    [&]() { initialize_data_structure(); },
    [&]() { some_optimizer(); },
    [&]() { return converged() ? 1 : 0; },
    [&]() { std::cout << "done!\n"; }
);
opt.succeed(init).precede(cond);
converged.precede(opt, stop);
    
```



CTFG goes beyond the limitation of traditional DAG-based frameworks (no in-graph control flow).



Dynamic Task Graph Programming in Taskflow

// Live: <https://godbolt.org/z/j76ThGbWK>

```
tf::Executor executor;


auto A = executor.silent_dependent_async([](){
    std::cout << "TaskA\n";
});

auto B = executor.silent_dependent_async([](){
    std::cout << "TaskB\n";
}, A);

auto C = executor.silent_dependent_async([](){
    std::cout << "TaskC\n";
}, A);

auto [D, Fu] = executor.dependent_async([](){
    std::cout << "TaskD\n";
}, B, C);

Fu.wait();
```



Specify arbitrary task dependencies on previously created tasks

Using Taskflow is **EXTREMELY EASY**

- **Taskflow is a header-only library built entirely with standard C++ libraries**
 - No wrangling with installation – just copy the headers and tell your compiler where to find them

```
# clone the Taskflow project
```

```
~$ git clone https://github.com/taskflow/taskflow.git
```

```
~$ cd taskflow
```

```
# compile your program and tell your compiler where to find Taskflow header files
```

```
~$ g++ -std=c++20 examples/simple.cpp -I ./ -O2 -pthread -o simple
```

```
~$ ./simple
```

```
TaskA
```

```
TaskC
```

```
TaskB
```

```
TaskD
```

- **Taskflow has been evolving over the years to a stable programming system**
 - Started in 2018 as a DARPA-sponsored research project to parallelize critical EDA applications



Thank you for using Taskflow! <https://taskflow.github.io/>

