#### LINEAR ALGEBRA. LECTURE 11

### Differential equations

The system of equations below describes how the values of variables  $u_1$  and  $u_2$  affect each other over time:

$$\frac{du_1}{dt} = -u_1 + 2u_2$$
$$\frac{du_2}{dt} = u_1 - 2u_2.$$

Just as we applied linear algebra to solve a difference equation, we can use it to solve this differential equation. For example, the initial condition  $u_1 = 1$ ,  $u_2 = 0$  can be written  $\mathbf{u}(0) = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$ .

# Differential equations $\frac{d\mathbf{u}}{dt} = A\mathbf{u}$

By looking at the equations above, we might guess that over time  $u_1$  will decrease. We can get the same sort of information more safely by looking at the eigenvalues of the matrix  $A = \begin{bmatrix} -1 & 2 \\ 1 & -2 \end{bmatrix}$  of our system  $\frac{d\mathbf{u}}{dt} = A\mathbf{u}$ . Because A is singular and its trace is -3 we know that its eigenvalues are  $\lambda_1 = 0$  and  $\lambda_2 = -3$ . The solution will turn out to include  $e^{-3t}$  and  $e^{0t}$ . As t increases,  $e^{-3t}$  vanishes and  $e^{0t} = 1$  remains constant. Eigenvalues equal to zero have eigenvectors that are *steady state* solutions.

 $\mathbf{x}_1 = \begin{bmatrix} 2 \\ 1 \end{bmatrix}$  is an eigenvector for which  $A\mathbf{x}_1 = 0\mathbf{x}_1$ . To find an eigenvector corresponding to  $\lambda_2 = -3$  we solve  $(A - \lambda_2 I)\mathbf{x}_2 = \mathbf{0}$ :

$$\begin{bmatrix} 2 & 2 \\ 1 & 1 \end{bmatrix} \mathbf{x}_2 = 0 \quad \text{so} \quad \mathbf{x}_2 = \begin{bmatrix} 1 \\ -1 \end{bmatrix}$$

and we can check that  $A\mathbf{x}_2 = -3\mathbf{x}_2$ . The general solution to this system of differential equations will be:

$$\mathbf{u}(t) = c_1 e^{\lambda_1 t} \mathbf{x}_1 + c_2 e^{\lambda_2 t} \mathbf{x}_2.$$

Is  $e^{\lambda_1 t} \mathbf{x}_1$  really a solution to  $\frac{d\mathbf{u}}{dt} = A\mathbf{u}$ ? To find out, plug in  $\mathbf{u} = e^{\lambda_1 t} \mathbf{x}_1$ :

$$\frac{d\mathbf{u}}{dt} = \lambda_1 e^{\lambda_1 t} \mathbf{x}_1,$$

which agrees with:

$$A\mathbf{u} = e^{\lambda_1 t} A \mathbf{x}_1 = \lambda_1 e^{\lambda_1 t} \mathbf{x}_1.$$

The two "pure" terms  $e^{\lambda_1 t} \mathbf{x}_1$  and  $e^{\lambda_2 t} \mathbf{x}_2$  are analogous to the terms  $\lambda_i^k \mathbf{x}_i$  we saw in the solution  $c_1 \lambda_1^k \mathbf{x}_1 + c_2 \lambda_2^k \mathbf{x}_2 + \cdots + c_n \lambda_n^k \mathbf{x}_n$  to the difference equation  $\mathbf{u}_{k+1} = A \mathbf{u}_k$ .

Plugging in the values of the eigenvectors, we get:

$$\mathbf{u}(t) = c_1 e^{\lambda_1 t} \mathbf{x}_1 + c_2 e^{\lambda_2 t} \mathbf{x}_2 = c_1 \begin{bmatrix} 2 \\ 1 \end{bmatrix} + c_2 e^{-3t} \begin{bmatrix} 1 \\ -1 \end{bmatrix}.$$

We know  $\mathbf{u}(0) = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$ , so at t = 0:

$$\left[\begin{array}{c}1\\0\end{array}\right]=c_1\left[\begin{array}{c}2\\1\end{array}\right]+c_2\left[\begin{array}{c}1\\-1\end{array}\right].$$

$$c_1 = c_2 = 1/3 \text{ and } \mathbf{u}(t) = \frac{1}{3} \begin{bmatrix} 2 \\ 1 \end{bmatrix} + \frac{1}{3}e^{-3t} \begin{bmatrix} 1 \\ -1 \end{bmatrix}.$$

This tells us that the system starts with  $u_1 = 1$  and  $u_2 = 0$  but that as t approaches infinity,  $u_1$  decays to 2/3 and  $u_2$  increases to 1/3. This might describe stuff moving from  $u_1$  to  $u_2$ .

The steady state of this system is  $\mathbf{u}(\infty) = \begin{bmatrix} 2/3 \\ 1/3 \end{bmatrix}$ .

#### Stability

Not all systems have a steady state. The eigenvalues of *A* will tell us what sort of solutions to expect:

- 1. Stability:  $\mathbf{u}(t) \to 0$  when  $\text{Re}(\lambda) < 0$ .
- 2. Steady state: One eigenvalue is 0 and all other eigenvalues have negative real part.
- 3. Blow up: if  $Re(\lambda) > 0$  for any eigenvalue  $\lambda$ .

If a two by two matrix  $A = \begin{bmatrix} a & b \\ c & d \end{bmatrix}$  has two eigenvalues with negative real part, its trace a+d is negative. The converse is not true:  $\begin{bmatrix} -2 & 0 \\ 0 & 1 \end{bmatrix}$  has negative trace but one of its eigenvalues is 1 and  $e^{1t}$  blows up. If A has a positive determinant and negative trace then the corresponding solutions must be stable.

### Applying S

The final step of our solution to the system  $\frac{d\mathbf{u}}{dt} = A\mathbf{u}$  was to solve:

$$c_1 \left[ \begin{array}{c} 2 \\ 1 \end{array} \right] + c_2 \left[ \begin{array}{c} 1 \\ -1 \end{array} \right] = \left[ \begin{array}{c} 1 \\ 0 \end{array} \right].$$

In matrix form:

$$\left[\begin{array}{cc} 2 & 1 \\ 1 & -1 \end{array}\right] \left[\begin{array}{c} c_1 \\ c_2 \end{array}\right] = \left[\begin{array}{c} 1 \\ 0 \end{array}\right].$$

or  $S\mathbf{c} = \mathbf{u}(0)$ , where S is the eigenvector matrix. The components of  $\mathbf{c}$  determine the contribution from each pure exponential solution, based on the initial conditions of the system.

In the equation  $\frac{d\mathbf{u}}{dt} = A\mathbf{u}$ , the matrix A couples the pure solutions. We set  $\mathbf{u} = S\mathbf{v}$ , where S is the matrix of eigenvectors of A, to get:

$$S\frac{d\mathbf{v}}{dt} = AS\mathbf{v}$$

or:

$$\frac{d\mathbf{v}}{dt} = S^{-1}AS\mathbf{v} = \Lambda\mathbf{v}.$$

This diagonalizes the system:  $\frac{dv_i}{dt} = \lambda_i v_i$ . The general solution is then:

$$\mathbf{v}(t) = e^{\Lambda t}\mathbf{v}(0),$$
 and  $\mathbf{u}(t) = Se^{\Lambda t}S^{-1}\mathbf{v}(0) = e^{At}\mathbf{u}(0).$ 

## Matrix exponential $e^{At}$

What does  $e^{At}$  mean if A is a matrix? We know that for a real number x,

$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} = 1 + x + \frac{x^2}{2} + \frac{x^3}{6} + \cdots$$

We can use the same formula to define  $e^{At}$ :

$$e^{At} = I + At + \frac{(At)^2}{2} + \frac{(At)^3}{6} + \cdots$$

Similarly, if the eigenvalues of At are small, we can use the geometric series  $\frac{1}{1-x} = \sum_{n=0}^{\infty} x^n \text{ to estimate } (I-At)^{-1} = I + At + (At)^2 + (At)^3 + \cdots.$ 

We've said that  $e^{At} = Se^{\Lambda t}S^{-1}$ . If A has n independent eigenvectors we can prove this from the definition of  $e^{At}$  by using the formula  $A = S\Lambda S^{-1}$ :

$$e^{At} = I + At + \frac{(At)^2}{2} + \frac{(At)^3}{6} + \cdots$$

$$= SS^{-1} + S\Lambda S^{-1}t + \frac{S\Lambda^2 S^{-1}}{2}t^2 + \frac{S\Lambda^3 S^{-1}}{6}t^3 + \cdots$$

$$= Se^{\Lambda t}S^{-1}.$$

It's impractical to add up infinitely many matrices. Fortunately, there is an easier way to compute  $e^{\Lambda t}$ . Remember that:

$$\Lambda = \left[ \begin{array}{cccc} \lambda_1 & 0 & \cdots & 0 \\ 0 & \lambda_2 & & 0 \\ \vdots & & \ddots & \vdots \\ 0 & \cdots & 0 & \lambda_n \end{array} \right].$$

When we plug this in to our formula for  $e^{At}$  we find that:

$$e^{\Lambda t} = \begin{bmatrix} e^{\lambda_1 t} & 0 & \cdots & 0 \\ 0 & e^{\lambda_2 t} & & 0 \\ \vdots & & \ddots & \vdots \\ 0 & \cdots & 0 & e^{\lambda_n t} \end{bmatrix}.$$

This is another way to see the relationship between the stability of  $\mathbf{u}(t) = Se^{\Lambda t}S^{-1}\mathbf{v}(0)$  and the eigenvalues of A.

#### Second order

We can change the second order equation y'' + by' + ky = 0 into a two by two first order system:

If 
$$u = \begin{bmatrix} y' \\ y \end{bmatrix}$$
, then 
$$u' = \begin{bmatrix} y'' \\ y' \end{bmatrix} = \begin{bmatrix} -b & -k \\ 1 & 0 \end{bmatrix} \begin{bmatrix} y' \\ y \end{bmatrix}.$$

We could use the methods we just learned to solve this system, and that would give us a solution to the second order scalar equation we started with.

If we start with a *k*th order equation we get a *k* by *k* matrix with coefficients of the equation in the first row and 1's on a diagonal below that; the rest of the entries are 0.

Let's solve second order equation in the proper manner for b=-1, k=-2 and for t=0  $y'(0) = y'_0 = 0$ ,  $y(0) = y_0 = 1$ :

$$\frac{d\vec{u}}{dt} = \frac{d}{dt} \begin{bmatrix} y' \\ y \end{bmatrix} = \begin{cases} \frac{dy'}{dt} = y' + 2y \\ \frac{dy}{dt} = y' \end{cases} \text{ or }$$

$$\frac{d}{dt} \begin{bmatrix} y' \\ y \end{bmatrix} = \begin{bmatrix} 1 & 2 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} y' \\ y \end{bmatrix} \Leftrightarrow \frac{d}{dt} \begin{bmatrix} y' \\ y \end{bmatrix} = \frac{1}{3} \begin{bmatrix} 2 & -1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} 2 & 0 \\ 0 & -1 \end{bmatrix} \begin{bmatrix} 1 & 1 \\ -1 & 2 \end{bmatrix} \begin{bmatrix} y' \\ y \end{bmatrix} \Leftrightarrow \begin{bmatrix} y'(t) \\ y(t) \end{bmatrix} = \frac{1}{3} \begin{bmatrix} 2 & -1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} e^{2t} & 0 \\ 0 & e^{-t} \end{bmatrix} \begin{bmatrix} 1 & 1 \\ -1 & 2 \end{bmatrix} \begin{bmatrix} y'_0 \\ y_0 \end{bmatrix} \Rightarrow \begin{bmatrix} y'(t) \\ y(t) \end{bmatrix} = \frac{1}{3} \begin{bmatrix} 2 & -1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} e^{2t} & 0 \\ 0 & e^{-t} \end{bmatrix} \begin{bmatrix} 1 & 1 \\ -1 & 2 \end{bmatrix} \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$
or
$$\begin{bmatrix} y'(t) \\ y(t) \end{bmatrix} = \frac{1}{3} \begin{bmatrix} 2 & -1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} e^{2t} & 0 \\ 0 & e^{-t} \end{bmatrix} \begin{bmatrix} 1 \\ 2 \end{bmatrix} = \frac{1}{3} \begin{bmatrix} 2 & -1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} e^{2t} \\ 2e^{-t} \end{bmatrix} = \frac{1}{3} \begin{bmatrix} 2e^{2t} - 2e^{-t} \\ 2e^{-t} \end{bmatrix}$$

So, we find the solution  $y(t) = \frac{1}{3}(e^{2t} + 2e^{-t})$  and its derivation  $y'(t) = \frac{2}{3}(e^{2t} - e^{-t})$ .