

Home > STM32F103C8Tx > Untitled - Pinout & Configuration > GENERATE CODE

Pinout & Configuration | Clock Configuration | Project Manager | Tools

Software Packs | Pinout

I2C Mode and Configuration

Mode: I2C I2C

Configuration

Reset Configuration

Parameter Settings

Configure the below parameters:

I2C Clock Speed (Hz): 100000

Slave Features

Clock No Stretch Mode: Disabled

Primary Address Length selection: 7-bit

Pinout view | System view

STM32F103C8Tx LQFP48

Pinout view | System view

Mode

Slave Mode: Disable

Trigger Source: Disable

Internal Clock: ☒

Channel1: Disable

Channel2: Disable

Channel3: Disable

Channel4: Disable

Combined Channels: Disable

XOR activation: ☐

One Pulse Mode: ☐

Configuration

Reset Configuration

Parameter Settings | User Constants | NVIC Settings | DMA Settings

NVIC Interrupt Table	Enabled	Preemption Priority	Sub Priority
TIM3 global interrupt	☒	0	0

File Window Help myST

Home > STM32F103C8Tx > Assignment2.ioc - Pinout & Configuration > GENERATE CODE

Pinout & Configuration | Clock Configuration | Project Manager | Tools

Software Packs | Pinout

GPIO Mode and Configuration

Group By Peripherals

GPIO

Search Signals

Show only Modified Pins

Pin No.	Signal on	GPIO outp	GPIO mode	GPIO Pul	Maximum	User Label	Modified
PA0-WK...	n/a	n/a	Input mode	Pull-up	n/a		☒
PA1	n/a	n/a	Input mode	Pull-up	n/a		☒
PA2	n/a	n/a	Input mode	Pull-up	n/a		☒
PB12	n/a	Low	Output Pu...	No pull-up...Low			☐

Select Pins from table to configure them. Multiple selection is Allowed.

Pinout view | System view

STM32F103C8Tx LQFP48

Pinout view | System view