

Here's a breakdown of the request:

```
// Request line
GET                                // HTTP method
/index.html                        // Request target
HTTP/1.1                          // HTTP version
\r\n                              // CRLF that marks the end of the request

// Headers
Host: localhost:4221\r\n          // Header that specifies the server's host
User-Agent: curl/7.64.1\r\n      // Header that describes the client's user
Accept: */*\r\n                  // Header that specifies which media types
\r\n                              // CRLF that marks the end of the headers

// Request body (empty)
```

The "request target" specifies the URL path for this request. In this example, the URL path is `/index.html`.

Note that each header ends in a CRLF, and the entire header section also ends in a CRLF.

Tests

The tester will execute your program like this:

```
$ ./your_program.sh
```

RECENT ATTEMPTS 11

	alex-ev...	<input type="text"/>
	glenn...	<input type="text"/>
	adama...	<input type="text"/>
	vhfmag	<input type="text"/>
	lucasm...	<input type="text"/>
	DanDFav	<input type="text"/>
	adamc...	<input type="text"/>
	kill-face	<input type="text"/>
	maxim...	<input type="text"/>
	matthe...	<input type="text"/>
	tasnuval	1/11 <input type="text"/>
	Invite a friend	



Private



leaderboards are

Tests failed. [Show logs](#)