

can still hardcode `+PONG\r\n` as the response. We'll get to parsing the incoming request in Stage 5 (Implement the ECHO command).

^ 40



↩ reply

**insufferablejake** 1 year ago

Found this immensely clarifying. Hosted by the Python site, but holds for all languages that provide a low level socket API.

<https://docs.python.org/3/howto/sockets.html#using-a-socket>

^ 10



↩ reply

**stonecharioteer** 1 year ago

Do you mean you need to do this within *one* connection? Because otherwise this suggests that being able to do `redis-cli ping` multiple times is good enough. And the solution for stage-2 would be sufficient for that purpose.

^ 9



↩ reply

**rohitpaulk** staff 1 year ago

Ah, good catch. I've updated the instructions to make this more clear:

*you'll respond to multiple PING commands sent by the same ~~client~~ connection.*

^ 17

**stonecharioteer** 1 year ago

Sweet!

^ 5

**kalexmills** 1 year ago

The test seems to be expecting servers to handle case-insensitive command keys, but I haven't been able to find anything in the spec which suggests that this is correct.

^ 2



↩ reply

**rohitpaulk** staff 11 months ago

This isn't defined in the [redis protocol spec](#), but it is mentioned in the [COMMAND](#)

Ready to run tests...

Show logs