



Instructions



Code Examples



Concepts



Forum

Stage #XU1

Pending

On one instance of the redis-cli, we'd add an entry and send a blocking XREAD command with 1000 as the time passed in and \$ as the id passed in.

```
$ redis-cli XADD some_key 1526985054069-0 temperature 36 humidity 95
"1526985054069-0"
$ redis-cli XREAD block 1000 streams some_key $
```

Then, on another instance of the redis-cli, we add another entry.

```
$ other-redis-cli XADD some_key 1526985054079-0 temperature 37 humidity 94
"1526985054079-0"
```

Similar to the behavior detailed in the earlier stages, if the command was sent within 1000 milliseconds, the redis-cli will respond with the new entry.

```
$ redis-cli XADD some_key 1526985054069-0 temperature 36 humidity 95
"1526985054069-0"
$ redis-cli XREAD block 1000 streams some_key 1526985054069-0
1) 1) "some_key"
   2) 1) 1) 1526985054079-0
      2) 1) temperature
        2) 37
        3) humidity
        4) 94
```

If not, the return type would still be a null representation of a bulk string.

```
$ redis-cli XADD some_key 1526985054069-0 temperature 36 humidity 95
"1526985054069-0"
$ redis-cli XREAD block 1000 streams some_key 1526985054069-0
(nil)
```

Tests

The tester will execute your program like this:

Ready to run tests...

Show logs