



Explore



OpenAPI definition v0 OAS 3.1

[/v3/api-docs](#)

Servers

track-controller



GET /api/tracks/{trackId}



Parameters

[Try it out](#)

Name	Description
------	-------------

trackId * requiredinteger(\$int64)
(path)

Responses

Code	Description	Links
------	-------------	-------

200

OK

No links

Media type

Controls Accept header.

Example Value Schema

Code	Description	Links
	<pre>{ "id": 0, "enterpriseId": 0, "name": "string", "description": "string", "tech": "string", "createdAt": "2026-08-07T05:46:33.597Z", "updatedAt": "2026-08-07T05:46:33.597Z" }</pre>	

PUT

/api/tracks/{trackId}

^

Parameters

Try it out

Name	Description
trackId * required integer(\$int64) (path)	trackId

Request body required

application/json

Example Value

Schema

```
{
  "name": "string",
  "description": "string",
  "tech": "string"
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0,</pre>	No links

Code	Description	Links
	<pre>"enterpriseId": 0, "name": "string", "description": "string", "tech": "string", "createdAt": "2026-08-07T05:46:33.609Z", "updatedAt": "2026-08-07T05:46:33.609Z" }</pre>	

DELETE

/api/tracks/{trackId}

Parameters

Try it out

Name	Description
trackId ★ required integer(\$int64) (path)	trackId

Responses

Code	Description	Links
200	OK	No links

GET

/api/tracks

Parameters

Try it out

Name	Description
q string (query)	q
tech string (query)	tech
pageable ★ required object	Example Value Schema

Name

Description

(query)

```
{
  "page": 0,
  "size": 1,
  "sort": [
    "string"
  ]
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 0, "name": "string", "description": "string", "tech": "string", "classCount": 0 }], "meta": { "page": 0, "size": 0, "total": 0 } }</pre>	

 No links |

POST

/api/tracks

^

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "name": "string",
  "description": "string",
  "tech": "string"
}
```

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "id": 0,
  "enterpriseId": 0,
  "name": "string",
  "description": "string",
  "tech": "string",
  "createdAt": "2026-08-07T05:46:33.626Z",
  "updatedAt": "2026-08-07T05:46:33.627Z"
}
```

project-controller



GET /api/projects/{projectId}/files/content



Parameters

Try it out

Name	Description
projectId * required	
integer(\$int64)	projectId

Name

Description

(path)

path★ required

string

(query)

path

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema { "path": "string", "content": "string" }	No links

PUT

/api/projects/{projectId}/files/content

Parameters

Try it out

Name

Description

projectId★ required

integer(\$int64)

(path)

projectId

Request body required

application/json

Example Value

Schema

{

"path": "string",

```
  "content": "string"
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "sessionId": 0, "path": "string", "importedBy": 0, "versionHash": "string", "fileCount": 0, "createdAt": "2026-08-07T05:46:33.090Z", "updatedAt": "2026-08-07T05:46:33.090Z" }</pre>	No links

POST /api/projects



Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "sessionId": 0,
  "path": "string",
  "importedBy": 0
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "sessionId": 0, "path": "string", "importedBy": 0, "versionHash": "string", "fileCount": 0, "createdAt": "2026-08-07T05:46:33.638Z", "updatedAt": "2026-08-07T05:46:33.638Z"}</pre>	No links

POST

/api/projects/import/local

^

Parameters

Try it out

No parameters

Request body required

application/json

Example Value

Schema

```
{  "sessionId": 0,  "files": {    "additionalProp1": "string"  }  }
```

Responses

Code	Description	Links
200	OK Media type */*	No links

Code	Description	Links
	Controls Accept header. Example Value Schema <pre>{ "projectId": 0, "sessionId": 0, "fileCount": 0, "versionHash": "string", "skippedFiles": [{ "path": "string", "reason": "string" }]}</pre>	

POST

/api/projects/import/git

^

Parameters

Try it out

No parameters

Request body **required**

application/json

Example Value

Schema

```
{  "sessionId": 0,  "repoUrl": "string",  "branch": "string",  "subPath": "string",  "pat": "string"}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema	No links

Code	Description	Links
	<pre>{ "projectId": 0, "sessionId": 0, "fileCount": 0, "versionHash": "string", "skippedFiles": [{ "path": "string", "reason": "string" }]}</pre>	

GET

/api/projects/{projectId}/files

^

Parameters

Try it out

Name	Description
projectId ★ required integer(\$int64) (path)	projectId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>[{ "path": "string", "size": 0 }]</pre>	No links

GET

/api/projects/current

^

Parameters

Try it out

Name	Description
sessionId ★ required integer(\$int64) (query)	sessionId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "sessionId": 0, "path": "string", "importedBy": 0, "versionHash": "string", "fileCount": 0, "createdAt": "2026-08-07T05:46:33.661Z", "updatedAt": "2026-08-07T05:46:33.661Z"}</pre>	No links

group-controller

^

GET /api/groups/{groupId}

^

Parameters

Try it out

Name	Description
groupId ★ required integer(\$int64) (path)	groupId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.667Z", "endedAt": "2026-08-07T05:46:33.667Z", "createdAt": "2026-08-07T05:46:33.667Z", "updatedAt": "2026-08-07T05:46:33.667Z" }</pre>	No links

PUT /api/groups/{groupId}



Parameters

Try it out

Name Description

groupId ★ required
integer(\$int64)
(path)

groupId

Request body required

application/json

Example Value Schema

```
{
  "name": "string",
  "description": "string",
  "startedAt": "2026-08-07T05:46:33.675Z",
  "endedAt": "2026-08-07T05:46:33.675Z"
}
```


Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.677Z", "endedAt": "2026-08-07T05:46:33.677Z", "createdAt": "2026-08-07T05:46:33.677Z", "updatedAt": "2026-08-07T05:46:33.677Z"}</pre>	No links

DELETE /api/groups/{groupId}

Parameters

Try it out

Name	Description
groupId ★ required integer(\$int64) (path)	groupId

Responses

Code	Description	Links
200	OK	No links

PATCH /api/groups/{groupId}

Parameters

Try it out

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.688Z", "endedAt": "2026-08-07T05:46:33.688Z", "memberCount": 0, "members": [{ "userId": 0, "name": "string", "email": "string", "role": "LEADER" }], "createdAt": "2026-08-07T05:46:33.688Z", "updatedAt": "2026-08-07T05:46:33.688Z"}</pre>	No links

GET	/api/groups	^
Parameters		Try it out
Name	Description	
classId * required integer(\$int64) (query)	classId	
Responses		
Code	Description	Links
200	OK Media type	No links

Code

Description

Links

/

Controls Accept header.

Example Value Schema

```
[
  {
    "id": 0,
    "classId": 0,
    "name": "string",
    "description": "string",
    "startedAt": "2026-08-07T05:46:33.692Z",
    "endedAt": "2026-08-07T05:46:33.692Z",
    "createdAt": "2026-08-07T05:46:33.692Z",
    "updatedAt": "2026-08-07T05:46:33.692Z"
  }
]
```

POST

/api/groups

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "classId": 0,
  "name": "string",
  "description": "string",
  "startedAt": "2026-08-07T05:46:33.695Z",
  "endedAt": "2026-08-07T05:46:33.695Z"
}
```

Responses

Code

Description

Links

200

OK

No links

Media type

/

Controls Accept header.

Code	Description	Links
	Example ValueSchema <pre>{ "id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.696Z", "endedAt": "2026-08-07T05:46:33.696Z", "createdAt": "2026-08-07T05:46:33.696Z", "updatedAt": "2026-08-07T05:46:33.696Z" }</pre>	

POST

/api/groups/{groupId}/duplicate

^

Parameters

Try it out

Name	Description
groupId * required integer(\$int64) (path) groupId	

Request body

application/json

Example ValueSchema

```
{
  "name": "string",
  "includeMembers": true
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example ValueSchema	No links

Code	Description	Links
	<pre>{ "id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.712Z", "endedAt": "2026-08-07T05:46:33.712Z", "memberCount": 0, "members": [{ "userId": 0, "name": "string", "email": "string", "role": "LEADER" }], "createdAt": "2026-08-07T05:46:33.712Z", "updatedAt": "2026-08-07T05:46:33.712Z" }</pre>	

POST

/api/groups/shuffle

Parameters

Try it out

Name	Description
classId * required integer(\$int64) (query)	classId

Request body required

application/json

Example Value

Schema

```
{
  "groupCount": 1,
  "assignLeader": true,
  "confirmed": true,
  "startedAt": "2026-08-07T05:46:33.717Z",
  "endedAt": "2026-08-07T05:46:33.717Z"
}
```

Responses

Code	Description	Links
200	OK	No links

Code	Description	Links
	Media type */* Controls Accept header. Example Value Schema [{ "id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.719Z", "endedAt": "2026-08-07T05:46:33.719Z", "memberCount": 0, "members": [{ "userId": 0, "name": "string", "email": "string", "role": "LEADER" }], "createdAt": "2026-08-07T05:46:33.719Z", "updatedAt": "2026-08-07T05:46:33.719Z" }]	

GET	/api/groups/{groupId}/detail	
Parameters		Try it out
Name	Description	
groupId * required integer(\$int64) (path)	groupId	
Responses		
Code	Description	Links
200	OK Media type */*	No links

Code	Description	Links
	Controls Accept header. Example Value Schema <pre>{ "id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.722Z", "endedAt": "2026-08-07T05:46:33.722Z", "memberCount": 0, "members": [{ "userId": 0, "name": "string", "email": "string", "role": "LEADER" }], "createdAt": "2026-08-07T05:46:33.722Z", "updatedAt": "2026-08-07T05:46:33.722Z"}</pre>	

GET

/api/groups/mine

Parameters

Try it out

Name	Description
classId ★ required integer(\$int64) (query)	classId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema [{	No links

Code	Description	Links
	<pre>"id": 0, "classId": 0, "name": "string", "description": "string", "startedAt": "2026-08-07T05:46:33.727Z", "endedAt": "2026-08-07T05:46:33.727Z", "memberCount": 0, "members": [{ "userId": 0, "name": "string", "email": "string", "role": "LEADER" }], "createdAt": "2026-08-07T05:46:33.727Z", "updatedAt": "2026-08-07T05:46:33.727Z" }</pre>	

GET

/api/groups/candidates

Parameters

Try it out

Name	Description
classId ★ required integer(\$int64) (query)	classId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>[{ "userId": 0, "name": "string", "email": "string" }]</pre>	No links

user-controller



GET

/api/users

^

Parameters

Try it out

Name	Description
role	Available values: MANAGER, STUDENT
string	--
(query)	
q	q
string	
(query)	
pageable * required	
object	
(query)	

Example Value

Schema

```
{
  "page": 0,
  "size": 1,
  "sort": [
    "string"
  ]
}
```

Code	Description	Links
------	-------------	-------

Media type

/

Controls Accept header.

Example Value	Schema
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

```
{
  "data": [
    {
      "id": 0,
      "name": "string",
      "email": "string",
      "role": "MANAGER",
      "phone": "string",
      "region": "string",
      "gender": "string",
      "weeklySessionCount": 0,
      "lastSessionCreatedAt": "2026-08-07T05:46:33.742Z"
    }
  ],
  "meta": {
    "page": 0,
    "size": 0,
    "total": 0
  }
}
```

POST

/api/users

⌵

Parameters

Try it out

No parameters

Request body required

application/json

Example Value

Schema

```
{
  "token": "string",
  "password": "stringst",
  "name": "string"
}
```

Responses

Code	Description	Links
201	Created Media type */* Controls Accept header. Example Value Schema <pre>{ "userId": 0, "enterpriseId": 0, "email": "string", "name": "string", "role": "MANAGER", "createdAt": "2026-08-07T05:46:33.749Z" }</pre>	

GET

/api/users/{userId}/report-summary

⌵

Parameters

Try it out

Name	Description
userId ★ required integer(\$int64) (path)	userId
classId ★ required integer(\$int64) (query)	classId

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "userReportId": 0,
  "ordinaryUserId": 0,
  "userName": "string",
  "classId": 0,
  "sessionCount": 0,
  "quizTotalCount": 0,
  "quizAttemptedCount": 0,
  "quizCorrectCount": 0,
  "quizSkippedCount": 0,
  "completionRate": 0,
  "accuracy": 0,
  "avgElapsedMs": 0,
  "difficultyRatio": {
    "additionalProp1": "string",
    "additionalProp2": "string",
    "additionalProp3": "string"
  },
  "conceptStats": {
    "additionalProp1": "string",
    "additionalProp2": "string",
    "additionalProp3": "string"
  },
  "rating": 0,
  "ratingFormulaVersion": "string",
  "aiComment": "string",
  "aiStrengths": [
    "string"
  ]
}
```

POST

/api/users/{userId}/report-summary

Parameters

Try it out

Name	Description
userId ★ required integer(\$int64) (path)	userId

Request body required

application/json

Example Value

Schema

```
{  "classId": 0,  "rating": 0,  "ratingFormulaVersion": "string"}
```

Responses

Code	Description	Links
201	Created Media type */* Controls Accept header. Example Value Schema <pre>{ "userReportId": 0, "ordinaryUserId": 0, "classId": 0, "issuedAt": "2026-08-07T05:46:33.767Z"}</pre>	

 No links |

GET

/api/users/{userId}

Parameters

Try it out

Name

Description

userId ★ required

integer(\$int64)
(path)

userId

Responses

Code

Description

Links

200

OK

No links

Media type

/

Controls Accept header.

Example Value

Schema

```
{
  "userId": 0,
  "enterpriseId": 0,
  "email": "string",
  "name": "string",
  "role": "string",
  "phone": "string",
  "region": "string",
  "gender": "string",
  "theme": "string",
  "createdAt": "2026-08-07T05:46:33.771Z",
  "updatedAt": "2026-08-07T05:46:33.771Z"
}
```

PATCH

/api/users/{userId}

Parameters

Try it out

Name

Description

userId ★ required

integer(\$int64)
(path)

userId

Request body required

application/json

Example Value Schema

```
{
  "name": "string",
  "currentPassword": "string",
  "newPassword": "stringst",
  "phone": "string",
  "region": "string",
  "gender": "string",
  "theme": "string"
}
```

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "userId": 0,
  "enterpriseId": 0,
  "email": "string",
  "name": "string",
  "role": "string",
  "phone": "string",
  "region": "string",
  "gender": "string",
  "theme": "string",
  "createdAt": "2026-08-07T05:46:33.780Z",
  "updatedAt": "2026-08-07T05:46:33.780Z"
}
```

GET /api/users/{userId}/session-reports



Parameters

Try it out

Name Description

userId ★ required
integer(\$int64)
(path)

userId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>[{ "sessionReportId": 0, "sessionId": 0, "sessionTitle": "string", "accuracy": 0, "quizRating": 0, "completionRate": 0, "issuedAt": "2026-08-07T05:46:33.785Z" }]</pre>	

No links

 |

student-comment-controller



GET /api/users/{userId}/comments

Parameters

Try it out

Name	Description
userId ★ required integer(\$int64) (path)	userId
classId integer(\$int64) (query)	classId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema [{ "id": 0, "ordinaryUserId": 0, "classId": 0, "authorId": 0, "authorName": "string", "content": "string", "createdAt": "2026-08-07T05:46:33.791Z", "updatedAt": "2026-08-07T05:46:33.791Z" }]	No links

POST

/api/users/{userId}/comments

^

Parameters

Try it out

Name	Description
userId ★ required integer(\$int64) (path)	userId

Request body

required

application/json

Example Value

Schema

{
 "classId": 0,
 "content": "string"
}

Responses

Code	Description	Links
201	Created	No links
	Media type */* Controls Accept header. Example Value Schema<pre>{ "id": 0, "ordinaryUserId": 0, "classId": 0, "authorId": 0, "authorName": "string", "content": "string", "createdAt": "2026-08-07T05:46:33.804Z", "updatedAt": "2026-08-07T05:46:33.804Z"}</pre>	

DELETE

/api/comments/{commentId}

Parameters

Try it out

Name	Description
commentId * required integer(\$int64) (path)	commentId

Responses

Code	Description	Links
200	OK	No links

PATCH

/api/comments/{commentId}

Parameters

Try it out

Name

Description

commentId ★ required

integer(\$int64)
(path)

commentId

Request body required

application/json

Example Value Schema

```
{  
  "content": "string"  
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "ordinaryUserId": 0, "classId": 0, "authorId": 0, "authorName": "string", "content": "string", "createdAt": "2026-08-07T05:46:33.820Z", "updatedAt": "2026-08-07T05:46:33.820Z" }</pre>	

 No links |

session-controller



GET /api/sessions

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "classId": 0,
  "groupId": 0,
  "title": "string",
  "classPublic": true,
  "classPublicRequested": true
}
```

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "id": 0,
  "classId": 0,
  "groupId": 0,
  "groupName": "string",
  "title": "string",
  "createdBy": 0,
  "active": true,
  "classPublic": true,
  "createdAt": "2026-08-07T05:46:33.835Z",
  "endedAt": "2026-08-07T05:46:33.835Z",
  "updatedAt": "2026-08-07T05:46:33.835Z"
}
```

GET /api/sessions/{sessionId}/reports



Parameters

Try it out

Name	Description
sessionId ★ required integer(\$int64) (path)	sessionId
userId integer(\$int64) (query)	userId

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "sessionReportId": 0,
  "sessionId": 0,
  "sessionTitle": "string",
  "ordinaryUserId": 0,
  "userName": "string",
  "quizSetId": 0,
  "quizTotalCount": 0,
  "quizAttemptedCount": 0,
  "quizCorrectCount": 0,
  "quizSkippedCount": 0,
  "completionRate": 0,
  "accuracy": 0,
  "avgElapsedMs": 0,
  "difficultyRatio": {
    "additionalProp1": "string",
    "additionalProp2": "string",
    "additionalProp3": "string"
  },
  "conceptStats": {
    "additionalProp1": "string",
    "additionalProp2": "string",
    "additionalProp3": "string"
  },
  "quizRating": 0,
  "aiComment": "string",
  "aiStrengths": [
    "string"
  ]
}
```

POST

/api/sessions/{sessionId}/reports

Parameters

Try it out

Name	Description
sessionId ★ required integer(\$int64) (path)	sessionId

Request body required

application/json

Example Value

Schema

```
{
  "ordinaryUserId": 0,
  "quizRating": 0,
  "aiComment": "string",
  "aiStrengths": [
    "string"
  ],
  "aiImprovements": [
    "string"
  ]
}
```

Responses

Code	Description	Links
201	Created Media type */* Controls Accept header. Example Value Schema <pre>{ "sessionReportId": 0, "sessionId": 0, "ordinaryUserId": 0, "issuedAt": "2026-08-07T05:46:33.851Z" }</pre>	

 No links |

POST

/api/sessions/{sessionId}/reports/all

Parameters

Try it out

Name	Description
sessionId ★ required integer(\$int64) (path)	sessionId

Responses

Code	Description	Links
201	Created Media type */* Controls Accept header. Example Value Schema <pre>{ "sessionId": 0, "issuedCount": 0}</pre>	No links

PATCH

/api/sessions/{sessionId}/reports/{userId}/manager-comment

⌵

Parameters

Try it out

Name	Description
sessionId ★ required integer(\$int64) (path)	sessionId
userId ★ required integer(\$int64) (path)	userId

Request body required

application/json

Example Value Schema

```
{
  "comment": "string"
}
```

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "sessionReportId": 0,
  "sessionId": 0,
  "sessionTitle": "string",
  "ordinaryUserId": 0,
  "userName": "string",
  "quizSetId": 0,
  "quizTotalCount": 0,
  "quizAttemptedCount": 0,
  "quizCorrectCount": 0,
  "quizSkippedCount": 0,
  "completionRate": 0,
  "accuracy": 0,
  "avgElapsedMs": 0,
  "difficultyRatio": {
    "additionalProp1": "string",
    "additionalProp2": "string",
    "additionalProp3": "string"
  },
  "conceptStats": {
    "additionalProp1": "string",
    "additionalProp2": "string",
    "additionalProp3": "string"
  },
  "quizRating": 0,
  "aiComment": "string",
  "aiStrengths": [
    "string"
  ]
}
```



GET /api/sessions/{id}



Parameters

Try it out

id ★ required id
integer(\$int64)
(*path*)

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "classId": 0, "groupId": 0, "groupName": "string", "title": "string", "createdBy": 0, "active": true, "classPublic": true, "createdAt": "2026-08-07T05:46:33.872Z", "endedAt": "2026-08-07T05:46:33.872Z", "updatedAt": "2026-08-07T05:46:33.872Z" }</pre> <td>No links</td>	No links

 $\wedge$

Try it out

id ★ required id
integer(\$int64)
(*path*)

Responses		
Code	Description	Links
200	OK	No links

PATCH

/api/sessions/{id}

Parameters

Try it out

Name	Description
id ★ required integer(\$int64) (path)	id

Request body required

application/json

Example Value

Schema

```
{  
  "title": "string",  
  "active": true  
}
```

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value

Schema

```
{  
  "id": 0,  
  "classId": 0,  
  "groupId": 0,  
  "groupName": "string",  
  "title": "string",  
}
```

Code	Description	Links
	<pre>"createdBy": 0, "active": true, "classPublic": true, "createdAt": "2026-08-07T05:46:33.885Z", "endedAt": "2026-08-07T05:46:33.885Z", "updatedAt": "2026-08-07T05:46:33.885Z" }</pre>	

GET

/api/sessions/{sessionId}/reports/roster

^

Parameters

Try it out

Name	Description
sessionId ★ required integer(\$int64) (path) sessionId	

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "sessionId": 0, "sessionTitle": "string", "issuedCount": 0, "avgAccuracy": 0.1, "avgCompletionRate": 0.1, "reports": [{ "sessionReportId": 0, "ordinaryUserId": 0, "userName": "string", "accuracy": 0, "quizRating": 0, "completionRate": 0, "issuedAt": "2026-08-07T05:46:33.891Z" }]}</pre>	No links

GET

/api/sessions/{id}/participants

^

Parameters

Try it out

Name	Description
id ★ required integer(\$int64) (path)	id

Responses

Code	Description	Links
200	OK Media type */*	No links

Code	Description	Links
	Controls Accept header.	
Example Value	Schema	
	<pre>[{ "userId": 0, "name": "string", "role": "string" }]</pre>	

GET /api/sessions/{id}/access ^

Parameters Try it out

Name	Description
id ★ required integer(\$int64) (path)	id

Responses

Code	Description	Links
200	OK	No links

session-help-request-controller ^

POST /api/sessions/{sessionId}/help ^

Parameters Try it out

Name

Description

sessionId ★ required

integer(\$int64)
(path)

sessionId

Responses

Code

Description

Links

201

Created

Media type

/

Controls Accept header.

Example Value

Schema

```
{
  "id": 0,
  "sessionId": 0,
  "classId": 0,
  "fromUserId": 0,
  "fromName": "string",
  "sessionTitle": "string",
  "createdAt": "2026-08-07T05:46:33.902Z"
}
```

No links

GET /api/classes/{classId}/help-requests

⌵

Parameters

Try it out

Name

Description

classId ★ required

integer(\$int64)
(path)

classId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>[{ "id": 0, "sessionId": 0, "classId": 0, "fromUserId": 0, "fromName": "string", "sessionTitle": "string", "createdAt": "2026-08-07T05:46:33.906Z" }]</pre>	No links

DELETE /api/help-requests/{id}

Parameters

Try it out

Name	Description
id ★ required integer(\$int64) (path) id	

Responses

Code	Description	Links
204	No Content	No links

quiz-controller

GET /api/quiz

Parameters

Try it out

Name	Description
project ★ required integer(\$int64) (query) project	

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>[{ "quizSetId": 0, "status": "QUEUED", "requestedCount": 0, "generatedCount": 0, "errorMessage": "string", "satisfactionRating": 0, "sourcePath": "string", "sourceKind": "string" }]</pre>	No links

POST /api/quiz

⌵

Parameters

Try it out

Name	Description
project ★ required integer(\$int64) (query) project	

Request body required

application/json

Example Value Schema

```
{
  "mode": "ASSESSMENT",
  "count": 1,
  "ratioEasy": 100,
  "ratioNormal": 100,
  "ratioHard": 100,
  "userPrompt": "string",
  "versionHash": "string",
  "targetFiles": [
    "string"
  ],
  "files": {
    "additionalProp1": "string"
  },
  "sourcePath": "string",
  "sourceKind": "string",
  "difficultyRatioValid": true
}
```

Responses

Code	Description	Links
202	Accepted	No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "quizSetId": 0,
  "status": "QUEUED",
  "requestedCount": 0
}
```

POST /api/quiz/{quizSetId}/satisfaction



Parameters

Try it out

Name Description

quizSetId * required

integer(\$int64)
(path)

quizSetId

Request body required

application/json

Example Value

Schema

```
{
  "rating": 1,
  "comment": "string"
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "quizSetId": 0, "status": "QUEUED", "requestedCount": 0, "generatedCount": 0, "errorMessage": "string", "satisfactionRating": 0, "sourcePath": "string", "sourceKind": "string" }</pre>	No links

POST

/api/quiz/{quizSetId}/questions/{quizId}/progress

Parameters

Try it out

Name	Description
quizSetId * required integer(\$int64) (path)	quizSetId

Name

Description

quizId ★ required

integer(\$int64)
(path)

quizId

Request body required

application/json

Example Value

Schema

```
{
  "status": "ATTEMPTED",
  "chosenChoiceIdx": 0,
  "startedAt": "2026-08-07T05:46:33.944Z",
  "finishedAt": "2026-08-07T05:46:33.944Z"
}
```

Responses

Code

Description

Links

201

Created

Media type

/

Controls Accept header.

Example Value

Schema

```
{
  "id": 0,
  "quizId": 0,
  "status": "ATTEMPTED",
  "chosenChoiceIdx": 0,
  "isCorrect": true,
  "elapsedMs": 0,
  "explanation": "string",
  "correctChoiceIdx": 0
}
```

No links

POST

/api/quiz/{quizSetId}/callback

⌵

Parameters

Try it out

Name

Description

quizSetId ★ required

integer(\$int64)
(path)

quizSetId

X-Ai-Callback-Secret

string
(header)

X-Ai-Callback-Secret

Request body required

application/json

Example Value

Schema

```
{
  "project": "string",
  "quiz_set_id": 0,
  "status": "PENDING",
  "quizzes": [
    {
      "purpose": "string",
      "difficulty": "string",
      "tested_concept": "string",
      "question": "string",
      "choices": [
        "string"
      ],
      "answer_index": 0,
      "explanation": "string",
      "file_path": "string",
      "line_start": 0,
      "line_end": 0
    }
  ],
  "error_message": "string",
  "meter": [
    {
      "stage": "string"
    }
  ]
}
```

Responses

Code

Description

Links

204

No Content

No links

GET

/api/quiz/{quizSetId}

Parameters

Try it out

Name	Description
quizSetId ★ required integer(\$int64) (path) quizSetId	

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "quizSetId": 0, "status": "QUEUED", "generationStage": "string", "requestedCount": 0, "generatedCount": 0, "errorMessage": "string", "quizzes": [{ "id": 0, "type": "MULTIPLE_CHOICE", "purpose": "CONCEPTUAL", "difficulty": "EASY", "testedConcept": "string", "question": "string", "explanation": "string", "filePath": "string", "lineStart": 0, "lineEnd": 0, "timeLimitSec": 0, "orderNo": 0, "choices": [{ "idx": 0, "content": "string", "answer": true }] }] }</pre>	

 No links |

GET

/api/quiz/{quizSetId}/satisfaction/me



Parameters

Try it out

Name	Description
------	-------------

quizSetId ★ requiredinteger(\$int64)
(path)

quizSetId

Responses

Code	Description	Links
------	-------------	-------

200

OK

No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "additionalProp1": true,
  "additionalProp2": true,
  "additionalProp3": true
}
```

GET

/api/quiz/{quizSetId}/questions



Parameters

Try it out

Name	Description
------	-------------

quizSetId ★ requiredinteger(\$int64)
(path)

quizSetId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "quizSetId": 0, "status": "QUEUED", "generationStage": "string", "requestedCount": 0, "quizzes": [{ "id": 0, "type": "MULTIPLE_CHOICE", "difficulty": "EASY", "testedConcept": "string", "question": "string", "filePath": "string", "lineStart": 0, "lineEnd": 0, "timeLimitSec": 0, "orderNo": 0, "choices": [{ "idx": 0, "content": "string", "answer": true }] }] }</pre>	No links

GET

/api/quiz/{quizSetId}/progress

^

Parameters

Try it out

Name	Description
quizSetId ★ required integer(\$int64) (path)	quizSetId
userId integer(\$int64) (query)	userId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "quizSetId": 0, "totalCount": 0, "attemptedCount": 0, "correctCount": 0, "items": [{ "quizId": 0, "status": "ATTEMPTED", "chosenChoiceIdx": 0, "isCorrect": true, "elapsedMs": 0, "explanation": "string", "correctChoiceIdx": 0 }]}</pre>	No links

GET /api/quiz/{quizSetId}/progress/roster



Parameters

Try it out

Name Description

quizSetId ★ required
integer(\$int64)
(path)

quizSetId

Responses

Code	Description	Links
200	OK Media type	No links

Code	Description	Links
	/ Controls Accept header. Example Value Schema <pre>{ "quizSetId": 0, "totalQuizCount": 0, "totalStudentCount": 0, "startedStudentCount": 0, "inProgressStudentCount": 0, "completedStudentCount": 0, "allCompleted": true, "students": [{ "userId": 0, "userName": "string", "answeredCount": 0, "correctCount": 0, "totalQuizCount": 0, "status": "string" }]}</pre>	

GET	/api/quiz/{quizSetId}/progress/incorrect	
Parameters		Try it out
Name	Description	
quizSetId * required integer(\$int64) (path)	quizSetId	
Responses		
Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema	No links

Code	Description	Links
	<pre>{ "quizSetId": 0, "incorrectCount": 0, "items": [{ "quizId": 0, "status": "ATTEMPTED", "chosenChoiceIdx": 0, "isCorrect": true, "elapsedMs": 0, "explanation": "string", "correctChoiceIdx": 0 }] }</pre>	

app-notification-controller

POST	/api/notifications/read-all	
Parameters		Try it out
No parameters		
Responses		
Code	Description	Links
200	OK	No links

GET	/api/notifications	
Parameters		Try it out
No parameters		
Responses		

Code	Description	Links
200	OK Media type */ Controls Accept header. Example Value Schema <pre>[{ "id": 0, "type": "string", "title": "string", "body": "string", "link": "string", "unread": true, "createdAt": "2026-08-07T05:46:33.985Z" }]</pre>	No links

GET /api/notifications/unread-count ^

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type */ Controls Accept header. Example Value Schema <pre>{ "additionalProp1": 0, "additionalProp2": 0, "additionalProp3": 0 }</pre>	No links



notice-controller

GET /api/notices



Parameters

Try it out

Name	Description
scope string (query)	<i>Available values:</i> ENTERPRISE, TRACK, CLASS --
trackId integer(\$int64) (query)	trackId
classId integer(\$int64) (query)	classId
forAudience boolean (query)	<i>Default value:</i> false false
pageable * required object (query)	Example ValueSchema <pre>{ "page": 0, "size": 1, "sort": ["string"]}</pre>



Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 0, "scope": "ENTERPRISE", "trackId": 0, "classId": 0, "targetName": "string", "title": "string", "body": "string", "pinned": true, "authorName": "string", "createdAt": "2026-08-07T05:46:33.996Z" }], "meta": { "page": 0, "size": 0, "total": 0 }}</pre>	No links

POST /api/notices

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{  "scope": "ENTERPRISE",  "trackId": 0,  "classId": 0,  "title": "string",  "body": "string",  "pinned": true}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "scope": "ENTERPRISE", "trackId": 0, "classId": 0, "title": "string", "body": "string", "pinned": true, "createdBy": 0, "createdByType": "MASTER", "createdAt": "2026-08-07T05:46:34.004Z", "updatedAt": "2026-08-07T05:46:34.004Z"}</pre>	No links

GET /api/notices/{noticeId}

Parameters

Try it out

Name	Description
noticeId * required integer(\$int64) (path)	noticeId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header.	No links

Code

Description

Links

Example Value

Schema

```
{
  "id": 0,
  "scope": "ENTERPRISE",
  "trackId": 0,
  "classId": 0,
  "targetName": "string",
  "title": "string",
  "body": "string",
  "pinned": true,
  "authorName": "string",
  "createdAt": "2026-08-07T05:46:34.009Z"
}
```

DELETE

/api/notices/{noticeId}

^

Parameters

Try it out

Name	Description
noticeId * required integer(\$int64) (path)	noticeId

Responses

Code	Description	Links
200	OK	No links

PATCH

/api/notices/{noticeId}

^

Parameters

Try it out

Name	Description
noticeId * required integer(\$int64) (path)	noticeId

Request body required

application/json

Example Value

Schema

```
{
  "title": "string",
  "body": "string",
  "pinned": true
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "scope": "ENTERPRISE", "trackId": 0, "classId": 0, "title": "string", "body": "string", "pinned": true, "createdBy": 0, "createdByType": "MASTER", "createdAt": "2026-08-07T05:46:34.033Z", "updatedAt": "2026-08-07T05:46:34.033Z" }</pre>	

No links

 |

demo-request-controller

POST

/api/marketing/demo-requests

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "lastName": "string",
  "firstName": "string",
  "workEmail": "user@example.com",
  "company": "string",
  "title": "string",
  "phone": "string",
  "useCases": [
    "string"
  ],
  "otherDetail": "string"
}
```

Responses

Code	Description	Links
204	No Content	No links

invitation-controller



POST /api/invitations



Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "email": "user@example.com",
  "classId": 0,
  "role": "MANAGER"
}
```

Responses

Code	Description	Links
201	Created Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "email": "string", "role": "MANAGER", "classId": 0, "className": "string", "expiresAt": "2026-08-07T05:46:34.045Z", "token": "string", "signUpUrl": "string" }</pre>	No links

POST

/api/invitations/bulk

^

Parameters

Try it out

Name	Description
classId * required integer(\$int64) (query)	classId
role * required string (query)	Available values: MANAGER, STUDENT MANAGER

Request body

multipart/form-data

file * required

string(\$binary)

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "total": 0, "invited": 0, "failed": 0, "results": [{ "rowNumber": 0, "email": "string", "invited": true, "message": "string" }]}</pre>	No links

GET /api/invitations/{token}

Parameters

Try it out

Name	Description
token ★ required string (path)	token

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema	No links

Code	Description	Links
	<pre>{ "email": "string", "role": "MANAGER", "classId": 0, "className": "string", "expiresAt": "2026-08-07T05:46:34.059Z" }</pre>	

class-controller



GET

/api/classes

^

Parameters

Try it out

Name	Description
trackId integer(\$int64) (query)	trackId
q string (query)	q
pageable * required object (query)	Example Value Schema <pre>{ "page": 0, "size": 1, "sort": ["string"] }</pre>

Responses



Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "data": [{ "id": 0, "trackId": 0, "classNumber": 0, "name": "string", "capacity": 0, "description": "string", "startedAt": "2026-08-07T05:46:34.066Z", "endedAt": "2026-08-07T05:46:34.066Z", "createdAt": "2026-08-07T05:46:34.066Z", "updatedAt": "2026-08-07T05:46:34.066Z" }], "meta": { "page": 0, "size": 0, "total": 0 }}</pre>	No links

POST /api/classes

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{  "trackId": 0,  "classNumber": 1,  "name": "string",  "capacity": 1,  "description": "string",  "startedAt": "2026-08-07T05:46:34.071Z",  "endedAt": "2026-08-07T05:46:34.071Z"}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "trackId": 0, "classNumber": 0, "name": "string", "capacity": 0, "description": "string", "startedAt": "2026-08-07T05:46:34.073Z", "endedAt": "2026-08-07T05:46:34.073Z", "createdAt": "2026-08-07T05:46:34.073Z", "updatedAt": "2026-08-07T05:46:34.073Z"}</pre>	No links

GET /api/classes/{classId}

Parameters

Try it out

Name	Description
classId * required integer(\$int64) (path)	classId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema	No links

Code	Description	Links
	<pre>{ "id": 0, "trackId": 0, "classNumber": 0, "name": "string", "capacity": 0, "description": "string", "startedAt": "2026-08-07T05:46:34.078Z", "endedAt": "2026-08-07T05:46:34.078Z", "createdAt": "2026-08-07T05:46:34.078Z", "updatedAt": "2026-08-07T05:46:34.078Z" }</pre>	

DELETE

/api/classes/{classId}

Parameters

Try it out

Name	Description
classId ★ required integer(\$int64) (path) classId	

Responses

Code	Description	Links
200	OK	No links

PATCH

/api/classes/{classId}

Parameters

Try it out

Name	Description
classId ★ required integer(\$int64) (path) classId	

Request body

required

application/json

Example Value

Schema

```
{
  "classNumber": 1,
  "name": "string",
  "capacity": 1,
  "description": "string",
  "startedAt": "2026-08-07T05:46:34.088Z",
  "endedAt": "2026-08-07T05:46:34.088Z"
}
```

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "trackId": 0, "classNumber": 0, "name": "string", "capacity": 0, "description": "string", "startedAt": "2026-08-07T05:46:34.091Z", "endedAt": "2026-08-07T05:46:34.091Z", "createdAt": "2026-08-07T05:46:34.091Z", "updatedAt": "2026-08-07T05:46:34.091Z" }</pre>	No links

GET

/api/classes/{classId}/users

Parameters

Try it out

Name	Description
classId * required integer(\$int64) (path)	classId

Name	Description
role string <i>(query)</i>	<i>Available values: </i> MANAGER, STUDENT --
q string <i>(query)</i>	q
pageable ★ required object <i>(query)</i>	Example ValueSchema <pre>{ "page": 0, "size": 1, "sort": ["string"]}</pre>



Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example ValueSchema <pre>{ "data": [{ "userId": 0, "name": "string", "email": "string", "role": "MANAGER", "groupId": 0, "groupName": "string", }]}</pre>	No links

Code	Description	Links
	<pre> "phone": "string" },], "meta": { "page": 0, "size": 0, "total": 0 } }</pre>	

GET /api/classes/me ^

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>[{ "id": 0, "trackId": 0, "classNumber": 0, "name": "string", "capacity": 0, "description": "string", "startedAt": "2026-08-07T05:46:34.104Z", "endedAt": "2026-08-07T05:46:34.104Z", "createdAt": "2026-08-07T05:46:34.104Z", "updatedAt": "2026-08-07T05:46:34.104Z" }]</pre>	No links

class-material-controller ^

GET /api/classes/{classId}/materials ^

Parameters

Try it out

Name	Description
classId ★ required integer(\$int64) (path)	classId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>[{ "id": 0, "classId": 0, "fileName": "string", "contentType": "string", "byteSize": 0, "uploadedBy": 0, "uploaderName": "string", "createdAt": "2026-08-07T05:46:34.109Z" }]</pre>	No links

POST /api/classes/{classId}/materials

⌵

Parameters

Try it out

Name	Description
classId ★ required integer(\$int64) (path)	classId

Request body

multipart/form-data

file * **required**
string(\$binary)

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "classId": 0, "fileName": "string", "contentType": "string", "byteSize": 0, "uploadedBy": 0, "uploaderName": "string", "createdAt": "2026-08-07T05:46:34.116Z" }</pre>	No links

GET /api/classes/{classId}/materials/{materialId}/download



Parameters

Try it out

Name	Description
classId * required integer(\$int64) (path)	classId
materialId * required integer(\$int64) (path)	materialId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema string	No links

DELETE /api/classes/{classId}/materials/{materialId}

Parameters

Try it out

Name	Description
classId ★ required integer(\$int64) (path)	classId
materialId ★ required integer(\$int64) (path)	materialId

Responses

Code	Description	Links
200	OK	No links

auth-controller

POST

/api/auth/refresh

Parameters

Try it out

Name	Description
REFRESH_TOKEN string (cookie)	REFRESH_TOKEN

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "name": "string", "email": "string", "role": "string", "enterpriseId": 0, "classId": 0}</pre>	No links

POST

/api/auth/logout

Parameters

Try it out

Name	Description
REFRESH_TOKEN string (cookie)	REFRESH_TOKEN

Responses		
Code	Description	Links
200	OK	No links

POST

/api/auth/login

^

Parameters

Try it out

No parameters

Request body required

application/json

Example Value

Schema

```
{
  "email": "user@example.com",
  "password": "string"
}
```

Responses

Code	Description	Links
200	OK	No links

Media type

/

Controls Accept header.

Example Value

Schema

```
{
  "id": 0,
  "name": "string",
  "email": "string",
  "role": "string",
  "enterpriseId": 0,
  "classId": 0
}
```

GET /api/auth/me ^

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "id": 0, "name": "string", "email": "string", "role": "string", "enterpriseId": 0, "classId": 0}</pre>	No links

password-reset-controller ^

POST /api/auth/password-reset ^

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{  "email": "user@example.com"}
```

Responses		
Code	Description	Links
204	No Content	No links

POST

/api/auth/password-reset/confirm

Parameters

Try it out

No parameters

Request body required

application/json

Example Value

Schema

```
{  "token": "string",  "newPassword": "stringst"}
```

Responses

Code	Description	Links
204	No Content	No links

voice-channel-controller

GET

/api/sessions/{sessionId}/voice/participants

Parameters

Try it out

Name

Description

sessionId ★ required

integer(\$int64)
(path)

sessionId

Responses

Code

Description

Links

200

OK

Media type

/

Controls Accept header.

Example Value

Schema

[
 {
 "userId": 0,
 "name": "string",
 "role": "string",
 "micMuted": true,
 "deafened": true
 }
]

No links

chat-controller



GET

/api/sessions/{sessionId}/messages

^

Parameters

Try it out

Name

Description

sessionId ★ required

integer(\$int64)
(path)

sessionId

beforeId

integer(\$int64)
(query)

beforeId

Name

Description

size

integer(\$int32)
(query)

size

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema [{ "id": 0, "sessionId": 0, "senderId": 0, "senderName": "string", "content": "string", "createdAt": "2026-08-07T05:46:34.162Z" }]	No links

report-controller



GET /api/reports/users/{userId}/export

Parameters

Try it out

Name	Description
userId * required integer(\$int64) (path)	userId

Name

Description

classId ★ required

integer(\$int64)
(query)

classId

Responses

Code

Description

Links

200

OK

Media type

/

Controls Accept header.

Example Value

Schema

string

No links

GET /api/reports/sessions/{sessionId}/export

^

Parameters

Try it out

Name

Description

sessionId ★ required

integer(\$int64)
(path)

sessionId

userId ★ required

integer(\$int64)
(query)

userId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema string	No links

analytics-controller



GET

/api/analytics/overview



Parameters

Try it out

No parameters

Responses

Code

Description

Links

200

OK

No links

Media type

/

Controls Accept header.

Example Value Schema

```
{
  "trackCount": 0,
  "activeClassCount": 0,
  "managerCount": 0,
  "studentCount": 0
}
```

GET

/api/analytics/classes/{classId}



Parameters

Try it out

Name

Description

classId * requiredinteger(\$int64)
(path)

classId

Responses

Code	Description	Links
200	OK Media type */* Controls Accept header. Example Value Schema <pre>{ "classId": 0, "studentCount": 0, "managerCount": 0, "groupCount": 0, "sessionCount": 0, "activeSessionCount": 0, "reportedStudentCount": 0, "avgAccuracy": 0.1, "avgCompletionRate": 0.1, "avgElapsedMs": 0 }</pre>	No links

Schemas

^

TrackUpdateRequest ^ Collapse all object

name* string [0, 100] characters

description string [0, 255] characters

tech string [0, 20] characters

TrackResponse ^ Collapse all object

id integer int64

enterpriseld integer int64

name string

description string

tech string

createdAt string date-time

updatedAt string date-time

ProjectFileUpdateRequest ^ Collapse all object

```
path* string [0, 500] characters
content* string
```

ProjectResponse ^ Collapse all object

```
id integer int64
sessionId integer int64
path string
importedBy integer int64
versionHash string
fileCount integer int32
createdAt string date-time
updatedAt string date-time
```

GroupUpdateRequest ^ Collapse all object

```
name* string [0, 100] characters
description* string [0, 255] characters
startedAt* string date-time
endedAt* string date-time
```

GroupResponse ^ Collapse all object

```
id integer int64
classId integer int64
name string
description string
startedAt string date-time
endedAt string date-time
createdAt string date-time
updatedAt string date-time
```

UserSignUpRequest ^ Collapse all object

```
token* string ≥ 1 characters
```

```
password* string [8, 64] characters
name* string [0, 50] characters
```

UserSignUpResponse ^ Collapse all object

```
userId integer int64
enterpriseId integer int64
email string
name string
role ^ Collapse all string
  Enum ^ Collapse all array
    #0="MANAGER"
    #1="STUDENT"
createdAt string date-time
```

UserReportCreateRequest ^ Collapse all object

```
classId* integer int64
rating number
ratingFormulaVersion string [0, 20] characters
```

UserReportCreateResponse ^ Collapse all object

```
userReportId integer int64
ordinaryUserId integer int64
classId integer int64
issuedAt string date-time
```

StudentCommentCreateRequest ^ Collapse all object

```
classId* integer int64
content* string [0, 2000] characters
```

StudentCommentResponse ^ Collapse all object

```
id integer int64
ordinaryUserId integer int64
```

```
classId integer int64

authorId integer int64

authorName string

content string

createdAt string date-time

updatedAt string date-time
```

TrackCreateRequest ^ Collapse all object

```
name* string [0, 100] characters

description string [0, 255] characters

tech string [0, 20] characters
```

SessionCreateRequest ^ Collapse all object

```
classId* integer int64

groupId integer int64

title* string [0, 100] characters

classPublic boolean

classPublicRequested boolean
```

SessionResponse ^ Collapse all object

```
id integer int64

classId integer int64

groupId integer int64

groupName string

title string

createdBy integer int64

active boolean

classPublic boolean

createdAt string date-time

endedAt string date-time

updatedAt string date-time
```

SessionReportCreateRequest ^ Collapse all object

```
ordinaryUserId* integer int64

quizRating number

aiComment string

aiStrengths ^ Collapse all array<string>
  items string

aiImprovements ^ Collapse all array<string>
  items string
```

SessionReportCreateResponse ^ Collapse all object

```
sessionReportId integer int64

sessionId integer int64

ordinaryUserId integer int64

issuedAt string date-time
```

SessionReportBulkResponse ^ Collapse all object

```
sessionId integer int64

issuedCount integer int32
```

HelpRequestResponse ^ Collapse all object

```
id integer int64

sessionId integer int64

classId integer int64

fromUserId integer int64

fromName string

sessionTitle string

createdAt string date-time
```

QuizGenerateRequest ^ Collapse all object

```
mode* ^ Collapse all string

Enum ^ Collapse all array
  #0="ASSESSMENT"
```

```

    #1="PRACTICE"

    count integer [1, 20] int32

    ratioEasy integer [0, 100] int32

    ratioNormal integer [0, 100] int32

    ratioHard integer [0, 100] int32

    userPrompt string [0, 500] characters

    versionHash* string [0, 64] characters

    targetFiles ^ Collapse all array<string>
        items string

    files* ^ Collapse all object ≥ 1 properties
        Additional properties string

    sourcePath string [0, 500] characters

    sourceKind string [0, 12] characters

    difficultyRatioValid boolean

```

QuizGenerateResponse ^ Collapse all object

```

    quizSetId integer int64

    status ^ Collapse all string

    Enum ^ Collapse all array
        #0="QUEUED"
        #1="GENERATING"
        #2="COMPLETED"
        #3="FAILED"

    requestedCount integer int32

```

QuizSatisfactionRequest ^ Collapse all object

```

    rating integer [1, 5] int32

    comment string [0, 500] characters

```

QuizSetSummaryResponse ^ Collapse all object

```

    quizSetId integer int64

    status ^ Collapse all string

    Enum ^ Collapse all array

```

```
#0="QUEUED"

#1="GENERATING"

#2="COMPLETED"

#3="FAILED"

requestedCount integer int32

generatedCount integer int32

errorMessage string

satisfactionRating integer int32

sourcePath string

sourceKind string
```

QuizProgressSubmitRequest ^ Collapse all object

```
status* ^ Collapse all string

  Enum ^ Collapse all array

    #0="ATTEMPTED"

    #1="SKIPPED"

    #2="TIMEOUT"

chosenChoiceIdx integer int32

startedAt* string date-time

finishedAt* string date-time
```

QuizProgressResponse ^ Collapse all object

```
id integer int64

quizId integer int64

status ^ Collapse all string

  Enum ^ Collapse all array

    #0="ATTEMPTED"

    #1="SKIPPED"

    #2="TIMEOUT"

chosenChoiceIdx integer int32

isCorrect boolean

elapsedMs integer int64

explanation string
```

```
correctChoiceIdx integer int32
```

AiLlmCall Collapse all object

```
stage string
```

AiQuiz Collapse all object

```
purpose string
```

```
difficulty string
```

```
tested_concept string
```

```
question string
```

```
choices  Collapse all array<string>
```

```
  items string
```

```
answer_index integer int32
```

```
explanation string
```

```
file_path string
```

```
line_start integer int32
```

```
line_end integer int32
```

AiQuizStatusResponse Collapse all object

```
project string
```

```
quiz_set_id integer int64
```

```
status  Collapse all string
```

```
  Enum  Collapse all array
```

```
    #0="PENDING"
```

```
    #1="GENERATING"
```

```
    #2="READY"
```

```
    #3="FAILED"
```

```
quizzes  Collapse all array<object>
```

```
  items  Collapse all object
```

```
    purpose string
```

```
    difficulty string
```

```
    tested_concept string
```

```
    question string
```



```
choices ^ Collapse all array<string>
  Items string
answer_index integer int32
explanation string
file_path string
line_start integer int32
line_end integer int32
error_message string
meter ^ Collapse all array<object>
  Items ^ Collapse all object
  stage string
```

ProjectCreateRequest ^ Collapse all object

```
sessionId* integer int64
path string [0, 500] characters
importedBy* integer int64
```

ProjectImportLocalRequest ^ Collapse all object

```
sessionId* integer int64
files* ^ Collapse all object ≥ 1 properties
  Additional properties string
```

ProjectImportResponse ^ Collapse all object

```
projectId integer int64
sessionId integer int64
fileCount integer int32
versionHash string
skippedFiles ^ Collapse all array<object>
  Items ^ Collapse all object
    path string
    reason string
```

SkippedFileResponse Collapse all object

```
path string
reason string
```

ProjectImportGitRequest Collapse all object

```
sessionId* integer int64
repoUrl* string [0, 500] characters
branch string [0, 100] characters
subPath string [0, 200] characters
pat string [0, 200] characters
```

NoticeCreateRequest Collapse all object

```
scope*  Collapse all string
  Enum  Collapse all array
    #0="ENTERPRISE"
    #1="TRACK"
    #2="CLASS"
trackId integer int64
classId integer int64
title* string [0, 200] characters
body* string ≥ 1 characters
pinned boolean
```

NoticeDetailResponse Collapse all object

```
id integer int64
scope  Collapse all string
  Enum  Collapse all array
    #0="ENTERPRISE"
    #1="TRACK"
    #2="CLASS"
trackId integer int64
classId integer int64
```

```
title string

body string

pinned boolean

createdBy integer int64

createdByType ^ Collapse all string

  Enum ^ Collapse all array
    #0="MASTER"
    #1="MANAGER"

createdAt string date-time

updatedAt string date-time
```

DemoRequest ^ Collapse all object

```
lastName* string [0, 50] characters

firstName* string [0, 50] characters

workEmail* string email [0, 255] characters

company* string [0, 100] characters

title* string [0, 100] characters

phone* string [0, 30] characters

useCases* ^ Collapse all array<string> ≥ 1 items
  Items string [0, 40] characters

otherDetail string [0, 2000] characters
```

InvitationCreateRequest ^ Collapse all object

```
email* string email [0, 255] characters

classId* integer int64

role* ^ Collapse all string

  Enum ^ Collapse all array
    #0="MANAGER"
    #1="STUDENT"
```

InvitationCreateResponse ^ Collapse all object

```
id integer int64

email string
```

```
role ^ Collapse all string
  Enum ^ Collapse all array
    #0="MANAGER"
    #1="STUDENT"
classId integer int64
className string
expiresAt string date-time
token string
signUpUrl string
```

BulkInvitationResponse ^ Collapse all object

```
total integer int32
invited integer int32
failed integer int32
results ^ Collapse all array<object>
  Items ^ Collapse all object
    rowNumber integer int32
    email string
    invited boolean
    message string
```

RowResult ^ Collapse all object

```
rowNumber integer int32
email string
invited boolean
message string
```

GroupCreateRequest ^ Collapse all object

```
classId* integer int64
name* string [0, 100] characters
description* string [0, 255] characters
startedAt* string date-time
endedAt* string date-time
```

GroupDuplicateRequest ^ Collapse all object

```
name string [0, 100] characters
includeMembers boolean
```

GroupDetailResponse ^ Collapse all object

```
id integer int64
classId integer int64
name string
description string
startedAt string date-time
endedAt string date-time
memberCount integer int32
members ^ Collapse all array<object>
  Items ^ Collapse all object
    userId integer int64
    name string
    email string
    role ^ Collapse all string
      Enum ^ Collapse all array
        #0="LEADER"
        #1="PARTICIPANT"
    createdAt string date-time
    updatedAt string date-time
```

GroupMemberResponse ^ Collapse all object

```
userId integer int64
name string
email string
role ^ Collapse all string
  Enum ^ Collapse all array
    #0="LEADER"
```

```
#1="PARTICIPANT"
```

GroupShuffleRequest ^ Collapse all object

```
groupCount* integer [1, 50] int32
assignLeader boolean
confirmed boolean
startedAt string date-time
endedAt string date-time
```

ClassCreateRequest ^ Collapse all object

```
trackId* integer int64
classNumber* integer ≥ 1 int32
name* string [0, 50] characters
capacity integer ≥ 1 int32
description string [0, 255] characters
startedAt string date-time
endedAt string date-time
```

ClassResponse ^ Collapse all object

```
id integer int64
trackId integer int64
classNumber integer int32
name string
capacity integer int32
description string
startedAt string date-time
endedAt string date-time
createdAt string date-time
updatedAt string date-time
```

ClassMaterialResponse ^ Collapse all object

```
id integer int64
```

```
classId integer int64

fileName string

contentType string

byteSize integer int64

uploadedBy integer int64

uploaderName string

createdAt string date-time
```

LoginResponse ^ Collapse all object

```
id integer int64

name string

email string

role string

enterprisId integer int64

classId integer int64
```

PasswordResetRequest ^ Collapse all object

```
email* string email ≥ 1 characters
```

PasswordResetConfirmRequest ^ Collapse all object

```
token* string ≥ 1 characters

newPassword* string [8, 64] characters
```

LoginRequest ^ Collapse all object

```
email* string email ≥ 1 characters

password* string ≥ 1 characters
```

UserProfileUpdateRequest ^ Collapse all object

```
name string [0, 50] characters

currentPassword string

newPassword string [8, 64] characters

phone string [0, 30] characters
```

```
region string [0, 50] characters
gender string [0, 10] characters
theme string [0, 10] characters
```

UserProfileResponse ^ Collapse all object

```
userId integer int64
enterpriseId integer int64
email string
name string
role string
phone string
region string
gender string
theme string
createdAt string date-time
updatedAt string date-time
```

SessionReportManagerCommentRequest ^ Collapse all object

```
comment* string [0, 2048] characters
```

SessionReportDetailResponse ^ Collapse all object

```
sessionReportId integer int64
sessionId integer int64
sessionTitle string
ordinaryUserId integer int64
userName string
quizSetId integer int64
quizTotalCount integer int32
quizAttemptedCount integer int32
quizCorrectCount integer int32
quizSkippedCount integer int32
completionRate number
```



```
accuracy number

avgElapsedMs integer int32

difficultyRatio ^ Collapse all object
  Additional properties any

conceptStats ^ Collapse all object
  Additional properties any

quizRating number

aiComment string

aiStrengths ^ Collapse all array<string>
  Items string

aiImprovements ^ Collapse all array<string>
  Items string

managerComment string

issuedAt string date-time
```

SessionUpdateRequest ^ Collapse all object

```
title string [0, 100] characters

active boolean
```

NoticeUpdateRequest ^ Collapse all object

```
title string [0, 200] characters

body string

pinned boolean
```

GroupEditRequest ^ Collapse all object

```
name string [0, 100] characters

description string [0, 255] characters

startedAt string date-time

endedAt string date-time

memberIds ^ Collapse all array<integer>
  Items integer int64

leaderId integer int64
```

StudentCommentUpdateRequest ^ Collapse all object

```
content* string [0, 2000] characters
```

ClassUpdateRequest ^ Collapse all object

```
classNumber integer ≥ 1 int32
name string [0, 50] characters
capacity integer ≥ 1 int32
description string [0, 255] characters
startedAt string date-time
endedAt string date-time
```

Pageable ^ Collapse all object

```
page integer ≥ 0 int32
size integer ≥ 1 int32
sort ^ Collapse all array<string>
  Items string
```

PageMeta ^ Collapse all object

```
page integer int32
size integer int32
total integer int64
```

PageResponseUserSummaryResponse ^ Collapse all object

```
data ^ Collapse all array<object>
  Items ^ Collapse all object
    id integer int64
    name string
    email string
    role ^ Collapse all string
      Enum ^ Collapse all array
        #0="MANAGER"
        #1="STUDENT"
```

```
    phone string

    region string

    gender string

    weeklySessionCount integer int64

    lastSessionCreatedAt string date-time

meta ^ Collapse all object

    page integer int32

    size integer int32

    total integer int64
```

UserSummaryResponse ^ Collapse all object

```
    id integer int64

    name string

    email string

    role ^ Collapse all string

    Enum ^ Collapse all array

        #0="MANAGER"

        #1="STUDENT"

    phone string

    region string

    gender string

    weeklySessionCount integer int64

    lastSessionCreatedAt string date-time
```

SessionReportSummaryResponse ^ Collapse all object

```
    sessionReportId integer int64

    sessionId integer int64

    sessionTitle string

    accuracy number

    quizRating number

    completionRate number

    issuedAt string date-time
```

UserReportDetailResponse ^ Collapse all object

```
userReportId integer int64
ordinaryUserId integer int64
userName string
classId integer int64
sessionCount integer int32
quizTotalCount integer int32
quizAttemptedCount integer int32
quizCorrectCount integer int32
quizSkippedCount integer int32
completionRate number
accuracy number
avgElapsedMs integer int32
difficultyRatio ^ Collapse all object
  Additional properties any
conceptStats ^ Collapse all object
  Additional properties any
rating number
ratingFormulaVersion string
aiComment string
aiStrengths ^ Collapse all array<string>
  Items string
aiImprovements ^ Collapse all array<string>
  Items string
issuedAt string date-time
```

PageResponseTrackSummaryResponse ^ Collapse all object

```
data ^ Collapse all array<object>
  Items ^ Collapse all object
    id integer int64
    name string
    description string
    tech string
```

```
classCount integer int64

meta ^ Collapse all object

page integer int32

size integer int32

total integer int64
```

TrackSummaryResponse ^ Collapse all object

```
id integer int64

name string

description string

tech string

classCount integer int64
```

VoiceParticipantResponse ^ Collapse all object

```
userId integer int64

name string

role string

micMuted boolean

deafened boolean
```

SessionReportRosterItemResponse ^ Collapse all object

```
sessionReportId integer int64

ordinaryUserId integer int64

userName string

accuracy number

quizRating number

completionRate number

issuedAt string date-time
```

SessionReportRosterResponse ^ Collapse all object

```
sessionId integer int64

sessionTitle string
```

```
issuedCount integer int32

avgAccuracy number double

avgCompletionRate number double

reports ^ Collapse all array<object>
  Items ^ Collapse all object
    sessionReportId integer int64

    ordinaryUserId integer int64

    userName string

    accuracy number

    quizRating number

    completionRate number

    issuedAt string date-time
```

ChatMessageResponse ^ Collapse all object

```
id integer int64

sessionId integer int64

senderId integer int64

senderName string

content string

createdAt string date-time
```

SessionParticipantResponse ^ Collapse all object

```
userId integer int64

name string

role string
```

ChoiceItem ^ Collapse all object

```
idx integer int32

content string

answer boolean
```

QuizItem ^ Collapse all object

```

    id integer int64

    type ^ Collapse all string
      Enum ^ Collapse all array
        #0="MULTIPLE_CHOICE"
        #1="TRUE_FALSE"
        #2="FILL_IN_BLANK"

    purpose ^ Collapse all string
      Enum ^ Collapse all array
        #0="CONCEPTUAL"
        #1="MICRO"

    difficulty ^ Collapse all string
      Enum ^ Collapse all array
        #0="EASY"
        #1="NORMAL"
        #2="HARD"

    testedConcept string

    question string

    explanation string

    filePath string

    lineStart integer int32

    lineEnd integer int32

    timeLimitSec integer int32

    orderNo integer int32

    choices ^ Collapse all array<object>
      Items ^ Collapse all object
        idx integer int32

        content string

        answer boolean

```

QuizSetDetailResponse ^ Collapse all object

```

    quizSetId integer int64

    status ^ Collapse all string
      Enum ^ Collapse all array

```

```
#0="QUEUED"

#1="GENERATING"

#2="COMPLETED"

#3="FAILED"

generationStage string

requestedCount integer int32

generatedCount integer int32

errorMessage string

quizzes ^ Collapse all array<object>
  Items ^ Collapse all object
    id integer int64

    type ^ Collapse all string
      Enum ^ Collapse all array
        #0="MULTIPLE_CHOICE"

        #1="TRUE_FALSE"

        #2="FILL_IN_BLANK"

    purpose ^ Collapse all string
      Enum ^ Collapse all array
        #0="CONCEPTUAL"

        #1="MICRO"

    difficulty ^ Collapse all string
      Enum ^ Collapse all array
        #0="EASY"

        #1="NORMAL"

        #2="HARD"

    testedConcept string

    question string

    explanation string

    filePath string

    lineStart integer int32

    lineEnd integer int32

    timeLimitSec integer int32

    orderNo integer int32

    choices ^ Collapse all array<object>
```


Items ^ Collapse all object

idx integer int32

content string

answer boolean

QuestionItem ^ Collapse all object

id integer int64

type ^ Collapse all string

Enum ^ Collapse all array

#0="MULTIPLE_CHOICE"

#1="TRUE_FALSE"

#2="FILL_IN_BLANK"

difficulty ^ Collapse all string

Enum ^ Collapse all array

#0="EASY"

#1="NORMAL"

#2="HARD"

testedConcept string

question string

filePath string

lineStart integer int32

lineEnd integer int32

timeLimitSec integer int32

orderNo integer int32

choices ^ Collapse all array<object>

Items ^ Collapse all object

idx integer int32

content string

answer boolean

QuizQuestionsResponse ^ Collapse all object

quizSetId integer int64

status ^ Collapse all string

```
Enum ^ Collapse all array
  #0="QUEUED"
  #1="GENERATING"
  #2="COMPLETED"
  #3="FAILED"

generationStage string

requestedCount integer int32

quizzes ^ Collapse all array<object>
  Items ^ Collapse all object
    id integer int64
    type ^ Collapse all string
      Enum ^ Collapse all array
        #0="MULTIPLE_CHOICE"
        #1="TRUE_FALSE"
        #2="FILL_IN_BLANK"
    difficulty ^ Collapse all string
      Enum ^ Collapse all array
        #0="EASY"
        #1="NORMAL"
        #2="HARD"
    testedConcept string
    question string
    filePath string
    lineStart integer int32
    lineEnd integer int32
    timeLimitSec integer int32
    orderNo integer int32
    choices ^ Collapse all array<object>
      Items ^ Collapse all object
        idx integer int32
        content string
        answer boolean
```

ProgressItem ^ Collapse all object

```
quizId integer int64
status ^ Collapse all string
  Enum ^ Collapse all array
    #0="ATTEMPTED"
    #1="SKIPPED"
    #2="TIMEOUT"
chosenChoiceIdx integer int32
isCorrect boolean
elapsedMs integer int64
explanation string
correctChoiceIdx integer int32
```

QuizProgressSummaryResponse ^ Collapse all object

```
quizSetId integer int64
totalCount integer int32
attemptedCount integer int32
correctCount integer int32
items ^ Collapse all array<object>
  Items ^ Collapse all object
    quizId integer int64
    status ^ Collapse all string
      Enum ^ Collapse all array
        #0="ATTEMPTED"
        #1="SKIPPED"
        #2="TIMEOUT"
    chosenChoiceIdx integer int32
    isCorrect boolean
    elapsedMs integer int64
    explanation string
    correctChoiceIdx integer int32
```

QuizProgressRosterItemResponse ^ Collapse all object

```
userId integer int64
userName string
answeredCount integer int32
correctCount integer int32
totalQuizCount integer int32
status string
```

QuizProgressRosterResponse ^ Collapse all object

```
quizSetId integer int64
totalQuizCount integer int32
totalStudentCount integer int32
startedStudentCount integer int32
inProgressStudentCount integer int32
completedStudentCount integer int32
allCompleted boolean
students ^ Collapse all array<object>
  items ^ Collapse all object
    userId integer int64
    userName string
    answeredCount integer int32
    correctCount integer int32
    totalQuizCount integer int32
    status string
```

QuizIncorrectProgressResponse ^ Collapse all object

```
quizSetId integer int64
incorrectCount integer int32
items ^ Collapse all array<object>
  items ^ Collapse all object
    quizId integer int64
    status ^ Collapse all string
```

Enum ^ Collapse all array

#0="ATTEMPTED"

#1="SKIPPED"

#2="TIMEOUT"

chosenChoiceIdx integer int32

isCorrect boolean

elapsedMs integer int64

explanation string

correctChoiceIdx integer int32

ProjectFileSummaryResponse ^ Collapse all object

path string

size integer int64

ProjectFileContentResponse ^ Collapse all object

path string

content string

AppNotificationResponse ^ Collapse all object

id integer int64

type string

title string

body string

link string

unread boolean

createdAt string date-time

NoticeResponse ^ Collapse all object

id integer int64

scope ^ Collapse all string

Enum ^ Collapse all array

#0="ENTERPRISE"

```
#1="TRACK"

#2="CLASS"

trackId integer int64

classId integer int64

targetName string

title string

body string

pinned boolean

authorName string

createdAt string date-time
```

PageResponseNoticeResponse ^ Collapse all object

```
data ^ Collapse all array<object>

  Items ^ Collapse all object

    id integer int64

    scope ^ Collapse all string

      Enum ^ Collapse all array

        #0="ENTERPRISE"

        #1="TRACK"

        #2="CLASS"

    trackId integer int64

    classId integer int64

    targetName string

    title string

    body string

    pinned boolean

    authorName string

    createdAt string date-time

  meta ^ Collapse all object

    page integer int32

    size integer int32

    total integer int64
```

InvitationPreviewResponse ^ Collapse all object

```
email string

role ^ Collapse all string
  Enum ^ Collapse all array
    #0="MANAGER"
    #1="STUDENT"

classId integer int64

className string

expiresAt string date-time
```

GroupMemberCandidateResponse ^ Collapse all object

```
userId integer int64

name string

email string
```

PageResponseClassResponse ^ Collapse all object

```
data ^ Collapse all array<object>
  Items ^ Collapse all object
    id integer int64
    trackId integer int64
    classNumber integer int32
    name string
    capacity integer int32
    description string
    startedAt string date-time
    endedAt string date-time
    createdAt string date-time
    updatedAt string date-time

meta ^ Collapse all object
  page integer int32
  size integer int32
  total integer int64
```

ClassMemberResponse ^ Collapse all object

```
userId integer int64
name string
email string
role ^ Collapse all string
  Enum ^ Collapse all array
    #0="MANAGER"
    #1="STUDENT"
groupId integer int64
groupName string
phone string
```

PageResponseClassMemberResponse ^ Collapse all object

```
data ^ Collapse all array<object>
  Items ^ Collapse all object
    userId integer int64
    name string
    email string
    role ^ Collapse all string
      Enum ^ Collapse all array
        #0="MANAGER"
        #1="STUDENT"
    groupId integer int64
    groupName string
    phone string
  meta ^ Collapse all object
    page integer int32
    size integer int32
    total integer int64
```

AnalyticsOverviewResponse ^ Collapse all object

```
trackCount integer int64
```



```
activeClassCount integer int64  
managerCount integer int64  
studentCount integer int64
```

ClassAnalyticsResponse ^ Collapse all object

```
classId integer int64  
studentCount integer int64  
managerCount integer int64  
groupCount integer int64  
sessionCount integer int64  
activeSessionCount integer int64  
reportedStudentCount integer int64  
avgAccuracy number double  
avgCompletionRate number double  
avgElapsedMs integer int32
```