

Mathematical Economics

Alpha Chiang

Chapter 9

Optimization: A Special Variety of Equilibrium Analysis


9.2 Relative Maximum and Minimum: First-Derivative Test

Example 1

```
In [1]: import matplotlib.pyplot as plt
import numpy as np

def f(x):
    return x**3 - 12*x**2 + 36*x + 8

plt.figure(figsize = (12, 7))
x1 = np.arange(-2, 10, 0.1)
plt.plot(x1, f(x1), label = '$x^3 - 12x^2 + 36x + 8$')
plt.xlabel('x ')
plt.ylabel('y ')
plt.grid(alpha =.6, linestyle = '--')
plt.legend()
plt.show()
```



```
In [2]: import numpy as np
from scipy import optimize
def f(x):
    return x**3 - 12*x**2 + 36*x + 8

grid = (-10, 10, 0.1)
xmin_global = optimize.brute(f, (grid, ))
print("Global minima found %s" % xmin_global)

# Constrain optimization
xmin_local = optimize.fminbound(f, -2, 10)
print("Local minimum found %s" % xmin_local)
```

```
Global minima found [-6.338253e+29]
Local minimum found 6.000000017351318
```

```
In [3]: root = optimize.root(f, 2) # our initial guess is 1
```

```
print("First root found %s" % root.x)
root2 = optimize.root(f, 6)
print("Second root found %s" % root2.x)
```


First root found [1.98350515]
Second root found [6.]

```
In [5]: import matplotlib.pyplot as plt
fig = plt.figure(figsize=(10, 6))
ax = fig.add_subplot(111)

ax.plot(x1, f(x1), 'b-', label="f(x)")


roots = np.array([root.x, root2.x])
ax.plot(roots, f(roots), 'kv', label="Roots")

ax.legend(loc='best')
ax.set_xlabel('x')
ax.set_ylabel('f(x)')
ax.axhline(0, color='gray')
plt.show()
```



Example 2

```
In [6]: def f(Q):  
        return Q**2 - 5*Q + 8  
  
        plt.figure(figsize = (12, 7))  
        Q1 = np.arange(-10, 10, 0.1)  
        plt.plot(Q1, f(Q1), label = '$Q^2 - 5Q + 8$')  
        plt.xlabel('Q')  
        plt.ylabel('f')  
        plt.grid(alpha = .6, linestyle = '--')  
        plt.legend()  
        plt.show()
```



```
In [7]: root = optimize.root(f, 2)  
        print("First root found %s" % root.x)
```

```
root2 = optimize.root(f, 6)
print("Second root found %s" % root2.x)
```


First root found [2.50000001]
Second root found [2.49907395]

```
In [8]: import matplotlib.pyplot as plt
fig = plt.figure(figsize=(10, 6))
ax = fig.add_subplot(111)

ax.plot(Q1, f(Q1), 'b-', label="f(x)")

roots = np.array([root.x, root2.x])
ax.plot(roots, f(roots), 'kv', label="Roots")


ax.legend(loc='best')
ax.set_xlabel('Q')
ax.set_ylabel('f(Q)')
ax.axhline(0, color='gray')
plt.show()
```



Example 3 --Page 238 --

```
In [14]: def f(Q):
          return -Q**3 + 59.25*Q**2 - 328.5*Q - 2000

          plt.figure(figsize = (12, 7))
          Q1 = np.arange(-5, 15, 0.1)
          plt.plot(Q1, f(Q1),label = '$-Q^3 + 59.25Q^2 - 328.5Q - 2000$')
          plt.xlabel('Q ')
          plt.ylabel('f ')
          plt.grid(alpha =.6, linestyle = '--')
          plt.legend()
          plt.show()
```



```
In [16]: root = optimize.root(f, 2)

root2 = optimize.root(f, 6)
grid = (-10, 10, 0.1)
xmin_global = optimize.brute(f, (grid, ))

xmin_local = optimize.fminbound(f, 0, 10)
```

```
In [18]: import matplotlib.pyplot as plt
fig = plt.figure(figsize=(10, 6))
ax = fig.add_subplot(111)

ax.plot(Q1, f(Q1), 'b-', label="f(x)")
```


```

xmins = np.array([xmin_global[0], xmin_local])
ax.plot(xmins, f(xmins), 'go', label="Minima")

roots = np.array([root.x, root2.x])
ax.plot(roots, f(roots), 'kv', label="Roots")

ax.legend(loc='best')
ax.set_xlabel('Q')
ax.set_ylabel('f(Q)')
ax.axhline(0, color='gray')
plt.show()

```



Example 4

```

In [19]: def f(Q):
          return -0.018*Q**3 + 1.1*Q**2 - 23*Q + 8000

          plt.figure(figsize = (12, 7))


```



```

Q1 = np.arange(-50, 100, 0.1)
plt.plot(Q1, f(Q1), label = '$-0.018Q^3 + 1.1Q^2 - 23Q + 8000$')
plt.xlabel('Q ')
plt.ylabel('f ')
plt.grid(alpha =.6, linestyle = '--')
plt.legend()
plt.show()

```



```

In [20]: root = optimize.root(f, 2)
print("First root found %s" % root.x)
root2 = optimize.root(f, 6)
print("Second root found %s" % root2.x)
grid = (-50, 10, 0.1)

xmin_local = optimize.fminbound(f, 0, 100)
print("Local minimum found %s" % xmin_local)

```

First root found [96.01406042]
Second root found [96.01406042]
Local minimum found 99.9999921581193


```
In [21]: import matplotlib.pyplot as plt
fig = plt.figure(figsize=(10, 6))
ax = fig.add_subplot(111)

ax.plot(Q1, f(Q1), 'b-', label="f(x)")

xmins = np.array(xmin_local)
ax.plot(xmins, f(xmins), 'go', label="Minima")

roots = np.array([root.x, root2.x])
ax.plot(roots, f(roots), 'kv', label="Roots")

ax.legend(loc='best')
ax.set_xlabel('Q')
ax.set_ylabel('f(Q)')
ax.axhline(0, color='gray')
plt.show()
```



In []: