

Shell Card Transaction Data API Specification Addendum

Date: 27 July 2020

Contents

1	API Directory.....	2
2	Input Parameters (Header).....	2
3	Priced Transactions	2
3.1	API URI	2
3.2	INPUT PARAMETERS.....	2
3.3	OUTPUT PARAMETERS	8
4	Multi-Payer Priced Transactions.....	21
4.1	API URI	21
4.2	INPUT PARAMETERS.....	21
4.3	OUTPUT PARAMETERS	25



1 API Directory

API	API End Point	Functionality
PricedTransactions	/v1/transaction/pricedtransactions	This API allows querying the transaction data (i.e. Billed and Unbilled sales items) from the Shell Card Platform. It provides flexible search criteria and supports paging.
MultipayerPricedTransactions	/v1/transaction/multipayerspricedtransactions	This API allows querying multiple payer's transaction data (i.e. Billed and Unbilled sales items) from the Shell Card Platform. It provides flexible search criteria and supports paging.

2 Input Parameters (Header)

All API endpoints require the following common header parameters.

Parameter	Data Type	Description
Authorization	String	Uses Basic Authorization Scheme Passing base64 encoded ConsumerKey + Secret as Authorization. Mandatory
APIKey	String	This is the API Key shared between the client application and Shell API Platform (SML). Mandatory
Content-Type	String	Content Type of the body i.e. application/json

3 Priced Transactions

3.1 API Uri

Uri	Description
/v1/transaction/pricedtransactions	All input parameters to this URI must be submitted using HTTP POST method. Format: JSON

3.2 Input Parameters

Parameter	Data Type	Description
RequestId	Guid	Unique request id passed in the request. This is returned for end to end traceability of a request and response.
ColCold	Integer/null	Collecting Company Id of the selected payer. Optional If ColCo Code is passed else Mandatory



ColCoCode	Integer/null	Collecting Company Code (Shell Code) of the selected payer. Optional If ColCo Id is passed else Mandatory Example: 86-Philippines 5-UK
PayerId	Integer/null	Payer Id of the selected payer. Optional if PayerNumber is passed else Mandatory Example: 123456
PayerNumber	String	Payer Number of the selected payer. Optional if PayerId is passed else Mandatory Example: GB000000123
AccountId	Integer/null	Account Id of the customer. Optional When both Account Id and Account number are not present on request, the response will have transactions of all accounts under the selected payer. Example: 123456
AccountNumber	String	Account Number of the customer. Optional When both Account Id and Account number are not present on request, the response will have transactions of all accounts under the selected payer. Example: GB000000123
CardId	Integer/null	Card Id of a card. Optional When both Card Id and Card PAN are not present on request, the response will have transactions of all cards under the selected payer or account. Example: 275549
CardPAN	String	Full Card PAN Optional When both Card Id and Card PAN are not present on request, the response will have transactions of all cards under the selected payer or account. Example: 7002051006629890645



DriverName	String	Driver Name linked to a card Optional Minimum of 4 characters should be provided else not considered Transactions linked to cards matching any part of the Driver Name will be returned Max Length: 40 Note: If IncludeFees is true then this filter will be ignored
VehicleRegistrationNumber	String	Vehicle Registration linked to a card Optional Minimum of 4 characters should be provided else not considered Transactions linked to cards matching any part of the VRN will be returned • Max Length: 2 Note: If IncludeFees is true then this filter will be ignored
InvoiceStatus	String	Invoice status of the transactions Mandatory Possible options: I - Invoiced U – Un-Invoiced A – All Max Length: 1
ProductId	Integer/null	Product Id in the Shell Card Platform Example: 21 Unleaded - High octane 22 Unleaded - Medium octane 23 Unleaded - Low octane 24 Unleaded Environmental Note: If IncludeFees is true then this filter will be ignored
ProductCode	String	Product Code in the Shell Card Platform Optional Max Length: 8 Example: 10 TMF Charges 11 Tunnel/Bridges



		12 Motorway toll 13 Ferries Note: If IncludeFees is true then this filter will be ignored
PurchasedInCountry	String	ISO Country Code (ex: UK, FR) Optional Max Length: 2 Note: If IncludeFees is true then this filter will be ignored
CardGroupId	Integer/null	Card Group Id in the Shell Card Platform Optional Example: 40000 Note: If IncludeFees is true then this filter will be ignored
CurrentPage	Integer/null	Page Number (as shown to the users) Optional Default value 1 Note: If IncludeFees is true then this filter will be ignored
PageSize	Integer/null	Page Size – Number of records to show on a page Optional Default value 50 Return all rows if -1 is supplied as page size. Note: If IncludeFees is true then this filter will be ignored
SortOrder	String	Allowed Sorting Options: 1. TransactionDateAscending 2. TransactionDateDescending 3. GrossAmountDescending 4. GrossAmountAscending 5. DriverNameAscending(If Driver Name is null then VRN value will be considered) 6. DriverNameDescending(If Driver Name is null then VRN value will be considered) 7. VRNAscending(If VRN is null then Driver Name value will be considered) 8. VRNDescending(If VRN is null then Driver Name value will be considered) 9. NetAmountAscending 10. NetAmountDescensding Example value to be passed: 1,3,7 Note: If IncludeFees is true then this filter will be ignored



FromDate	String/null	Transactions from Date/Time Should be within last 7 months Optional Format: yyyyMMdd
ToDate	String/null	Transactions to Date/Time Optional When blank and FromDate is provided on the input, all transactions took place after the given from date/time should be returned.. Format: yyyyMMdd
Period	Integer/null	Transactions Period. This is ignored when FromDate/Todate is supplied on the request. 1. Last 7 Days 2. Last 30 Days 3. Last 90 Days Example : Pass 1 for Last 7 days transactions
SiteCode	String	Site Code as configured in the Shell Card Platform Example: 050001 -CHARNOCK RICHARD NTHBOUND MWSA 0755 050002 -CHARNOCK RICHARD STHBOUND MWSA 0755 050005 -HARTSHEAD MOOR EASTBOUND MWSA 0761. 050006 -HARTSHEAD MOOR WESTBOUND MWSA. Note: If IncludeFees is true then this filter will be ignored
SiteGroupId	Integer/null	Site Group Id in the Shell Card Platform Optional E.g.: 202 Note: If IncludeFees is true then this filter will be ignored
PostingDateFrom	String/null	Transaction Posting Date/time in the Cards Platform - From Date/time Optional When the value of both PostingDateFrom and PostingDateTo are present in the request then the value of PostingDateFrom must be less than PostingDateTo Format: yyyyMMdd HH:mm:ss Note: If IncludeFees is true then this filter will be ignored
PostingDateTo	String/null	Transaction Posting Date/time in the Cards Platform – To Date/time



		Optional When the value of both PostingDateFrom and PostingDateTo are present in the request then the value of PostingDateFrom must be less than PostingDateTo Format: yyyyMMdd HH:mm:ss Note: If IncludeFees is true then this filter will be ignored
SalesItemId	Long/Null	Unique SalesItemId (Either Billed on Unbilled) Optional Note: If IncludeFees is true then this filter will be ignored
TransactionId	String	Unique Transaction Id Optional Note: If IncludeFees is true then this filter will be ignored
InvoiceDate	String/null	Optional Format: yyyyMMdd If passed then will ignore the status and will returns the billed transaction for the given invoice date. Note: If IncludeFees is true then this filter will be ignored
InvoiceNumber	String/null	Optional If passed then will ignore the status and will returns the billed transaction for the given invoice number. Note: If IncludeFees is true then this filter will be ignored
ValidInvoiceDateOnly	Boolean/null	True/False Optional Default value: True. When passed as 'True' the transactions records with report date not equal to 9999-12-30 will be returned. When passed as 'False' the above condition will not be checked. Note: If IncludeFees is true then this filter will be ignored
InvoiceFromDate	String/null	Invoice From Date, this is a search criterion to filter invoiced transactions within invoice date from this date. Optional Should be within last 13 months Maximum of 90 days duration allowed per search When provided, InvoiceFromDate less than or equal to InvoiceToDate When InvoiceToDate is provided and InvoiceFromDate is null, then InvoiceFromDate will be calculated as (InvoiceToDate – 90 days) or (CurrentDate – 13 months) whichever is greater.



		Format: yyyyMMdd Note: If IncludeFees is true then this filter will be ignored
InvoiceToDate	String/null	Invoice To Date, this is a search criterion to filter invoiced transactions within invoice date until this date. Optional When InvoiceFromDate is provided and InvoiceToDate is null, then InvoiceToDate will be calculated as (InvoiceFromDate + 90 days) or (CurrentDate) whichever is lesser. Format: yyyyMMdd Note: If IncludeFees is true then this filter will be ignored
FuelOnly	Boolean/null	True/False Optional Default value: False. When passed as 'True' Only returned records with Fuel transactions. When passed as 'False' the above condition will not be checked. Note: If IncludeFees is true then this filter will be ignored
IncludeFees	Boolean/null	True/False Optional Default value: False When passed as 'True' then ignore complex filters, all sales items along with fees included on the same response

3.3 Output Parameters

Parameter	Data Type	Description
RequestId	String	Unique request id passed in the request. This is returned for end to end traceability of a request and response.
Error	Entity: ErrorDetails	Error Entity
Parent: ErrorDetails Member: Code	String	Contains Error code 0000 if success
Parent: ErrorDetails Member: Description	String	Error Description as defined in API



Transactions	Entity List<Transaction>	List of Transaction records i.e. Transaction Entity
Parent: Transaction Member: Type	String	TransactionType is the type of transaction. Example: SalesItem /FeelItem
Parent: Transaction Member: CardId	Integer/null	Unique Card Id in the Shell Card Platform Example: 275549
Parent: Transaction Member: CardPAN	String	Card PAN PAN is masked if the setting is configured and all digits except the last 6 digits are masked. If not enabled, the full PAN is returned. Example: 7002051006629890645
Parent: Transaction Member: CardExpiry	String/null	Card Expiry Date Format: yyyyMMdd
Parent: Transaction Member: TransactionDate	String/null	Local Transaction Date of where the transaction took place Format: yyyyMMdd Note : For a fee item, this parameter will be populated with fee date.
Parent: Transaction Member: TransactionTime	String/null	Local Transaction Time of where the transaction took place Format: HH:mm:ss (24 hours format) Note : For a fee item, this parameter will be populated with fee date.
Parent: Transaction Member: UTCOffset	String/null	UTC Offset extracted from Sales Date time. Note: This may not be accurate for all TPN transactions Format: +/-HH:mm:ss (24 hours format)
Parent: Transaction Member: FleetIdInput	String/null	Fleet Id Input as entered by the drivers at the time of transaction Example: XYZ1234
Parent: Transaction Member: OdometerInput	Integer/null	Odometer Input as entered by the drivers at the time of transaction Example: 12345



Parent: Transaction Member: DriverName	String	Driver Name embossed on the card Example: ANDREW GILBERRY
Parent: Transaction Member: VehicleRegistration	String	Vehicle Registration Number embossed on the card Example: MV65YLH
Parent: Transaction Member: InvoiceCurrencyCode	String/null	ISO currency code Example: GBP
Parent: Transaction Member: InvoiceCurrencySymbol	String/null	Currency symbol of the Invoice Currency Code Example: £, \$
Parent: Transaction Member: TransactionCurrencyCode	String	ISO currency code Example: GBP
Parent: Transaction Member: TransactionCurrencySymbol	String	Currency symbol of the Transaction Currency Code Example: £, \$
Parent: Transaction Member: TransactionNetAmount	Decimal/null	Net Amount
Parent: Transaction Member: TransactionTax	Decimal/null	Tax Amount
Parent: Transaction Member: TransactionGrossAmount	Decimal/null	Gross Amount
Parent: Transaction Member: InvoiceNetAmount	Decimal/Null	Invoiced Net Amount Note: For a fee item, this parameter will be populated with fee InvoiceNetAmount.
Parent: Transaction Member: InvoiceTax	Decimal/null	Invoiced Tax Amount
Parent: Transaction Member: InvoiceGrossAmount	Decimal/Null	Invoice Gross Amount Note: For a fee item, this parameter will be populated with fee InvoiceGrossAmount.
Parent: Transaction Member: PurchasedInCountry	String/null	Country of Purchase Example: France, Germany
Parent: Transaction	Integer	Account Id



Member: AccountId		Example: 29484
Parent: Transaction Member: AccountNumber	String	Account Number Example: GB99215176
Parent: Transaction Member: AccountName	String	Account Name Example: MATTHEW ALGIE & COMPANY LIMITED
Parent: Transaction Member: AccountShortName	String	Account Short Name
Parent: Transaction Member: Quantity	Decimal	Quantity/Volume
Parent: Transaction Member: FuelProduct	Boolean/null	True if the product on transaction is listed as a fuel product else return false
Parent: Transaction Member: UnitPriceInTransactionCurrency	Decimal/null	Product Unit Price in transaction currency
Parent: Transaction Member: UnitPriceInInvoiceCurrency	Decimal/null	Product Unit Price in invoice currency
Parent: Transaction Member: UnitDiscountTransactionCurrency	Decimal/null	Unit Discount in transaction currency
Parent: Transaction Member: UnitDiscountInvoiceCurrency	Decimal/null	Unit Discount in invoice currency
Parent: Transaction Member: IsInvoiced	Boolean/null	True when the transaction is already invoice, else return False
Parent: Transaction Member: InvoiceNumber	String	Invoice Number if invoiced S04500493 S04478304 S04490319 3200330976 3200330975 3200330974
Parent: Transaction Member: InvoiceDate	String/null	Invoice Date Format: yyyyMMdd HH:mm:ss Note: Clients to convert this to appropriate DateTime type.



Parent: Transaction Member: SiteCode	String/null	Site Code Example: 050001 -CHARNOCK RICHARD NTHBOUND MWSA 0755 050002 -CHARNOCK RICHARD STHBOUND MWSA 0755 050005 -HARTSHEAD MOOR EASTBOUND MWSA 0761. 050006 -HARTSHEAD MOOR WESTBOUND MWSA.
Parent: Transaction Member: SiteName	String/null	Site Name Example: 050001 -CHARNOCK RICHARD NTHBOUND MWSA 0755 050002 -CHARNOCK RICHARD STHBOUND MWSA 0755 050005 -HARTSHEAD MOOR EASTBOUND MWSA 0761. 050006 -HARTSHEAD MOOR WESTBOUND MWSA.
Parent: Transaction Member: SiteCountry	String/null	Site Country Example: France, Germany
Parent: Site Member: Location	SiteLocation/null	Geography Location entity for Site Location
Parent: SiteLocation Member: Latitude	String/null	Latitude for the Site Geographic Location E.g: 37.4224764
Parent: SiteLocation Member: Longitude	String/null	Longitude for the Site Geographic Location E.g: -122.0842499
Parent: Transaction Member: CardGroupName	String	Card Group Name Example: 006240 FIRE BRIGHT SOLUTIONS
Parent: Transaction Member: ReceiptNumber	String	Receipt Number Example: 01234
Parent: Transaction Member: ProductCode	String	Product Code 10 TMF Charges 11 Tunnel/Bridges



		12 Motorway toll 13 Ferries
Parent: Transaction Member: ProductName	String	Product Name Unleaded - High octane Unleaded - Medium octane Unleaded - Low octane Unleaded Environmental
Parent: Transaction Member: ProductGroupId	Integer	Product Group Id Example: 1 Parent Product Group 2 All Fuels 3 Motor gasoline 4 2 stroke 5 Autogas 6 CNG 7 Automotive Gas Oil 8 Alternative Fuel 9 Industrial/domestic gas oil 10 Non-Fuel 11 Lubricants 12 Non Food 13 Food 14 Non-alcoholic beverages 15 Alcoholic beverages 16 Tobacco 17 Controlled Road Services 18 Car wash 19 Parking 20 Breakdown Services 21 Fees 22 Card related fees 23 Monetary Adjustment 24 Service Fee 25 Set up Fee 26 Other Fee 27 TMF



		28 TMF Charges 29 TMF VAT exempt 30 Essential road services
Parent: Transaction Member: ProductGroupName	String	Product Group Name Example: 1 Parent Product Group 2 All Fuels 3 Motor gasoline 4 2 stroke 5 Autogas 6 CNG 7 Automotive Gas Oil 8 Alternative Fuel 9 Industrial/domestic gas oil 10 Non-Fuel 11 Lubricants 12 Non Food 13 Food 14 Non-alcoholic beverages 15 Alcoholic beverages 16 Tobacco 17 Controlled Road Services 18 Car wash 19 Parking 20 Breakdown Services 21 Fees 22 Card related fees 23 Monetary Adjustment 24 Service Fee 25 Set up Fee 26 Other Fee 27 TMF 28 TMF Charges 29 TMF VAT exempt 30 Essential road services
Parent: Transaction	Decimal/null	DelCo Exchange Rate (Site exchange rate)



Member: DelCoExchangeRate		
Parent: Transaction Member: ColCoExchangeRate	Decimal	ColCo Exchange Rate (Customer exchange rate)
Parent: Transaction Member: IsShellSite	Boolean/null	True when transaction occurred at a Shell site else return False
Parent: Transaction Member: Network	String/null	Network as configured in the Shell Card Platform (Shell PH, ESSO, etc.,) 100013 STEINDORFER 100015 S.A. BELGIAN SHELL N.V. 100016 ESSO BE
Parent: Transaction Member: SiteGroupId	Integer/null	Site Group Id E.g.: 202
Parent: Transaction Member: SiteGroupName	String/null	Site GroupName E.g.: CZ 9100 ECONOMY NETWORK
Parent: Transaction Member: PostingDate	String/null	Transaction Posting Date Format: yyyyMMdd HHmmss Note: Clients to convert this to appropriate DateTime type.
Parent: Transaction Member: IssuerCode	String	First digits of the Card PAN 7002 = Fleet 7077 = CRT The value could be null/blank for fees item.
Parent: Transaction Member: PurchasedInCountryCode	String/NULL	ISO code of the country where the transaction took place E.g.: "NL"
Parent: Transaction Member: CustomerCountryCode	String	ISO code of the Customer Country E.g.: NL
Parent: Transaction Member: CustomerCountry	String	Name of the Customer Country E.g.: Netherlands
Parent: Transaction Member: ReleaseCode	String/null	Release code, 7th Digit of the Card PAN E.g.: 8 for 702188
Parent: Transaction	String	Card group ID (auto generated by Cards Platform)



Member: CardGroupld		
Parent: Transaction Member: CardSequenceNumber	String	3 digits, Card sequence number and Check digit (Digit 16,17 and 18 on the card pan) E.g.: 002
Parent: Transaction Member: CheckDigit	String	Check digit, Last number of the card pan
Parent: Transaction Member: FleetIDDescription	String	FleetId/CRN description in Card Platform configured at the account level
Parent: Transaction Member: VATRate	Double/null	VAT Percentage 0.20 for 20%
Parent: Transaction Member: VATCategory	String	VAT Category Id-Description 1-Zero Rated 2-A1 PH-O 12% Sales Domestic 3-VAT exempt
Parent: Transaction Member: VATCountry	String	VAT Country E.g. Netherlands
Parent: Transaction Member: EffectiveDiscountInTrxCurrency	Double/null	Effective Discount (excluding VAT, in transaction currency) 4 digits e.g.: 0.0000
Parent: Transaction Member: TransactionType	String	Transaction Type E.g.: Purchase when Card is Present else Blank
Parent: Transaction Member: PINIndicator	String	Pin Indicator (Indicates whether PIN used or not used at the time of transaction) E.g.: "PIN Used" or "No PIN" or "Unknown" The value could be null/blank for fees item.
Parent: Transaction Member: VATApplicable	String	Is VAT Applicable for this transaction E.g.: "Y" or "N"
Parent: Transaction Member: NetInvoiceIndicator	String	Net Invoice Indicator, Will the customer receive an invoice without VAT? E.g.: "Y" or "N" The value could be null/blank for fees item.



Parent: Transaction Member: CustomerCurrencyCode	String	Customer currency code E.g. GBP
Parent: Transaction Member: CustomerCurrencySymbol	String	Customer currency Symbol E.g. £
Parent: Transaction Member: EffectiveUnitDiscountInCustomerCurrency	Decimal/null	Effective Unit Discount (excluding VAT in Customer currency)
Parent: Transaction Member: EffectiveDiscountInCustomerCurrency	Decimal/Null	Effective Discount (excluding VAT in Customer currency)
Parent: Transaction Member: VATonNetAmountInCustomerCurrency	Decimal/null	VAT on Net Amount (in Customer currency)
Parent: Transaction Member: DiscountType	String	Discount Type E.g.: 1-None 2-Pence per unit 3-Percentage
Parent: Transaction Member: TransactionStatus	String	Transaction status "U" or "I" "U" stands for Uninvoiced "I" stands for Invoiced
Parent: Transaction Member: SalesItemId	Long	Unique Sales Item Identifier E.g.: 18315958002 Note: For a fee item, this parameter will be populated with SalesItemId.
Parent: Transaction Member: PayerGroup	String	Payer Group applicable for the Large Customer NL+8 digit code
Parent: Transaction Member: PayerGroupName	String	Payer Group Name E.g.: 12119008 - SHELL GROUP OF COMPANIES
Parent: Transaction Member; RefundFlag	String	Refund Flag "N" for Not Refunded and "Y" for Refunded.
Parent: Transaction Member: OriginalSalesItemId	String	Shows Sales Item Id of the original item that was refunded
Parent: Transaction	String	Delco Name



Member: DelcoName		E.g.: SHELL NEDERLAND VERKOOPMAATSCHAPPIJ BV
Parent: Transaction Member: DelcoCode	String	Delco Code 014, 018, etc.,
Parent: Transaction Member: PayerNumber	String	Payer number (Country code+8 digits) E.g.: NL10042616
Parent: Transaction Member: PayerName	String	Payer name E.g: V.M. LE COMTE
Parent: Transaction Member: CardExpiryPeriod	String	Year/Month of the Card Expiry captured on the transaction E.g.: 1901
Parent: Transaction Member: AuthorisationCode	String	Authorisation code of the transaction E.g.: 011256
Parent: Transaction Member: TransactionId	String	Unique id of the transaction that may include one or more salesitems E.g.: io9KVXk1UkW57XWKyeaHHg
Parent: Transaction Member: TransactionLine	String/null	Transaction line item number E.g.: 1
Parent: Transaction Member: AllowClearing	String/null	Is the Sales Item allowed for clearing? i.e. not written off E.g.: "Y" or "N" The value could be null/blank for fees item.
Parent: Transaction Member: CRMNumber	String/null	CRM Case number if the sales item is in dispute
Parent: Transaction Member: DisputeStatus	String	Sales Item Dispute Status if disputed 0 No Dispute 1 In Dispute 2 Re-Instated 3 Adjusted 4 Written Off by Colco 5 Written Off by Delco 6 Charged Back to Site
Parent: Transaction	Decimal/null	Unit discount in customer currency.



Member: RebateRate		E.g.: -28.279000
Parent: Transaction Member: DelCoToColCoExchangeRate	Decimal/null	Exchange rate from transaction currency to customer currency. E.g.: 1
Parent: Transaction Member: NetEuroAmount	Decimal/null	Net euro amount. E.g.: 37.93
Parent: Transaction Member: EuroRebateAmount	Decimal/null	Euro rebate amount. E.g.: 0
Parent: Transaction Member: EuroVATAmount	Decimal/null	Euro VAT amount. E.g.: 7.96
Parent: Transaction Member: ParentCustomerNumber	String	Parent customer number
Parent: Transaction Member: ParentCustomerName	String	Parent customer name.
Parent: Transaction Member: ParentCustomerId	Integer/null	Parent customer id.
Parent: Transaction Member: IncomingSiteNumber	String	Incoming Site Number Example: 100021
Parent: Transaction Member: IncomingSiteDescription	String	Incoming Site Description Example: HN3 INTI_02-82.02
Parent: Transaction Member: IncomingCurrencyCode	String/null	Incoming Currency Code Example: GBP
Parent: Transaction Member: IncomingProductCode	String/null	Incoming Product Code Example: 30
Parent: Transaction Member: CreditDebitCode	String	Credit Debit Code Example: "D" or "C" The value could be null/blank for fees item.
Parent: Transaction Member: CorrectionFlag	String	Correction Flag Example: "Y" or "N" The value could be null/blank for fees item.



Parent: Transaction Member: Additional1	String/null	Additional1
Parent: Transaction Member: Additional2	String/null	Additional2
Parent: Transaction Member: Additional3	String/null	Additional3
Parent: Transaction Member: Additional4	String/null	Additional4
Parent: Transaction Member: RebateonNetAmountInCustomerCurrency	Decimal/null	Rebate on Net Amount In Customer Currency Example: -0.735000000000
Parent: Transaction Member: RebateonNetAmountInTransactionCurrency	Decimal/null	Rebate on Net Amount In Transaction Currency Example: -0.735000000000
Parent: Transaction Member: NetworkCode	String/null	Network Code Example: AVEE PTUAZONW CUBFAO COSFS
Parent: Transaction Member: TrnIdentifier	String	Transaction Identifier
Parent: Transaction Member: CardType	String	Card Type
Parent: Transaction Member: DelcoListPriceUnitNet	Decimal/null	Delco List Price Unit Net Example: 30.500000
Parent: Transaction Member: DelcoRetailPriceUnitNet	Decimal/null	Retail Net Price (or pump net price) per Unit in transaction currency Example: 1.921000
Parent: Transaction Member: DelcoRetailPriceUnitGross	Decimal/null	Retail gross price (or pump gross price) per unit in transaction currency
Parent: Transaction Member: DelcoRetailValueTotalNet	Decimal/null	Retail net price (or net pump price) in transaction currency
Parent: Transaction Member: DelcoRetailValueTotalGross	Decimal/null	Retail gross price (or gross pump price) in transaction currency



Parent: Transaction Member: CustomerRetailPriceUnitGross	Decimal/null	Retail gross price (or pump gross price) per unit in customer currency
Parent: Transaction Member: CustomerRetailValueTotalGross	Decimal/null	Retail gross price (or gross pump price) in customer currency
Parent: Transaction Member: CustomerRetailValueTotalNet	Decimal/null	Retail net price (or net pump price) in customer currency
Parent: Transaction Member: TransactionTypeDescription	String	Transaction Type Description
CurrentPage	Integer/null	Current Page
RowCount	Integer	Total row count matched for the given input criteria
TotalPages	Integer/null	Calculated page count based on page size from the incoming API request and total number of rows matched for the given input criteria. Return 1 if the page size is - 1 as all records are returned.

4 Multi-Payer Priced Transactions

4.1 API Uri

Uri	Description
v1/customer/multipayerspricedtransactions	All input parameters to this URI must be submitted using HTTP POST method. Format: JSON

4.2 Input Parameters

Parameter	Data Type	Description
RequestId	Guid	Unique request id passed in the request. This is returned for end to end traceability of a request and response.
ColCold	Integer/null	Collecting Company Id of the selected payer. Optional If ColCo Code is passed else Mandatory



ColCoCode	Integer/null	Collecting Company Code (Shell Code) of the selected payer. Optional If ColCo Id is passed else Mandatory Example: 86-Philippines 5-UK
Accounts	List< AccountDetail>	List of Payers/Accounts entity. Mandatory. Note: At least one payer should be present. Accounts information are optional.
Parent: AccountDetail PayerId	Integer/null	Payer Id of the selected payer. Optional if PayerNumber is passed else Mandatory Example: 123456
Parent: AccountDetail PayerNumber	String	Payer Number (Ex: GB000000123) of the selected payer. Optional if PayerId is passed else Mandatory Example: GB000000123
Parent: AccountDetail AccountId	Integer/null	Account Id of the selected account. Optional When both Account Id and Account number are not present on the request, the response will include the transactions of all accounts to which the logged in user have access under the selected payer. Example: 123456
Parent: AccountDetail AccountNumber	String	Account Number (ex: GB000000123) of the selected account. Optional When both Account Id and Account number are not present on the request, the response will include the transactions of all accounts to which the logged in user have access under the selected payer. Example: GB000000123
InvoiceStatus	String	Invoice status of the transactions Mandatory Possible options: I - Invoiced U – Un-Invoiced A – All



		Max Length: 1
PurchasedInCountry	String	ISO Country Code (ex: UK, FR) Optional Max Length: 2 Example: UK, NL Note: If IncludeFees is true then this filter will be ignored
FromDate	String/null	Transactions from Date/Time Should be within last 7 months Optional Format: yyyyMMdd
ToDate	String/null	Transactions to Date/Time Optional When blank and FromDate is provided on the input, all transactions took place after the given from date/time should be returned.. Format: yyyyMMdd
Period	Integer/null	Transactions Period. This is ignored when FromDate/Todate is supplied on the request. - Last 7 Days - Last 30 Days - Last 90 Days Example : Pass 1 for Last 7 days transactions
PostingDateFrom	String/null	Transaction Posting Date/time in the Cards Platform - From Date/time Optional When the value of both PostingDateFrom and PostingDateTo are present in the request then the value of PostingDateFrom must be less than PostingDateTo Format: yyyyMMdd HH:mm:ss Note: If IncludeFees is true then this filter will be ignored
PostingDateTo	String/null	Transaction Posting Date/time in the Cards Platform – To Date/time Optional When the value of both PostingDateFrom and PostingDateTo are present in the request then the value of PostingDateFrom must be less than PostingDateTo



		Format: yyyyMMdd HH:mm:ss Note: If IncludeFees is true then this filter will be ignored
InvoiceDate	String/null	Optional Format: yyyyMMdd If passed then will ignore the status and will returns the billed transaction for the given invoice date. Note: If IncludeFees is true then this filter will be ignored
InvoiceNumber	String/null	Optional If passed then will ignore the status and will returns the billed transaction for the given invoice number. Note: If IncludeFees is true then this filter will be ignored
ValidInvoiceDateOnly	Boolean/null	True/False Optional Default value: True. When passed as 'True' the transactions records with report date not equal to 9999-12-30 will be returned. When passed as 'False' the above condition will not be checked. Note: If IncludeFees is true then this filter will be ignored
InvoiceFromDate	String/null	Invoice From Date, this is a search criterion to filter invoiced transactions within invoice date from this date. Optional Should be within last 13 months Maximum of 90 days duration allowed per search When provided, InvoiceFromDate less than or equal to InvoiceToDate When InvoiceToDate is provided and InvoiceFromDate is null, then InvoiceFromDate will be calculated as (InvoiceToDate – 90 days) or (CurrentDate – 13 months) whichever is greater. Format: yyyyMMdd Note: If IncludeFees is true then this filter will be ignored
InvoiceToDate	String/null	Invoice To Date, this is a search criterion to filter invoiced transactions within invoice date until this date. Optional When InvoiceFromDate is provided and InvoiceToDate is null, then InvoiceToDate will be calculated as (InvoiceFromDate + 90 days) or (CurrentDate) whichever is lesser. Format: yyyyMMdd Note: If IncludeFees is true then this filter will be ignored
FuelOnly	Boolean/null	True/False Optional



		Default value: False. When passed as 'True' Only returned records with Fuel transactions. When passed as 'False' the above condition will not be checked.. Note: If IncludeFees is true then this filter will be ignored
IncludeFees	Boolean/null	True/False Optional Default value: False When passed as 'True' then ignore complex filters, all sales items along with fees included on the same response
CurrentPage	Integer/null	Page Number (as shown to the users) Optional Default value 1 Note: If IncludeFees is true then this filter will be ignored
PageSize	Integer/null	Page Size – Number of records to show on a page Optional Default value 50 Return all rows if -1 is supplied as page size. Note: If IncludeFees is true then this filter will be ignored
SortOrder	String	Allowed Sorting Options: 1. TransactionDateAscending 2. TransactionDateDescending 3. GrossAmountDescending 4. GrossAmountAscending 5. NetAmountAscending 6. NetAmountDescensding Example value to be passed: 1,3,7 Note: If IncludeFees is true then this filter will be ignored

4.3 Output Parameters

Parameter	Data Type	Description
RequestId	String	Unique request id passed in the request. This is returned for end to end traceability of a request and response.
Error	Entity: ErrorDeails	Error Entity
Parent: ErrorDetails	String	Contains Error code



Member: Code		0000 if success
Parent: ErrorDetails Member: Description	String	Error Description as defined in API
Transactions	Entity List<Transaction>	List of Transaction records i.e. Transaction Entity
Parent: Transaction Member: Type	String	TransactionType is the type of transaction. Example: SalesItem /Feeltem
Parent: Transaction Member: CardId	Integer/null	Unique Card Id in the Shell Card Platform Example: 275549
Parent: Transaction Member: CardPAN	String	Card PAN PAN is masked if the setting is configured and all digits except the last 6 digits are masked. If not enabled, the full PAN is returned. Example: 7002051006629890645
Parent: Transaction Member: CardExpiry	String/null	Card Expiry Date Format: yyyyMMdd Note: Clients to convert this to appropriate DateTime type.
Parent: Transaction Member: TransactionDate	String/null	Local Transaction Date of where the transaction took place Format: yyyyMMdd Note: Clients to convert this to appropriate DateTime type. Note: For a fee item, this parameter will be populated with fee date.
Parent: Transaction Member: TransactionTime	String/null	Local Transaction Time of where the transaction took place Format: HH:mm:ss (24 hours format) Note: Clients to convert this to appropriate DateTime type. Note: For a fee item, this parameter will be populated with fee date.
Parent: Transaction Member: UTCOffset	String/null	UTC Offset extracted from Sales Date time. Note: This may not be accurate for all TPN transactions



		Format: +/-HH:mm:ss (24 hours format)
Parent: Transaction Member: FleetIdInput	String/null	Fleet Id Input as entered by the drivers at the time of transaction Example: XYZ1234
Parent: Transaction Member: OdometerInput	Integer/null	Odometer Input as entered by the drivers at the time of transaction Example: 12345
Parent: Transaction Member: DriverName	String	Driver Name embossed on the card Example: ANDREW GILBERRY
Parent: Transaction Member: VehicleRegistration	String	Vehicle Registration Number embossed on the card Example: MV65YLH
Parent: Transaction Member: InvoiceCurrencyCode	String/null	ISO currency code Example: GBP
Parent: Transaction Member: InvoiceCurrencySymbol	String/null	Currency symbol of the Invoice Currency Code Example: £, \$
Parent: Transaction Member: TransactionCurrencyCode	String	ISO currency code Example: GBP
Parent: Transaction Member: TransactionCurrencySymbol	String	Currency symbol of the Transaction Currency Code Example: £, \$
Parent: Transaction Member: TransactionNetAmount	Decimal/null	Net Amount
Parent: Transaction Member: TransactionTax	Decimal/null	Tax Amount
Parent: Transaction Member: TransactionGrossAmount	Decimal/null	Gross Amount .
Parent: Transaction Member: InvoiceNetAmount	Decimal/Null	Invoiced Net Amount Note : For a fee item, this parameter will be populated with fee InvoiceNetAmount.
Parent: Transaction Member: InvoiceTax	Decimal/null	Invoiced Tax Amount



Parent: Transaction Member: InvoiceGrossAmount	Decimal/Null	Invoice Gross Amount Note : For a fee item, this parameter will be populated with fee InvoiceGrossAmount.
Parent: Transaction Member: PurchasedInCountry	String/null	Country of Purchase Example: France, Germany
Parent: Transaction Member: AccountId	Integer	Account Id Example: 29484
Parent: Transaction Member: AccountNumber	String	Account Number Example: GB99215176
Parent: Transaction Member: AccountName	String	Account Name Example: MATTHEW ALGIE & COMPANY LIMITED
Parent: Transaction Member: AccountShortName	String	Account Short Name
Parent: Transaction Member: Quantity	Decimal	Quantity/Volume
Parent: Transaction Member: FuelProduct	Boolean/null	True if the product on transaction is listed as a fuel product else return false
Parent: Transaction Member: UnitPriceInTransactionCurrency	Decimal/null	Product Unit Price in transaction currency
Parent: Transaction Member: UnitPriceInInvoiceCurrency	Decimal/null	Product Unit Price in invoice currency
Parent: Transaction Member: UnitDiscountTransactionCurrency	Decimal/null	Unit Discount in transaction currency
Parent: Transaction Member: UnitDiscountInvoiceCurrency	Decimal/null	Unit Discount in invoice currency
Parent: Transaction Member: IsInvoiced	Boolean/null	True when the transaction is already invoice, else return False
Parent: Transaction Member: InvoiceNumber	String	Invoice Number if invoiced S04500493 S04478304 S04490319



		3200330976 3200330975 3200330974
Parent: Transaction Member: InvoiceDate	String/null	Invoice Date Format: yyyyMMdd HH:mm:ss Note: Clients to convert this to appropriate DateTime type.
Parent: Transaction Member: SiteCode	String/null	Site Code Example: 050001 -CHARNOCK RICHARD NTHBOUND MWSA 0755 050002 -CHARNOCK RICHARD STHBOUND MWSA 0755 050005 -HARTSHEAD MOOR EASTBOUND MWSA 0761. 050006 -HARTSHEAD MOOR WESTBOUND MWSA.
Parent: Transaction Member: SiteName	String/null	Site Name Example: 050001 -CHARNOCK RICHARD NTHBOUND MWSA 0755 050002 -CHARNOCK RICHARD STHBOUND MWSA 0755 050005 -HARTSHEAD MOOR EASTBOUND MWSA 0761. 050006 -HARTSHEAD MOOR WESTBOUND MWSA.
Parent: Transaction Member: SiteCountry	String/null	Site Country Example: France, Germany
Parent: Site Member: Location	SiteLocation/null	Geography Location entity for Site Location
Parent: SiteLocation Member: Latitude	String/null	Latitude for the Site Geographic Location E.g : 37.4224764
Parent: SiteLocation Member: Longitude	String/null	Longitude for the Site Geographic Location E.g : -122.0842499
Parent: Transaction	String	Card Group Name



Member: CardGroupName		Example: 006240 FIRE BRIGHT SOLUTIONS
Parent: Transaction Member: ReceiptNumber	String	Receipt Number Example: 01234
Parent: Transaction Member: ProductCode	String	Product Code 10 TMF Charges 11 Tunnel/Bridges 12 Motorway toll 13 Ferries
Parent: Transaction Member: ProductName	String	Product Name Unleaded - High octane Unleaded - Medium octane Unleaded - Low octane Unleaded Environmental
Parent: Transaction Member: ProductGroupId	Integer	Product Group Id Example: 1 Parent Product Group 2 All Fuels 3 Motor gasoline 4 2 stroke 5 Autogas 6 CNG 7 Automotive Gas Oil 8 Alternative Fuel 9 Industrial/domestic gas oil 10 Non-Fuel 11 Lubricants 12 Non Food 13 Food 14 Non-alcoholic beverages 15 Alcoholic beverages 16 Tobacco 17 Controlled Road Services 18 Car wash 19 Parking 20 Breakdown Services



		21 Fees 22 Card related fees 23 Monetary Adjustment 24 Service Fee 25 Set up Fee 26 Other Fee 27 TMF 28 TMF Charges 29 TMF VAT exempt 30 Essential road services
Parent: Transaction Member: ProductGroupName	String	Product Group Name Example: 1 Parent Product Group 2 All Fuels 3 Motor gasoline 4 2 stroke 5 Autogas 6 CNG 7 Automotive Gas Oil 8 Alternative Fuel 9 Industrial/domestic gas oil 10 Non-Fuel 11 Lubricants 12 Non Food 13 Food 14 Non-alcoholic beverages 15 Alcoholic beverages 16 Tobacco 17 Controlled Road Services 18 Car wash 19 Parking 20 Breakdown Services 21 Fees 22 Card related fees 23 Monetary Adjustment 24 Service Fee



		25 Set up Fee 26 Other Fee 27 TMF 28 TMF Charges 29 TMF VAT exempt 30 Essential road services
Parent: Transaction Member: DelCoExchangeRate	Decimal/null	DelCo Exchange Rate (Site exchange rate)
Parent: Transaction Member: ColCoExchangeRate	Decimal	ColCo Exchange Rate (Customer exchange rate)
Parent: Transaction Member: IsShellSite	Boolean/null	True when transaction occurred at a Shell site else return False
Parent: Transaction Member: Network	String/null	Network as configured in the Shell Card Platform (Shell PH, ESSO, etc.,) 100013 STEINDORFER 100015 S.A. BELGIAN SHELL N.V. 100016 ESSO BE
Parent: Transaction Member: SiteGroupId	Integer/null	Site Group Id E.g.: 202
Parent: Transaction Member: SiteGroupName	String/null	Site GroupName E.g.: CZ 9100 ECONOMY NETWORK
Parent: Transaction Member: PostingDate	String/null	Transaction Posting Date Format: yyyyMMdd HHmmss Note: Clients to convert this to appropriate DateTime type.
Parent: Transaction Member: IssuerCode	String	First digits of the Card PAN 7002 = Fleet 7077 = CRT The value could be null/blank for fees item.
Parent: Transaction Member: PurchasedInCountryCode	String/NULL	ISO code of the country where the transaction took place E.g.: "NL"
Parent: Transaction	String	ISO code of the Customer Country



Member: CustomerCountryCode		E.g.: NL
Parent: Transaction Member: CustomerCountry	String	Name of the Customer Country E.g.: Netherlands
Parent: Transaction Member : ReleaseCode	String/null	Release code, 7th Digit of the Card PAN E.g.: 8 for 702188
Parent: Transaction Member: CardGroupId	String	Card group ID (auto generated by Cards Platform)
Parent: Transaction Member : CardSequenceNumber	String	3 digits, Card sequence number and Check digit (Digit 16,17 and 18 on the card pan) E.g.: 002
Parent: Transaction Member: CheckDigit	String	Check digit, Last number of the card pan
Parent: Transaction Member: FleetIDDescription	String	FleetId/CRN description in Card Platform configured at the account level
Parent: Transaction Member : VATRate	Double/null	VAT Percentage 0.20 for 20%
Parent: Transaction Member : VATCategory	String	VAT Category Id-Description 1-Zero Rated 2-A1 PH-O 12% Sales Domestic 3-VAT exempt
Parent: Transaction Member: VATCountry	String	VAT Country E.g. Netherlands
Parent: Transaction Member: EffectiveDiscountInTrxCurrency	Double/null	Effective Discount (excluding VAT, in transaction currency) 4 digits e.g.: 0.0000
Parent: Transaction Member: TransactionType	String	Transaction Type E.g.: Purchase when Card is Present else Blank
Parent: Transaction Member: PINIndicator	String	Pin Indicator (Indicates whether PIN used or not used at the time of transaction) E.g.: "PIN Used" or "No PIN" or "Unknown" The value could be null/blank for fees item.



Parent: Transaction Member: VATApplicable	String	Is VAT Applicable for this transaction E.g.: "Y" or "N"
Parent: Transaction Member: NetInvoiceIndicator	String	Net Invoice Indicator, Will the customer receive an invoice without VAT? E.g.: "Y" or "N" The value could be null/blank for fees item.
Parent: Transaction Member: CustomerCurrencyCode	String	Customer currency code E.g. GBP
Parent: Transaction Member: CustomerCurrencySymbol	String	Customer currency Symbol E.g. £
Parent: Transaction Member: EffectiveUnitDiscountInCustomerCurrency	Decimal/null	Effective Unit Discount (excluding VAT in Customer currency)
Parent: Transaction Member: EffectiveDiscountInCustomerCurrency	Decimal/Null	Effective Discount (excluding VAT in Customer currency)
Parent: Transaction Member: VATonNetAmountInCustomerCurrency	Decimal/null	VAT on Net Amount (in Customer currency)
Parent: Transaction Member: DiscountType	String	Discount Type E.g.: 1-None 2-Pence per unit 3-Percentage
Parent: Transaction Member: TransactionStatus	String	Transaction status "U" or "I" "U" stands for Uninvoiced "I" stands for Invoiced
Parent: Transaction Member: SalesItemId	Long	Unique Sales Item Identifier E.g.: 18315958002 Note: For a fee item, this parameter will be populated with SalesItemId.
Parent: Transaction Member: PayerGroup	String	Payer Group applicable for the Large Customer NL+8 digit code



Parent: Transaction Member: PayerGroupName	String	Payer Group Name E.g.: 12119008 - SHELL GROUP OF COMPANIES
Parent: Transaction Member: RefundFlag	String	Refund Flag "N" for Not Refunded and "Y" for Refunded.
Parent: Transaction Member: OriginalSalesItemId	String	Shows Sales Item Id of the original item that was refunded
Parent: Transaction Member: DelcoName	String	Delco Name E.g.: SHELL NEDERLAND VERKOOPMAATSCHAPPIJ BV
Parent: Transaction Member: DelcoCode	String	Delco Code 014, 018, etc.,
Parent: Transaction Member: PayerId	Integer	Payer Id E.g.: 2615
Parent: Transaction Member: PayerNumber	String	Payer number (Country code+8 digits) E.g.: NL10042616
Parent: Transaction Member: PayerName	String	Payer name E.g.: V.M. LE COMTE
Parent: Transaction Member: CardExpiryPeriod	String	Year/Month of the Card Expiry captured on the transaction E.g.: 1901
Parent: Transaction Member: AuthorisationCode	String	Authorisation code of the transaction E.g.: 011256
Parent: Transaction Member: TransactionId	String	Unique id of the transaction that may include one or more salesitems E.g.: io9KVXk1UkW57XWKyeaHHg
Parent: Transaction Member: TransactionLine	String/null	Transaction line item number E.g.: 1
Parent: Transaction Member: AllowClearing	String/null	Is the Sales Item allowed for clearing? i.e. not written off E.g.: "Y" or "N" The value could be null/blank for fees item.



Parent: Transaction Member: CRMNumber	String/null	CRM Case number if the sales item is in dispute
Parent: Transaction Member: DisputeStatus	String	Sales Item Dispute Status if disputed 0 No Dispute 1 In Dispute 2 Re-Instated 3 Adjusted 4 Written Off by Colco 5 Written Off by Delco 6 Charged Back to Site
Parent: Transaction Member: RebateRate	Decimal/null	Unit discount in customer currency. E.g.: -28.279000
Parent: Transaction Member: DelCoToColCoExchangeRate	Decimal/null	Exchange rate from transaction currency to customer currency. E.g.: 1
Parent: Transaction Member: NetEuroAmount	Decimal/null	Net euro amount. E.g.: 37.93
Parent: Transaction Member: EuroRebateAmount	Decimal/null	Euro rebate amount. E.g.: 0
Parent: Transaction Member: EuroVATAmount	Decimal/null	Euro VAT amount. E.g.: 7.96
Parent: Transaction Member: ParentCustomerNumber	String	Parent customer number
Parent: Transaction Member: ParentCustomerName	String	Parent customer name.
Parent: Transaction Member: ParentCustomerId	Integer/null	Parent customer id.
Parent: Transaction Member: IncomingSiteNumber	String	Incoming Site Number Example: 100021
Parent: Transaction Member: IncomingSiteDescription	String	Incoming Site Description Example: HN3 INTI_02-82.02
Parent: Transaction Member: IncomingCurrencyCode	String/null	Incoming Currency Code Example: GBP



Parent: Transaction Member: IncomingProductCode	String/null	Incoming Product Code Example: 30
Parent: Transaction Member: CreditDebitCode	String	Credit Debit Code Example: "D" or "C" The value could be null/blank for fees item.
Parent: Transaction Member: CorrectionFlag	String	Correction Flag Example: "Y" or "N" The value could be null/blank for fees item.
Parent: Transaction Member: Additional1	String/null	Additional1
Parent: Transaction Member: Additional2	String/null	Additional2
Parent: Transaction Member: Additional3	String/null	Additional3
Parent: Transaction Member: Additional4	String/null	Additional4
Parent: Transaction Member: RebateonNetAmountInCustomerCurrency	Decimal/null	Rebate on Net Amount in Customer Currency Example: -0.735000000000
Parent: Transaction Member: RebateonNetAmountInTransactionCurrency	Decimal/null	Rebate on Net Amount in Transaction Currency Example: -0.735000000000
Parent: Transaction Member: NetworkCode	String/null	Network Code Example: AVEE PTUAZONW CUBFAO COSFS
Parent: Transaction Member: TrnIdentifier	String	Transaction Identifier
Parent: Transaction Member: CardType	String	Card Type
Parent: Transaction Member: DelcoListPriceUnitNet	Decimal/null	Delco List Price Unit Net Example: 30.500000



Parent: Transaction Member: DelcoRetailPriceUnitNet	Decimal/null	Retail Net Price (or pump net price) per Unit in transaction currency Example: 1.921000
Parent: Transaction Member: DelcoRetailPriceUnitGross	Decimal/null	Retail gross price (or pump gross price) per unit in transaction currency
Parent: Transaction Member: DelcoRetailValueTotalNet	Decimal/null	Retail net price (or net pump price) in transaction currency
Parent: Transaction Member: DelcoRetailValueTotalGross	Decimal/null	Retail gross price (or gross pump price) in transaction currency
Parent: Transaction Member: CustomerRetailPriceUnitGross	Decimal/null	Retail gross price (or pump gross price) per unit in customer currency
Parent: Transaction Member: CustomerRetailValueTotalGross	Decimal/null	Retail gross price (or gross pump price) in customer currency
Parent: Transaction Member: CustomerRetailValueTotalNet	Decimal/null	Retail net price (or net pump price) in customer currency
Parent: Transaction Member: TransactionTypeDescription	String	Transaction Type Description
CurrentPage	Integer/null	Current Page
RowCount	Integer	Total row count matched for the given input criteria
TotalPages	Integer/null	Calculated page count based on page size from the incoming API request and total number of rows matched for the given input criteria. Return 1 if the page size is -1 as all records are returned.

