MOBILE-ID TECHNOLOGIES AND SERVICES JOINT STOCK COMPANY
Level 9, Thuy Loi 4 Building, 286-288 Nguyen Xi Street, Ward 13, Binh Thanh District, Ho Chi Minh City
Tel: +84 28 3622 2982- Fax: +84 28 3622 2983 – Hotline: 1900 6884
info@mobile-id.vn – https://www.mobile-id.vn

GoPaperless Workflow Service

RESTful API Specification

Version 2.1.260505

Ho Chi Minh - 2026

MOBILE-ID TECHNOLOGIES AND SERVICES JOINT STOCK COMPANY
Level 9, Thuy Loi 4 Building, 286-288 Nguyen Xi Street, Ward 13, Binh Thanh District, Ho Chi Minh City
Tel: +84 28 3622 2982- Fax: +84 28 3622 2983 – Hotline: 1900 6884
info@mobile-id.vn – https://www.mobile-id.vn

History

Version	Date	Description	Author
1.0	20230623	Begin	GIATK
1.1	20240206	+Update all APIs need to start new project	GIATK
1.2	20240216	+Add all APIs : - Enterprise Management - Account Management	GIATK
1.3	20240219	+ Add all APIS: - ADMIN APIs + Add APIs in Enterprise Management - Get Enterprise Users - Get Enterprise User - Get Roles - Get Role Users - Delete Role - Add Role + Rename "Set new Password" into "Reset Enterprise User Password"	GIATK
1.4	20240221	+ Update Session "Document Processing"	GIATK
1.5	20240704	+ Update request payload "Get All Packages"	GIATK
1.6	20240820	+ Update Document Schema + Add Flow "RSSP Processing"	GIATK
1.7	20240904	+ Change parameters name: uploaded_on -> created_at create_by -> created_by + Add more parameter for those APIs: Get/Update Workflow Details (add "deadline_at") Get Workflow Users (add "invitation_time") + API "Get Document Hash": Change name "signed_hash" into "hashing_algo" Change name "signature_algorithm" into "signing_algo" Return "hashing_algo", "signing_algo" in response	GIATK
1.8	20240913	+ Update Request parameter of "Get Filtered Credential List" + Update Response of "Get RSSP Information"	GIATK
1.9	20240917	+ Add API "Check status of Signature Field" + Update API "Get Document Hash" Parameter "signer_contact" change into "contact_information"	GIATK
1.10	20241028	+ Add "signing_reason" attribute request in API "Add User to Workflow"	GIATK

Version	Date	Description	Author
1.11	20241029	+ Update API "Add Contact" + Add API "Get Address Book" + Update API "Create Account"	GIATK
1.12	20241105	+ Update API "Update Workflow Detail" and "Get Workflow Detail"	GIATK
1.13	20241119	+ Update APIs to make it correctly the format of date + Add API "Get All Workflow"	GIATK
1.14	20241125	+ Update domain of service	GIATK
1.15	20241127	+ Add header parameters in API "Sign Document via RSSP Directly"	GIATK
1.16	20241205	+ Add parameter "appearance_design" in API "Sign document via RSSP Directly"	GIATK
1.17	20241208	+ Add parameter "company_name" in API "Add User to Workflow" and "Get Workflow Users"	GIATK
1.18	20250109	+ Update parameter request name of "Get Filtered Credential List" + Make "appearance_design" become an enumeration + Add APIs" - Get List Smart-ID Connector - Get List Internal Signing Service Connector - Get Signature Settings - Add Signature Appearance	GIATK
1.19	20250117	+ Update response parameter for API "Get Workflow Details" + Add API "Get Credentials Info"	GIATK
1.20	20250120	+ Add API "Send OTP via RSSP"	GIATK
1.21	20250209	+ Add Section "Application/Device Management"	GIATK
1.22	20250211	+ Update Response/Response table of APIs: - Get Workflow Details + Add APIs: - Register Certificate via RSSP - Authorize Mobile Number to Register Certificate - Authorize Email to Register Certificate - Resend Mobile Number to Register Certificate - Resend Email to Register Certificate	GIATK
2.0	20250416	+ Update and reformat the Documentation	GIATK
2.1	20250609	+ Update and reformat the Documentation + Add APIs: - All APIs about PlaceHolder	GIATK

Version	Date	Description	Author
		- All APIs about Template	
2.2	20250626	+ Add parameters about webhook in API "Sign Document via RSSP Directly"	GIATK
2.3	20250708	+ Move some APIs to correct folder - All APIs about personal contact - All APIs about personal information - All APIs about address book	GIATK
2.4	20250717	+ Add APIs Get Templates in Personal Management Section	GIATK
2.5	20250905	+ Update all document format	GIATK

TABLE OF CONTENTS

HISTORY **1**

1 INTRODUCTION **13**

1.1 Target **13**

1.2 Abbreviation **13**

2 API SPECIFICATION **14**

2.1 Authenticate – Log in **14**

2.1.1 Client Credentials Authentication *14*

2.1.2 Password Authentication *16*

2.1.3 Single Sign On Authentication *19*

2.1.4 OTP Login Authentication *21*

2.1.5 Revoke refresh token *23*

2.1.6 Get Information *24*

2.1.7 Pre Login Authentication *26*

2.2 Document Package **28**

2.2.1 Pre Upload Document *28*

2.2.2 Add Document Package *30*

2.2.3 Share Document Package/ Share Workflow *32*

2.2.4 Upload Document *33*

2.2.5 Upload Document (base64) *35*

2.2.6 Download Package *37*

2.2.7 Download Package (base64) *39*

2.2.8 Download Document *41*

2.2.9 Download Document (base64) *43*

2.2.10 Get All Package 44
2.2.11 Get Document Image 48
2.2.12 Get Document Image Base64 50
2.2.13 Get Document Details 52
2.2.14 Get Document Verification 55
2.2.15 Get Package Verification 58
2.2.16 Get Package Details 61
2.2.17 Rename Package 63
2.2.18 Rename Document 65
2.2.19 Delete Package 67
2.2.20 Delete Document 68
2.2.21 Update Document 70
2.2.22 Update Document (base64) 72
2.2.23 Upload Attachment 74
2.2.24 Get Attachments 76
2.2.25 Delete Attachment 78
2.2.26 Download Attachment 80
2.2.27 Download Attachment (base64) 81
2.2.28 Merge Document 83
2.2.29 Apply Workflow Template 85
2.3 Document Workflow 88
2.3.1 Start new Workflow 88
2.3.2 Add Electronic Seal to Workflow 90
2.3.3 Add User to Workflow 92
2.3.4 Get All Workflow 95
2.3.5 Update Workflow Details 98
2.3.6 Get Workflow Details 101
2.3.7 Get Worklow Users 104
2.3.8 Update Workflow User 107
2.3.9 Delete Workflow User 109
2.3.10 Update Workflow Reminders 111
2.3.11 Get Workflow Reminders 113
2.3.12 Get Workflow History 115
2.3.13 Add Workflow Comment/Message 116
2.3.14 Get Workflow Comment/Message 118
2.3.15 Delete Workflow Comment/Message 120
2.3.16 Get Workflow User Authentication(Document Opening) 121
2.3.17 Update Workflow User Authentication(Document Opening) 125
2.3.18 Get Workflow User Permissions 128

2.3.19 Update Workflow User Permissions 130
2.3.20 Create new Category 132
2.3.21 Update Category 134
2.3.22 Get list of Category 136
2.3.23 Add Placeholder to Workflow 138
2.3.24 Update Placeholder in Workflow 140
2.4 Document Preparation 143
2.4.1 Add Digital Signature Field 143
2.4.2 Update Digital Signature Field 147
2.4.3 Add TextBox Field 150
2.4.4 Update TextBox Field 153
2.4.5 Add Initital Field 156
2.4.6 Update Initial Field 159
2.4.7 Assign Document Field 162
2.4.8 Delete Document Field 164
2.4.9 Get Document Fields 166
2.4.10 Check status of Signature Field 169
2.4.11 Add In-person Field 171
2.4.12 Update In-person Field 175
2.4.13 Add Datetime Field 178
2.4.14 Update Datetime Field 182
2.4.15 Add CheckBox Field 185
2.4.16 Update CheckBox Field 188
2.4.17 Add RadioBox Field 192
2.4.18 Update RadioBox Field 195
2.4.19 Add QR Field 199
2.4.20 Update QR Field 202
2.4.21 Add Qrypto Field 205
2.4.22 Update Qrypto Field 208
2.4.23 Add ComboBox Field 211
2.4.24 Update ComboBox Field 215
2.4.25 Add Toggle Field 218
2.4.26 Update Toggle Field 221
2.4.27 Add Numeric Stepper Field 225
2.4.28 Update Numeric Stepper Field 228
2.4.29 Add Hyperlink Field 232
2.4.30 Update Hyperlink Field 235
2.4.31 Add Stamp Field 239
2.4.32 Update Stamp Field 241

2.4.33 Add Camera Field 244
2.4.34 Update Camera Field 247
2.4.35 Add Attachment Field 250
2.4.36 Update Attachment Field 253
2.4.37 Add CheckBox Field Version 2 256
2.4.38 Update CheckBox Field Version 2 259
2.4.39 Add RadioBox Field Version 2 263
2.4.40 Update RadioBox Field Version 2 266
2.5 Document Processing 269
2.5.1 Approve Document 269
2.5.2 Decline Document 270
2.5.3 Sign with GoPaperless Workflow 272
2.5.4 Two Step Signing 277
2.5.5 Fill Form Fields 282
2.5.6 Fill Initials 287
2.5.7 Submit Document 289
2.6 Connector 291
2.6.1 Get List USB-Token Connector 291
2.6.2 Get List Smart-ID Connector 292
2.6.3 Get List Internal Signing Service Connector (ISS) 294
2.6.4 Get Certificate Profile of Connector 295
2.7 RSSP Processing 297
2.7.1 Get RSSP Information 297
2.7.2 Get Filtered Credential List 299
2.7.3 Sign Document via RSSP Directly 301
2.7.4 RSSP Credential Authorization 305
2.7.5 Get Signing Status (TSE MID) 307
2.7.6 Get Credentials Info 309
2.7.7 Send OTP via RSSP 311
2.8 Register Certificate Processing 312
2.8.1 Get Information of Citizen card 312
2.8.2 Register Certificate via RSSP 314
2.8.3 Send OTP to Certificate Registration 316
2.8.4 Verify OTP for Certificate Registration 318
2.8.5 Get List Tax Codes 320
2.8.6 Finish Register Certificate 321
2.9 Enterprise Management 323
2.9.1 Register Enterprise User 323

2.9.2 Get Workflow User Permissions of Enterprise Package 326
2.9.3 Update Workflow User Permissions of Enterprise Package 328
2.9.4 Get Workflow User Authentication(Document Opening) of Enterprise Package 330
2.9.5 Update Workflow User Authentication of Enterprise Package 333
2.9.6 Reset Enterprise User Password 336
2.9.7 Change User Service Plan 338
2.9.8 Get Enterprise Users 339
2.9.9 Get Enterprise User 341
2.9.10 Update Enterprise User 343
2.9.11 Delete Enterprise User 346
2.9.12 Get Groups 347
2.9.13 Delete Groups 349
2.9.14 Add Member into Group 351
2.9.15 Delete Member in Group 352
2.9.16 Get Roles 354
2.9.17 Get Role Users 356
2.9.18 Delete Role 357
2.9.19 Add Role 359
2.10 Account Management 361
2.10.1 Get Account Invitations 361
2.10.2 Accept Account Invitations 362
2.10.3 Reject All Account Invitations 364
2.10.4 Register Enterprise User (Free Trial) 365
2.10.5 Get Account 368
2.10.6 Send Forgot Password Request 371
2.10.7 Account Usage Statistic 372
2.10.8 Document Statistic 374
2.10.9 Get User Activity Logs 376
2.10.10 Get Group 378
2.10.11 Change Pasword 380
2.10.12 Update Security Settings 382
2.11 Personal Settings 385
2.11.1 Get Signature Settings 385
2.11.2 Add Signature Appearance 387
2.11.3 Update Signature Appearance 390
2.11.4 Delete Signature Appearance 392
2.11.5 Get General Profile Information 393
2.11.6 Update General Profile Information 395
2.11.7 Get Address Book 397

2.11.8 Add Address Book 399
2.11.9 Update Address Book 401
2.11.10 Delete Address Book 402
2.11.11 Add Contact into Address Book 403
2.11.12 Remove Contact in Address Book 405
2.12 Application/Device Management 409
2.12.1 Register Application User 409
2.12.2 Add Personal Contact 413
2.12.3 Get Contacts 415
2.12.4 Update Personal Contact 417
2.12.5 Delete Personal Contact 419
2.13 Template 421
2.13.1 Save Workflow as Template 421
2.14 ADMIN APIs 429
2.14.1 Admin Authentication 429
2.14.2 Create Account 430
2.14.3 Change User Service Plan 432
2.14.4 Get Accounts 434
2.14.5 Service Plan Reset 436
3 ..... ERROR CODE HTTP 438
4 ..... REQUEST/RESPONSE OBJECT 439
4.1 AddUserToWorkflowRequest 439
4.2 AddUserToWorkflowResponse 439
4.3 GetWorkflowHistoryResponse 440
4.4 VerificationSignatureRequest 440
4.5 AssignDocumentRequest 441
4.6 RegisterUserRequest 441
4.7 UpdateWorkflowPermissionRequest 442
4.8 GetFilteredCredentialListResponse 443
4.9 GetListWorkflowResponse 443
4.10 BaseFillFormRequest 444
4.11 AddPlaceholderToWorkflowRequest 445
4.12 AddPlaceholderToWorkflowResponse 445
4.13 GetAttachmentsResponse 445
4.14 GetCertificateProfilesResponse 446

5 RELATIVE OBJECT 446

5.1 RemarkError 446
5.2 Package 446
5.3 NextSigner 447
5.4 Access_duration_1 (Get Packages request) 447
5.5 Decline 447
5.6 Certify 448
5.7 DocumentVerification 448
5.8 PackageVerification 449
5.9 Document 450
5.10 Workflow 450
5.11 User 452
5.12 Reminder 454
5.13 Action 454
5.14 Information 455
5.15 Comment/Message 455
5.16 Sender 455
5.17 Authentication (for Workflow User Authentication) 456
5.18 Password 456
5.19 Sms 456
5.20 Authentication_Signing (for Workflow User Authentication) 456
5.21 Access_duration (for Workflow User Authentication) 457
5.22 DurationByDate 457
5.23 DurationByDays 457
5.24 DurationDays 458
5.25 DurationDate 458
5.26 Permission 458
5.27 Dimension 459
5.28 FieldAuthentication 459
5.29 Otp 460
5.30 Font 460
5.31 AlignmentOption 460
5.32 SignatureFieldAttribute 461
5.33 VerificationData 462

5.34 TextFieldAttribute 463
5.35 CheckboxFieldAttribute 465
5.36 QRFieldAttribute 466
5.37 InitialFieldAttribute 467
5.38 RSSPService 467
5.39 Owner(Package Details) 468
5.40 Document(Package Details) 468
5.41 Authentication(SigningRequest) 469
5.42 Authentication (Workflow User Authentication) 469
5.43 UserOfEnterprise 469
5.44 Group 470
5.45 Member 470
5.46 Role 471
5.47 Invitation 471
5.48 ServicePlan 471
5.49 Constraints 472
5.50 Setting 473
5.51 Billing 473
5.52 Enterprise 474
5.53 Consumer 474
5.54 UserActivity 475
5.55 Information 475
5.56 General 476
5.57 Security 476
5.58 Locale 476
5.59 Contact 476
5.60 Account 477
5.61 Connector 477
5.62 Address Book 478
5.63 WorkflowDetail 478
5.64 Category 478
5.65 SignatureAppearance 479
5.66 MetadataSignature 479
5.67 CredentialConfiguration 480
5.68 AssignedField 480

5.69 CredentialInfo 480
5.70 PersonalInformation 481
5.71 Items 482
5.72 ChooseItems 483
5.73 ChooseItem 483
5.74 Date 484
5.75 NumericItems 484
5.76 File 484
5.77 Frame 485
5.78 Image 485
5.79 Template 485
5.80 CertificateProfile 485
5.81 IssuingProvider 486
6 ENUMERATION 486
6.1 WorkflowMode 486
6.2 WorkflowStatus 486
6.3 LevelOfAssurance 487
6.4 LockAction 487
6.5 LockPermission 487
6.6 AnnotationPosition 488
6.7 DocumentType 488
6.8 SigningAlgorithm 488
6.9 HashingAlgorithm 489
6.10 AppearanceDesign 489
6.11 AppearanceAlignment 489
6.12 WorkflowState 489
6.13 FieldTypes 490
6.14 AuthorizeMode 491
6.15 Role 491
6.16 DocumentTypeForEID 491
6.17 Color 492
6.18 FontName 492
7 EXAMPLE 495

7.1 Items request 495

1 INTRODUCTION

This document subscriber in detail the API (parameters,..) for interaction between Relying Party with GoPaperless Workflow Service. Besides, this document doesn't contain the script for creating the Database GoPaperless Workflow.

1.1 Target

The document is suitable for customers/companies whose would like to interact with the GoPaperless Workflow Service.

1.2 Abbreviation

Notation	Description
API	Application Programming Interface
RSSP	Remote Signing Service Provider
M	Mandatory parameter
O	Optional parameter
RC	Required Condition
RSA	Rivest-Shamir-Adleman
ECDSA	Elliptic Curve Digital Signature Algorithm
DSA	Digital Signature Algorithm
OS IANA	Operating System Internet Assigned Numbers Authority

1.3 System Connection Information

The following table lists connection parameters used to build API endpoint URLs.

No	Name	Value	Description
1	domain	prd-gopaperless.mobile-id.vn	Current production domain
2	contextPath	/workflow/api	API context path
3	baseUrl	https://{domain}/{contextPath}/XXX	Template for API endpoint URLs

2 API SPECIFICATION

All of the APIs in this document are HTTP web service RESTful.

2.1 Authenticate – Log in

2.1.1 Client Credentials Authentication

This function is responsible for retrieving an access token, which is required for subsequent function calls.

The client must provide credentials issued by the service provider (GoPaperless Workflow Service). The server will authenticate these credentials and, if valid, return an access token for use in subsequent API requests.

Sample Request

POST https://{domain}/{contextPath}/v1/authenticate
Content-Type: application/json
x-language-name: en

```
{
  "grant_type": "client_credentials",
  "client_id": "Application_name",
  "client_secret": "client_secret",
  "remember_me_enabled": true
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "access_token": "Token",
  "token_type": "bearer",
  "expires_in": 300,
  "refresh_token": "refreshtoken",
  "refresh_token_expires_in": 1800
}
```

Http Code: 401
Content-type: application/json

```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	grant_type	String	M	Defines the type of access token to be returned (following OAuth 2.0). Supported value: "client_credentials".
2	client_id	String	M	The Application Name that was configured in your Enterprise Account during the integration setup.
3	client_secret	String	M	The API key which be generated in Enterprise Account.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
4	remember_me_enabled	Boolean	O	If this parameter is true (enabled) => GoPaperless Workflow Service will return a refresh token embedded into the response. Default is false.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	access_token	String	M	The access token will be used later to connect with other APIs.
5	token_type	String	M	Type of the token returned. It is always set to "bearer".
6	expires_in	Integer	M	Number of seconds for which this access token is valid.
7	refresh_token	String	M	This is a token related to access token. Can use this token to revoke.
8	refresh_token_expires_in	Integer	M	Number of seconds for which this refresh token is valid.

2.1.2 Password Authentication

This function retrieves an access token, which will be used in subsequent API calls.

The client must provide user credentials issued by the service provider (GoPaperless Workflow Service). The server will validate the provided credentials and return an access token if they are correct.

Sample Request

POST https://{domain}/{contextPath}/v1/authenticate
Content-Type: application/json
x-language-name: en

```
{
  "grant_type": "password",
  "client_id": "Application_name",
  "client_secret": "client_secret",
  "username": "admin@mobile-id.vn",
  "password": "OneTwoThreeFour",
  "scope": "giatk@mobile-id.vn",
  "remember_me_enabled": true
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "access_token": "Token",
  "token_type": "bearer",
  "expires_in": 300,
  "refresh_token": "refreshtoken",
  "refresh_token_expires_in": 1800
}
```

Http Code: 401
Content-type: application/json

```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	grant_type	String	M	Define which type of access token will be returned (through the OAuth 2.0): + "password" + "refresh_token"
2	client_id	String	M	Application Name that you have configured in your Enterprise Account when configuring the Integration options.
3	client_secret	String	M	The API key which be generated in Enterprise Account.
4	username	String	M	GoPaperless Workflow email address identifying the target user account - this can be an Enterprise Admin or an Enterprise User account. Note an enterprise user can use an API Key created for the enterprise by an enterprise administrator.
5	password	String	M	Password for the account defined in the 'username' parameter.
6	remember_me_enabled	Boolean	O	If this parameter is true (enabled) => GoPaperless Workflow Service will return a refresh token embedded into the response. Default is false.
7	scope	String	O	Used when the Enterprise Admin user is identified in 'username' and you wish to identify an Enterprise User as the target. That is, set an enterprise user as the current user for operations.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
4	access_token	String	M	The access token will be used later to connect with other APIs.
5	token_type	String	M	Type of the token returned. It is always set to "bearer".
6	expires_in	Integer	M	Number of seconds for which this access token is valid.
7	refresh_token	String	M	This is a token related to access token. Can use this token to revoke.
8	refresh_token_expires_in	Integer	M	Number of seconds for which this refresh token is valid.

2.1.3 Single Sign On Authentication

This function retrieves an access token, which will be used in subsequent API calls.

A business application can call this API to obtain a user's access token by making a request to a third-party service, based on the provided method and token.

Sample Request

POST https://{domain}/{contextPath}/v1/authenticate/sso
Content-Type: application/json
x-language-name: en

```
{
  "token": "String",
  "code": "String",
  "method": "String",
  "profile_name": "String",
  "profile_id": 0,
  "remember_me_enabled": true
}
```

Sample Response

Http Code: 200
Content-type: application/json


```
{
  "access_token": "Token",
  "token_type": "bearer",
  "expires_in": 300,
  "refresh_token": "refreshtoken",
  "refresh_token_expires_in": 1800
}
```


Http Code: 401
Content-type: application/json


```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	token	String	M	Token obtained from 3rd party (Ex: JWT,..)
2	code	String	M	
3	method	String	M	Supported method type: + "OAUTH2"
4	profile_name	String	M	Authentication profile name, required for "OAUTH2" and "OIDC"
5	profile_id	Integer	M	Authentication profile id, Its an alternate of profile_name
6	remember_me_enabled	Boolean	O	If this parameter is true (enabled) => GoPaperless Workflow Service will return

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				a refresh token embedded into the response. Default is false.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	access_token	String	M	The access token will be used later to connect with other APIs.
5	token_type	String	M	Type of the token returned. It is always set to "bearer".
6	expires_in	Integer	M	Number of seconds for which this access token is valid.
7	refresh_token	String	M	This is a token related to access token. Can use this token to revoke.
8	refresh_token_expires_in	Integer	M	Number of seconds for which this refresh token is valid.

2.1.4 OTP Login Authentication

This function retrieves an access token, which will be used in subsequent API calls.

GoPaperless Workflow supports two-factor authentication (2FA) using a One-Time Password (OTP) during login. To enable OTP-based authentication, the Enterprise Administrator must configure this option in the Enterprise Role settings.

At least one SMS provider must be configured in the GoPaperless Workflow Service to use this API.

Sample Request

POST https://{domain}/{contextPath}/v1/authenticate/otp
Content-Type: application/json
x-language-name: en

```
{
  "mobile_number": "String",
  "method": "SMS"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "access_token": "Token",
  "token_type": "bearer",
  "expires_in": 300,
  "refresh_token": "refreshtoken",
  "refresh_token_expires_in": 1800
}
```

Http Code: 401
Content-type: application/json

```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	mobile_number	String	M	Define the mobile number of user. The OTP will be send to Application.
2	method	String	M	Method possible values are: + SMS + EMAIL

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	access_token	String	M	The access token will be used later to connect with other APIs.
5	token_type	String	M	Type of the token returned. It is always set to "bearer".
6	expires_in	Integer	M	Number of seconds for which this access token is valid.
7	refresh_token	String	M	This is a token related to access token. Can use this token to revoke.
8	refresh_token_expires_in	Integer	M	Number of seconds for which this refresh token is valid.

2.1.5 Revoke refresh token

This function revokes the refresh tokens issued for a user.

A refresh token is generated and sent when an authentication request is successfully processed.

Sample Request

```
DELETE https://{domain}/{contextPath}/v1/tokens
Content-Type: application/json
x-language-name: en
{
  "refresh_token": "refresh_token_of_accesstoken",
  "token_type_hint": "refresh_token"
}
```

Sample Response

Http Code: 200
Content-Type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	refresh_token	String	M	OAuth refresh access token to revoke
2	token_type_hint	String	M	Type of token. Currently only "refresh_token" is supported

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.1.6 Get Information

This function retrieves information about GoPaperless Workflow Services.

Additionally, this API can be used to verify the validity of an access token by including it in the request header.

Sample Request

GET https://{domain}/{contextPath}/v1/info
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
    "gopaperless.workflow.app.langs": "en;vn",
    "gopaperless.workflow.app.name": "GoPaperless Workflow Services",
    "gopaperless.workflow.app.dateformat": "dd/MM/yyyy",
    "gopaperless.workflow.app.region": "region1",
    "gopaperless.workflow.app.logo": "https://gopaperless.workflow.mobile-id.vn",
    "gopaperless.workflow.app.methods": [
"info",
"authenticate",
"tokens",
"workflow"
]
    "gopaperless.workflow.app.version": "23.02.24",
    "gopaperless.workflow.app.authType": [
"basic",
"oauth2code"
]
    "gopaperless.workflow.app.description": "GoPaperless Workflow is a smart workflow management"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	access_token	String	O	When you send this parameter to this API. If the access token is valid, the response will be returned. Otherwise, it will not be returned.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.1.7 Pre Login Authentication

This function retrieves the authentication method for the user based on the configuration set in the enterprise role.

Sample Request

```
GET https://{domain}/{contextPath}/v1/authenticate/pre
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "email": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "profile_id": 0,
  "profile_name": "String",
  "method": "String",
  "app_id": "String",
  "tenant_id": "String",
  "url": "String",
  "scope": "String",
  "resource ": "String"
}
```


Http Code: 401
Content-type: application/json


```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	email	String	M	Defines the email of the User. The service will check that email in system and return a valid data to the client.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	status	String	M	Status of the user. Possible values are + NOT_FOUND + ACTIVE

2.2 Document Package

2.2.1 Pre Upload Document

Business Applications can use this service API to pre check a document before call subsequence APIs.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/documents/pre
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
```
{
  "file_data": "Base64 of file"
}
```

POST https://{domain}/{contextPath}/v1/packages/documents/pre
Content-Type: application/octet-stream
Authorization: "Bearer {accesstoken}"
x-language-name: en
```
{
    File(binary)
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "document_status": 0,
  "document_status_name": "This document exists an PdfFormField"
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes

No	Name	Type	Presence	Description
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes

No	Name	Type	Presence	Description
1	file_data	String	RC (If content-type is application/json)	Data of the file in Base64 format.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	document_status	Integer	M	Status of the document. Possible values are: + 0 : Exist a Form Field + 1 : Document is empty
5	document_status_name	String	M	Name of the status

2.2.2 Add Document Package

After authenticating into GoPaperless Workflow Service (e.g., Business Application), this mandatory function must be called first to create a package in GoPaperless Workflow.

This API is used to create a blank package containing one or more documents. Additionally, the package can be used to add fields, data, and other elements to initiate a new workflow.

Sample Request

POST https://{domain}/{contextPath}/v1/packages
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "package_name": "String"
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "package_id": 0
}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	package_name	String	M	Defines the name of the package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	package_id	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

2.2.3 Share Document Package/ Share Workflow

Business applications can use this API to share a document package with signers and initiate a new workflow.

Additionally, the document package must be prepared using the Preparation API before sharing it with signers.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/share
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				"Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	package_name	String	M	Defines the name of the package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.4 Upload Document

The client can use this API to add a document to a document package, which is linked to a user account. The document metadata is sent in the HTTP header, while the document data (binary) is sent in the HTTP body.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/{packageId}/documents
Content-Type: application/octet-stream
Authorization: "Bearer {accesstoken}"
x-file-name: "Name of file"
x-language-name: en
{
File(binary)
}

Sample Response

Http Code: 201
Content-Type: application/json

```
{
  "documentid": 0
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/octet-stream" to upload your document with binary format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	Name	Type	Presence	Description
1		Byte[]	M	Binary of the document

Response Attributes				
No	Name	Type	Presence	Description
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	documentid	Integer	M	The document ID to be used to share, download or append it into workflow

2.2.5 Upload Document (base64)

The client can use this service API to add a document to a document package, which is linked to a user account. The document metadata is sent in the HTTP headers, while the document data (Base64-encoded) is sent in the HTTP body

Sample Request

```
POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/base64
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-file-name: "Name of file"
x-language-name: en
{
  "document": "Base64"
}
```

Sample Response

Http Code: 201
Content-Type: application/json

```
{
  "documentid": 0
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/json" to upload your document with base64 format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	document	String	M	Base64 encoded of the document

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	documentid	Integer	M	The document ID to be used to share, download or append it into workflow

2.2.6 Download Package

Business applications can use this service API to download a document package in binary format. If the package contains a single document, the downloaded file will be a binary PDF. However, if the package includes multiple documents, the download will be a binary ZIP file containing all documents.

Note: The parameters x-password and x-otp are required if the package owner (the user who created the package) has enabled this option during the workflow creation phase.

Sample Request

```
GET https://{domain}/{contextPath}/v1/packages/{packageId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-password: "password123"
x-otp: "otp"
{}
```

Sample Response

Http Code: 200
Content-type: application/octet-stream

```
{
    File(binary)
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-password	String	O	Password of the document
4	x-otp	String	O	OTP value for opening the document

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4		Byte[]	M	File data in binary format

2.2.7 Download Package (base64)

Business applications can use this service API to download a document package in base64 format. If the package contains a single document, the downloaded file will be a binary PDF. However, if the package includes multiple documents, the download will be a binary ZIP file containing all documents.

Note: The parameters x-password and x-otp are required if the package owner (the user who created the package) has enabled this option during the workflow creation phase.

Sample Request

GET https://{domain}/{contextPath}/v1/packages/{packageId}/base64
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-password: "password123"
x-otp: "otp"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "file_data": "Base64"
}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-password	String	O	Password of the document
4	x-otp	String	O	OTP value for opening the document

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	file_data	String	M	File data in base64 format

2.2.8 Download Document

Business applications can use this service API to download a document in binary format. The client must provide both the package ID and the document ID to retrieve the document successfully

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-password: "Password 123"
x-otp: "otp"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/octet-stream

```
{
    File(Binary)
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-password	String	O	Password of the document
4	x-otp	String	O	OTP value for opening the document

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	This is the ID of the document that was created and belongs to the packageId.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4		Byte[]	M	File data in binary format

2.2.9 Download Document (base64)

Business application can use this service API to download a document in binary format. The client must provide both the package ID and the document ID to retrieve the document.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/base64
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-password: "Password 123"
x-otp: "otp"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "file_data": "Base64"
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.
3	x-password	String	O	Password of the document
4	x-otp	String	O	OTP value for opening the document

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	file_data	String	M	Data of the document in base64 format

2.2.10 Get All Package

Business applications can use this service API to get all document package in GoPaperless Workflow.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{document_status}/{page_no}/{records_per_page}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-search-text: "c2FsZXMgY29udHJhY3QgMTA1"
x-total-records : 100
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json
x-total-records: 100


```
{
    "packages": [
{
"package_id": 123,
"package_name": "Package name",
            "package_owner": "giatk@mobile-id.vn",
            "owner_name": "Tat Khanh Gia",
    "package_status": "ACTIVE"
                    "unread": false,
            "next_signer_email": ["giatk@mobile-id.vn"]
            "created_at": "2023-07-21T11:12:13",
            "created_by": "giatk@mobile-id.vn",
            "modified_at": "2023-07-21T11:12:13",
            "modified_by": "giatk@mobile-id.vn",
                    "acccess_duration":{
                    "date_from": "07212023",
                    "date_to": "07212024"
},
            "decline": [
            "reason": "For testing",
            "declined_by": "giatk@mobile-id.vn"
    ]
            },
            {…
            }
    ]
}
```

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-search-text	String	O	The string name (after encode base64) uses to find the workflow label(in services)
4	x-total-records	Integer	O	The number of records that the client wants to get. Note 1: when this parameter is defined. All the parameters "page_no" and "records_per_page" will be ignored. Note 2: Default value of this parameter is 100.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	document_status	String	M	Filter by workflow status. Possible values are "ACTIVE", "INACTIVE", "ALL".

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	page_no	Integer	O	Page number, according the division of records per page.
3	records_per_page	Integer	O	Number of records that are needed to be fetched in one request.

Header Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	x-total-records	Integer	M	The length of the list of records

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	PackagesString	M	Error code identifying the failure.
2	error_description	PackagesString	M	Detailed description of the error.
3	message	PackagesString	M	Human-readable error message.
4	packages	List<Packages>	M	The list of <Package>.

2.2.11 Get Document Image

Business Applications can use this service API to get an image of the document.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/images/{pageNo}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-page-width: 600
x-page-height: 800
x-image-type: "PNG"
x-otp: "OTP"
x-password: "Password"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/octet-stream

```
{
    File(Binary data)
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-page-width	Integer	O	Width of the image returned in response.
2	x-page-height	Integer	O	Height of the image returned in response.
3	x-image-type	String	O	Defines the type of the image
4	x-otp	String	O	Password of the document
5	x-password	String	O	OTP value for opening the document
6	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
7	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	pageNo	Integer	M	Page number in the document for which the image is requested.
3	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4		Byte[]	M	Binary data of the image

2.2.12 Get Document Image Base64

Business Applications can use this service API to get an image of the document in base64 format.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/images/{pageNo}/base64
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-page-width: 600
x-page-height: 800
x-image-type: "PNG"
x-otp: "OTP"
x-password: "Password"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json

{
"file_data": "Base64 of the Image",
"image_format": "PNG"
}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-page-width	Integer	O	Width of the image returned in response.
2	x-page-height	Integer	O	Height of the image returned in response.
3	x-image-type	String	O	Defines the type of the image
4	x-otp	String	O	Password of the document
5	x-password	String	O	OTP value for opening the document
6	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
7	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	pageNo	Integer	M	Page number in the document for which the image is requested.
3	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	file_data	String	M	Data of the image in base64 format
5	image_format	String	M	Format of the image

2.2.13 Get Document Details

Business applications can use this service API to retrieve detailed information about a document contained within a package.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/details

Content-Type: application/json

Authorization: "Bearer {accesstoken}"

x-password: "Password"

x-otp: "OTP"

x-language-name: en

{}

Sample Response

Http Code: 200
Content-type: application/json


```
{
  "document_id": 0,
  "document_name": "Name",
  "document_order": 0,
  "document_type": "PDF",
  "document_width": 100,
  "document_height": 100,
  "document_pages": 1,
  "form_fields": true,
  "lock_form_fields": true,
  "created_at": "date",
  "modified_at": "date"
}
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	document_id	Integer	M	ID of the newly created document.
5	document_name	String	M	The name of the document.
6	document_order	Integer	O	Order of the document (Sequence number of document belongs to the package)
7	document_type	String	M	Type of the document e.g. "PDF".
8	document_width	Integer	M	Width of the document in PDF format.
9	document_height	Integer	M	Height of the document in PDF format.
10	document_source	String	M	
11	document_pages	Integer	M	Total pages of the document.
12	form_fields	Boolean	M	True if document has form fields.
13	lock_form_fields	Boolean	M	True if locking of form fields with the last signature is enabled.
14	created_at	String	M	Date of the decline to know when it was uploaded in ISO format
15	created_by	String	M	Name of the user who created this decline
16	modified_at	String	O	Date of the decline to know when it was modified in ISO format
17	modified_by	String	O	Name of the user who modified this decline

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
18	certify	Certify	O	Certified signature settings for the document.
19	template			

2.2.14 Get Document Verification

Business Applications cans use this service API to get the verificate result for all the digital signature fields of a document in a package.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/verification
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200

Content-type: application/json


```
[
 {
    "status": "String",
    "field_name": "String",
    "signer_name": "String",
    "signer_photo": "String",
    "signer_photo_url": "String",
    "signature_status": "String",
    "signing_reason": "String",
    "signing_location": "String",
    "contact_information": "String",
    "signing_time”: "String",
    "ltv": false,
    "qualified": true,
    "certified": true,
    "cerfify_permission": "String",
    "timestamp_at": "String",
    "timestamp_authority": "String",
    "subject_dn": "String",
    "issuer_dn": "String",
    "cert_valid_from": "String",
    "cert_valid_to": "String",
    "signature_type": "String",
    "signature_algorithm”: "String",
    "signed_hash": "String",
    "display": true,
    "page_number": 1
 },
 {},..
]
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
4		List<documentVerification>	M	List of Document Verification object

2.2.15 Get Package Verification

Business applications can use this service API to retrieve the verification results for all digital signature fields across all documents within a package.

Sample Request

GET https://{domain}/{contextPath}/v1/packages/{packageId}/verification
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json


```
[
   {
    "document_id": 1,
    "fields": [
            {
                    "status": "String",
                    "field_name": "String",
                    "signer_name": "String",
                    "signer_photo": "String",
                    "signer_photo_url": "String",
                    "signature_status": "String",
                    "signing_reason": "String",
                    "signing_location": "String",
                    "contact_information": "String",
                    "signing_time": "String",
                    "ltv": false,
                    "qualified": true,
                    "certified": true,
                    "cerfify_permission": "String",
                    "timestamp_at": "String",
                    "timestamp_authority": "String",
                    "subject_dn": "String",
                    "issuer_dn": "String",
                    "cert_valid_from": "String",
                    "cert_valid_to": "String",
                    "signature_type": "String",
                    "signature_algorithm": "String",
                    "signed_hash": "String",
                    "display": true,
                    "page_number": 1
            },
            {},..
]
   }
   ,{},…
]
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
4		List<packageVerification>	M	List of Package verification

2.2.16 Get Package Details

Business applications can use this service API to obtain the verification results for all digital signature fields across all documents within a package.

Sample Request

GET https://{domain}/{contextPath}/v1/packages/{packageId}/details
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json


```
{
  "name": "Package Name",
  "owner": {
    "name": "String",
    "email": "email"
  },
  "document_status": "String",
  "documents": [
    {
      "id": 0,
      "name": "String",
      "created_at": "String",
      "modified_at": "String",
      "size": 0,
      "type": "String",
      "source": "String"
    }
  ]
}
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	name	String	M	Name of the package
5	owner	owner	M	Owner data
6	document_status	String	M	Status of the document. Possible values are + ACTIVE/ENABLED + INACTIVE/DISABLED
7	documents	List<document>	M	List of document belongs to this package

2.2.17 Rename Package

Business applications can use this service API to rename the name of the package.

Sample Request

PUT https://{domain}/{contextPath}/v1/packages/{packageId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "package_name": "New Name"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	package_name	String	M	New name of the document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.18 Rename Document

Business Applications cans use this service API this rename to name of document which is inside the package.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "document_name": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	document_name	String	M	New name of the document.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.19 Delete Package

Business Applications cans use this service API to delete the package.

Sample Request

DELETE **https://{domain}/{contextPath}/v1/packages/{packageId}**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json
{}

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.20 Delete Document

Business Applications cans use this service API to delete the document of package.

Sample Request

DELETE
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json
{}

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.21 Update Document

Business applications can use this service API to update a document of a document package. The document information is sent in the HTTP request header and document bytes are sent in the HTTP request body.

GoPaperless Workflow supports a wide variety of document formats, each of which can be converted to PDF format upon upload.

Note PDF documents are not altered upon upload to the system.

Note a package must already exist before you can add a document using this call.

Note this feature is supported only for PDF documents.

Sample Request

```
PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/update
Content-Type: application/octet-stream
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-file-name: "Test.pdf"
{
    File(binary)
}
```

Sample Response

Http Code: 200
Content-Type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/octet-stream" to upload your document with binary format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Request Attributes				
No	Name	Type	Presence	Description
1		Byte[]	M	Binary of the document

Response Attributes				
No	Name	Type	Presence	Description
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.22 Update Document (base64)

Business applications can use this service API to update a document of a document package. The document information is sent in the HTTP request header and document bytes are sent in the HTTP request body.

GoPaperless Workflow supports a wide variety of document formats, each of which can be converted to PDF format upon upload.

Note PDF documents are not altered upon upload to the system.

Note a package must already exist before you can add a document using this call.

Note this feature is supported only for PDF documents.

Sample Request

```
PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/update/base64
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-file-name: "Test.pdf"
{
  "document": "Base64"
}
```

Sample Response

Http Code: 200
Content-Type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/json" to upload your document with base64 format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	document	String	M	Base64 encoded of the document

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.23 Upload Attachment

Business applications can use this service API to upload an attachment to a document package. The document information is sent in the HTTP request header and document bytes are sent in the HTTP request body.

Note PDF documents are not altered upon upload to the system.

Note a package must already exist before you can add a document using this call.

Note this feature is supported only for PDF documents.

Sample Request

```
PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/attachments
Content-Type: application/octet-stream
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-file-name: "Test.pdf"
{
    File in binary format
}
```

Sample Response

Http Code: 200
Content-Type: application/json

{
"attachment_id": 0
}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/octet-stream" to upload your document with binary format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	attachment_id	Integer	M	Id of the attachment.

2.2.24 Get Attachments

Business applications can use this service API to get all attachments in document package.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/attachments
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "attachments": [
    {
      "attachment_id": 0,
      "attachment_name ": "name of attachment"
    }
  ]
}
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/json" to upload your document with binary format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	attachments	List<attachment>	M	List of the attachment

2.2.25 Delete Attachment

Business applications can use this service API to delete the attachment in document.

Sample Request

DELETE
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/attachments/{attachmentId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

Sample Response

Http Code: 200
Content-Type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/json" to upload your document with binary format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.
3	attachmentId	Integer	M	Id of the attachment

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	attachment_id	Integer	M	Id of the attachment.

2.2.26 Download Attachment

Business applications can use this service API to download attachment in document

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/attachments/{attachmentId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

Sample Response

Http Code: 200
Content-Type: application/octet-stream
{
File in binary format
}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/json" to upload your document with binary format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.
3	attachmentId	Integer	M	Id of the attachment

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.27 Download Attachment (base64)

Business applications can use this service API to download the attachment in document.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/attachments/{attachmentId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "base64": "String"
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-file-name	String	O	Name of the document.
4	Content-Type	String	M	Using "application/json" to upload your document with binary format.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.
3	attachmentId	Integer	M	Id of the attachment

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	attachment_id	Integer	M	Id of the attachment.

2.2.28 Merge Document

Business applications can use this api to seamlessly integrate documents into workflow processes.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/merge
Content-Type: application/octect-stream
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-append-to-top: true
{
File in binary format
}

Sample Response

Http Code: 200
Content-type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	Content-Type	String	M	Using "application/octet-stream" to upload your document with binary format.
4	x-append-to-top	Boolean	O	True if the file should be prepended to the document. Default is false

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.2.29 Apply Workflow Template

Business applications can use this service API to apply a workflow template to a document. The document ID on which template has to be applied is provided in the resource URL. While applying the template it is important to remember these two important points:
Point 1 - If the template being applied is created using a PDF which already contained form fields then ensure that the document on which this template is now being applied must contain these form fields in advance and GoPaperless Workflow will NOT create those form fields via the template rather only apply the form data and assign to the respective users.
Point 2 - If the template being applied is created where form fields are manually added (hence not present in the PDF originally) via GoPaperless Workflow e.g. signature field, initial, in-person signature, check boxes, radio buttons, text fields etc. then on applying such a template, these form fields will be created on the target document even if these form fields were already present in the document.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/template
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "template_name": "String",
  "apply_to_all": false
}
```

Sample Response

Http Code: 200
Content-type: application/json


```
{
  "document_id": 0,
  "document_name": "Name",
  "document_order": 0,
  "document_type": "PDF",
  "document_width": 100,
  "document_height": 100,
  "document_pages": 1,
  "form_fields": true,
  "lock_form_fields": true,
  "created_at": "date",
  "modified_at": "date",
  "template": {
    "template_name": "String",
    "read_only": true
  }
}
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				"Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	Content-Type	String	M	Using "application/octet-stream" to upload your document with binary format.
4	x-append-to-top	Boolean	O	True if the file should be prepended to the document. Default is false

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID is required for sharing, downloading, or appending the document to a workflow.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	template_name	String	M	Name of template to be applied on the document.
2	apply_to_all	Boolean	O	True, if template is to be applied on all the documents in the package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	document_id	Integer	M	ID of the newly created document.
5	document_name	String	M	The name of the document.
6	document_order	Integer	O	Order of the document (Sequence number of document belongs to the package)

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	document_type	String	M	Type of the document e.g. "PDF".
8	document_width	Integer	M	Width of the document in PDF format.
9	document_height	Integer	M	Height of the document in PDF format.
10	document_source	String	M	
11	document_pages	Integer	M	Total pages of the document.
12	form_fields	Boolean	M	True if document has form fields.
13	lock_form_fields	Boolean	M	True if locking of form fields with the last signature is enabled.
14	created_at	String	M	Date of the decline to know when it was uploaded in ISO format
15	created_by	String	M	Name of the user who created this decline
16	modified_at	String	O	Date of the decline to know when it was modified in ISO format
17	modified_by	String	O	Name of the user who modified this decline
18	certify	Certify	O	Certified signature settings for the document.
19	template	Template	O	Template details, if the template is applied on the document.

2.3 Document Workflow

2.3.1 Start new Workflow

Business applications can use this service API to initiate a new workflow from a given `packageId`. Converting the package into a workflow enables seamless processing of subsequent API calls.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/{packageId}/workflow
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
    "deadline_at": "Deadline of the workflow",
    "workflow_mode: "SERIAL"
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	workflow_mode	String	O	Mode of the workflow. Possible values in here
2	deadline_at	String	O	Deadline of the workflow
3	filter_level	String	O	Filter level of Credentials

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.2 Add Electronic Seal to Workflow

Business applications can use this service API to add an Electronic Seal recipient to a workflow. This call will only add a recipient to the workflow. That is, no fields currently on the document will be automatically assigned to the new Electronic Seal recipient(s), nor will this create any new fields. Note the Electronic Seal recipient(s) will be added as the last person in the workflow. Hence further work may be required to remove a current Electronic Seal recipient(s) already present in the workflow. At least one recipient must exist in a workflow before fields can be added to the document. Note: the input accepts one or more Electronic Seal recipient(s) in a single call. Note: only PDF type document is supported.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/electronic-seals
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "name": "String",
  "signing_order": 0
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "name": "String",
  "signing_order": 0,
  "level_of_assurance": "String"
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	name	String	M	The name of the new user to be added/updated in workflow. If no value is provided, old value will be retained.
2	signing_order	Integer	M	Order in which the workflow will be signed by the recipients. This signing order is important when workflow type is set to "CUSTOM".

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	name	String	M	Name
5	signing_order	Integer	M	Signing Order
6	level_of_assurance	String	M	Level of Assurance

2.3.3 Add User to Workflow

After creating a workflow, the business application can use this service API to add a user to the workflow. This API call adds only one recipient at a time, and the newly added user will be placed as the last participant in the workflow.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/users

Content-Type: application/json

Authorization: "Bearer {accesstoken}"

x-language-name: en

```
{
    "users":[
{
     "user_email": "giatk@mobile-id.vn",
     "user_first_name": "Gia",
     "user_last_name": "Tat",
     "user_national_id": "National ID"
     "email_notification": true,
     "role": "SIGNER",
     "signing_order": 0,
     "reason": "Reason to Signing",
     "country"      : "VietNam",
              "company_name": "MID"
},{},…
    ]
}
```

Sample Response

Http Code: 200

Content-type: application/json

```
{
    "users":[
{
     "user_email": "giatk@mobile-id.vn",
     "order": 1,
     "signing_order": 0,
     "guest_user": true,
     "email_language_code": "en"
},{},…
    ]
}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	users	List<addUserRequest>	M	Arrays of the User

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.
4	users	List<addUserResponse>	M	Arrays of the User

2.3.4 Get All Workflow

Business applications can use this service API to retrieve all workflows in GoPaperless Workflow.

Sample Request

GET
https://{domain}/{contextPath}/v1/workflow/{criteria}/{page_no}/{records_per_page}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-search-text: "c2FsZXMgY29udHJhY3QgMTA1"
x-total-records : 100
x-language-name: en
x-search-text: "Hello"
x-category-id: 1
{}

Sample Response

Http Code: 200
Content-type: application/json
x-total-records: 100


```
{
    "workflows": [
{
"package_id": 123,
"package_name": "Package name",
            "package_owner": "owner2@mobile-id.vn",
            "owner_name": "New Owner2",
    "workflow_state": "PENDING",
    "workflow_status ": "SIGNED"
            "next_signer_email": [
                "giatk2@mobile-id.vn"
            ]
            "created_at": "2023-07-21T11:12:13",
            "created_by": "giatk@mobile-id.vn",
            "modified_at": "2023-07-21T11:12:13",
            "modified_by": "giatk@mobile-id.vn",
                "acccess_duration":{
                "date_from": "07212023",
                "date_to": "07212024"
},
            "decline": [
            "reason": "For testing",
            "declined_by": "giatk@mobile-id.vn"
    ]
            },
            {…
            }
    ]
}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-search-text	String	O	The string name (after encode base64) uses to find the workflow label(in services)
4	x-total-records	Integer	O	The number of records that the client wants to get. Note 1: when this parameter is defined. All the parameters "page_no" and "records_per_page" will be ignored. Note 2: Default value of this parameter is 100.
5	x-category-id	Integer	O	Category to find the workflow

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page_no	Integer	O	Page number, according the division of records per page.
2	records_per_page	Integer	O	Number of records that are needed to be fetched in one request.
3	criteria	String	M	Filter by workflow status. Possible values are here

Header Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	x-total-records	Integer	M	The length of the list of records

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	workflows	List<getListWorkflowResponse>	M	The list of workflow.

2.3.5 Update Workflow Details

Business applications can use this service API to update the workflow details of a package.

Sample Request

PUT https://{domain}/{contextPath}/v1/packages/{packageId}/workflow
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-time-zone: "IANA Time Zone"

```
{
  "workflow_mode": "String",
  "continue_on_decline": true,
  "message": "String",
  "comments": true,
  "deadline_at": "Deadline Time",
  "details": {
    "filter_level": "All"
  },
  "category_id": 1
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-time-zone	String	O	The timezone of the client. (Showing in audit trail when update deadline). Note: This parameter must be in IANA format

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	workflow_type	String	O	The process type of the workflow.
2	workflow_mode	String	O	Mode of the workflow. Possible values are in here
3	continue_on_decline	Boolean	O	True, if workflow needs to continue even if any recipient declines the document. If no value is provided, old value will be retained.
4	message	String	O	A custom string message from the document owner to every recipient, this message appears in the sharing email as well as on the screen. If no value is provided, old value will be retained.
5	comments	Boolean	O	Allow comments
6	deadline_at	String	O	Deadline of the workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	category_id	Integer	O	Id of the category
8	details	List<WorkflowDetail>	O	An array of the detail belongs to workflow

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.6 Get Workflow Details

Business applications can use this service API to retrieve workflow details for a given package.

Sample Request

```
GET https://{domain}/{contextPath}/v1/packages/{packageId}/workflow
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-type: application/json


```
{
    "package_id": 1,
    "package_name": "String",
    "package_owner": "giatk@mobile-id.vn",
    "owner_name": "Tat Khanh Gia",
    "package_status": "ACTIVE",
    "next_signer_email": [
            "giatk@mobile-id.vn"
    ],
    "created_at": "date",
    "modified_at": "date",
    "workflow":{
    "workflow_type": "SERIAL",
    "continue_on_decline": true,
    "workflow_state": "PENDING"
    "workflow_status": "IN_PRGORESS",
    "workflow_mode": "ONLY_ME",
    "message": "None message",
    "read_only": true,
    "post_process": {},
    "comments": true,
    "deadline_at": "Deadline Time",
        "details":{
            "filter_level": "All"
}
    "category_id": 1
    }
    "documents": [
    //response like API "Get Document Details"
    ],
    "users": [
    //response like API "Get Workflow Users"
]
}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	documents	List<document>	M	Arrays of Document belongs to this package
5	users	List<user>	M	Arrays of the User belongs to this package
6	workflow	workflow	M	Workflow data
7	package_id	Integer	M	The ID of the package

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	package_name	String	M	The name of the package
9	package_owner	Integer	M	Defines the email of user
10	owner_name	String	M	The name of the user who created this package.
11	package_status	String	M	Status of the package. Possible values are: + enABLED +DISABLED
12	unread	Boolean	M	
13	next_signer	String	M	Defines the name of the user who is the next signer to sign this package
14	next_signer_email	List<String>	M	List of email of the participant
15	created_at	String	M	Date of the package to know when it was created in ISO format
16	created_by	String	M	Name of the user who created this package
17	modified_at	String	M	Date of the package to know when it was modified in ISO format
18	modified_by	String	M	Name of the user who modified this package

2.3.7 Get Worklow Users

Business applications can use this service API to retrieve a list of users assigned to the workflow of a package.

Sample Request

```
GET https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/users
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200

Content-type: application/json


```
{
    "users":[
    {
            "order": 1,
            "user_email": "giatk@mobile-id.vn",
            "user_name": "TatKhanhGia",
            "user_photo_url": "String",
            "group_name": "String",
            "group_member":[
{
  "user_email": "email"
}
            ],
            "role": "SIGNER",
            "reason": "Reason why decline or Signing",
            "process_status": "SIGNED",
            "processed_as": "String",
            "processed_by": "String",
            "processed_on": "Date",
            "placeholder": "String",
            "signing_order": 1,
            "user_national_id": "079200011199",
            "guest_user": false,
            "email_language_code": "String",
            "invitation_time": "DateTime when the user has been invited"
    }, {}, …
]
}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	users	List<user>	M	Arrays of the User

2.3.8 Update Workflow User

Business applications can use this service API to update user data in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/{order}/user
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "giatk@mobile-id.vn",
  "user_name": "tat Khanh Gia",
  "email_notification": true,
  "mobile_number": "1234567890",
  "role": "SIGNER",
  "signing_order": 1,
  "email_language_code": "String"
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "user_email": "giatk@mobile-id.vn",
  "signing_order": 1,
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	order	Integer	M	SigningOrder of the User

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	user_email	String	O	Email of the user that you wants to update.
2	user_name	String	O	User name of the user
3	email_notification	Boolean	O	If set as true, GoPaperless Workflow will send notifications to the user via email as per the document owner and user notification settings. A value of false means no notifications will be sent to user throughout the workflow.
4	mobile_number	String	O	Mobile number of the user
5	role	String	O	Role of the participant. Possible values are here
6	signing_order	Integer	O	Order of the recipient in the workflow. This signing order is mandatory when workflow type is "CUSTOM".
7	email_language_code	String	O	Parameter to define language in email.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	user_email	String	M	Email of the user
5	signing_order	Integer	M	Signing Order of the User
6	guest_user	Boolean	M	The flag if the user is a guest
7	email_language_code	String	M	Email language code

2.3.9 Delete Workflow User

Business applications can use this service API to remove a user from the workflow.

Sample Request

```
DELETE
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/{order}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	order	Integer	M	SigningOrder of the User

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.10 Update Workflow Reminders

Business applications can use this service API to update reminders. The reminder service (e.g., SMTP) will notify the user after a configured period of time.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/reminders
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "apply_to_all": true,
  "enabled": true,
  "frequency": "String",
  "remind_after": 1,
  "keep_reminding_after": 1,
  "total_reminders": 1
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Integer	M	True, if reminder settings are to be enabled..
2	frequency	String	M	Reminder Frequency. Possible Values are DAYS | HOURS
3	remind_after	Integer	M	Required, in case of enabled property will true. The number of days after which the first reminder would be sent to workflow user.
4	keep_reminding_after	Integer	M	Required, in case of enabled property will true. The number of days after which the subsequent reminders would be sent to workflow user
5	total_reminders	Integer	M	Required, in case of enabled property will true. The number of subsequent reminders would be sent to workflow user.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.11 Get Workflow Reminders

Business applications can use this service API to get the reminder of the workflow.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/reminders
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "apply_to_all": true,
  "enabled": true,
  "remind_after": 1
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	enabled	Integer	M	True, if reminder settings are to be enabled..
5	frequency	String	M	Reminder Frequency. Possible Values are DAYS | HOURS
6	remind_after	Integer	M	Required, in case of enabled property will true. The number of days after which the first reminder would be sent to workflow user.
7	keep_reminding_after	Integer	M	Required, in case of enabled property will true. The number of days after which the subsequent reminders would be sent to workflow user
8	total_reminders	Integer	M	Required, in case of enabled property will true. The number of subsequent reminders would be sent to workflow user.

2.3.12 Get Workflow History

Business applications can use this service API to get the list of actions performed on the document

Sample Request

GET https://{domain}/{contextPath}/v1/packages/{packageId}/log
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "workflow_id": 0,
  "actions": [
    {
      "log_id": 0,
      "date_time": "String",
      "user_email": "String",
      "user_name": "String",
      "enterprise_name": "String",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	workflow_id	Integer	M	The ID of the package
5	actions	List<Action>	M	Arrays of the Actions

2.3.13 Add Workflow Comment/Message

Business applications can use this service API to add a Comment/Message to the workflow.

Sample Request

POST`https://{domain}/{contextPath}/v1/packages/{packageId}/comments`
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "send_to_owner": true,
  "order": [
    0,
    1
  ],
  "text": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	send_to_owner	Boolean	O	If document owner is included in everyone's drop down but not a part of workflow collaborators. Default is true
2	order	List<Integer>	M	If user wanna send comments to multiple recipients
3	text	String	M	Workflow Comment text

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.14 Get Workflow Comment/Message

Business applications can use this service API to get the Comment/Message of the workflow.

Sample Request

GET **https://{domain}/{contextPath}/v1/packages/{packageId}/comments**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "comments": [
    {
      "id": 0,
      "text": "String",
      "date": "String",
      "private": true,
      "read": true,
      "sender": {
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	comments	List<comment>	M	List of comment in workflow

2.3.15 Delete Workflow Comment/Message

Business applications can use this service API to delete the Comment/Message of the workflow.

Sample Request

DELETE
https://{domain}/{contextPath}/v1/packages/{packageId}/comments/{commentId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	commentId	Integer	M	ID of the comment

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.16 Get Workflow User Authentication(Document Opening)

Business Applications can use this service API to get the access security settings enabled for the package. Recipients will not be able to access document package outside the scope of this duration if the access security is enabled. Document owner can also configure authentication based security of the package for a recipient.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/{order}/authentication
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "authentication": {
    "enabled": true,
    "password": {
      "enabled": true
    },
    "sms_otp": {
      "enabled": true,
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "authentication_signing": {
    "enabled": true,
    "sms_otp": {
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "access_duration": {
    "enabled": true,
```


Http Code: 401
Content-type: application/json


```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
3	order	Integer	M	Order ID of the User

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	authentication	authentication	M	Authentication object with the details of authentication methods applied on the document for the recipient.
5	authentication_signing	authenticationSigning	M	Authentication Signing for the package

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	access_duration	accessDuration	M	Access duration object with the details of access securities for the recipient.

2.3.17 Update Workflow User Authentication(Document Opening)

Business Applications can use this service API to update the access security settings enabled for the package. Recipients will not be able to access document package outside the scope of this duration if the access security is enabled. Document owner can also configure authentication based security of the package for a recipient

Sample Request

PUT

https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/{order}/authentication

Content-Type: application/json

Authorization: "Bearer {accesstoken}"

x-language-name: en

```
{
  "apply_to_all": true,
  "authentication": {
    "enabled": true,
    "password": {
      "enabled": true
    },
    "sms_otp": {
      "enabled": true,
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "authentication_signing": {
    "enabled": true,
    "sms_otp": {
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "access_duration": {
    "enabled": true,
    "duration_by_date": {
      "enabled": true,
      "accessible": true,
      "duration": {
        "total_days": 1
      }
    }
  }
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 401
Content-type: application/json


```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
3	order	Integer	M	Order ID of the User

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	authentication	authentication	O	Authentication object with the details of authentication methods applied on the document for the recipient.
2	authentication_signing	authenticationSigning	O	Authentication Signing for the package
3	access_duration	accessDuration	O	Access duration object with the details of access securities for the recipient.
4	apply_to_all	Boolean	O	True, if the access security or authentications are to be applied on all the recipients in the workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.18 Get Workflow User Permissions

Business Applications can use this service API to get the document permissions for a User in that workflow. This API can also be used by the enterprise administartor.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/{order}/permissions
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

{
"print": true,
"download": true,
"add_text": true

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	order	Integer	M	Order ID of the User

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	print	Boolean	M	True, if printing is allowed for this recipient.
5	download	Boolean	M	True, if download is allowed.
6	add_text	Boolean	M	True, if add text annotation on the document is allowed.
7	change_recipients	Boolean	M	True, if the recipient on the current order can change other recipients in the workflow after workflow is shared.
8	add_attachment	Boolean	M	True, if attachments and merging of PDF documents is allowed.

2.3.19 Update Workflow User Permissions

Business Applications can use this service API to update the document permissions for a User in that workflow. This API can also be used by the enterprise administartor.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/{order}/permissions
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "apply_to_all": true,
  "permissions": {
    "print": true,
    "download": true,
    "add_text": true,
    "change_recipients": true,
    "add_attachment": true
  }
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
3	order	Integer	M	Order ID of the User

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	apply_to_all	Boolean	M	True, if the permissions are to be applied on all the recipients in the workflow
2	permissions	permission	M	It has all the permissions to be allowed in the workflow

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.20 Create new Category

Using this API to create new category to filter that workflow.

Sample Request

POST https://{domain}/{contextPath}/v1/category
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "category_name": "Name of the category",
  "category_icon": "Color of the icon",
  "category_parent_id": 1
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "category_id": 1
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	category_name	String	M	Name of the category
2	category_icon	String	M	Color of the category logo in HEX format. Ex: #000000, #01FF12
3	category_parent_id	Integer	O	Parent of this category

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	category_id	Integer	M	Id of the category

2.3.21 Update Category

Using this API to update the category.

Sample Request

```
PUT https://{domain}/{contextPath}/v1/category/{categoryId}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "category_name": "Name of the category",
  "category_icon": "Color of the icon",
  "category_parent_id": 1
}
```

Sample Response

Http Code: 200
Content-type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	categoryId	Integer	M	Id of the category

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	category_name	String	O	Name of the category
2	category_icon	String	O	Color of the category logo in HEX format. Ex: #000000, #01FF12

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	category_parent_id	Integer	O	Parent of this category

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.3.22 Get list of Category

Using this API to all the category belongs to the user.

Sample Request

```
GET https://{domain}/{contextPath}/v1/category
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-type: application/json


```
{
    "categories":[
            {
                    "category_id": 1,
                    "category_name": "Cate1",
                    "category_parent_id": 2,
                    "category_icon": "#000001"
            },…
    ]
}
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	categories	List<Category>	M	Array of the category

2.3.23 Add Placeholder to Workflow

Business applications can use this service API to add placeholder to a workflow in a package. A place holder is required when you do not know the identity of the intended recipient in a workflow.

Note the placeholder will be added as the last user in the workflow.Hence further work may be required to remove a current user/group, already present in the workflow.

Adding a place holder allows you to proceed and add signature and/or input fields to the document, which can then be assigned to individual users at a later stage. While XML type document preparation, only supported role types are "SIGNER", "REVIEWER" and "CARBON_COPY".

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/placeholder
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "placeholders": [
    {
      "placeholder": "PlaceHolder Name",
      "email_notification": true,
      "role": "SIGNER",
      "signing_order": 1
    }
  ]
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "placeholders": [
    {
      "placeholder": "PlaceHolder Name",
      "order": 1
    }
  ]
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	placeholders	List<addPlaceholderRequest>	M	Arrays of the Placeholder

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	placeholders	List<addPlaceholderResponse>	M	List of Placeholders

2.3.24 Update Placeholder in Workflow

Business applications can use this service API to update a placeholder in the workflow. Normally this call is useful after a template has been applied to a document and business applications wants to override the details of a specific place holder within the workflow. The ID of the workflow document is provided in the resource URL, and the workflow place

holder is identified by the order at which it is added to the workflow. While XML type document preparation, only supported role types are "SIGNER", "REVIEWER" and "CARBON_COPY".

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/workflow/{order}/placeholder
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "placeholder": "PlaceHolder Name",
  "email_notification": true,
  "role": "SIGNER",
  "signing_order": 1
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	order	Integer	M	Order id of the placeholder

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	placeholder	String	M	Placeholder name
2	email_notification	Boolean	M	If set as true, GoPaperless Workflow will send notifications to the user via email as per the document owner and user notification settings. A value of false means no notifications will be sent to user throughout the workflow.
3	role	String	M	Role of the participant. Possible values are here
4	signing_order	Integer	M	Order of the recipient in the workflow. This signing order is mandatory when workflow type is "CUSTOM".

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4 Document Preparation

2.4.1 Add Digital Signature Field

Business applications can use this service API to add a new signature field into the workflow.

Sample Request

POST

https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/signature

Content-Type: application/json

Authorization: "Bearer {accesstoken}"

x-language-name: en

x-dimension-unit: "percentage"


```
{
  "field_name": "signature 1",
  "page": 1,
  "dimension": {
    "x": 0,
    "y": 0,
    "width": 100,
    "height": 100
  },
  "visible_enabled": true,
  "level_of_assurance": [
    "ELECTRONIC_SIGNATURE",
    "cades signature"
  ],
  "verification": {
    "lock_action": "include",
    "lock_permission": "formfillingandannotation"
  }
}
```


Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	level_of_assurance	List<String>	O	Top location of the field in pixel. Level Of Assurance to be added. Possible Values are here
6	authentication_signing	FieldAuthentication	O	Field Authentication data
7	verification	verificationSignatureRequest	O	Data of the signature field to define more information (lock field, …)
8	required	Object	O	The object to show required in your application.
9	suffix	String	O	Suffix of the field.
10	remark	Object	O	Remark in your application
11	annotation_position	String	O	Position of the signature. Possible values are here
12	appearance_design	String	O	The appearance of Signature frame. Possible values are here

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.2 Update Digital Signature Field

Business applications can use this service API to update a signature field of the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/signature
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
    "page": 1,
    "field_name": "Field1",
    "renamed_as": "Field2",
    "level_of_assurance":[
    ],
    "dimension":[
            "x": 0,
            "y": 0,
            "width": 100,
            "height": 50
    ],
    "visible_enabled": true
}
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	level_of_assurance	List<String>	O	Top location of the field in pixel. Level Of Assurance to be added. Possible Values are here
7	authentication_signing	FieldAuthentication	O	Field Authentication data
8	verification	verificationSignatureRequest	O	Data of the signature field to define more information (lock field, …)
9	required	Object	O	The object to show required in your application.
10	suffix	String	O	Suffix of the field.
11	remark	Object	O	Remark in your application
12	annotation_position	String	O	Position of the signature. Possible values are here
13	appearance_design	String	O	The appearance of Signature frame. Possible values are here

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.3 Add TextBox Field

Business applications can use this service API to add a new textBox field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/text
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	color	String	O	Color of the text. Possible values are here

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	align_option	alignmentOption	O	Alignment object to show the position of the text.
8	value	String	RC(Required attribute for processing.)	Data of the field.
9	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
10	max_length	Integer	O	The number of the length in the field.
11	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
12	font	font	O	Font of the text in the field.
13	place_holder	String	O	Place holder of the field.
14	tool_tip_text	String	O	To show tool tip text of the field.
15	type	String	M	The type of the text field. Possible values are here
16	required	Object	O	The object to show required in your application.
17	suffix	String	O	Suffix of the field.
18	remark	Object	O	Remark in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
4	field_name	String	M	Name of the field

2.4.4 Update TextBox Field

Business applications can use this service API to update a textBox field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/text
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	color	String	O	Color of the text. Possible values are here
8	align_option	alignmentOption	O	Alignment object to show the position of the text.
9	value	String	RC(Required attribute for processing.)	Data of the field.
10	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
11	max_length	Integer	O	The number of the length in the field.
12	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
13	font	font	O	Font of the text in the field.
14	place_holder	String	O	Place holder of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
15	tool_tip_text	String	O	To show tool tip text of the field.
16	required	Object	O	The object to show required in your application.
17	suffix	String	O	Suffix of the field.
18	remark	Object	O	Remark in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.5 Add Initital Field

Business applications can use this service API to add a initial field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/initials
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-dimension-unit: "percentage"
x-language-name: en

```
{
  "field_name": "initial",
  "page": 1,
  "visible_enabled": true,
  "dimension": {
    "x": 0,
    "y": 0,
    "width": 100,
    "height": 100
  },
  "image": "Base64Image"
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field.
2	page	Integer	M	Page to define where the field embedded at.
3	dimension	dimension	M	Dimension of the field.
4	visible_enabled	Boolean	M	Show the field if this flag is true.
5	image	String	RC(Required attribute for processing.)	Image data of the Initial field.
6	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	replicate_all_pages	Boolean	O	True if the client wants to replicate the initial field on all pages
10	apply_to_all	Boolean	O	True if the client wants to set the image of this initial field for all initial fields in the workflow.
11	replicate_pages	List<Integer>	O	List the page numbers to which the client wants this initial field to be replicated.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.6 Update Initial Field

Business applications can use this service API to update a QR field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/initials
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-dimension-unit: "percentage"
x-language-name: en

```
{
  "page": 1,
  "field_name": "Init",
  "renamed_as": "Init2",
  "dimension": {
    "x": 0,
    "y": 0,
    "width": 100,
    "height": 100
  }
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	field_name	String	M	Name of the field.
3	page	Integer	O	Page to define where the field embedded at.
4	dimension	dimension	O	Dimension of the field.
5	visible_enabled	Boolean	O	Show the field if this flag is true.
6	image	String	O	Image data of the Initial field.
7	required	Object	O	The object to show required in your application.
8	suffix	String	O	Suffix of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
9	remark	Object	O	Remark in your application
10	replicate_all_pages	Boolean	O	True if the client wants to replicate the initial field on all pages
11	apply_to_all	Boolean	O	True if the client wants to set the image of this initial field for all initial fields in the workflow.
12	replicate_pages	List<Integer>	O	List the page numbers to which the client wants this initial field to be replicated.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.7 Assign Document Field

Business applications can use this service API to assign user to the field (QR field, Digital Signature Field, …). The field must be already be present in the document and the users must be present in the workflow. This API call allows you to assign a user by their workflow order number, to an input field on the document.

Sample Request

PUT
https://{domain}/{contextPath}/v4/packages/{packageId}/documents/{documentId}/fields/assign
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "fields_assign": [
    {
      "field_name": "FieldA",
      "radio_group_name": "Radio Group",
      "order": 1
    },
    {}
  ]
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	fields_assign	List<assignDocumentField>	M	The Arrays of fields

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.8 Delete Document Field

Business applications can use this service API to delete the document field.

Sample Request

DELETE
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields Content-Type: application/json
Authorization: Bearer {accesstoken}"
x-language-name: en

```
{
  "field_name": "field"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.9 Get Document Fields

Business applications can use this service API to get the document field.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "textbox": [
    {
      "type": "COMPANY",
      "field_name": "COMPANY3",
      "page": 1,
      "process_status": "UN_PROCESSED",
      "dimension": {
        "x": 40.0,
        "y": 10.000002,
        "width": 10.0,
        "height": 4.9999995
      },
      "visible_enabled": true,
      "required": [],
      "rotate": 0,
      "suffix": "139da7",
      "remark": [
        "1",
        "2",
        "3"
      ],
      "value": "19 Đ?ng Ti?n Đông",
      "read_only": false,
      "multiline": false,
      "max_length": 100,
```

Http Code: 400

Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	textbox	List<textFieldAttribute>	M	Object representing to the Textbox Attribute.
5	checkbox	List<checkboxFieldAttribute>	M	Object representing to the Checkbox Attribute.
6	radiobox	List<radioboxFieldAttribute>	M	Object representing to the Radiobox Attribute.
7	qr	List<qrFieldAttribute>	M	Object representing to the Qr Attribute.
8	initial	List<initialFieldAttribute>	M	Object representing to the Initial Attribute.
9	inperson	List<signatureFieldAttribute>	M	Object representing to the Inperson Attribute.
10	signature	List<signatureFieldAttribute>	M	Object representing to the Signature Attribute.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
11	combobox	List<comboBoxFieldAttribute>	M	Object representing to the ComboBox Attribute.
12	datetime	List<dateTimeFieldAttribute>	M	Object representing to the DateTime Attribute.
13	qrypto	List<qryptoFieldAttribute>	M	Object representing to the Qrypto Attribute.
14	stamp	List<imageFieldAttribute>	M	Object representing to the Stamp Attribute.
15	camera	List<cameraFieldAttribute>	M	Object representing to the Camera Attribute.
16	attachment	List<attachmentFieldAttribute>	M	Object representing to the Attachment Attribute.
17	hyperlink	List<hyperLinkFieldAttribute>	M	Object representing to the HyperLink Attribute.
18	toggle	List<toggleFieldAttribute>	M	Object representing to the Toggle Attribute.
19	stepper	List<numericFieldAttribute>	M	Object representing to the Numeric Stepper Attribute.
20	checkboxV2	List<checkboxFieldAttributeV2>	M	Object representing to the Checkbox V2 Attribute.
21	radioboxV2	List<radioboxFieldAttributeV2>	M	Object representing to the Radiobox V2 Attribute.

2.4.10 Check status of Signature Field

Business applications can use this service API to check the status of signature field is signed.

Sample Request

GET
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/signature/status
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "field_name": "signature 1"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	status	String	M	Status of the signature field. Possible values are: + SIGNED + UNSIGNED

2.4.11 Add In-person Field

Business applications can use this service API to an add in-person signature field to a document in a package.

At least one user must exist in a workflow before fields(input and signature) can be added to the document in this way.The order number corresponds to the recipient in the workflow.Therefore, this number must be equal or less than the total number of users in the workflow. The below example assigns this new signature field to the first person in the workflow.

See Add Users to Workflow for more information. Note if you have a document with a template applied, or have applied one using the APIs, then the workflow will already contain users.

In order to host an in-person meeting a GoPaperless Workflow user must be part of the workflow.They must either be added with Role "INPERSON_HOST" or "SIGNER". For the host option they do not require a signature or input field on the document, and the in-person signature field can be signed by the non-GoPaperless Workflow registered user.

Note this is a special workflow scenario whereby it is expected that the GoPaperless Workflow user and recipient would be in the same location.This type of signature is not intended for use whereby a document is shared with recipients over email link in the normal loose integration method.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/in_person_signature
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "order": 1,
  "field_name": "signature 1",
  "page": 1,
  "dimension": {
    "x": 0,
    "y": 0,
    "width": 100,
    "height": 100
  },
  "visible_enabled": true,
  "level_of_assurance": [
    "ELECTRONIC_SIGNATURE"
  ]
}
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	level_of_assurance	List<String>	O	Top location of the field in pixel. Level Of Assurance to be added. Possible Values are here
6	authentication_signing	FieldAuthentication	O	Field Authentication data
7	verification	verificationSignatureRequest	O	Data of the signature field to define more information (lock field, …)
8	required	Object	O	The object to show required in your application.
9	suffix	String	O	Suffix of the field.
10	remark	Object	O	Remark in your application
11	annotation_position	String	O	Position of the signature. Possible values are here
12	appearance_design	String	O	The appearance of Signature frame. Possible values are here
13	order	Integer	M	Order id of the participant.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.12 Update In-person Field

Business applications can use this service API to update an in-person signature field of a document in a package.

Note all of the input parameters can be changed.Where you wish to retain the current setting submit it in the call unchanged.You can therefore use the same parameters as when you added the input field, or the information as returned by Get Document Fields.The latter can be used when a template was applied or the document was created using the GUI interface.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/in_person_signature
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "order": 1,
  "field_name": "signature 1",
  "page": 1,
  "dimension": {
    "x": 0,
    "y": 0,
    "width": 100,
    "height": 100
  },
  "visible_enabled": true,
  "level_of_assurance": [
    "ELECTRONIC_SIGNATURE"
  ]
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	level_of_assurance	List<String>	O	Top location of the field in pixel. Level Of Assurance to be added. Possible Values are here
7	authentication_signing	FieldAuthentication	O	Field Authentication data
8	verification	verificationSignatureRequest	O	Data of the signature field to define more information (lock field, …)
9	required	Object	O	The object to show required in your application.
10	suffix	String	O	Suffix of the field.
11	remark	Object	O	Remark in your application
12	annotation_position	String	O	Position of the signature. Possible values are here
13	appearance_design	String	O	The appearance of Signature frame. Possible values are here
14	order	Integer	O	Order id of the participant.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.13 Add Datetime Field

Business applications can use this service API to add a new date time field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/datetime
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	color	String	O	Color of the text. Possible values are here
7	align_option	alignmentOption	O	Alignment object to show the position of the text.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	value	String	RC(Required attribute for processing.)	Data of the field.
9	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
10	max_length	Integer	O	The number of the length in the field.
11	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
12	font	font	O	Font of the text in the field.
13	place_holder	String	O	Place holder of the field.
14	tool_tip_text	String	O	To show tool tip text of the field.
15	required	Object	O	The object to show required in your application.
16	suffix	String	O	Suffix of the field.
17	remark	Object	O	Remark in your application
18	date	date	M	Data of the date

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.14 Update Datetime Field

Business applications can use this service API to update a date time field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/datetime
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	color	String	O	Color of the text. Possible values are here
8	align_option	alignmentOption	O	Alignment object to show the position of the text.
9	value	String	RC(Required attribute for processing.)	Data of the field.
10	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
11	max_length	Integer	O	The number of the length in the field.
12	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
13	font	font	O	Font of the text in the field.
14	place_holder	String	O	Place holder of the field.
15	tool_tip_text	String	O	To show tool tip text of the field.
16	required	Object	O	The object to show required in your application.
17	suffix	String	O	Suffix of the field.
18	remark	Object	O	Remark in your application
19	date	date	O	Data of the date

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.15 Add CheckBox Field

Business applications can use this service API to add a new checkbox field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/checkbox
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	color	String	O	Color of the text. Possible values are here
7	align_option	alignmentOption	O	Alignment object to show the position of the text.
8	value	String	RC(Required attribute for processing.)	Data of the field.
9	group_name	String	O	Name of the group (one group can have multiple checkbox field).
10	check_box_type	String	O	Type of the checkbox. Possible values are: + CHECK/Check/check + CIRCLE/Circle/circle + CROSS/Cross/cross + DIAMOND/Diamond/diamond + SQUARE/Square/square + STAR/Star/star.
11	checked	Boolean	O	The flag to define if the checkbox field is checked.
12	font	font	O	Font of the text in the field.
13	place_holder	String	O	Place holder of the field.
14	tool_tip_text	String	O	To show tool tip text of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
15	multiple_checked	Boolean	O	The flag to define if the field can be have more than 2 check in one group.
16	required	Object	O	The object to show required in your application.
17	suffix	String	O	Suffix of the field.
18	remark	Object	O	Remark in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.16 Update CheckBox Field

Business applications can use this service API to update a checkbox field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/checkbox
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	color	String	O	Color of the text. Possible values are here

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	align_option	alignmentOption	O	Alignment object to show the position of the text.
9	value	String	RC(Required attribute for processing.)	Data of the field.
10	group_name	String	O	Name of the group (one group can have multiple checkbox field).
11	check_box_type	String	O	Type of the checkbox. Possible values are: + CHECK/Check/check + CIRCLE/Circle/circle + CROSS/Cross/cross + DIAMOND/Diamond/diamond + SQUARE/Square/square + STAR/Star/star.
12	checked	Boolean	O	The flag to define if the checkbox field is checked.
13	font	font	O	Font of the text in the field.
14	place_holder	String	O	Place holder of the field.
15	tool_tip_text	String	O	To show tool tip text of the field.
16	multiple_checked	Boolean	O	The flag to define if the field can be have more than 2 check in one group.
17	required	Object	O	The object to show required in your application.
18	suffix	String	O	Suffix of the field.
19	remark	Object	O	Remark in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.

2.4.17 Add RadioBox Field

Business applications can use this service API to add a new radiobox field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/radiobox
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	color	String	O	Color of the text. Possible values are here
7	align_option	alignmentOption	O	Alignment object to show the position of the text.
8	value	String	RC(Required attribute for processing.)	Data of the field.
9	radio_group_name	String	O	Name of the group (one group can have multiple radiobox field).
10	check_box_type	String	O	Type of the radiobox. Possible values are: + CHECK/Check/check + CIRCLE/Circle/circle + CROSS/Cross/cross + DIAMOND/Diamond/diamond + SQUARE/Square/square + STAR/Star/star.
11	checked	Boolean	O	The flag to define if the radiobox field is checked.
12	font	font	O	Font of the text in the field.
13	place_holder	String	O	Place holder of the field.
14	tool_tip_text	String	O	To show tool tip text of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
15	multiple_checked	Boolean	O	The flag to define if the field can be have more than 2 check in one group.
16	required	Object	O	The object to show required in your application.
17	suffix	String	O	Suffix of the field.
18	remark	Object	O	Remark in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.18 Update RadioBox Field

Business applications can use this service API to update a radiobox field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/radiobox
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	color	String	O	Color of the text. Possible values are here

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	align_option	alignmentOption	O	Alignment object to show the position of the text.
9	value	String	RC(Required attribute for processing.)	Data of the field.
10	radio_group_name	String	O	Name of the group (one group can have multiple radiobox field).
11	check_box_type	String	O	Type of the radiobox. Possible values are: + CHECK/Check/check + CIRCLE/Circle/circle + CROSS/Cross/cross + DIAMOND/Diamond/diamond + SQUARE/Square/square + STAR/Star/star.
12	checked	Boolean	O	The flag to define if the radiobox field is checked.
13	font	font	O	Font of the text in the field.
14	place_holder	String	O	Place holder of the field.
15	tool_tip_text	String	O	To show tool tip text of the field.
16	multiple_checked	Boolean	O	The flag to define if the field can be have more than 2 check in one group.
17	required	Object	O	The object to show required in your application.
18	suffix	String	O	Suffix of the field.
19	remark	Object	O	Remark in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.

2.4.19 Add QR Field

Business applications can use this service API to add a new QR field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/qrcode
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	is_transparent	Boolean	O	The flag to define if the QR Code background is transparent.
10	image_qr	String	RC(Required attribute for processing.)	Image data of the QR Code (when you have and qr image, just send it with this parameter).
11	value	String	RC(Required attribute for processing.)	The data of QR Code. Note: If you send data in String, the GoPaperless Workflow Service will generate QRCode based on your data.
12	allow_unauthenticated_workflow_view	Boolean	O	If this flag is enabled, the GoPaperless Workflow will generate a UUID. This UUID will then be combined with a custom URL (configured in Enterprise Settings or provided as a

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				parameter) and embedded within the QR code.
13	custom_url	String	O	This custom URL provides an alternative for the client to define the target URL, instead of using the URL configured within the Enterprise Settings.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.20 Update QR Field

Business applications can use this service API to update a QR field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/qrcode
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	is_transparent	Boolean	O	The flag to define if the QR Code background is transparent.
11	image_qr	String	RC(Required attribute for processing.)	Image data of the QR Code (when you have and qr image, just send it with this parameter).

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.21 Add Qrypto Field

Business applications can use this service API to add a new Qrypto field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/qrypto
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	remark	Object	O	Remark in your application
9	is_transparent	Boolean	O	The flag to define if the QR Code background is transparent.
10	items	List<items>	RC(Required attribute for processing.)	Data of the Qrypto Code.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.22 Update Qrypto Field

Business applications can use this service API to update a Qrypto field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/qryto
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	is_transparent	Boolean	O	The flag to define if the QR Code background is transparent.
11	items	items	RC(Required attribute for processing.)	Data of the Qrypto Code.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.23 Add ComboBox Field

Business applications can use this service API to add a new combo box field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/combobox
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	remark	Object	O	Remark in your application
9	color	String	O	Color of the text. Possible values are here
10	align_option	alignmentOption	O	Alignment object to show the position of the text.
11	value	String	RC(Required attribute for processing.)	Data of the field.
12	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
13	max_length	Integer	O	The number of the length in the field.
14	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
15	font	font	O	Font of the text in the field.
16	place_holder	String	O	Place holder of the field.
17	tool_tip_text	String	O	To show tool tip text of the field.
18	combo_item	chooseItems	RC(Required attribute for processing.)	Data of the combobox

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.24 Update ComboBox Field

Business applications can use this service API to update a combo box field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/combobox
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	color	String	O	Color of the text. Possible values are here
11	align_option	alignmentOption	O	Alignment object to show the position of the text.
12	value	String	RC(Required attribute for processing.)	Data of the field.
13	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
14	max_length	Integer	O	The number of the length in the field.
15	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
16	font	font	O	Font of the text in the field.
17	place_holder	String	O	Place holder of the field.
18	tool_tip_text	String	O	To show tool tip text of the field.
19	combo_item	chooseItems	RC(Required attribute for processing.)	Data of the combobox

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.25 Add Toggle Field

Business applications can use this service API to add a new toggle field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/toggle
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	color	String	O	Color of the text. Possible values are here
10	align_option	alignmentOption	O	Alignment object to show the position of the text.
11	value	String	RC(Required attribute for processing.)	Data of the field.
12	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
13	max_length	Integer	O	The number of the length in the field.
14	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
15	font	font	O	Font of the text in the field.
16	place_holder	String	O	Place holder of the field.
17	tool_tip_text	String	O	To show tool tip text of the field.
18	toggle_item	chooseItems	RC(Required attribute for processing.)	Data of the toggle

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.26 Update Toggle Field

Business applications can use this service API to update a toggle field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/toggle
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	color	String	O	Color of the text. Possible values are here
11	align_option	alignmentOption	O	Alignment object to show the position of the text.
12	value	String	RC(Required attribute for processing.)	Data of the field.
13	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
14	max_length	Integer	O	The number of the length in the field.
15	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
16	font	font	O	Font of the text in the field.
17	place_holder	String	O	Place holder of the field.
18	tool_tip_text	String	O	To show tool tip text of the field.
19	toggle_item	chooseItems	RC(Required attribute for processing.)	Data of the toggle

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.

2.4.27 Add Numeric Stepper Field

Business applications can use this service API to add a new numeric stepper field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/numeric_stepper
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	color	String	O	Color of the text. Possible values are here
10	align_option	alignmentOption	O	Alignment object to show the position of the text.
11	value	String	RC(Required attribute for processing.)	Data of the field.
12	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
13	max_length	Integer	O	The number of the length in the field.
14	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
15	font	font	O	Font of the text in the field.
16	place_holder	String	O	Place holder of the field.
17	tool_tip_text	String	O	To show tool tip text of the field.
18	numeric_stepper_items	numericItems	RC(Required attribute for processing.)	Data of the numeric stepper

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.28 Update Numeric Stepper Field

Business applications can use this service API to update a numeric stepper field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/numeric_stepper
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	color	String	O	Color of the text. Possible values are here
11	align_option	alignmentOption	O	Alignment object to show the position of the text.
12	value	String	RC(Required attribute for processing.)	Data of the field.
13	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
14	max_length	Integer	O	The number of the length in the field.
15	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
16	font	font	O	Font of the text in the field.
17	place_holder	String	O	Place holder of the field.
18	tool_tip_text	String	O	To show tool tip text of the field.
18	numeric_stepper_items	numericItems	RC(Required attribute for processing.)	Data of the numeric stepper

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.

2.4.29 Add Hyperlink Field

Business applications can use this service API to add a new hyperlink field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/hyperlink
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	color	String	O	Color of the text. Possible values are here
10	align_option	alignmentOption	O	Alignment object to show the position of the text.
11	value	String	RC(Required attribute for processing.)	Data of the field.
12	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
13	max_length	Integer	O	The number of the length in the field.
14	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
15	font	font	O	Font of the text in the field.
16	place_holder	String	O	Place holder of the field.
17	tool_tip_text	String	O	To show tool tip text of the field.
18	address	String	RC(Required attribute for processing.)	Data of the hyperlink field

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.30 Update Hyperlink Field

Business applications can use this service API to update a hyperlink field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/hyperlink
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	color	String	O	Color of the text. Possible values are here
11	align_option	alignmentOption	O	Alignment object to show the position of the text.
12	value	String	RC(Required attribute for processing.)	Data of the field.
13	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
14	max_length	Integer	O	The number of the length in the field.
15	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
16	font	font	O	Font of the text in the field.
17	place_holder	String	O	Place holder of the field.
18	tool_tip_text	String	O	To show tool tip text of the field.
18	address	String	RC(Required attribute for processing.)	Data of the hyperlink field

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.

2.4.31 Add Stamp Field

Business applications can use this service API to add a new stamp field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/stamp
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	place_holder	String	O	Place holder of the field.
10	tool_tip_text	String	O	To show tool tip text of the field.
11	image	String	RC(Required attribute for processing.)	Data of the image in base64 format

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.32 Update Stamp Field

Business applications can use this service API to update a stamp field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/stamp
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	required	Object	O	The object to show required in your application.
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	place_holder	String	O	Place holder of the field.
11	tool_tip_text	String	O	To show tool tip text of the field.
12	image	String	RC(Required attribute for processing.)	Data of the image in base64 format

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.33 Add Camera Field

Business applications can use this service API to add a new camera field into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/camera
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	remark	Object	O	Remark in your application
9	place_holder	String	O	Place holder of the field.
10	tool_tip_text	String	O	To show tool tip text of the field.
11	camera	image	RC(Required attribute for processing.)	Date of the camera field

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.34 Update Camera Field

Business applications can use this service API to update a camera field in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/camera
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	place_holder	String	O	Place holder of the field.
11	tool_tip_text	String	O	To show tool tip text of the field.
12	camera	image	RC(Required attribute for processing.)	Date of the camera field

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.35 Add Attachment Field

Business applications can use this service API to add a new attachment into the workflow.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/attachment
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	remark	Object	O	Remark in your application
9	place_holder	String	O	Place holder of the field.
10	tool_tip_text	String	O	To show tool tip text of the field.
11	file	file	RC(Required attribute for processing.)	Date of the attachment field
12	show_icon_enabled	Boolean	O	The flag to define if the icon next to camera is show in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.36 Update Attachment Field

Business applications can use this service API to update an attachment in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/attachment
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	O	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	O	Location of the field
5	visible_enabled	Boolean	O	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	place_holder	String	O	Place holder of the field.
11	tool_tip_text	String	O	To show tool tip text of the field.
12	file	file	RC(Required attribute for processing.)	Date of the attachment field
13	show_icon_enabled	Boolean	O	The flag to define if the icon next to camera is show in your application

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.37 Add CheckBox Field Version 2

Business applications can use this service API to add a new checkbox field version 2 into the workflow.
Note: Users cannot interact with this field while the file is being processed. This type of field will render an image instead of a FormField.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/checkboxV2
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"


```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```


Sample Response

Http Code: 200
Content-Type: application/json


```
{
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	remark	Object	O	Remark in your application
9	place_holder	String	O	Place holder of the field.
10	tool_tip_text	String	O	To show tool tip text of the field.
11	checked	Boolean	M	True if the field is selected.
12	text_next_to	String	O	Text next to the checkbox
13	font	font	O	Font of the text in the field.
14	group_name	String	O	Name of the group (one group can have multiple checkbox field).
15	align_option	alignmentOption	O	Alignment object to show the position of the text.
16	multiple_checked	Boolean	O	The flag to define if the group in checkbox field can have multiple checker.
17	checkbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the "checked" is "true"
18	uncheckbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the "checked" is "false"

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.38 Update CheckBox Field Version 2

Business applications can use this service API to update an checkbox in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/checkboxV2
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	M	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	M	Location of the field
5	visible_enabled	Boolean	M	True if the field is visible
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	required	Object	O	The object to show required in your application.
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	place_holder	String	O	Place holder of the field.
11	tool_tip_text	String	O	To show tool tip text of the field.
12	checked	Boolean	M	True if the field is selected.
13	text_next_to	String	O	Text next to the checkbox
14	font	font	O	Font of the text in the field.
15	group_name	String	O	Name of the group (one group can have multiple checkbox field).
16	align_option	alignmentOption	O	Alignment object to show the position of the text.
17	multiple_checked	Boolean	O	The flag to define if the group in checkbox field can have multiple checker.
18	checkbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the "checked" is "true"
19	uncheckbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the "checked" is "false"

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.4.39 Add RadioBox Field Version 2

Business applications can use this service API to add a new radiobox field version 2 into the workflow.
Note: Users cannot interact with this field while the file is being processed. This type of field will render an image instead of a FormField.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/radioboxV2
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "DateTime 1",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	page	Integer	M	Page number at which the field is about to be created.
2	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
3	dimension	dimension	M	Location of the field
4	visible_enabled	Boolean	M	True if the field is visible
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	place_holder	String	O	Place holder of the field.
10	tool_tip_text	String	O	To show tool tip text of the field.
11	checked	Boolean	M	True if the field is selected.
12	text_next_to	String	O	Text next to the checkbox
13	font	font	O	Font of the text in the field.
14	group_name	String	O	Name of the group (one group can have multiple checkbox field).
15	align_option	alignmentOption	O	Alignment object to show the position of the text.
16	multiple_checked	Boolean	O	The flag to define if the group in checkbox field can have multiple checker.
17	checkbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the "checked" is "true"
18	uncheckbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the "checked" is "false"

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	field_name	String	M	Name of the field

2.4.40 Update RadioBox Field Version 2

Business applications can use this service API to update an radiobox in the workflow.

Sample Request

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields/radioboxV2
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-dimension-unit: "percentage"

```
{
  "field_name": "text box 1",
  "renamed_as": "text2",
  "page": 1,
  "type": "TEXTBOX",
  "value": "String",
  "max_length": 0,
  "format": "String",
  "format_type": "Number",
  "multiline": true,
  "font": {
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-dimension-unit	String	O	The unit of the dimension. Possible values are: + percentage + point (default)
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	renamed_as	String	O	If this parameter is not null => the field_name will be updated
2	page	Integer	M	Page number at which the field is about to be created.
3	field_name	String	M	Name of the field that is to be added. If not provided, system will assign an unique auto generated name to the field.
4	dimension	dimension	M	Location of the field
5	visible_enabled	Boolean	M	True if the field is visible

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
7	required	Object	O	The object to show required in your application.
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	place_holder	String	O	Place holder of the field.
11	tool_tip_text	String	O	To show tool tip text of the field.
12	checked	Boolean	M	True if the field is selected.
13	text_next_to	String	O	Text next to the checkbox
14	font	font	O	Font of the text in the field.
15	group_name	String	O	Name of the group (one group can have multiple checkbox field).
16	align_option	alignmentOption	O	Alignment object to show the position of the text.
17	multiple_checked	Boolean	O	The flag to define if the group in checkbox field can have multiple checker.
18	checkbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the “checked” is “true”
19	uncheckbox_frame	frame	RC(Required attribute for processing.)	Data of the checkbox frame when the “checked” is “false”

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.

2.5 Document Processing

2.5.1 Approve Document

Business application can use this service API to approve the document before sign it.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/{packageId}/approve
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-password: "String"
x-otp: "Otp"
x-language-name: en

```
{
  "reason": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-password	String	O	Password of the workflow
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
3	x-otp	String	O	OTP of the workflow
4	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	reason	String	M	The reason for approving a package

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.5.2 Decline Document

Business application can use this service API to decline the document.
Note that: the user must send the reason.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/{packageId}/decline
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "reason": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	reason	String	M	The reason for decline a package

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.5.3 Sign with GoPaperless Workflow

2.5.3.1 Sign Document

Business applications can use this service API to sign the document.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/sign
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-otp: "Otp"
x-language-name: en

```
{
  "field_name": "String",
  "hand_signature_image": "Base64",
  "signing_reason": "String",
  "signing_location": "String",
  "contact_information": "String",
  "appearance_design": "String",
  "signing_capacity": "String",
  "skip_verification": false,
  "signing_server": "String",
  "connector_name": "String",
  "authentication": {
    "mechanism": "String",
    "password": "String",
    "token": "String",
    "user_identifier": "String"
  },
  "time_zone": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-otp	String	O	OTP value
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Unique identifier of the signature field in the document.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	hand_signature_image	String	O	Base64 encoded string image of the visible signature appearance
3	signing_reason	String	O	Reason of signing provided by the recipient.
4	signing_location	Boolean	O	Locale of the signer provided by the recipient..
5	contact_information	String	O	Contact information of the signer provided by the recipient..
6	appearance_design	String	O	Name of the signature appearance provided by user .
7	signing_capacity	String	O	Name of certification profile/signing capacity using which the document is to be signed.
8	skip_verification	Boolean	O	No signature verification returns in response body when it is set as true. Default value for this parameter set to false.
9	signing_server	String	RC (When connector name is have the same name)	Name of signing server using which the document is to be signed.
10	authentication	Authentication	O	it contains authentication releated options
11	connector_name	String	M	Name of the connector (signing Server) to call and sign.
12	time_zone	String	O	Timezone in IANA format.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.5.3.2 Sign Eseal

Business applications can use this service API to sign eseal. Only the owner is an enterprise account can sign Eseal.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/sign_eseal
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-otp: "Otp"
x-language-name: en

```
{
  "field_name": "String",
  "skip_verification": false,
  "time_zone": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	x-otp	String	O	OTP value
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Unique identifier of the signature field in the document.
2	skip_verification	Boolean	O	No signature verification returns in response body when it is set as true. Default value for this parameter set to false.
3	time_zone	String	O	Timezone in IANA format.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.5.4 Two Step Signing

2.5.4.1 Get Document Hash

Business applications can use this service API to get the hash of signature Field in the document.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/hash
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "field_name": "String",
  "signing_order": 1,
  "hand_signature_image": "Base64",
  "signing_reason": "String",
  "signing_location": "String",
  "contact_information": "String",
  "signing_algo": "String",
  "hashing_algo": "String",
  "certificate_chain": [
    "Signer"
  ],
  "time_zone": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "hash": "String",
  "state": "String",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Field name to determine which field will be processed
2	hand_signature_image	String	O	Base64 Encoded string image of the visible signature appearance
3	signing_algo	String	M	The algorithm to be signed. Possible values are here
4	contact_information	String	O	The contact name of the signature
5	hashing_algo	String	M	The algorithm to hash data to be sign. Possible values are here
6	signing_reason	String	O	The reason of the signature
7	signing_location	String	O	The location of the signature
8	skip_verification	Boolean	O	If true, show the verification of signature when processed successfully

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
9	certificate_chain	List<String>	M	The array list of certificate chain. Format like this: [Certificate_User, //Must contain Certificate_CA1, //Option Certificate_RootCA //Option]
10	signing_order	Integer	M	Signing Order of the User
11	time_zone	String	O	Timezone in IANA format.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	hash	String	M	Data of the hash
5	state	String	M	Unique alphanumeric value per transaction
6	hashing_algo	String	M	Oid of hashing algorithm using which document hash is computed

2.5.4.2 Embed Signature

Business applications can use this service API to embed signature in PDF/XML document.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/embed_signature
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
    "field_name": "String",
"signature_value": "string",
"skip_verification": true,
"hash_value": "HashData",
"certificate_chain": [chain]
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Field name
2	signature_value	String	M	Data of the signature. Value after signed in any platform
3	certificate_chain	List<String>	M	The array list of certificate chain. Format like this: [Certificate_User, //Must contain Certificate_CA1, //Option Certificate_RootCA //Option]
4	hash_value	String	M	Hash of the field.
5	skip_verification	Boolean	O	The flag to show the verification of document after sign.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.5.5 Fill Form Fields

Business Applications can use this service API to fill in the form field in the document.

Sample Request

MOBILE-ID TECHNOLOGIES AND SERVICES JOINT STOCK COMPANY
Level 9, Thuy Loi 4 Building, 286-288 Nguyen Xi Street, Ward 13, Binh Thanh District, Ho Chi Minh City
Tel: +84 28 3622 2982- Fax: +84 28 3622 2983 – Hotline: 1900 6884
info@mobile-id.vn – https://www.mobile-id.vn

PUT
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/fields
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
    "text": [
            {
                    "field_name": "textbox1",
                    "value": "Name one two three"
            },{}
    ],
    "radio": [
            {
                    "field_name": "radio1",
                    "value": true
            },{}
    ],
    "checkbox": [
{
  "field_name": "checkbox1",
  "value": true
}
    ],
    "stamp": [
                    "field_name": "Seal1",
                    "value": "String"
    ],
    "camera": [
{
  "field_name": "Camera1",
  "value": "String"
}
    ],
"attachment": [
{
  "field_name": "attachment1",
  "file_name": "attachment.png",
  "value": "String"
}
    ],
"hyperlink": [
{
```

```
"toggle": [
{
  "field_name": "DateTime",
  "value": "String"
}
        ],
    "numeric_stepper": [
{
  "field_name": "DateTime",
  "value": "String"
}
        ],
    "checkboxV2":[
{
  "field_name": "{{checkboxV2}}"
}
       ],
    "radioboxV2":[
{
  "field_name": "{{radioboxV2}}"
}
       ]
}
```


Sample Response

Http Code: 200
Content-type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.
3	x-idempotency-skip-error	Boolean	O	Allows skipping error responses when an idempotent operation is requested but the desired resource or state already exists or has been previously processed. Instead of an error, the API will return a successful response (e.g., 200 OK or 204 No Content) without performing any changes.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	text	List<BaseFormFillRequest>	O	Data of the text fields
2	radio	List<BaseFormFillRequest>	O	Data of the radio fields
3	checkbox	List<BaseFormFillRequest>	O	Data of the checkbox fields
4	stamp	List<BaseFormFillRequest>	O	Data of the stamp fields
5	camera	List<BaseFormFillRequest>	O	Data of the camera fields

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	attachment	List<BaseFormFillRequest>	O	Data of the attachment fields
7	hyperlink	List<BaseFormFillRequest>	O	Data of the hyperlink fields
8	date	List<BaseFormFillRequest>	O	Data of the date fields
9	combo	List<BaseFormFillRequest>	O	Data of the combo fields
10	toggle	List<BaseFormFillRequest>	O	Data of the toggle fields
11	numeric_stepper	List<BaseFormFillRequest>	O	Data of the numeric stepper fields
12	checkboxV2	List<BaseFormFillRequest>	O	Data of the checkboxV2 fields
13	radioboxV2	List<BaseFormFillRequest>	O	Data of the radioboxV2 fields

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.5.6 Fill Initials

Business Applications can use this service API to fill Initials in the document.

Sample Request

POST
https://{domain}/{contextPath}/v1/packages/{packageId}/documents/{documentId}/initial
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "field_name": "Field 1",
  "image": "String",
  "apply_to_all": false
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field
2	image	String	M	Base64 Image used for the filling of the initials
3	apply_to_all	Boolean	O	True if all initials are to be filled.
4	initial_pages	List<Integer>	O	Arrays of the pages that the client would like to stamp in.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.5.7 Submit Document

One of the GoPaperless Workflow roles is called "Editor". This allows a recipient to edit input fields on a document, but does not require a signature. Once completed the recipient submits their changes. The button used in the GUI is called "Submit".

This is the equivalent operation for an editor to submit their changes via an API call.

Sample Request

POST https://{domain}/{contextPath}/v1/packages/{packageId}/submit
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-password: "password"
x-otp: "otp"
{}

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-password	String	O	Password of the workflow
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
3	x-otp	String	O	OTP of the workflow
4	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.6 Connector

2.6.1 Get List USB-Token Connector

Business application can use this service API to get USB-Token that need to perform Signing USB Token (2 step signing).

Sample Request

GET https://{domain}/{contextPath}/v1/connectors/usbtoken
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json


```
[
{
        "connector_name": "USB_TOKEN_VNPT-CA",
        "provider": "USB_TOKEN_SIGNING",
    "logo": "Base64Logo",
        "data": "InformationData",
    "status": "ENABLED"
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-search-server	String	O	Define the name of to find in system.
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4		List<connector>	M	Array of USB Connector

2.6.2 Get List Smart-ID Connector

Business application can use this service API to get Smart-ID that need to perform Signing.

Sample Request

GET https://{domain}/{contextPath}/v1/connectors/smartid
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json


```
[
{
        "connector_name": "USB_TOKEN_VNPT-CA",
        "provider": "USB_TOKEN_SIGNING",
        "logo": "Base64Logo",
        "status": "ENABLED"
    },
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-search-server	String	O	Define the name of to find in system.
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4		List<connector>	M	Array of SmartID Connector

2.6.3 Get List Internal Signing Service Connector (ISS)

Business application can use this service API to get ISS that need to perform Signing.

Sample Request

GET https://{domain}/{contextPath}/v1/connectors/iss
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
[
{
        "connector_name": "USB_TOKEN_VNPT-CA",
        "provider": "USB_TOKEN_SIGNING",
        "logo": "Base64Logo",
        "status": "ENABLED"
    },
```

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-search-server	String	O	Define the name of to find in system.
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4		List<connector>	M	Array of ISS Connector

2.6.4 Get Certificate Profile of Connector

Business application can use this service API to get all Certificate Profile for Connector.

Sample Request

GET https://{domain}/{contextPath}/v1/connectors/certificate-profiles
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-connector-name: ""
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
    "certificate_profiles":[
            {
                    "level_of_assurance": "",
                    "certificate_profile": {
                            "name": "",
                            "remark": ""
},
                    "issuing_provider": {
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-search-server	String	O	Define the name of to find in system.
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	certificate_profiles	List<GetCertificateProfilesResponse>	M	Array of Certificate profile

2.7 RSSP Processing

2.7.1 Get RSSP Information

Business application can use this service API to get RSSP that need to perform Signing.

Sample Request

```
GET https://{domain}/{contextPath}/v1/system/signing/servers
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-search-server: "Name of Signing Server"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
    "signing_servers":[
            {
                "signing_server": "String",
                "connector_name": "RSSP",
                "host_url": "String",
                "client_id": "String",
                "authentication_required": true,
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-search-server	String	M	Define the name to find in the system. Note: this is the name of the connector that is gotten from these APIs in "Connector"
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	signing_servers	List<RSSPService>	M	Array of Signing Server

2.7.2 Get Filtered Credential List

Business application can use this service API to get credential list from RSSP (remote signing service provider).

Sample Request

POST https://{domain}/{contextPath}/v1/csc/credentials/list
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "signing_server": "NameOfSigningServer",
  "connector_name": "NameOfConnector",
  "document_type": "USERNAME",
  "value": "07920001****"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "credentialIDs": [
    {
      "credential_id": "Id",
```

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-search-server	String	O	Define the name of to find in system.
2	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
3	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	signing_server	String	RC(When the connector_name have the same name)	Name of the RSSP Provider. This parameter will be contained when this API returns an error type "Too many Relying Parties have the same name".
2	document_type	String	M	Type of the document. Possible values are here
3	value	String	M	Data of the user. Example: + Usertype = "USERNAME" => user_type = "giatk" + Usertype = "CCCD" => user_type = "079200011***"
4	connector_name	String	M	Name of the Connector that returned in API "Get RSSP Information"

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	credentialIDs	List<GetListResponse>	M	Array of Signing Server

2.7.3 Sign Document via RSSP Directly

Business applications can use this service API to sign PDF/XML.
This API will generate D2S (Data to be Signed), get Signature from RSSP directly and then perform signature embedding.

Sample Request

POST
https://{domain}/{contextPath}/v1/csc/packages/{packageId}/documents/{documentId}/sign_rssp
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-client-ip: "192.168.0.0"
x-os-name: "Windows 10"
x-browser-name: "Browser name"

```
{
  "connector_name": "NameOfConnector",
  "field_name": "",
  "signing_server": "",
  "credential_id": "",
  "skip_verification": "",
  "hand_signature_image": "",
  "signing_reason": "",
  "signing_location": "",
  "contact_information": "",
  "signing_algo": "String",
  "hashing_algo": "String",
  "appearance_design": "String",
  "time_zone": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-client-ip	String	O	The IP address of the client (this parameter will be displayed in the TSE application).
3	x-os-name	String	O	The operating system of the client (this parameter will be displayed in the TSE application).
4	x-browser-name	String	O	The browser name of the client (this parameter will be displayed in the TSE application).
5	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	documentId	Integer	M	The document ID to be used to share, download or append it into workflow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Field name to determine which field will be processed
2	hand_signature_image	String	O	Base64 Encoded string image of the visible signature appearance
3	signing_algo	String	M	The algorithm to be signed. Possible values are here
4	signer_contact	String	O	The contact name of the signature

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
5	hashing_algo	String	M	The algorithm to hash data to be sign. Possible values are here
6	signing_reason	String	O	The reason of the signature
7	signing_location	String	O	The location of the signature
8	skip_verification	Boolean	O	If true, show the verification of signature when processed successfully
9	credential_id	String	M	Credential id of the signer. Get it from "Get Filtered Credential List"
10	appearance_design	String	O	The appearance of Signature frame. Possible values are here
11	connector_name	String	M	Name of the Connector that returned in API "Get RSSP Information"
12	time_zone	String	O	Timezone in IANA format.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	validity_period	String	RC(When the credential's mode is TSE)	The validity period of a TSE defines the timeframe during which the device is authorized to operate and generate valid fiscal data.
5	vc_code	String	RC(When the credential's mode is TSE)	The unique, randomly generated string that is used to identify and track a specific transaction.

2.7.4 RSSP Credential Authorization

Business applications can use this service API for credentials authorization from RSSP (remote signing service provider)

Sample Request

POST https://{domain}/{contextPath}/v1/csc/credentials/authorization
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "credential_id": "String",
  "package_id": 0,
  "document_id": 0,
  "field_name": "String",
  "otp": "String",
  "pin": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 401
Content-type: application/json

```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	credential_id	String	M	The unique identifier associated to the credential.
2	otp	String	O/M	The OTP provided by the user. It SHALL be used only when authMode from credentials/info method, is "explicit" and OTP/presence is not "false".
3	pin	String	O/M	The PIN provided by the user. It SHALL be used only when authMode from credentials/info is "explicit" and PIN/presence is not "false".
4	package_id	Integer	M	The identifier of the package with which the client interacts.
5	document_id	Integer	M	The id of document that client interact with.
6	field_name	String	M	Name of the field that client interact with

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.7.5 Get Signing Status (TSE MID)

Business applications can use this service API to get the status of Signing when the credential mode "TSE".

Sample Request

POST https://{domain}/{contextPath}/v1/csc/packages/sign/status
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "transaction_id": ""
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	transaction_id	String	M	TransactionID which returned when called "Sign Document via RSSP Directly" and that credentialID's mode is "TSE"

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	status	String	M	Status of the signing process

2.7.6 Get Credentials Info

Business applications can use this service API to get credential info from RSSP.

Sample Request

```
POST https://{domain}/{contextPath}/v1/csc/credentials/info
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "connector_name": "Connector Name",
  "signing_server": "Signing Server",
  "credential_id": "Credential ID",
  "certificate_encoded": "Certificate Encoded"
}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
    "cert": {
            "status": "String",
            "certificates": ["String"],
            "issuer_dn": "String",
            "serial_number": "String",
            "subject_dn": "String",
            "valid_from": "String",
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	connector_name	String	M	Connector name that credential_id belongs to

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	signing_server	String	RC(When the connector_name is have the same name in DB)	Signing server that contains connector
3	credential_id	String	RC(When signing via RSSP,… except USB-Token)	Credential ID
4	certificate_encoded	String	RC(When signing via USB-Token => Get from USB)	Certificate encoded. When provided this parameter. System will be analysied this certificate based on this parameter.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	cert	certificateInfo	M	Information about certificate
5	auth_mode	String	M	Auth mode of the certificate
6	SCAL	Integer	M	SCAL of the certificate (data from RSSP)
7	multisign	Integer	M	Number of signature

2.7.7 Send OTP via RSSP

Business applications can use this service API to send otp via RSSP.

Sample Request

```
POST https://{domain}/{contextPath}/v1/csc/credentials/send-otp
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "transaction_id": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 401
Content-type: application/json


```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	transaction_id	String	M	TransactionID which returned when called "Sign Document via RSSP Directly" and that credentialID's mode is "TSE"

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.8 Register Certificate Processing

2.8.1 Get Information of Citizen card

Business applications can use this service API to register new Certificate via RSSP.

Sample Request

POST https://{domain}/{contextPath}/v1/csc/credentials/document/details
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "document_type": "",
  "value": ""
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "personal_informations": {
    "personal_number": "079200011188",
    "full_name": "Tất Khánh Gia",
    "birth_date": "07/09/2000",
    "gender": "Nam",
    "nationality": "Việt Nam",
    "ethnic": "Hoa",
    "religion": "Không",
    "place_of_origin": "China",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	document_type	String	M	Document Type. Possible values are here
2	value	String	M	Value of the Document

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	personal_informations	personalInformation	M	All information about user

2.8.2 Register Certificate via RSSP

Business applications can use this service API to register new Certificate via RSSP.

Sample Request

POST https://{domain}/{contextPath}/v1/csc/credentials/register
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "level_of_assurance": "",
  "document_type": "",
  "value": "",
  "face_image": ""
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "session_id": "",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>"

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	connector_name	String	O	Connector name
2	signing_server	String	RC(When the connector_name is have the same name in DB)	Signing server that contains connector
3	level_of_assurance	String	M	Level of Assurance that user wants to created. Possible values are: + ELECTRONIC_SEAL + QUALIFIED_ELECTRONIC_SEAL + ADVANCED_ELECTRONIC + QUALIFIED_ELECTRONIC_SIGNATURE
4	document_type	String	M	Document Type. Possible values are here
5	value	String	M	Value of the Document
6	face_image	String	M	Facial Image of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	session_id	String	M	The unique string that identifies the process flow of registering a certificate
5	is_email_verified	Boolean	M	When this flag is true => Call Sent OTP to Register Certificate with user email to verified.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	is_mobile_verified	Boolean	M	When this flag is true => Call Sent OTP to Register Certificate with user mobile number to verified.

2.8.3 Send OTP to Certificate Registration

Business applications can use this service API to send OTP to your SMS or Email.

Sample Request

POST https://{domain}/{contextPath}/v1/csc/credentials/{session_id}/send-otp
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "email": "",
  "mobile": ""
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{}
```

Http Code: 401
Content-type: application/json

```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	session_id	String	M	Session id of the process flow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	otp	String	M	OTP that has been sent to your SMS
2	user_email	String	M	The user email to which the system will send the next OTP.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.8.4 Verify OTP for Certificate Registration

Business applications can use this service API to verify your OTP to register certificate.

Sample Request

POST https://{domain}/{contextPath}/v1/csc/credentials/{session_id}/verify
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "otp": ""
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{}
```

Http Code: 401
Content-type: application/json

```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	session_id	String	M	Session id of the process flow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	otp	String	M	OTP that has been sent to your SMS
2	user_email	String	M	The user email to which the system will send the next OTP.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.8.5 Get List Tax Codes

Business applications can use this service API to get list Tax Codes (when your level of assurance is electronic seal or qualified electronic seal).

Sample Request

GET https://{domain}/{contextPath}/v1/csc/credentials/{session_id}/taxcode
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
    "tax_codes":[
            {
                ""
            }
```

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	session_id	String	M	Session id of the process flow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	otp	String	M	OTP that has been sent to your SMS
2	user_email	String	M	The user email to which the system will send the next OTP.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.8.6 Finish Register Certificate

Business applications can use this service API to finish your flow to register new Certificate.

Sample Request

POST https://{domain}/{contextPath}/v1/csc/credentials/{session_id}/finish
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "certificate_profile": "",
  "tax_code": ""
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	session_id	String	M	Session id of the process flow

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	certificate_profile	String	M	Certificate profile. Get from API "Get Certificate Profile for Connector"
2	tax_code	String	RC	Tax code to finish generate new certificate
3	issuing_provider	String	RC	Issuing provider data. Get from API "Get Certificate Profile for Connector" Note: This parameter is necessary when a single connector integrates with or provides access to multiple issuing providers

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9 Enterprise Management

2.9.1 Register Enterprise User

Business Applications can use this service API to register Enterprise User. New users inherit the Enterprise Admin Service Plan and all associated permissions. And there are different scenarios to consider when registering a user.

Users will get an "account activation" email on successful registration, if password, security question and answer parameters are not provided in the call. Email notification flag would be ignored by the GoPaperless Workflow.

Users will get an "account activation" email on successful registration,if password, security question and answer parameters are provided in the call. Email notification flag should be set to True

Users will not get any email on successful registration, if password, security question and answer parameters are provided in the call => Email notification flag set to False

Sample Request

POST https://{domain}/{contextPath}/v1/enterprise/users
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_name": "String",
  "user_email": "String",
  "user_password": "String",
  "security_question": "String",
  "security_answer": "String",
  "enterprise_role": "String",
  "email_notification": true,
  "certificate_id": 1,
  "job_title": "String",
  "company_name": "String",
  "mobile_number": "String",
  "country": "String",
  "time_zone": "String",
  "language": "String",
  "user_national_id": "String",
  "common_name": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	user_name	String	M	The name of the user to be registered.
2	user_email	String	M	The email address of the user account to be registered.
3	user_password	String	M	The password of the user account
4	security_question	String	M	Security question used to reset password if user forgets his password.
5	security_answer	Boolean	O	Security answer used to reset the password if user forgets his password.
6	enterprise_role	String	M	The enterprise role to be assigned to this user

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	email_notification	String	M	This defines whether enterprise user would get an email notification about the account creation. Default value is 'false'.
8	certificate_id	String	O	Certificate ID
9	job_title	String	O	Job title of user
10	company_name	String	O	Company name of user
11	mobile_number	String	O	Mobile number of user
12	country	String	O	Country name for the user
13	time_zone	String	O	Timezone name for the user
14	language	String	O	Language selected for the user
15	user_national_id	String	O	National identity number of the user
16	user_csp_id	String	O	User ID of the user registered in CSP service inside SigningHub Engine (ADSS Server).
17	user_ra_id	String	O	User ID of the user registered in SAM service inside SigningHub Engine (ADSS Server).
18	user_csc_id	String	O	
19	common_name	String	O	An identifiable name for the user that added as Common Name (CN) in identity certificate.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.2 Get Workflow User Permissions of Enterprise Package

Business Applications can use this service API to get the document permissions for a User in that workflow. This API can also be used by the enterprise administartor.

Sample Request

GET
https://{domain}/{contextPath}/v1/enterprise/packages/{packageId}/workflow/{order}/permissions
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "print": true,
  "download": true,
  "add_text": true
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	String	M	
2	order	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
2	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
3	order	Integer	M	Order ID of the User

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	print	Boolean	M	True, if printing is allowed for this recipient.
5	download	Boolean	M	True, if download is allowed.
6	add_text	Boolean	M	True, if add text annotation on the document is allowed.
7	change_recipients	Boolean	M	True, if the recipient on the current order can change other recipients in the workflow after workflow is shared.
8	add_attachment	Boolean	M	True, if attachments and merging of PDF documents is allowed.

2.9.3 Update Workflow User Permissions of Enterprise Package

Business Applications can use this service API to update the document permissions for a User in that workflow. This API can also be used by the enterprise administartor.

Sample Request

PUT
https://{domain}/{contextPath}/v1/enterprise/packages/{packageId}/workflow/{order}/permissions
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "apply_to_all": true,
  "permissions": {
    "print": true,
    "download": true,
    "add_text": true,
    "change_recipients": true,
    "add_attachment": true
  }
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	String	M	
2	order	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
3	order	Integer	M	Order ID of the User
4	apply_to_all	Boolean	M	True, if the permissions are to be applied on all the recipients in the workflow
5	permissions	workflowPermissionRequest	M	It has all the permissions to be allowed in the workflow

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.4 Get Workflow User Authentication(Document Opening) of Enterprise Package

Business Applications can use this service API to get the access security settings enabled for the package. Recipients will not be able to access document package outside the scope of this duration if the access security is enabled. Document owner can also configure authentication based security of the package for a recipient

Sample Request

```
GET
https://{domain}/{contextPath}/v1/enterprise/packages/{packageId}/workflow/{order}/authentication
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "authentication": {
    "enabled": true,
    "password": {
      "enabled": true
    },
    "sms_otp": {
      "enabled": true,
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "authentication_signing": {
    "enabled": true,
    "sms_otp": {
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "access_duration": {
    "enabled": true,
    "duration_by_date": {
```


Http Code: 401
Content-type: application/json


```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	String	M	
2	order	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.
3	order	Integer	M	Order ID of the User

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	authentication	authentication	M	Authentication object with the details of authentication methods applied on the document for the recipient.
5	authentication_signing	authenticationSigning	M	Authentication Signing for the package

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	access_duration	accessDuration	M	Access duration object with the details of access securities for the recipient.

2.9.5 Update Workflow User Authentication of Enterprise Package

Business Applications can use this service API to update the access security settings enabled for the package. Recipients will not be able to access document package outside the scope of this duration if the access security is enabled. Document owner can also configure authentication based security of the package for a recipient

Sample Request

PUT

https://{domain}/{contextPath}/v1/enterprise/packages/{packageId}/workflow/{order}/authentication

Content-Type: application/json

Authorization: "Bearer {accesstoken}"

x-language-name: en

```
{
  "apply_to_all": true,
  "authentication": {
    "enabled": true,
    "password": {
      "enabled": true
    },
    "sms_otp": {
      "enabled": true,
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "authentication_signing": {
    "enabled": true,
    "sms_otp": {
      "otp_length": 0,
      "retry_duration": 0,
      "mobile_number": "String"
    }
  },
  "access_duration": {
    "enabled": true,
    "duration_by_date": {
      "enabled": true,
      "accessible": true,
      "duration": {
        "total_days": 1
      }
    }
  }
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 401
Content-type: application/json


```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	String	M	
2	order	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	order	Integer	M	Order ID of the User
4	authentication	authentication	M	Authentication object with the details of authentication methods applied on the document for the recipient.
5	authentication_signing	authenticationSigning	M	Authentication Signing for the package
6	access_duration	accessDuration	M	Access duration object with the details of access securities for the recipient.
7	apply_to_all	Boolean	M	True, if the access security or authentications are to be applied on all the recipients in the workflow.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.6 Reset Enterprise User Password

Business Applications can use this service API to reset Enterprise User Password.

Sample Request

POST https://{domain}/{contextPath}/v1/enterprise/users/{id}/reset-password
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	id	String	M	Id of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.7 Change User Service Plan

Business Applications can use this service API to update a user's service plan.

Sample Request

PUT https://{domain}/{contextPath}/v1/admin/accounts
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "String",
  "service_plan": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_email	String	M	Email of the user
3	service_plan	String	M	New service plan name

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.8 Get Enterprise Users

Business Applications can use this service API to get a list of user belong to this Enterprise.

Sample Request

```
GET
https://{domain}/{contextPath}/v1/enterprise/users/{pageNo}/{recordsPerPage}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-search-text: "String"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
    "users":[
            {
                    "user_id": 0,
                    "created_on": "String",
                    "user_name": "String",
                    "enterprise_role": "String",
                    "mobile_number": "String",
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	pageNo	String	M	
2	recordsPerPage	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request
4	x-search-text	String	O	Search if required

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	users	List<userOfEnterprise>	M	The array of user

2.9.9 Get Enterprise User

Business Applications can use this service API to get a user

Sample Request

```
GET https://{domain}/{contextPath}/v1/enterprise/users/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-search-text: "String"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "user_id": 0,
  "created_on": "String",
  "user_name": "String",
  "enterprise_role": "String",
  "mobile_number": "String",
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	x-search-text	String	O	Search if required

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	id	Integer	M	The id of enterprise user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	user_id	Integer	M	User Id
5	created_on	String	M	Created on date of the registered user.
6	user_name	String	M	The full name of the user.
7	user_email	String	M	The email address of the registered user.
8	enterprise_role	String	M	The enterprise role under which the user is registered.
9	mobile_number	String	M	The mobile number of the registered user.
10	job_title	String	M	The Job Title of the registered user.
11	company_name	String	M	The company name of the registered user.
12	status	String	M	The current status of the user e.g. "ACTIVATED" or "REGISTERED". If status is registered, it means user is registered but not activated yet.
13	enabled	Boolean	M	True, if user is enabled and false if user is not enabled by the application administrators.

2.9.10 Update Enterprise User

Business Applications can use this service API to update the information of an user.

Sample Request

PUT https://{domain}/{contextPath}/v1/enterprise/users
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "string",
  "user_name": "string",
  "job_title": "string",
  "company_name": "string",
  "mobile_number": "string",
  "user_old_password": "string",
  "user_new_password": "string",
  "security_question": "string",
  "security_answer": "string",
  "enterprise_role": "string",
  "enabled": true
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_email	String	M	The email address of the user account to be updated.
3	user_name	String	O	The name of the user to be updated.
4	job_title	String	O	Job title of user.
5	company_name	String	O	Company Name of user.
6	mobile_number	String	O	Mobile number of user.
7	user_old_password	String	O	The old password of the user account.
8	user_new_password	String	O	The new password of the user account.
9	security_question	String	O	Security question used to reset password if user forgets his password.
10	security_answer	String	O	Security answer used to reset the password if user forgets his password.
11	enterprise_role	String	O	The enterprise role to be assigned to this user - these are managed within the Enterprise account.
12	enabled	Boolean	O	Setting this to false would disable the user and vice versa

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.11 Delete Enterprise User

Business Applications can use this service API to delete a user.

Sample Request

DELETE **https://{domain}/{contextPath}/v1/enterprise/users**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "string"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	user_email	String	M	The email address of the user account to be updated.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.12 Get Groups

Business Applications can use this service API to get the list of groups

Sample Request

GET
https://{domain}/{contextPath}/v1/settings/groups/{recordPerPage}/{pageNo}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-search-text: "String"
x-total-records: "String"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "groups": [
    {
      "id": 0,
      "group_name": "String",
      "group_members": [
        {
          "user_email": "String",
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-search-text	String	O	Search text if required. This is optional and without it the entire list is returned. Furthermore, recommended value for search text parameter is in Base64 encoded format.
3	x-total-enterprise	String	O	Total number of records found with the provided search criteria.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	recordPerPage	String	M	
2	pageNo	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	groups	List<group>	M	The array of groups

2.9.13 Delete Groups

Business Applications can use this service API to delete the group.

Sample Request

DELETE https://{domain}/{contextPath}/v1/settings/groups/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	Id	Integer	O	Id of the group

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.14 Add Member into Group

Business Applications can use this service API to add a new member into the group.

Sample Request

POST https://{domain}/{contextPath}/v1/enterprise/groups/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "group_name": "String",
  "user_email": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**

1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	id	Integer	O	Id of the group
3	group_name	String	M	New group name
4	user_email	String	M	Email of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.15 Delete Member in Group

Business Applications can use this service API to delete a member into the group.

Sample Request

DELETE **https://{domain}/{contextPath}/v1/enterprise/groups/{id}**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	id	Integer	O	Id of the group
3	group_name	String	M	Group name that the user will be removed
4	user_email	String	M	Email of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	message	String	M	Human-readable error message.

2.9.16 Get Roles

Business Applications can use this service API to get roles for enterprise.

Sample Request

GET
https://{domain}/{contextPath}/v1/enterprise/roles/{pageNo}/{recordPerPage}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-search-text: "String"
x-total-records: "10"
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
    "roles":[
            {
                    "id": 0,
                    "name": "String",
                    "description": "String",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-search-text	String	O	Search text if required
3	x-total-records	String	O	Total number of records

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	pageNo	String	M	
2	recordPerPage	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	roles	List<role>	M	List of role

2.9.17 Get Role Users

Business Applications can use this service API to get a list of user that belongs to the role

Sample Request

GET
https://{domain}/{contextPath}/v1/enterprise/roles/{id}/users/{pageNo}/{recordPerPage}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-total-records: "10"
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
    "users":[
            {
                    "user_name": "String",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-total-records	String	O	Total number of records

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	
2	pageNo	String	M	
3	recordPerPage	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request
4	id	Integer	M	Id of the role

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	users	List<member>	M	List of member belongs to the role

2.9.18 Delete Role

Business Applications can use this service API to get a list of user that belongs to the role

Sample Request

DELETE **https://{domain}/{contextPath}/v1/enterprise/roles/{id}**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	id	Integer	M	Id of the role

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.9.19 Add Role

Business Applications can use this service API to add a role for Enterprise.

Sample Request

POST https://{domain}/{contextPath}/v1/enterprise/roles
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "name": "String",
  "description": "String",
  "default": true
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "id": 0,
  "name": "String",
```

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	name	Integer	M	Name of the role
3	description	String	M	Description of the role
4	default	Boolean	M	Default of the role

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	id	Integer	M	Id of the role
5	name	Integer	M	Name of the role
6	description	String	M	Description of the role
7	default	Boolean	M	Default of the role

2.10 Account Management

2.10.1 Get Account Invitations

Business Applications can use this service API to get a list of invitations from different enterprises.

Sample Request

GET **https://{domain}/{contextPath}/v1/account/invitations**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
    "invitations":[
            {
            "enterprise_id": 0,
            "enterprise_name": "String",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_email	String	M	Email of the user to get the invitation

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	invitations	List<invitation>	M	Data of the invitation

2.10.2 Accept Account Invitations

Business Applications can use this service API to accept an invitation and reject all the other invitations.

Sample Request

```
PUT https://{domain}/{contextPath}/v1/account/invitations
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "enterprise_name ": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	enterprise_name	String	M	Name of the enterprise whose invitation is to be accepted.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.10.3 Reject All Account Invitations

Business Applications can use this service API to reject all invitations.

Sample Request

DELETE **https://{domain}/{contextPath}/v1/account/invitations**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.10.4 Register Enterprise User (Free Trial)

Business Applications can use this service API to register a new user

Sample Request

```
POST https://{domain}/{contextPath}/v1/account
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "user_name": "String",
  "user_email": "String",
  "user_password": "String",
  "security_question": "String",
  "security_answer": "String",
  "enterprise_role": "String",
  "email_notification": true,
  "certificate_id": 1,
  "job_title": "String",
  "company_name": "String",
  "mobile_number": "String",
  "country": "String",
  "time_zone": "String",
  "language": "String",
  "user_national_id": "String",
  "common_name": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_name	String	M	The name of the user to be registered.
3	user_email	String	M	The email address of the user account to be registered.
4	user_password	String	M	The password of the user account
5	security_question	String	M	Security question used to reset password if user forgets his password.
6	security_answer	Boolean	O	Security answer used to reset the password if user forgets his password.
7	enterprise_role	String	M	The enterprise role to be assigned to this user

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
8	email_notification	String	M	This defines whether enterprise user would get an email notification about the account creation. Default value is 'false'.
9	certificate_id	String	O	
10	job_title	String	O	Job title of user
11	company_name	String	O	Company name of user
12	mobile_number	String	O	Mobile number of user
13	country	String	O	Country name for the user
14	time_zone	String	O	Timezone name for the user
15	language	String	O	Language selected for the user
16	user_national_id	String	O	National identity number of the user
17	user_csp_id	String	O	User ID of the user registered in CSP service inside SigningHub Engine (ADSS Server).
18	user_ra_id	String	O	User ID of the user registered in SAM service inside SigningHub Engine (ADSS Server).
19	user_csc_id	String	O	
20	common_name	String	O	An identifiable name for the user that added as Common Name (CN) in identity certificate.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.10.5 Get Account

Business Applications can use this service API to get the account information of a logged in user

Sample Request

```
GET https://{domain}/{contextPath}/v1/account
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "user_email": "string",
  "user_name": "string",
  "created_on": "string",
  "enabled": true,
  "two_factor_authentication_enabled": true,
  "service_plan": {
    "name": "string",
    "type": "string",
    "features": [
      "string"
    ],
    "constraints": {
      "users": "string",
      "signatures": "string",
      "advanced_electronic_signatures": "string",
      "high_trust_advanced_signatures": "string",
      "qualified_electronic_signatures": "string",
      "electronic_seals": "string",
      "advanced_electronic_seals": "string",
      "qualified_electronic_seals": "string",
      "simple_electronic_signatures": "string",
      "storage": "string",
      "workflows": "string",
      "max_upload_size": "string",
      "templates": "string"
    },
    "settings": {
      "pdf_compliant": true,
      "signing_keys_with_password": true,
      "signature_type": "string",
      "authorized_signing": true,
      "sms_otp": true,
      "email_otp": true,
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	user_email	Boolean	M	Email address of the user.
5	user_name	Object	O	Name of user for which the authentication token is provided.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
6	created_on	Boolean	M	Account created on.
7	enabled	Boolean	M	True, if user is enabled and can access the application. False otherwise.
8	two_factor_authentication_enabled	Boolean	M	True, if user is configured the Two factor authentication
9	service_plan	servicePlan	M	Service plan of the account
10	enterprise	enterprise	M	Enterprise information.

2.10.6 Send Forgot Password Request

Business Applications can use this service API to send an email with instructions to reset a password.

Sample Request

POST https://{domain}/{contextPath}/v1/account/password/reset
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_email	String	M	Email of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.10.7 Account Usage Statistic

Business Applications can use this service API to get the account usage statistics

Sample Request

GET https://{domain}/{contextPath}/v1/account/statistics/usage
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "storage": {
    "consumed": 0,
    "allowed": 100
  },
  "signature": {
    "consumed": 0,
    "allowed": 20
  },
  "workflow": {
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	storage	consumer	M	Storage of the user
5	signature	consumer	M	Total signature of the user
6	workflow	consumer	M	Workflow of the user
7	user	consumer	M	User belongs to the user

2.10.8 Document Statistic

Business Applications can use this service API to get the documents count with respect to their statuses.

Sample Request

GET https://{domain}/{contextPath}/v1/account/statistics/documents
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "draft": 0,
  "pending": 0,
  "shared": 0,
  "signed": 0,
  "approved": 0,
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	draft	Integer	M	Total number of documents in draft status.
5	pending	Integer	M	Total number of documents in pending status.
6	shared	Integer	M	Total number of documents in shared status.
7	signed	Integer	M	Total number of documents in signed status.
8	approved	Integer	M	Total number of documents in approved status.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
9	declined	Integer	M	Total number of documents in declined status.
10	completed	Integer	M	Total number of documents in completed status.
11	updated	Integer	M	Total number of documents in updated status.
12	archived	Integer	M	Total number of documents in archived status.

2.10.9 Get User Activity Logs

Business Applications can use this service API to get the list of actions performed by a user

Sample Request

GET https://{domain}/{contextPath}/v1/account/log/{pageNo}/{recordsPerPage}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "user_activities": [
    {
      "log_id": 0,
      "date_time": "string",
      "action_type": "string",
      "action_type_label": "string",
      "user_email": "string",
      "user_name": "string",
      "enterprise_name": "string",
      "information": {
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	pageNo	String	M	
2	recordsPerPage	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	user_activities	List<userActivity>	M	The array of actions

2.10.10 Get Group

Business Applications can use this service API to get the list of groups for the current user

Sample Request

```
GET
https://{domain}/{contextPath}/v1/settings/groups/{recordPerPage}/{pageNo}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-search-text: "String"
x-enterprise: "String"
x-total-records: "String"
x-language-name: en
{}
```

Sample Response

```
Http Code: 200
Content-Type: application/json
{
  "groups": [
    {
      "id": 0,
      "group_name": "name",
      "group_member": [
        {
          "user_email": "String",
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-search-text	String	O	Search text if required. This is optional and without it the entire list is returned. Furthermore, recommended value for search text parameter is in Base64 encoded format.
3	x-enterprise	String	O	If set as "true" only enterprise groups list will be returned. In case of "false"only the user's groups list will be returned.If you do not set the header, then both enterprise and user's groups lists will be returned.
4	x-total-records	String	O	Total number of records found with the provided search criteria.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	recordPerPage	String	M	
2	pageNo	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	groups	List<group>	M	The array of groups

2.10.11 Change Pasword

Business Applications can use this service API to change the pasword of the current user

Sample Request

```
PUT https://{domain}/{contextPath}/v1/settings/profile/password
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "user_old_password": "String",
  "user_new_password": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

{
"access_token": "Token",
"token_type": "bearer",
"expires_in": 300

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_old_password	String	M	Old password of the user
3	user_new_password	String	M	New password of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	access_token	String	M	The access token will be used later to connect with other APIs.
5	token_type	String	M	Type of the token returned. It is always set to "bearer".
6	expires_in	Integer	M	Number of seconds for which this access token is valid.
7	refresh_token	String	M	This is a token related to access token. Can use this token to revoke.
8	refresh_token_expires_in	Integer	M	Number of seconds for which this refresh token is valid.

2.10.12 Update Security Settings

Business Applications can use this service API to update profile's security information of the current user.

Sample Request

PUT https://{domain}/{contextPath}/v1/settings/profile/security
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "password": "String",
  "question": "String",
  "answer": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	password	String	M	Password of the user for the authentication
3	question	String	M	New security question
4	answer	String	M	New security answer

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.10.13 Add Identity for a User

By default, the application identifies users using their email address. To provide more flexibility, clients can assign a unique identifier to a user via the API below. Currently, only identity verification through the VNeID service is supported.

Sample Request

POST https://{domain}/{contextPath}/v1/account/identity
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "sync_user_from_connector": "NameOfConnector",
  "webhook_url": "Your url"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "message": "PROCESSING"
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + VI

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	sync_user_from_connector	String	M	The name of the connector through which the user wishes to synchronize identity information.
2	webhook_url	String	M	The webhook URL where you want to receive status updates.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	validity_period	Integer	M	The validity period during which the processing request remains active.

2.11 Personal Settings

2.11.1 Get Signature Settings

Business applications can use this service API to get the signature settings for the current user. This means the enterprise administrator or the enterprise user if the "scope" variable was used in the authentication request.

Sample Request

GET https://{domain}/{contextPath}/v1/settings/signatures
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json


```
{
    "signatures":[
            {
                    "appearance_id": 1,
                    "metadata":{
                            "signing_reason": "Reason",
                            "signing_location": "Location",
                            "signer_name": "Name",
                            "signing_date": "Date",
                            "signing_logo": "Base64",
                            "signing_distinguished_name": "Name2",
                            "itext_version": "1.2.1",
                            "signing_labels": "labels",
                            "align_option": "LEFT",
                            "remark": "Digi format",
                            "hand_signature_image": "Base64 hand signature image"
                    },
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	signatures	List<signatureApperance>	M	List of the appearance

2.11.2 Add Signature Appearance

Business applications can use this service API to add new signature appearance for the current user. This means the enterprise administrator or the enterprise user if the "scope" variable was used in the authentication request.

Sample Request

POST https://{domain}/{contextPath}/v1/settings/signatures

Authorization: "Bearer {accesstoken}"

x-language-name: en

```
{
  "metadata": {
    "signing_reason": "Reason",
    "signing_location": "Location",
    "signer_name": "Name",
    "signing_date": "Date",
    "signing_logo": "Base64",
    "signing_distinguished_name": "Name2",
    "itext_version": "1.2.1",
    "signing_labels": "labels",
    "align": "LEFT",
    "remark": "Digi format",
    "hand_signature_image": "Base64 hand signature image"
  },
  "credential_configuration": {
    "signing_server": "SMART_ID_SIGNING",
    "connector_name": "SMART_ID_MOBILE_ID",
    "document_type": "USERNAME",
    "value": "Value",
    "credential_id": "Value",
    "appearance_design": "QUALIFIED_ELECTRONIC_SIGNATURE",
    "icon": "Base64 icon"
  }
}
```

Sample Response

Http Code: 200

Content-Type: application/json

```
{
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	metadata	metadataSignature	M	Metadata of the appearance
3	credential_configuration	credentialConfiguration	M	Credential configuration of the appearance

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	appearance_id	Integer	M	ID of the appearance

2.11.3 Update Signature Appearance

Business applications can use this service API to update the signature appearance for the current user. This means the enterprise administrator or the enterprise user if the "scope" variable was used in the authentication request.

Sample Request

PUT https://{domain}/{contextPath}/v1/settings/signatures/{appearance_id}
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "metadata": {
    "signing_reason": "Reason",
    "signing_location": "Location",
    "signer_name": "Name",
    "signing_date": "Date",
    "signing_logo": "Base64",
    "signing_distinguished_name": "Name2",
    "itext_version": "1.2.1",
    "signing_labels": "labels",
    "align": "LEFT",
    "remark": "Digi format",
    "hand_signature_image": "Base64 hand signature image"
  },
  "credential_configuration": {
    "signing_server": "SMART_ID_SIGNING",
    "connector_name": "SMART_ID_MOBILE_ID",
    "document_type": "USERNAME",
    "value": "Value",
    "credential_id": "Value",
    "appearance_design": "QUALIFIED_ELECTRONIC_SIGNATURE",
    "icon": "Base64 icon"
  }
}
```

Sample Response

Http Code: 200

```
{}
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	appearance_id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	appearance_id	Integer	M	Id of the appearance.
3	metadata	metadataSignature	M	Metadata of the appearance
4	credential_configuration	credentialConfiguration	M	Credential configuration of the appearance

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.11.4 Delete Signature Appearance

Business applications can use this service API to delete the signature appearance for the current user. This means the enterprise administrator or the enterprise user if the "scope" variable was used in the authentication request.

Sample Request

DELETE **https://{domain}/{contextPath}/v1/settings/signatures/{appearance_id}**
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
{}

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	appearance_id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	appearance_id	Integer	M	Id of the appearance.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.11.5 Get General Profile Information

Business Applications can use this service API to get the general profile information of the current user

Sample Request

GET https://{domain}/{contextPath}/v1/settings/profile
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "general": {
    "user_email": "string",
    "user_name": "string",
    "job_title": "string",
    "company_name": "string",
    "mobile_number": "string",
    "enterprise_role": "string",
    "ra_userid": "string",
    "user_national_id": "string"
  },
  "security": {
    "question": "string"
  },
  "locale": {
    "country": "string"
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	general	general	M	Object of the general profile information
5	security	security	M	Security information of the logged in user
6	locale	locale	M	Locale related information
7	enterprise	enterprise	M	Enterprise information of the logged in user

2.11.6 Update General Profile Information

Business Applications can use this service API to update the general profile information of the current user

Sample Request

PUT https://{domain}/{contextPath}/v1/settings/profile/general
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_name": "string",
  "job_title": "string",
  "company_name": "string",
  "mobile_number": "string",
  "country": "string",
  "time_zone": "string",
  "language": "string",
  "user_national_id": "string"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_name	String	M	Name of the user
3	job_title	String	O	Job title of the user
4	company_name	String	O	Company name for the user
5	mobile_number	String	O	Mobile number of the user
6	country	String	O	Country of the user
7	time_zone	String	O	Timezone name for the user
8	language	String	O	Language selected for the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.11.7 Get Address Book

Business Applications can use this service API to get an address book for the current user.

Sample Request

```
GET https://{domain}/{contextPath}/v1/settings/addressbook
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "address_books": [
    {
      "address_book_name": "addressBook1",
      "contacts": [
        {
          "contact_id": 1,
          "user_first_name": "G",
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	address_books	List<addressBook>	M	An array that representing the address book that belongs to the user.

2.11.8 Add Address Book

Business Applications can use this service API to add an new address book for the current user.

Sample Request

```
POST https://{domain}/{contextPath}/v1/settings/addressbook
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "address_book_name": "Address Book1",
  "description": ""
}
```

Sample Response

```
Http Code: 200
Content-Type: application/json
{
  "address_book_id": 1
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	address_book_name	String	M	Name of the address book
3	description	String	O	Description of the address book

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	address_book_id	Integer	M	Id of the address book

2.11.9 Update Address Book

Business Applications can use this service API to update the address book for the current user.

Sample Request

PUT https://{domain}/{contextPath}/v1/settings/addressbook/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "address_book_name": "Address Book1"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**

1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	address_book_name	String	O	Name of the address book
3	description	String	O	Description of the address book

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.11.10 Delete Address Book

Business Applications can use this service API to delete the address book for the current user.

Sample Request

DELETE https://{domain}/{contextPath}/v1/settings/addressbook/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	Id	Integer	M	Id of the address book

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.11.11 Add Contact into Address Book

Business Applications can use this service API to add a contact into address book.

Sample Request

PUT https://{domain}/{contextPath}/v1/settings/addressbook
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "address_book_name": "Address Book1",
  "contact_email": "email Contact 1"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "address_books": [
    "addressA",
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	address_book_name	String	M	Name of the address book
3	contact_email	String	M	Email of the contact

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	address_books	List<String>	M	An array that representing the address book that belongs to the user.

2.11.12 Remove Contact in Address Book

Business Applications can use this service API to add a contact into address book.

Sample Request

```
PUT https://{domain}/{contextPath}/v1/settings/addressbook
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "address_book_name": "Address Book1",
  "contact_email": "email Contact 1"
}
```

Sample Response

```
Http Code: 200
{
```

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	address_book_name	String	M	Name of the address book
3	contact_email	String	M	Email of the contact

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.11.13 Get Templates

This API allows business applications to retrieve a list of templates for the current user. You can search these templates by providing criteria under the 'x-search-text' header.

The API also supports searching for personal templates or enterprise-wide templates, depending on the user's role and permissions granted by their enterprise administrator.

Sample Request

GET
https://{domain}/{contextPath}/v1/settings/templates/{recordPerPage}/{pageNo}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-search-text: "{base64}"
x-enterprise: true
x-total-records: 10
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "templates": [
    {
      "template_id": 0,
      "template_name": "name",
      "template_public": true,
      "read_only": true,
      "created_at": "",
      "description": "String",
      "enterprise": false,
      "documents": [
        {
          "id": 0,
```

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	name	String	M	Name of the template that is to be added.
2	description	String	O	Name of the description that is to be added.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	Id	Integer	M	Id of the template

2.12 Application/Device Management

2.12.1 Register Application User

Business Applications can use this service API to register User that belongs to the application. New users inherit the User Service Plan and all associated permissions. And there are different scenarios to consider when registering a user.

Users will get an "account activation" email on successful registration, if password, security question and answer parameters are not provided in the call. Email notification flag would be ignored by the GoPaperless Workflow.

Users will get an "account activation" email on successful registration,if password, security question and answer parameters are provided in the call. Email notification flag should be set to True

Users will not get any email on successful registration, if password, security question and answer parameters are provided in the call => Email notification flag set to False

Sample Request

POST https://{domain}/{contextPath}/v1/application/users

Content-Type: application/json

Authorization: "Bearer {accesstoken}"

x-language-name: en

```
{
    "user_name": "String",
    "user_email": "String",
    "user_password": "String",
    "security_question": "String",
    "security_answer": "String",
    "enterprise_role": "String",
    "email_notification": true,
    "job_title": "String",
    "company_name": "String",
    "mobile_number": "String",
    "country": "String",
    "time_zone": "String",
    "language": "String",
    "user_national_id": "String",
    "common_name": "String"
    //Identity data
    "full_name": " String ",
"user_national_id": "String",
"date_of_birth": "1990-01-15T08:30:00",
"gender": 1",
"permanent_address": " String ",
"residential_address": " String ",
"eid_account_level": 2,
"account_type": " String ",
"date_of_issue": "2020-06-01T00:00:00",
"date_of_expiry": "2030-06-01T00:00:00"

}
```

Sample Response

Http Code: 200

Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_first_name	String	M	First name of the new user
3	user_last_name	String	M	Last name of the new user
4	user_email	String	M	The email address of the user account to be registered.
5	user_password	String	O	The password of the user account
6	security_question	String	O	Security question used to reset password if user forgets his password.
7	security_answer	Boolean	O	Security answer used to reset the password if user forgets his password.
8	email_notification	String	O	This defines whether enterprise user would get an email notification about the account creation. Default value is 'false'.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
9	certificate_id	String	O	Certificate ID
10	job_title	String	O	Job title of user
11	company_name	String	O	Company name of user
12	mobile_number	String	O	Mobile number of user
13	country	String	O	Country name for the user
14	time_zone	String	O	Timezone name for the user
15	language	String	O	Language selected for the user
16	user_national_id	String	O	National identity number of the user
17	user_csp_id	String	O	User ID of the user registered in CSP service inside SigningHub Engine (ADSS Server).
18	user_ra_id	String	O	User ID of the user registered in SAM service inside SigningHub Engine (ADSS Server).
19	user_csc_id	String	O	
20	common_name	String	O	An identifiable name for the user that added as Common Name (CN) in identity certificate.
21	full_name	String	O	Full legal name of the user.
22	date_of_birth	String	O	User's date and time of birth (ISO 8601 format).
23	gender	Integer	O	User's gender. Possible values are: - 1: MALE - 2: FEMALE
24	permanent_address	String	O	User's officially registered permanent address.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
25	residential_address	String	O	User's current residential address.
26	eid_account_level	Integer	O	User's electronic ID account level.
27	account_type	String	O	Type of user account (e.g., CITIZEN)
28	date_of_issue	String	O	Date and time the ID or account was issued.
29	date_of_expiry	String	O	Expiration date and time of the ID or account.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.12.2 Add Personal Contact

Business Applications can use this service API to add a contact for the current user.

Sample Request

POST https://{domain}/{contextPath}/v1/settings/contacts
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_first_name": "G",
  "user_last_name": "T",
  "position": "Staff",
  "company_name": "Mobile-ID",
  "user_email": "String",
  "address_book_name": "Name of the address book"
}
```

Sample Response

Http Code: 200
Content-Type: application/json
{

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_first_name	String	M	User name of the user to be added as a contact
3	user_email	String	M	Email address of the user to be added as a contact
4	user_last_name	String	M	Last name of the user
5	position	String	O	Position of the user in the company
6	company_name	String	O	Company name that user belongs to

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	address_book_name	String	O	If the user already have the address book. Can provide this parameter to add Contact into that address book
8	personal_code	String	O	Personal code of the contact
9	mobile_number	String	O	Mobile number of the contact

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	contact_id	Integer	M	Id of the contact

2.12.3 Get Contacts

Business Applications can use this service API to get a list of contacts for the current user.

Sample Request

```
GET
https://{domain}/{contextPath}/v1/settings/contacts/{pageNo}/{recordPerPage}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-search-text: "String",
x-enterprise: "String",
x-total-records: "String"
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "contacts": [
    {
      "contact_id": 1,
      "user_first_name": "string",
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-search-text	String	O	Search text if required. This is optional and without it the entire list is returned. Furthermore, recommended value for search text parameter is in Base64 encoded format.
3	x-enterprise	String	O	If set as "true" only enterprise groups list will be returned. In case of "false"only the user's groups list will be returned.If you do not set the header, then both enterprise and user's groups lists will be returned.
4	x-total-records	String	O	Total number of records found with the provided search criteria.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**

1	pageNo	String	M	
2	recordPerPage	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	contacts	List<contact>	M	The array of the contact

2.12.4 Update Personal Contact

Business Applications can use this service API to update the contact for the current user.

Sample Request

PUT https://{domain}/{contextPath}/v1/settings/contacts/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_first_name": "G",
  "user_last_name": "T",
  "position": "Staff",
  "company_name": "Mobile-ID",
  "user_email": "String"
}
```

Sample Response

Http Code: 200

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	id	Integer	M	Id of the contact
3	user_first_name	String	M	User name of the user to be added as a contact
4	user_email	String	M	Email address of the user to be added as a contact
5	user_last_name	String	M	Last name of the user
6	position	String	O	Position of the user in the company
7	company_name	String	O	Company name that user belongs to
8	personal_code	String	O	Personal code of the contact
9	mobile_number	String	O	Mobile number of the contact

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.12.5 Delete Personal Contact

Business Applications can use this service API to delete the contact for the current user.

Sample Request

DELETE **https://{domain}/{contextPath}/v1/settings/contacts/{id}**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
{}

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	id	Integer	M	Id of the contact

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.13 Template

2.13.1 Save Workflow as Template

Business applications can use this service API to save workflow as template. This API can also be used by the business application to perform action on behalf of the enterprise user via "Scope Authentication".

Sample Request

```
POST https://{domain}/{contextPath}/v1/packages/{packageId}/template
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "name": "String",
  "description": "String"
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{
  "id": 0
}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	packageId	Integer	M	This is the ID of the package that was created. Using this ID to Interact with that document package.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	name	String	M	Name of the template that is to be added.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	description	String	O	Name of the description that is to be added.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	Id	Integer	M	Id of the template

2.13.2 Get Template By ID

Business applications can use this service API to get a personal/enterprise template. This API can also be used by the business application to perform action on behalf of the enterprise user via "Scope Authentication".

Sample Request

```
GET https://{domain}/{contextPath}/v1/templates/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}
```

Sample Response

Http Code: 200
Content-type: application/json


```
{
  "name": "Name",
  "public": true,
  "read_only": true,
  "description": "Description",
  "created_at": "String",
  "enteprise": true,
  "documents": [
    {
      "id": 0,
      "name": "Name"
    }
  ]
}
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	Integer	M	The ID of personal/enterprise template.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	name	Integer	M	Name of the template.
5	public	Boolean	M	Response is "true" if enterprise template is marked as public. Otherwise "false" would be returned
6	read_only	Boolean	M	Response of "true" if the template is read only, and user cannot make any changes to the workflow after applying this template. Otherwise "false".
7	description	String	M	Description of the template
8	created_at	String	M	Date and time when the template was created
9	enterprise	Boolean	M	True, if user belong to an enterprise.
10	documents	List<TemplateDocumentResponse>	M	Documents data belongs to this template

2.13.3 Update Template

Business applications can use this service API to update personal/enterprise template. This API can also be used by the business application to perform action on behalf of the enterprise user via "Scope Authentication".

Sample Request

PUT https://{domain}/{contextPath}/v1/templates/{id}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "name": "Name",
  "public": true,
  "read_only": true,
  "description": "Description"
}
```

Sample Response

Http Code: 200
Content-type: application/json

```
{}
```

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	Integer	M	The ID of personal/enterprise template.

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
4	name	Integer	O	Name of the template.
5	public	Boolean	O	Response is "true" if enterprise template is marked as public. Otherwise "false" would be returned
6	read_only	Boolean	O	Response of "true" if the template is read only, and user cannot make any changes to the workflow after applying this template. Otherwise "false".
7	description	String	O	Description of the template

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.13.4 Delete Template

Business applications can use this service API to update personal/enterprise template. This API can also be used by the business application to perform action on behalf of the enterprise user via "Scope Authentication".

Sample Request

DELETE **https://{domain}/{contextPath}/v1/templates/{id}**
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{}

Sample Response

Http Code: 200
Content-type: application/json
{}

Http Code: 400
Content-type: application/json

{
"error_description": "Cannot verify token",
"error_code": "-17",
"message": "Không thể kiểm tra tính hợp lệ của token"
}

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	Authorization	String	M	The authentication token (accessToken) required to access the API. Must be provided in the format "Bearer <accessToken>" Note: the accessToken is obtained after a successful authorization.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	id	Integer	M	The ID of personal/enterprise template.

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.14 ADMIN APIs

2.14.1 Admin Authentication

This API can be used to authenticate to GoPaperless Workflow Service Administrator. It requires a current, valid client TLS certificate

The API call should present a client TLS certificate in the HTTPS call

Sample Request

POST https://{domain}/{contextPath}/v1/admin/authenticate/client_cert
Content-Type: application/json
x-language-name: en
x-password: "String"
{}

Sample Response

Http Code: 200
Content-Type: application/json

```
{
  "access_token": "string",
```

Http Code: 401
Content-type: application/json

```
{
  "error_description": "Invalid Request data",
  "error_code": "1101261",
  "message": "Your client_id is invalid. Please try again"
}
```

Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are:

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
				+ en + vi
2	x-password	String	O	Password of GoPaperless Workflow Administrator if required

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	access_token	String	M	User authentication access token – bearer token for subsequent authorisation to other API calls
5	token_type	String	M	Type of the token returned by authoriation server. It is always set to "Bearer"
6	expires_in	Integer	M	Number of seconds for which this access token is valid

2.14.2 Create Account

This API can be used to create a new account in GoPaperless Workflow.
You must authenticate using your Paperless Workflow Administration client TLS certificate

The API call should present a client TLS certificate in the HTTPS call

Sample Request

```
POST https://{domain}/{contextPath}/v1/admin/accounts
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
{
  "user_first_name": "string",
  "user_email": "string",
  "enterprise_name": "string",
  "job_title": "string",
  "company_name": "string",
  "mobile_number": "string",
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_first_name	String	M	First name of the new user
3	user_email	String	M	Email address of the new user
4	enterprise_name	String	O/M	Name of the enterprise for the new account
5	job_title	String	O	Job title of the new user
6	company_name	String	O	Company name of the new user

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
7	mobile_number	String	O	Mobile number of the new user
8	service_plan	String	M	Specifies the service plan to be used for this account
9	notifications	Boolean	O	This defines whether registered user would get an email notification about the account creation
10	user_password	String	O	The password of the new user
11	security_question	String	O	Security question of the new user
12	security_answer	String	O	Security answer of the new user
13	service_agreements	Boolean	M	User consent terms of service and privacy policies for account registration
14	user_last_name	String	M	Last name of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.14.3 Change User Service Plan

Applications can call this API update a user's service plan. This requires GoPaperless Workflow Administrator permission.

Sample Request

PUT https://{domain}/{contextPath}/v1/admin/accounts
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "String",
  "service_plan": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes

No	Name	Type	Presence	Description
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes

No	Name	Type	Presence	Description
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	user_email	String	M	Email of the user

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
3	service_plan	String	M	New service plan name

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

2.14.4 Get Accounts

API is used to get accounts and filter them based on the search criteria.

Sample Request

```
GET
https://{domain}/{contextPath}/v1/admin/accounts/{pageNo}/{recordsPerPage}
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en
x-user-name: "String"
x-user-email: "String"
x-enterprise-name: "String"
x-billing-mode: "String"
x-payment-type: "String"
x-service-plan: "String"
x-activated: "String"
x-enabled: "String"
x-from: "String"
x-to: "String"
x-total-records: "String"
{}
```

Sample Response

Http Code: 200
Content-Type: application/json


```
{
  "accounts": [
    {
      "user_name": "string",
      "user_email": "string",
      "service_plan": "string",
      "enterprise_id": 0,
```


Http Code: 400
Content-type: application/json


```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```


Attributes description

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi
2	x-user-name	String	O	Name of the account user to be searched
3	x-user-email	String	O	Email of the account user to be searched.
4	x-enterprise-name	String	O	Name of enterprise by which the account is to be searched.
5	x-billing-mode	String	O	Billing mode for the account, possible values are ONLINE, OFFLINE. If developers intend to ignore billing mode, it's optional.
6	x-payment-type	String	O	Payment type for the account search, possible values are PAY_REGULARLY, PAY_AS_YOU_GO.
7	x-service-plan	String	O	Name of service plan to search
8	x-activated	String	O	True, if accounts are activated.
9	x-enabled	String	O	True, if accounts are enabled.

Header Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
10	x-from	String	O	Date value in ISO format from where the account is to be searched.
11	x-to	String	O	Date value in ISO format to which the account is to be searched.
12	x-total-records	String	O	Total number of records found with the provided search criteria.

Path Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	pageNo	String	M	
2	recordsPerPage	String	M	

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize
2	pageNo	Integer	O	Page number, according the division of records perpage
3	recordsPerPage	Integer	O	Number of records that are needed to be fetched in one request

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	accounts	List<account>	M	The array of accounts

2.14.5 Service Plan Reset

Business applications can use this API to reset the Service Plan statistics for a user. Every user in GoPaperless Workflow has an associated Service Plan. Within this the number of

signatures, workflows, templates, etc., are recorded. This API call allows the calling application to reset these statistics for the given user.

Sample Request

POST https://{domain}/{contextPath}/v1/admin/accounts/statisics/reset
Content-Type: application/json
Authorization: "Bearer {accesstoken}"
x-language-name: en

```
{
  "user_email": "String"
}
```

Sample Response

Http Code: 200
Content-Type: application/json

Http Code: 400
Content-type: application/json

```
{
  "error_description": "Cannot verify token",
  "error_code": "-17",
  "message": "Không thể kiểm tra tính hợp lệ của token"
}
```

Attributes description

Header Request Attributes

No	Name	Type	Presence	Description
1	x-language-name	String	O	Display the error message in the specified language. Possible values are: + en + vi

Request Attributes

No	Name	Type	Presence	Description
1	accesstoken	String	M	The token used to authorize into GoPaperless Workflow Service. It is response in API Authorize

Request Attributes				
No	**Name**	**Type**	**Presence**	**Description**
2	user_email	String	M	Email of the user

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.

3 ERROR CODE HTTP

CODE	MESSAGE	DESCRIPTION
200	OK	- The request send successfully and get the response from server.
201	Created	- Your request has been created
400	Bad request	- Your request doesn't contain enough values or your payload have a problem.
401	Unauthorized	- Didn't authorized yet and call subsequence API.
403	Forbidden	- Error occurred by your account (permission,..) or processing the request fail.
404	Not found	- Your data request not found in Service.
500	Internal Server Error	- An Internal Server error occurred while processing the request

4 REQUEST/RESPONSE OBJECT

4.1 AddUserToWorkflowRequest

AddUserToWorkflowRequest				
No	**Name**	**Type**	**Presence**	**Description**
1	user_email	String	M	Email of the user
2	user_first_name	String	M	First name of the recipient to be added in the workflow.
3	user_last_name	String	M	Last name of the recipient to be added in the workflow.
4	email_notification	Boolean	M	If set as true, GoPaperless Workflow will send notifications to the user via email as per the document owner and user notification settings. A value of false means no notifications will be sent to user throughout the workflow.
5	role	String	M	Role of the participant. Possible values are here
6	signing_order	Integer	M	Order of the recipient in the workflow. This signing order is mandatory when workflow type is "CUSTOM".
7	reason	String	O	Define the reason of the participant to perform signing procession
8	company_name	String	O	Name of the company

4.2 AddUserToWorkflowResponse

AddUserToWorkflowResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	user_email	String	M	Email of the user
2	signing_order	Integer	M	Order of the recipient in the workflow. This signing order is mandatory when workflow type is "CUSTOM".
3	guest_user	Boolean	M	True if this user is a guest

AddUserToWorkflowResponse				
No	**Name**	**Type**	**Presence**	**Description**
4	email_language_code	String	M	Email language code

4.3 GetWorkflowHistoryResponse

GetWorkflowHistoryResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	package_id	Integer	M	The ID of the package
2	package_name	String	M	The name of the package
3	package_owner	Integer	M	Defines the email of user
4	owner_name	String	M	The name of the user who created this package.
5	package_status	String	M	Status of the package. Possible values are: + ALL + DRAFT + INPROGRESS + SIGNED + COMPLETED + DECLINED
6	next_signer	String	M	Defines the name of the user who is the next signer to sign this package
8	next_signer_email	List<String>	M	List of email of the participant
8	documents	List<Document>	M	Data of the Documents belongs the workflow
9	actions	List<Action>	M	Arrays of the Actions

4.4 VerificationSignatureRequest

VerificationSignatureRequest				
No	**Name**	**Type**	**Presence**	**Description**
1	lock_action	String	O	To know that the field is lock action after signed it. Possible values are here

VerificationSignatureRequest				
No	**Name**	**Type**	**Presence**	**Description**
2	lock_permission	String	O	To know that the field is lock permission after signed it. Possible values are here

4.5 AssignDocumentRequest

AssignDocumentRequest				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the signature field that is to be assigned.
2	radio_group_name	String	O/M	provide group name for radio box
3	order	Integer	M	The order of the user in workflow, to which the field is being assigned.

4.6 RegisterUserRequest

RegisterUserRequest				
No	**Name**	**Type**	**Presence**	**Description**
1	user_name	String	M	The name of the user to be registered.
2	user_email	String	M	The email address of the user account to be registered.
3	user_password	String	M	The password of the user account
4	security_question	String	M	Security question used to reset password if user forgets his password.
5	security_answer	Boolean	O	Security answer used to reset the password if user forgets his password.
6	enterprise_role	String	M	The enterprise role to be assigned to this user
7	email_notification	String	M	This defines whether enterprise user would get an email notification about the account creation. Default value is 'false'.
8	certificate_id	String	O	
9	job_title	String	O	Job title of user
10	company_name	String	O	Company name of user

RegisterUserRequest				
No	**Name**	**Type**	**Presence**	**Description**
11	mobile_number	String	O	Mobile number of user
12	country	String	O	Country name for the user
13	time_zone	String	O	Timezone name for the user
14	language	String	O	Language selected for the user
15	user_national_id	String	O	National identity number of the user
16	user_csp_id	String	O	User ID of the user registered in CSP service inside SigningHub Engine (ADSS Server).
17	user_ra_id	String	O	User ID of the user registered in SAM service inside SigningHub Engine (ADSS Server).
18	user_csc_id	String	O	
19	common_name	String	O	An identifiable name for the user that added as Common Name (CN) in identity certificate.

4.7 UpdateWorkflowPermissionRequest

UpdateWorkflowPermissionRequest				
No	**Name**	**Type**	**Presence**	**Description**
1	print	Boolean	M	True, if printing is allowed for this recipient.
2	download	Boolean	M	True, if download is allowed.
3	add_text	Boolean	M	True, if add text annotation on the document is allowed.
4	change_recipients	Boolean	M	True, if the recipient on the current order can change other recipients in the workflow after workflow is shared.
5	add_attachment	Boolean	M	True, if attachments and merging of PDF documents is allowed.

4.8 GetFilteredCredentialListResponse

GetFilteredCredentialListResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	credential_id	String	M	Credential id belongs to the user
2	mode	String	M	Authorize mode of the credential. Possible value are here.
3	status	String	M	Status of the credential
4	cert	String	O	Certificate data in base64 format
5	issuer_dn	List<String>	O	This is a common format for representing X.509 Distinguished Names (DNs) in a key-value pair format. Example:["C": "VN", "ST": "Ho Chi minh",…]
6	subject_dn	List<String>	O	This is a common format for representing X.509 Distinguished Names (DNs) in a key-value pair format. Example:["C": "VN", "ST": "Ho Chi minh",…]
7	valid_from	String	O	This field specifies the date and time when the certificate becomes valid (in ISO format)
8	valid_to	String	O	This field specifies the date and time when the certificate expires. After this date (in ISO format)

4.9 GetListWorkflowResponse

GetListWorkflowResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	package_id	Integer	M	The ID of the package

GetListWorkflowResponse				
No	**Name**	**Type**	**Presence**	**Description**
2	package_name	String	M	The name of the package
3	package_owner	Integer	M	Defines the email of user
4	owner_name	String	M	The name of the user who created this package.
5	workflow_state	String	M	Overall state of the workflow
6	workflow_status	String	M	Status of the Workflow based on user.
7	next_signer_email	List<String>	M	List of email of the participant
8	created_at	String	M	Date of the package to know when it was workflow in ISO format
9	created_by	String	M	Name of the user who created this workflow
10	modified_at	String	M	Date of the package to know when it was workflow in ISO format
11	modified_by	String	M	Name of the user who modified this workflow
12	access_duration	Access_duration_1	M	The object show the duration to access to this workflow.
13	decline	decline	M	The object show the decline of the workflow.
14	total_comments	Integer	M	Total comments in workflow

4.10 BaseFillFormRequest

BaseFillFormRequest				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field.
2	value	String	M	Data of the field.
3	radio_group_name	String	O	Group name to which the radio button belongs.

4.11 AddPlaceholderToWorkflowRequest

AddPlaceholderToWorkflowRequest				
No	**Name**	**Type**	**Presence**	**Description**
1	placeholder	String	M	Placeholder name
2	email_notification	Boolean	M	If set as true, GoPaperless Workflow will send notifications to the user via email as per the document owner and user notification settings. A value of false means no notifications will be sent to user throughout the workflow.
3	role	String	M	Role of the participant. Possible values are here
4	signing_order	Integer	M	Order of the recipient in the workflow. This signing order is mandatory when workflow type is "CUSTOM".

4.12 AddPlaceholderToWorkflowResponse

AddPlaceHolderToWorkflowResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	placeholder	String	M	Placeholder name
2	signing_order	Integer	M	Order of the recipient in the workflow. This signing order is mandatory when workflow type is "CUSTOM".

4.13 GetAttachmentsResponse

GetAttachmentsResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	attachment_id	Integer	M	ID of the attachment
2	attachment_name	String	M	Name of the attachment

4.14 GetCertificateProfilesResponse

GetCertificatesProfileResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	level_of_assurance	String	O	Level of assurance of Certificate
2	certificate_profile	certificateProfile	M	Data of the certificate profile
3	issuing_provider	issuingProvider	O	Data of the issuing provider

4.15 TemplateDocumentResponse

GetCertificatesProfileResponse				
No	**Name**	**Type**	**Presence**	**Description**
1	id	Integer	M	Id of the template document
2	name	String	M	Name of the template document.

5 RELATIVE OBJECT

5.1 RemarkError

RemarkError				
No	**Name**	**Type**	**Presence**	**Description**
1	language_name	String	M	Language name.
2	remark_message	String	M	Message of the error.

5.2 Package

Package				
No	**Name**	**Type**	**Presence**	**Description**
1	package_id	Integer	M	The ID of the package
2	package_name	String	M	The name of the package
3	package_owner	String	M	Defines the email of user
4	owner_name	String	M	The name of the user who created this package.
5	package_status	String	M	Status of the package. Possible values are: + enABLED

Package				
No	**Name**	**Type**	**Presence**	**Description**
				+DISABLED
6	unread	Boolean	M	
7	next_signer	String	M	Defines the name of the user who is the next signer to sign this package
8	next_signer_email	List<String>	M	List of email of the participant
9	created_at	String	M	Date of the package to know when it was created in ISO format
10	created_by	String	M	Name of the user who created this package
11	modified_at	String	M	Date of the package to know when it was modified in ISO format
12	modified_by	String	M	Name of the user who modified this package
13	access_duration	Access_duration_1	M	The object show the duration to access to this package.
14	decline	decline	M	The object show the decline of the package.

5.3 NextSigner

NextSigner				
No	**Name**	**Type**	**Presence**	**Description**
1	user_email	String	M	Email of the signer
2	signing_order	Integer	M	Order of the signer

5.4 Access_duration_1 (Get Packages request)

Access_duration_1				
No	**Name**	**Type**	**Presence**	**Description**
1	date_from	String	M	Date of the package to show when it valid.
2	date_to	String	M	Date of the package to show when it invalid.

5.5 Decline

Decline				
No	**Name**	**Type**	**Presence**	**Description**
1	reason	String	M	The reason of the package to show why it was declined.

Decline				
No	**Name**	**Type**	**Presence**	**Description**
2	declined_by	String	M	Defines the email of the user who declined this package.

5.6 Certify

Certify				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	String	M	True if certify signature is enabled for the document.
2	permission	String	M	It is the certify permissions to be applied on the PDF document when the first signature is created. The possible values are "NO_CHANGES_ALLOWED", "FORM_FILLING_ALLOWED" and "FORM_FILLING_WITH_ANNOTATIONS_ALLOWED".

5.7 DocumentVerification

DocumentVerification				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Field name of the field.
2	signer_name	String	M	Name of the signer.
3	signer_photo	String	M	Base64 image of the signer's avatar.
4	signer_photo_url	String	M	API endpoint to access the resource
5	signature_status	String	M	If the overall status of the signature is valid or not. Possible values are "VALID" or "INVALID".
6	signing_reason	String	M	Reason provided by the user while signing the field.
7	signing_location	String	M	Location entered by the user while signing the field.
8	contact_infomation	String	M	Contact information entered by the user while signing the field.
9	signing_time	String	M	Date and time of signing in 8601 format. Default timezone from SH Admin is followed the the time.
10	ltv	Boolean	M	True, if signature is LTV.
11	qualified	Boolean	M	True, if signatures are qualified.
12	certified	Boolean	M	True, if signatures are certified.

DocumentVerification				
No	**Name**	**Type**	**Presence**	**Description**
13	certify_permission	String	M	Permission level for certified digital signature.
14	timestamp_at	String	M	Date and time when signature was timestamped.
15	timestamp_authority	String	M	Authority by which the signature was timestamped.
16	subject_dn	String	M	Subject DN from the certificate used while signing the field.
17	issuer_dn	String	M	Issuers DN from the certificate used while signing the field.
18	cert_valid_from	String	M	Date and time from which the certificate is valid.
19	cert_valid_to	String	M	Date and time to which the certificate is valid.
20	signature_type	String	M	Type of signatures, possible values are "PADES_PART2" or "PADES_PART4".
21	signature_application	String	M	Application name from where the field was signed.
22	signature_algorithm	String	M	Signature algorithm used while signing the field.
23	signed_hash	String	M	Hash of the document that was signed in respective signature.
24	display	Boolean	M	Visibility of the signature field.
25	page_number	Integer	M	Page number of the signature field
26	error_message	String	O	Returns error in case verification fails.

5.8 PackageVerification

PackageVerification				
No	**Name**	**Type**	**Presence**	**Description**
1	document_id	Integer	M	The ID of the document containing verification results of respective fields.
2	fields	documentVerification	M	Data verification of the field

5.9 Document

Document				
No	**Name**	**Type**	**Presence**	**Description**
1	document_id	Integer	M	ID of the newly created document.
2	document_name	String	M	The name of the document.
3	document_order	Integer	M	
4	document_type	String	M	Type of the document e.g. "PDF".
5	document_width	Integer	M	Width of the document in PDF format.
6	document_height	Integer	M	Height of the document in PDF format.
7	document_source	String	M	
8	document_pages	Integer	M	Total pages of the document.
9	form_field	Boolean	M	True if document has form fields.
10	lock_form_fields	Boolean	M	True if locking of form fields with the last signature is enabled.
11	created_at	String	M	Date of the decline to know when it was created in ISO format
12	created_by	String	M	Name of the user who created this decline
13	modified_at	String	M	Date of the decline to know when it was modified in ISO format
14	modified_by	String	M	Name of the user who modified this decline
15	certify	certify	O	Certified signature settings for the document.
16	template			

5.10 Workflow

Workflow				
No	**Name**	**Type**	**Presence**	**Description**
1	workflow_type	String	M	Type of the workflow, there are four types of workflows supported in the application. Possible values are "SERIAL", "PARALLEL",

Workflow				
No	**Name**	**Type**	**Presence**	**Description**
				"INDIVIDUAL" and "CUSTOM".
2	continue_on_decline	Boolean	M	Data verification of the field True, if workflow needs to be continued even after a recipient declines at his turn.
3	workflow_status	String	M	Processing status of the workflow. Possible values are here
4	workflow_state	String	M	State of the workflow (note based on user). Possible values are here
4	workflow_mode	String	M	Mode of the workflow, there are three types of workflow modes supported in application. Possible values are "ONLY_ME", "ME_AND_OTHERS" and "ONLY_OTHERS"
5	message	String	M	Any custom string message that is to be sent to all the recipient of the workflow by the document owner.
6	read_only	Boolean	M	If any template applied on the documents in this workflow is read only or locked template then the workflow is read only. SigningHub will not allow the end users to make any changes to this workflow in draft state and this workflow is to be shared as it is.
7	post_process	Object	M	
8	comments	Boolean	M	If this workflow have an comment => True
9	deadline_at	String	O	Deadline of the workflow
10	category_id	Integer	O	Id of the Category

Workflow				
No	**Name**	**Type**	**Presence**	**Description**
11	details	List<WorkflowDetail>	O	An array of the details

5.11 User

User				
No	**Name**	**Type**	**Presence**	**Description**
1	order	Integer	M	Order of the recipient in the workflow.
2	user_name	String	M	Name of the recipient if recipient is not a group. If recipient is a placeholder it will contain the name of the placeholder.
3	user_email	String	M	Email address of the recipient if recipient is not a group or placeholder.
4	user_photo_url	String	M	API endpoint to access the resource, This will be provided only for main signers. e.g it will be null for group/delegator/gatekeeper etc. This URL does not make sure that signer image is exist. If image exist it will be provided by hitting the defined url otherwise it will be an empty string.
5	group_name	String	M	Name of the group if recipient is a group.
6	group_member	List<String>	M	List of all the email addresses and names of the users.
7	delegator	String	M	Email address of the user who is delegator to this recipient.
8	role	String	M	Role of the recipient i.e., "SIGNER", "REVIEWER", "EDITOR","CARBON_COPY" or "INPERSON_HOST".
9	process_status	String	M	Document processing status for the recipient. Possible values are "UN_PROCESSED", "IN_PROGRESS", "SIGNED",

User				
No	**Name**	**Type**	**Presence**	**Description**
				"REVIEWED", "DECLINED", "EDITED" or "INVALID"
10	processed_on	String	M	Date and time on which the document was processed.
11	processed_as	String	M	User may processed the field as COLLABORATOR, DELEGATOR, GROUP_MEMBER or OWNER.
12	processed_by	String	M	Email address of the user who processed the document
13	reason	String	M	Reason provided by the user when declining, approving or submitting a document
14	placeholder	String	M	Placeholder text if the recipient is a placeholder.
15	permission		M	Permissions for the recipient set by the owner of the document package.
16	authentications		M	Authentications object with the details of any authentications and access securities configured for the recipient.
17	reminder		M	Reminder object with the details of reminder settings
18	signing_order	Integer	M	Order in which the workflow will be signed by the recipients. This signing order is important when workflow type is set to "CUSTOM".
19	user_national_id	String	M	National identity number of the user. This helps to identify user in the workflow
20	guest_user	Boolean	M	True if this user is a guest
21	email_language_code	String	M	Email language code
22	electronic_seal		M	
23	invitation_time	String	M	Date time when the user has been invited into Workflow
24	company_name	String	M	Name of the company
25	assigned_field	List<assignedField>	O	The array of assigned field belongs to the user

5.12 Reminder

Reminder				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Integer	M	True, if reminder settings are to be enabled..
2	frequency	String	M	Reminder Frequency. Possible Values are DAYS | HOURS
3	remind_after	Integer	M	Required, in case of enabled property will true. The number of days after which the first reminder would be sent to workflow user.
4	keep_reminding_after	Integer	M	Required, in case of enabled property will true. The number of days after which the subsequent reminders would be sent to workflow user
5	total_reminders	Integer	M	Required, in case of enabled property will true. The number of subsequent reminders would be sent to workflow user.

5.13 Action

Action				
No	**Name**	**Type**	**Presence**	**Description**
1	log_id	String	M	ID of an action performed on the document
2	date_time	String	M	Date and time when the action was performed.
3	action_type	String	O	Action name
4	user_email	String	O	Email of the user who performed the action
5	user_name	String	O	Name of the user who performed the action.
6	enterprise_name	String	O	The name of Enterprise to which the user belongs. If the user doesn't belong to an enterprise, then this element is not present.
7	information	information	M	Data information

Action				
No	**Name**	**Type**	**Presence**	**Description**
8	application_name	String	O	Name of the application

5.14 Information

Information				
No	**Name**	**Type**	**Presence**	**Description**
1	detail	String	M	The detail String that show action detail
2	icon	String	M	Icon of the action

5.15 Comment/Message

Comment/Message				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	Id of the Comment
2	text	String	M	Workflow Comment text
3	date	String	M	Date when the comment has been created
4	private	Boolean	M	Is this comment is private
5	read	Boolean	M	Is this comment can read
6	sender	sender	M	Define who send the message

5.16 Sender

Sender				
No	**Name**	**Type**	**Presence**	**Description**
1	name	String	M	Name of the user who create this comment
2	email	String	M	Email of the user who create this comment
3	photo_url	String	M	Photo of the user who create this comment

5.17 Authentication (for Workflow User Authentication)

Authentication				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M	True, if authentication is enabled for the package.
2	password	password	O	Password authentication object.
3	sms_otp	sms	O	SMS OTP authentication object.

5.18 Password

Password				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M	True, if password authentication is enabled for the package.

5.19 Sms

Sms				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M	True, if SMS OTP authentication is enabled for the package.
2	otp_length	Integer	O	Length of OTP
3	retry_duration	Integer	O	Duration to retry
4	mobile_number	String	O	Mobile number of the recipient. Mobile number is needed to send the SMS to the recipient for the authentication

5.20 Authentication_Signing (for Workflow User Authentication)

Authentication_Signing				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M	True, if authentication is enabled for the package.
2	sms_otp	sms	O	SMS OTP authentication object.

5.21 Access_duration (for Workflow User Authentication)

Access_duration				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M	True, if access duration security is enabled for the package.
2	duration_by_date	durationByDate	M/O	Duration by date object with the details of duration in dates.
3	duration_by_days	durationByDays	M/O	Date from where the access is allowed for the recipient.

5.22 DurationByDate

DurationByDate				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M/O	True if access security is enabled for a duration by date and time.
2	accessible	Boolean	O	True if the package can be accessed
3	duration	durationDays	M/O	Duration object with the details of duration in to and from dates.

5.23 DurationByDays

DurationByDays				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M/O	True, if access security is enabled for a duration by number of days.
2	accessible	Boolean	O	True if the package can be accessed
3	duration	durationDays	M/O	Duration object with the details of total days.

5.24 DurationDays

DurationDays				
No	**Name**	**Type**	**Presence**	**Description**
1	total_days	Integer	O	Total number of days for which the package will be accessible to the recipient after receiving the package.

5.25 DurationDate

DurationDate				
No	**Name**	**Type**	**Presence**	**Description**
1	start_date_time	String	O	Date and time from where the package will be accessible to the recipient.
2	end_date_time	String	O	Date and time after which the package will not be accessible to the recipient.

5.26 Permission

Permission				
No	**Name**	**Type**	**Presence**	**Description**
1	print	Boolean	M	True, if printing is allowed for this recipient.
2	download	Boolean	M	True, if download is allowed.
3	add_text	Boolean	M	True, if add text annotation on the document is allowed.
4	change_recipients	Boolean	M	True, if the recipient on the current order can change other recipients in the workflow after workflow is shared.
5	add_attachment	Boolean	M	True, if attachments and merging of PDF documents is allowed.

5.27 Dimension

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	x	Float	M	Left location of the field in pixel.
5	y	Float	M	Top location of the field in pixel.
6	width	Float	M	Width of the field in pixel
7	height	Float	M	Height of the field in pixel.

5.28 FieldAuthentication

Response Attributes				
No	**Name**	**Type**	**Presence**	**Description**
1	error_code	String	M	Error code identifying the failure.
2	error_description	String	M	Detailed description of the error.
3	message	String	M	Human-readable error message.
4	enabled	Boolean	M	True, if authentication is enabled for the field
5	otp	otp	O	OTP Authentication Object
6	totp			

5.29 Otp

Otp				
No	Name	Type	Presence	Description
1	otp.enabled	Boolean	M	True, if SMS/Email OTP Authentication is enabled for the field
2	otp.mobile_number	String	M	Mobile number of the recipient to which the field is assigned

5.30 Font

Font				
No	Name	Type	Presence	Description
1	name	String	O	Name of the font selected for the text field. Possible values are here
2	size	Integer	O	Size of the font selected for the text field. Possible values are 8, 10, 12, 14, 16, 18, 20
3	embedded_size	Integer	O	Size of the font in the original PDF document.

5.31 AlignmentOption

AlignmentOption				
No	Name	Type	Presence	Description
1	horizontal_alignment	String	O	Horizontal alignment of the field or the text. Possible values are: + LEFT + CENTER + RIGHT
2	vertical_alignment	String	O	Vertical alignment of the field or the text. Possible values are: + TOP + MIDDLE + BOTTOM
3	alignment	String	O	Both Horizontal and Vertical. Format like this: {vertical}_{horizontal } Example: + MIDDLE_LEFT + TOP_CENTER

AlignmentOption				
No	**Name**	**Type**	**Presence**	**Description**
				Note: If you change any parameter inside Alignment Option => The new variable will be generated to fit (alignment is priority)

5.32 SignatureFieldAttribute

SignatureFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field.
2	page	Integer	M	Page to define where the field embedded at.
3	dimension	dimension	M	Dimension of the field.
4	visible_enabled	Boolean	M	Show the field if this flag is true.
5	level_of_assurance	List<String>	O	Level of the signature. Possible values are: + cades signature + electronic signature (default)
6	verification	verificationData	O	Data of the signature field to define more information (lock field, …)
7	required	Object	O	The object to show required in your application.
8	suffix	String	O	Suffix of the field.
9	remark	Object	O	Remark in your application
10	process_status	String	O	Status of the field
11	processed_on	String	O	Date when the field processed in. Based on the ISO 8601 standard
12	processed_by	String	O	The user that processed this field

5.33 VerificationData

VerificationData				
No	**Name**	**Type**	**Presence**	**Description**
1	signature_name	String	M	Signature name of the signature
2	signing_location	String	M	Signing location to show where the signature has been signed
3	signing_reason	String	M	Status of the document.
4	image_enabled	Boolean	M	Enabled if the signature is an image
5	signature_status	String	M	Status of the signature. Possible values are: + INVALID + VALID
6	signing_time	Integer	M	Time when the signature has been signed
7	ltv	Boolean	M	The flag to show LTV is enabled or not
8	qualified	Boolean	M	The flag to show signature is qualified or not
9	certified	Boolean	M	The flag to show signature is certified or not
10	subject_dn	String	M	Subject DN data of the signature
11	issuer_dn	String	M	Issuer DN data of the signature
12	cert_valid_from	Integer	M	Time when the certificate of the signature is valid from
13	cert_valid_to	Integer	M	Time when the certificate of the signature is valid to
14	signature_type	String	M	Type of the signature
15	signature_algorithm	String	M	Algorithm to sign the signature. Example: RSA, ECDSA,…
16	signed_hash	String	M	The hash algorithm. Example: SHA1, SHA256,…
17	signing_time_iso	String	M	Signing time of the signature in ISO format

VerificationData				
No	**Name**	**Type**	**Presence**	**Description**
18	cert_valid_from_iso	String	M	Certificate valid time of the signature in ISO format
19	cert_valid_to_iso	String	M	Certificate valid time of the signature in ISO format
20	issuer_dn_object	issuerDNObject	M	Data details of the issuer DN
21	lock_action	String	O	To know that the field is lock action after signed it. Possible values are here
22	lock_permission	String	O	To know that the field is lock permission after signed it. Possible values are here

5.34 TextFieldAttribute

TextFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field.
2	page	Integer	M	Page to define where the field embedded at.
3	dimension	dimension	M	Dimension of the field.
4	visible_enabled	Boolean	M	Show the field if this flag is true.
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true
6	color	String	O	Color of the text. Possible values are here
7	align_option	alignmentOption	O	Alignment object to show the position of the text.
8	value	String	O	Data of the field.
9	multiline	Boolean	O	The flag to define if the field can have multiple line. Default is false.
10	max_length	Integer	O	The number of the length in the field.

TextFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
11	format_type	String	O	Format type of the field. Possible values are: + ALPHANUMERIC + NUMBER + TEXT + EMAIL + TIME + DATE
12	font	font	O	Font of the text in the field.
13	place_holder	String	O	Place holder of the field.
14	tool_tip_text	String	O	To show tool tip text of the field.
15	type	String	M	The type of the text field. Possible values are: + TEXTBOX + NAME + EMAIL + JOBTITLE + COMPANY + TEXTFIELD + TEXTAREA + NUMBER + MULTILINE + LABEL + DOCUMENTID + LOCATION
16	required	Object	O	The object to show required in your application.
17	suffix	String	O	Suffix of the field.
18	remark	Object	O	Remark in your application
19	process_status	String	O	Status of the field
20	processed_on	String	O	Date when the field processed
21	processed_by	String	O	The user that processed this field

5.35 CheckboxFieldAttribute

CheckboxFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field.
2	page	Integer	M	Page to define where the field embedded at.
3	dimension	dimension	M	Dimension of the field.
4	visible_enabled	Boolean	M	Show the field if this flag is true.
5	read_only	Boolean	O	The flag to define if the field can be interact. Default is true.
6	value	String	O	Data of the field (“true” or “false)
7	font	font	O	Font of the text in the field.
8	align_option	alignmentOption	O	Alignment object to show the position of the text.
9	tool_tip_text	String	O	To show tool tip text of the field.
10	multiple_checked	Boolean	O	The flag to define if the field can be have more than 2 check in one group.
11	checked	Boolean	O	The flag to define if the checkbox field is checked.
12	group_name	String	O	Name of the group (one group can have multiple checkbox field).
13	check_box_type	String	O	Type of the checkbox. Possible values are: + CHECK/Check/check + CIRCLE/Circle/circle + CROSS/Cross/cross + DIAMOND/Diamond/diamond + SQUARE/Square/square + STAR/Star/star.
14	required	Object	O	The object to show required in your application.
15	suffix	String	O	Suffix of the field.

CheckboxFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
16	remark	Object	O	Remark in your application
17	process_status	String	O	Status of the field
18	processed_on	String	O	Date when the field processed
19	processed_by	String	O	The user that processed this field

5.36 QRFieldAttribute

QRFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field.
2	page	Integer	M	Page to define where the field embedded at.
3	dimension	dimension	M	Dimension of the field.
4	visible_enabled	Boolean	M	Show the field if this flag is true.
5	value	String	O	The data of QR Code. Note: If you send data in String, the FPS will generate QRCode based on your data.
6	is_transparent	Boolean	O	The flag to define if the QR Code background is transparent.
7	image_qr	String	O	Image data of the QR Code (when you have and qr image, just send it with this parameter).
8	required	Object	O	The object to show required in your application.
9	suffix	String	O	Suffix of the field.
10	remark	Object	O	Remark in your application
11	process_status	String	O	Status of the field

QRFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
12	processed_on	String	O	Date when the field processed
13	processed_by	String	O	The user that processed this field

5.37 InitialFieldAttribute

InitialFieldAttribute				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Name of the field.
2	page	Integer	M	Page to define where the field embedded at.
3	dimension	dimension	M	Dimension of the field.
4	visible_enabled	Boolean	M	Show the field if this flag is true.
5	image	String	O	Image data of the Initial field.
6	required	Object	O	The object to show required in your application.
7	suffix	String	O	Suffix of the field.
8	remark	Object	O	Remark in your application
9	process_status	String	O	Status of the field
10	processed_on	String	O	Date when the field processed
11	processed_by	String	O	The user that processed this field

5.38 RSSPService

RSSP Service				
No	**Name**	**Type**	**Presence**	**Description**
1	host_url	String	M/O	Contains url of Signing Server
2	client_id	String	M/O	Client id of the RSSP

RSSP Service				
No	**Name**	**Type**	**Presence**	**Description**
3	authentication_required	Boolean	M/O	True if client_secret is required by RSSP
4	authorization_required	Boolean	M/O	True if access to authorization servers is restricted
5	auth_type	String	M/O	Configured service authorization mechanisms for CSC signing server in its connector. Possible values are AUTHORIZATION_CODE, CLIENT_CREDENTIALS
6	rssp_rp_name	String	M/O	Relying Party name of the connector.
7	rssp_rp_user	String	M/O	Relying Party user of the connector.
8	signing_server	String	M	Name of the signing Server
9	connector_name	String	M	Name of the Connector that the signing Server belongs to

5.39 Owner(Package Details)

Owner				
No	**Name**	**Type**	**Presence**	**Description**
1	name	String	M	Name of the owner
2	email	String	M	Email of the owner

5.40 Document(Package Details)

Document				
No	**Name**	**Type**	**Presence**	**Description**
1	id	String	M	ID of the document
2	name	String	M	Name of the document
3	created_at	String	M	Date and time when the document was uploaded in ISO format
4	created_by	String	M	Name of the user who uploaded this document
5	modified_at	String	O	Date and time when the document was last modified in ISO format

Document				
No	**Name**	**Type**	**Presence**	**Description**
6	modified_by	String	O	Name of the user who modified this document
7	size	Integer	M	Size if the document in bytes
8	type	String	M	Type of the document e.g. "PDF".
9	source	String	O	Identifies where the document was uploaded

5.41 Authentication(SigningRequest)

Authentication				
No	**Name**	**Type**	**Presence**	**Description**
1	mechanism	String	M	Mechanism of Signing Request
2	password	String	O	Password of user
3	token	String	O	Token of user
4	user_identifier	String	O	Data of user

5.42 Authentication (Workflow User Authentication)

Authentication				
No	**Name**	**Type**	**Presence**	**Description**
1	enabled	Boolean	M	True, if authentication is enabled for the package.
2	password	password	O	Password authentication object.
3	sms_otp	sms	O	SMS OTP authentication object.

5.43 UserOfEnterprise

UserOfEnterprise				
No	**Name**	**Type**	**Presence**	**Description**
1	user_id	Integer	M	ID of the user

UserOfEnterprise				
No	**Name**	**Type**	**Presence**	**Description**
2	created_at	String	M	Date and time when the user was created in ISO format
3	user_name	String	M	User name of the user
4	enterprise_role	String	M	Role name of the user
5	mobile_number	String	O	Mobile number of the user
6	job_title	String	O	Job title of the user
7	company_name	String	O	Company name of the user
8	status	String	M	Status of the user
9	enabled	Boolean	M	True, if user is enabled and false if user is not enabled by the application administrators

5.44 Group

Group				
No	**Name**	**Type**	**Presence**	**Description**
1	id	Integer	M	Group id
2	group_name	String	M	Name of the group
3	group_members	List<groupMember>	M	The array of the member

5.45 Member

Member				
No	**Name**	**Type**	**Presence**	**Description**
1	user_email	String	M	Email address of the group member
2	user_name	String	M	User name of the group member

5.46 Role

Role				
No	**Name**	**Type**	**Presence**	**Description**
1	id	Integer	M	Id of the role
2	name	String	M	Name of the role
3	description	String	M	Description
4	default	Boolean	M	Default
5	user_count	Integer	M	User count

5.47 Invitation

Invitation				
No	**Name**	**Type**	**Presence**	**Description**
1	enterprise_id	Integer	M	Id of enterprise from which the invitation is sent.
2	enterprise_name	String	M	Name of enterprise from which the invitation is sent.
3	enterprise_role	String	M	Enterprise role in which the user is invited.
4	invited_by	String	M	Email address of the member who invited the user.

5.48 ServicePlan

ServicePlan				
No	**Name**	**Type**	**Presence**	**Description**
1	name	Boolean	M	True, if access duration security is enabled for the package.
2	type	Object	O	Duration by date object with the details of duration in dates.
3	features	Boolean	M	True if access security is enabled for a duration by date and time.
4	constraints	constraints	M	Constraints of usage according to the service plan.

ServicePlan				
No	**Name**	**Type**	**Presence**	**Description**
5	setting	setting	M	Data setting of the service plan
6	billing	billing	M	Billing object for the service plan.

5.49 Constraints

Constraints				
No	**Name**	**Type**	**Presence**	**Description**
1	users	Integer	M	Total number of users allowed in the service plan
2	signatures	Integer	M	Total signatures allowed
3	advanced_electronic_signatures	Integer	M	True if access security is enabled for a duration by date and time.
4	high_trust_advanced_signatures	Integer	M	Total High Trust Advanced Signatures allowed
5	qualified_electronic_signatures	Integer	M	Total Qualified Electronic Signatures allowed.
6	electronic_seals	Integer	M	Total Electronic Seals allowed.
7	advanced_electronic_seals	Integer	M	Total Advanced Electronic Seals allowed.
8	qualified_electronic_seals	Integer	M	Total Qualified Electronic Seals allowed
9	simple_electronic_signatures	Integer	M	Total simple electronic signatures allowed.
10	storage	Integer	M	Total allowed storage for documents.
11	workflows	Integer	M	Total number of workflows allowed in the service plan.
12	max_upload_size	Integer	M	Maximum file size allowed to be uploaded.
13	templates	Integer	M	Total number of templates allowed to be created.

5.50 Setting

Setting				
No	**Name**	**Type**	**Presence**	**Description**
1	pdf_compliant	Boolean	M	True if PDF Compliant
2	signing_keys_with_password	Boolean	O	True if signing certificate is protected by the user's provided password.
3	signature_type	String	O	Signature types allowed in the service plan for the user. Possible values are "ELECTRONIC_SIGNATURE", "DIGITAL_SIGNATURE" and "ALL"
4	authorized_signing	Boolean	M	True if authorized remote signing is enabled.
5	sms_otp	Boolean	M	True if SMS OTP are enabled for the service plan.
6	email_otp	Boolean	M	True if Email OTP are enabled for the service plan.
7	sms_otp_length	Integer	M	Character count of OTP to be generated for authentication.
8	sms_otp_retry_duration	Integer	M	Duration in seconds for which the retry button of OTP should be disabled before sending a new OTP
9	workflow_envidence	String	O	Level of workflow evidence details to be recorded for the account. Possible values are "BASIC", "DETAILED"
10	auto_archiving	Boolean	M	True if auto archiving of the document is turned on.
11	auto_deletion	Boolean	M	True if auto deletion of the documents is turned on based on configured period.

5.51 Billing

Billing				
No	**Name**	**Type**	**Presence**	**Description**
1	mode	String	M	Billing mode can be "NONE | ONLINE | OFFLINE".
2	payment_type	String	M	Payment type can be "REGULARLY | PAYG".

Billing				
No	**Name**	**Type**	**Presence**	**Description**
3	price	String	M	Price of the plan. In case of regular payment the price is monthly. In case of PAYG the price is for year.
4	yearly_price	String	M	In case of yearly price defined for a regular paid plan, yearly_price will have the value.
5	next_billing_date	String	M	Next Billing date

5.52 Enterprise

Enterprise				
No	**Name**	**Type**	**Presence**	**Description**
1	enterprise_id	Integer	M	Id of the enterprise to which the user belongs.
2	enterprise_name	String	M	Name of the enterprise to which the user belongs.
3	owner	String	M	Name of enterprise owner.
4	owner_email	String	M	Email address of the enterprise owner.
5	mobile_number	String	M	Mobile number used for contacting enterprise.
6	support_email	String	M	Support contact email for enterprise

5.53 Consumer

Consumer				
No	**Name**	**Type**	**Presence**	**Description**
1	consumed	Integer	M	Consumed quota by the account so far.
2	allowed	Integer	M	Total allowed quota by the service plan.

5.54 UserActivity

UserActivity				
No	**Name**	**Type**	**Presence**	**Description**
1	log_id	Integer	M	ID for the action performed by the user.
2	date_time	String	M	Date and time of the action.
3	action_type	String	M	Type of action performed by the user. Possible values are different Enumerations with exact translation of the action in the attribute action_type_label.
4	action_type_label	String	M	Language translation of action_type.
5	user_email	String	M	Email address of the user.
6	user_name	String	M	Name of the user.
7	enterprise_name	String	M	Name of enterprise if the user belongs to an enterprise.
8	information	information	M	Data of Information

5.55 Information

Information				
No	**Name**	**Type**	**Presence**	**Description**
1	type	String	M	Type of action
2	type_label	String	M	Language translation for type attribute.
3	value	String	M	Value of the type attribute.
4	value_label	String	M	Language translation for value attribute.

5.56 General

General				
No	**Name**	**Type**	**Presence**	**Description**
1	user_email	String	M	Email address of the logged in user
2	user_name	String	M	User name of the logged in user
3	job_title	String	M	Job title of the logged in user
4	company_name	String	M	Company name of the logged in user
5	mobile_number	String	M	Mobile number of the logged in user
6	enterprise_role	String	M	Name of the enterprise role that the logged in user belongs to

5.57 Security

Security				
No	**Name**	**Type**	**Presence**	**Description**
1	question	String	M	Security question of the logged in user

5.58 Locale

Locale				
No	**Name**	**Type**	**Presence**	**Description**
1	country	String	M	Country name of the logged in user
2	timezone	String	M	Time zone of the logged in user
3	language	String	M	Language of the logged in user

5.59 Contact

Contact				
No	**Name**	**Type**	**Presence**	**Description**
1	user_first_name	String	M	First name of the contact

Contact				
No	**Name**	**Type**	**Presence**	**Description**
2	user_email	String	M	Email address of the contact.
3	contact_id	Integer	M	ID of the contact.
4	user_last_name	String	O	Last name of the contact
5	position	String	O	Position of the contact
6	company_name	String	O	Company name of the contact
7	personal_code	String	O	Personal code of the contact
8	mobile_number	String	O	Mobile number of the contact

5.60 Account

Account				
No	**Name**	**Type**	**Presence**	**Description**
1	user_name	String	M	User's name
2	user_email	String	M	User's email address
3	service_plan	String	M	User's service plan name
4	enterprise_id	Integer	M	User's enterprise id
5	enterprise_name	String	M	User's enterprise name
6	created_on	String	M	Date on which account is created

5.61 Connector

Connector				
No	**Name**	**Type**	**Presence**	**Description**
1	connector_name	String	M	Name of the connector
2	provider	String	M	Name of the provider

Connector				
No	**Name**	**Type**	**Presence**	**Description**
3	logo	String	O	Image base64 of the connector
4	data	String	O	Data information of the connector
5	status	String	O	Status of the connector

5.62 Address Book

AddressBook				
No	**Name**	**Type**	**Presence**	**Description**
1	address_book_name	String	M	Name of the address book
2	contacts	List<contact>	M	The list of contact that belongs to the address book

5.63 WorkflowDetail

WorkflowDetail				
No	**Name**	**Type**	**Presence**	**Description**
1	filter_level	String	O	Level of the certificate to fillter. Ex: "ALL", "AES"

5.64 Category

Category				
No	**Name**	**Type**	**Presence**	**Description**
1	category_id	Integer	M	Id of the category
2	category_name	String	M	Name of the category
3	category_icon	String	M	Color of the icon
4	category_parent_id	Integer	O	Parent id of the cat

5.65 SignatureAppearance

SignatureAppearance				
No	**Name**	**Type**	**Presence**	**Description**
1	appearance_id	Integer	M	Id of the appearance
2	metadata	metadataSignature	M	Metadata of the appearance
3	credential_configuration	credentialConfiguration	M	Data of signature of the appearance

5.66 MetadataSignature

MetadataSignature				
No	**Name**	**Type**	**Presence**	**Description**
1	signing_reason	String	O	Reason to show in appearance
2	signing_location	String	O	Location to show in appearance
3	signer_name	String	O	Name of the signer to show in appearance
4	signing_date	String	O	Data to show in appearance
5	signing_logo	String	O	Logo to show in appearance
6	signing_distinguished_name	String	O	Distinguished name to show in appearance
7	itext_version	String	O	Version of iText to show in appearance
8	signing_labels	String	O	Labels to show in appearance
9	align_option	String	O	Aligment of the text in appearance. Possible values are here
10	remark	String	O	Remark
11	hand_signature_image	String	O	Hand signature image of the appearance

5.67 CredentialConfiguration

CredentialConfiguration				
No	**Name**	**Type**	**Presence**	**Description**
1	signing_server	String	M	Name of the signing Server
2	connector_name	String	M	Name of the connector
3	document_type	String	M	Type of the document. Possible values are here
4	value	String	M	Value of the document
5	credential_id	String	M	Credential id of the signer
6	appearance_design	String	M	Appearance Design of the Credential. Possible values are here
7	icon	String	O	Icon of the title

5.68 AssignedField

AssignedField				
No	**Name**	**Type**	**Presence**	**Description**
1	field_name	String	M	Field name
2	document_id	Integer	M	Id of the document

5.69 CredentialInfo

CredentialInfo				
No	**Name**	**Type**	**Presence**	**Description**
1	mode	String	M	Authorize mode of the credential. Possible value are: + EXPLICIT_OTP_EMAIL + EXPLICIT_OTP_SMS + EXPLICIT_PIN + IMPLICIT_TSE
2	status	String	M	Status of the credential

CredentialInfo				
No	**Name**	**Type**	**Presence**	**Description**
3	cert	String	O	Certificate data in base64 format
4	issuer_dn	List<String>	O	This is a common format for representing X.509 Distinguished Names (DNs) in a key-value pair format. Example:["C": "VN", "ST": "Ho Chi minh",…]
5	subject_dn	List<String>	O	This is a common format for representing X.509 Distinguished Names (DNs) in a key-value pair format. Example:["C": "VN", "ST": "Ho Chi minh",…]
6	valid_from	String	O	This field specifies the date and time when the certificate becomes valid (in ISO format)
7	valid_to	String	O	This field specifies the date and time when the certificate expires. After this date (in ISO format)

5.70 PersonalInformation

PersonalInformation				
No	**Name**	**Type**	**Presence**	**Description**
1	personal_number	String	M	Personal number of the user
2	full_name	String	M	Full name of the user
3	birth_date	String	M	Birth date of the user
4	gender	String	M	Gender of the user
5	nationality	String	M	Nationality of the user

PersonalInformation				
No	**Name**	**Type**	**Presence**	**Description**
6	ethnic	String	M	Ethnic of the user
7	religion	String	M	Religion of the user
8	place_of_origin	String	M	Place of origin of the user
9	personal_identification	String	M	Personal identification of the user
10	issuance_date	Stringh	M	Issuance date of the user
11	expiry_date	String	M	Expiry date of the user
12	dg1_value	String	M	DG1 value of the user
13	dg2_value	String	M	DG2 value of the user
14	subject_id	String	M	Subject id
15	identity_document_type	String	M	Type of the identity document
16	email	String	M	Email of the user
17	mobile	String	M	Mobile number of the user
18	portrait	String	M	Portrait image of the user

5.71 Items

Items				
No	**Name**	**Type**	**Presence**	**Description**
1	field	String	M	This parameter will define the name of the field
2	type	Integer	M	This parameter will define the type of that field. Possible values are: + 1 : String (Text) + 2 : Boolean + 3 : Int + 4 : Date (TimeStamp.UNIX)

Items				
No	**Name**	**Type**	**Presence**	**Description**
				+ 5 : Binary / Base 64 (for file/image) + 6 : Text Bold + 7 : Choice + 8 : Table + 9 : File + 10: URL + 11: ID Picture with 4 Labels + 12: Non-Editable Element + 13: Empty **See this example for more details: example
3	value	Object	M	Data of the field. The structure based on these example
4	remark	String	O	Remark of the field
5	mandatory_enabled	Boolean	O	The flag to ensure that field is mandatory

5.72 ChooseItems

ChooseItems				
No	**Name**	**Type**	**Presence**	**Description**
1	default_item	String	M	Default item of the Field
2	items	List<chooseItem>	M	List of the item in Field

5.73 ChooseItem

ChooseItem				
No	**Name**	**Type**	**Presence**	**Description**
1	text	String	M	Text of the item
2	value	String	M	Value of the item

5.74 Date

Date				
No	**Name**	**Type**	**Presence**	**Description**
1	maximum_date	String	O	Maximum date of the field
2	date_format	String	O	Format date of the field
3	default_date	String	RC	Default date of the field
4	minimum_date	String	O	Minimum date of the field
5	default_date_enabled	Boolean	O	True if the field using default Date

5.75 NumericItems

NumericItems				
No	**Name**	**Type**	**Presence**	**Description**
1	default_value	Integer	RC	Default value of the field
2	maximum_value	Integer	O	Maximum value of the field
3	minimum_value	Integer	O	Minimum value of the field
4	unit_of_change	Integer	O	Unit of change of the field

5.76 File

File				
No	**Name**	**Type**	**Presence**	**Description**
1	file_extension	String	M	Extensio of the file/image
2	file_data	String	M	Image/File info in base64 format
3	file_name	String	M	Name of the file

5.77 Frame

Frame				
No	Name	Type	Presence	Description
1	background_rgbcode	String	O	Color Code of the background
2	border_rgbcode	String	O	Color Code of the Border
3	checked_rgbcode	String	O	Color Code of the Checked

5.78 Image

Image				
No	Name	Type	Presence	Description
1	image	String	O	Image data in base64 format
2	format	String	O	Format of the image

5.79 Template

Template				
No	Name	Type	Presence	Description
1	template_name	String	M	Name of template to be applied on the document.
2	read_only	Boolean	M	True if the applied template is read only. User will not be able to make any changes if a read only template is applied.

5.80 CertificateProfile

CertificateProfile				
No	Name	Type	Presence	Description
1	name	String	M	Name of the profile
2	remark	String	M	Remark of the profile

5.81 IssuingProvider

IssuingProvider				
No	**Name**	**Type**	**Presence**	**Description**
1	name	String	M	Name of the profile
2	remark	String	M	Remark of the profile

6 ENUMERATION

6.1 WorkflowMode

No	Name	Description
1	CUSTOM	The workflow allows for asynchronous signing, where signers can sign at their convenience without adhering to a specific sequence.
2	PARALLEL	The workflow enables concurrent signing, allowing multiple signers to sign simultaneously.
3	SERIAL	The workflow requires sequential signing, with signers signing one after another in a predetermined order.
4	INDIVIDUAL	None

6.2 WorkflowStatus

No	Name	Description
1	DRAFT	A preliminary version of the workflow that is still under development or review.
2	PENDING	The workflow is pending user action (signing, approval, etc.).
3	INPROGRESS	The workflow is being processed by other participant.
4	COMPLETED	The workflow has been fully executed and all required actions have been completed. All participants have signed and the workflow has reached its final state.
5	DECLINED	The workflow has been rejected and will not proceed further.
6	EXPIRED	This status indicates that the workflow has been prematurely ended due to an issue or problem.
7	SIGNED	The workflow has been signed by this user

No	Name	Description
8	EXPIRING	The workflow will expire in 7 days.

6.3 LevelOfAssurance

No	Name	Description
1	electronic signature	An electronic signature is a digital signature that authenticates the identity of a person and their intent to approve or endorse an electronic document
2	electronic seal	An electronic seal is a digital representation of an organization's official seal.
3	cades signature	CAdES is a standard for advanced electronic signatures. It's a framework for creating and verifying digital signatures that provide a high level of security and legal validity. CAdES signatures can include additional attributes like timestamping, non-repudiation, and revocation information.

6.4 LockAction

No	Name	Description
1	include	
2	exclude	
3	all	

6.5 LockPermission

No	Name	Description
1	FORM_FILLING_AND_ANNOTATION	When enabled this type -> The document can only be signed with the Signature Field. Otherwise, can append more Annotation/Stamp/Widget into it (not make the signature invalid)
2	FORM_FILLING	When enabled this type -> The document can only be signed with the Signature Field (cannot append any type of Annotation/Stamp/Widget)
3	NO_CHANGES_ALLOWED	When enabled this type -> The document cannot be changed by any type of action. One little change will make the signature become into “invalid”

6.6 AnnotationPosition

No	Name	Description
1	FIRST_PAGE_TOP	Signature will be placed at the top of the first page.
2	FIRST_PAGE_BOTTOM	Signature will be placed at the bottom of the first page
3	LAST_PAGE_TOP	Signature will be placed at the top of the last page.
4	LAST_PAGE_BOTTOM	Signature will be placed at the bottom of the last page.
5	CUSTOM	Signature will be placed based on the Dimensions

6.7 DocumentType

No	Name	Description
1	USERNAME	Type USERNAME in RSSP
2	PERSONAL-ID	Type PERSONAL-ID in RSSP
3	CITIZEN-IDENTITY-CARD	Type CITIZEN-IDENTITY-CARD in RSSP
4	BUDGET-CODE	Type BUDGET-CODE in RSSP
5	PASSPORT-ID	Type PASSPORT-ID in RSSP
6	TAX-CODE	Type TAX-CODE in RSSP
7	UUID	Type UUID in RSSP

6.8 SigningAlgorithm

No	Name	Description
1	RSA	RSA Signing Algorithm (Default)
2	ECDSA	ECDSA Signing Algorithm
3	DSA	DSA Signing Algorithm

6.9 HashingAlgorithm

No	Name	Description
1	SHA1	SHA1 Hashing Algorithm
2	SHA256	SHA256 Hashing Algorithm (Default)
3	SHA384	SHA384 Hashing Algorithm
4	SHA512	SHA512 Hashing Algorithm

6.10 AppearanceDesign

No	Name	Description
1	ADVANCED_ELECTRONIC_SIGNATURE	Type of the credential is Advanced electronic signature
2	ELECTRONIC_SEAL	Type of the credential is Electronic Seal
3	QUALIFIED_ELECTRONIC_SIGNATURE	Type of the credential is Qualified Electronic Signature
4	QUALIFIED_ELECTRONIC_SEAL	Type of the credential is Qualified Electronic Seal

6.11 AppearanceAlignment

No	Name	Description
1	LEFT	The text of appearance will align left
2	AUTO	The text of appearance will align auto
3	RIGHT	The text of appearance will align right

6.12 WorkflowState

No	Name	Description
1	DRAFT	A preliminary version of the workflow that is still under development or review.

No	Name	Description
2	PENDING	The workflow is waiting for the next action or approval.
3	INPROGRESS	The workflow is currently being processed or executed.
4	COMPLETED	The workflow has been fully executed and all required actions have been completed. All participants have signed and the workflow has reached its final state.
5	DECLINED	The workflow has been rejected and will not proceed further.
6	TERMINATED	This status indicates that the workflow has been prematurely ended due to an issue or problem.

6.13 FieldTypes

No	Name	Description
1	TEXTBOX	Default type of text field
2	NAME	Field for put name into
3	EMAIL	Field for put email into
4	JOBTITLE	Field for put job title into
5	COMPANY	Field for put company into
6	TEXTFIELD	Field for put text field into
7	TEXTAREA	Field for put text area field into
8	NUMBER	Field for put number into
9	MULTILINE	Field for put multiline into
10	LABEL	Field for put label into
11	DOCUMENTID	Field for put document id into
12	LOCATION	Field for put location into
13	IP_ADDRESS	Field for put ip address into
14	CLIENT_DETAILS	Field for put client details into

6.14 AuthorizeMode

No	Name	Description
1	EXPLICIT_OTP_EMAIL	Authorize RSSP via email
2	EXPLICIT_OTP_SMS	Authorize RSSP via SMS
3	EXPLICIT_PIN	Authorize RSSP via Pin code
4	IMPLICIT_TSE	Authorize RSSP via TSE Application

6.15 Role

No	Name	Description
1	SIGNER	Signs the workflow.
2	REVIEWER	Reviews and approves the workflow.
3	EDITOR	Edits the workflow.
4	INPERSON_HOST	This role needs to meet the host.
5	CARBON_COPY	This role will receive the document.

6.16 DocumentTypeForEID

No	Name	Description
1	CITIZEN_CARD	Type Citizen card in EID
2	PASSPORT	Type Passport in EID
3	DRIVER_LICENSE	Type Driver license in EID
4	IDENTITY_CARD	Type Identity card in EID
5	FACE_SCAN	Type Face scan in EID
6	FACE_FRAME	Type Face frame in EID

No	Name	Description
7	IDENTIFICATION	Type Identification in EID

6.17 Color

No	Name	Description
1	black	Color of the text is Black
2	blue	Color of the text is Blue
3	cyan	Color of the text is Cyan
4	dark_gray	Color of the text is Dark Gray
5	gray	Color of the text is Gray
6	green	Color of the text is Green
7	light_gray	Color of the text is Light Gray
8	magenta	Color of the text is Magenta
9	orange	Color of the text is Orange
10	pink	Color of the text is Pink
11	red	Color of the text is Red
12	white	Color of the text is White
13	yellow	Color of the text is Yellow

6.18 FontName

No	Name	Description
1	opensans_bold	Color of the text is Black
2	opensans_bold_italic	Color of the text is Blue

No	Name	Description
3	opensans_extrabold	Color of the text is Cyan
4	opensans_extrabolditalic	Color of the text is Dark Gray
5	opensans_italic	Color of the text is Gray
6	opensans_italic_variablefont	Color of the text is Green
7	opensans_light	Color of the text is Light Gray
8	opensans_lightitalic	Color of the text is Magenta
9	opensans_medium	Color of the text is Orange
10	opensans_mediumitalic	Color of the text is Pink
11	opensans_regular	Color of the text is Red
12	opensans_semibold	Color of the text is White
13	opensans_semibolditalic	Color of the text is Yellow
14	opensans_variablefont	
15	roboto_black	
16	roboto_bold	
17	roboto_thin	
18	roboto_regular	
19	d_arial	
20	d_times	
21	funkysignature_regular	
22	fz_jim_sintergate	
23	myriadpro_regular	

No	Name	Description
24	montserrat_black	
25	montserrat_black_italic	
26	montserrat_bold	
27	montserrat_bold_italic	
28	montserrat_extra_bold	
29	montserrat_extra_bold_italic	
30	montserrat_extra_light	
31	montserrat_extra_light_italic	
32	montserrat_italic	
33	montserrat_italic_variablefont	
34	montserrat_light	
35	montserrat_light	
36	montserrat_medium	
37	montserrat_medium_italic	
38	montserrat_regular	
39	montserrat_semibold	
40	montserrat_semibold_italic	
41	montserrat_thin	
42	montserrat_thin_italic	
43	montserrat_regular_otf	
44	font_times_new_roman	

No	Name	Description
45	svn_times_new_roman_2_bold_italic	
46	svn_times_new_roman_2_bold	
47	svn_times_new_roman_2_italic	
48	svn_times_new_roman_2	
49	svn_times_new_roman_bold_italic	
50	svn_times_new_roman_bold	
51	svn_times_new_roman_italic	
52	svn_times_new_roman	
53	times_new_roman_400	
54	times_new_roman_bold_italic	
55	times_new_roman_bold	
56	times_new_roman_italic	
57	times_new_roman	
58	times_new_roman_14	
59	times	

7 EXAMPLE

7.1 Items request

Type	Example
1 - String	{ "items":[{ "field": "Text Field",

Type	Example
	"type": 1, "value": "Value of field" }] }

2 - Boolean	{
	"items":[
	{
	"field": "Male",
	"type": 2,
	"value": true
	}
	]
	}

3 - Number	{
	"items":[
	{
	"field": "Age",
	"type": 3,
	"value": 18
	}
	]
	}

4 - Date	{
	"items":[
	{
	"field": "Date start",
	"type": 4,
	"value": "2023-12-15"
	}
	]
	}

5 – Base64(for file/image)	{
	"items":[
	{
	"field": "Photo",
	"type": 5,
	"value": "{Base_64_image}"
	}
	]
	}

6 – Text Bold	{ "items":[{ "field": "Text Bold", "type": 6,

Type	Example
	"value": "Testing" //if null, the field name will be chosen }] }

7 – Choice	{
	"items":[
	{
	"field": "Choice",
	"type": 7,
	"value": [
	{
	"element": "Nhan vien",
	"choice": false
	},{
	"element": "Truong Phong",
	"choice": true
	},{
	"element": "Giam Doc",
	"choice": false
	}
	]
	}
	]
	}

8 – Table	{
	"items":[
	{
	"field": "Table",
	"type": 8,
	"value": [
	//Row
	{
	"column_1": "A",
	"column_2": "B",
	"column_3": "C",
	"text": "mini text"
	}
	]
	}
	]
	}

9 – File	{ "items":[{ "field": "File1",

Type	Example
	"type": 9, "value": "{Base64_of_file}" "file_field": "randomString(1)", "file_format": "image/png", "file_name": "Hand.png" }] }

10 - URL	{
	"items":[
	{
	"field": "Link GoPaperless",
	"type": 10,
	"value": {
	"url": "https://uat-portal.qrypto.ee/portal/login/sign-in",
	"label": "Website"
	}
	]
	}

11 – ID Picture with 4 Labels	{
	"items":[
	{
	"field": "Photo",
	"type": 11,
	"value": {
	"label_1": "one",
	"label_2": "two",
	"label_3": "three",
	"label_4": "four",
	"file_data": "{Base64_of_file}"
	},
	"file_field": "fileA",
	"file_format": "image/png",
	"file_name": "hello.png"
	}
	]
	}

12 – Non-Editable Element	{
	"items":[
	{
	"field": "Non-Editable",
	"type": 12,
	"value": "Cannot edit this field"
	}
	]

Type	Example
	}
13 - Empty	