

Install and start for hydra cluster

0. Preparation

Before installing srcroot make sure that the essential modules are added and FairRoot, FairSoft is connected

```
module add CMake/v3.26.5 libexpat libxml2 GSL
```

```
source /cvmfs/bmn.jinr.ru/config/x86_64-alma9/cluster_config.sh
```

Installing the srcroot framework

- **Go to the installation directory**

Go to the directory where you want to install the srcroot software, e. g. home directory:

```
cd ~
```

- **Clone GIT repository**

• Clone GIT repository of the last developer srcroot version with HTTPS (read-only access, e.g. for unregistered users)

```
git clone -b main --recursive https://github.com/tatovullaev-lgtm/srcroot
```

- **Installation procedure for srcroot:**

• Set environment:

NOTE: By default, in the SetEnv.sh file SIMPATH points to /opt/fairsoft/install, and FAIRROOTPATH - /opt/fairroot/install directories. If you installed FairSoft or FairRoot to another directory, please, change SIMPATH and FAIRROOTPATH variables in the file ("export SIMPATH=[your FairSoft install path]" and "export FAIRROOTPATH=[your FairRoot install path]").

```
cd srcroot
```

```
mkdir build
```

```
. SetEnv.sh
```

• Build the framework:

```
cd build
```

```
cmake ..
```

```
make -j4  
. config.sh
```

Put relevant pathes in **start_srcroot_cluster.sh**

Running the srcroot

- Run “srcroot/start_srcroot_cluster.sh” every time you run terminal to work with srcroot