1N4242–1N4279B

TYPE	MATERIAL	REPLACEMENT	REF.	IDENTIFICATION	RECTIFIERS					ZENER DIODES			
					V_R (volts)	V_F (volts)	I_O (Amps)	I_R (mA)	I_{surge} (Amps)	V_Z (min)	V_Z (nom) * / V_Z (max)	Tol V_Z %	P_D
					SIGNAL DIODES					REFERENCE DIODES			
					PRV (volts)	V_F @ I_F (volts)		I_R	t_{rr} (μs)	TC %/°C	V_Z	T (min) °C	T (max) °C
1N4242	S			DS	40	1.0	20M	0.1N	2.0				
1N4243	S			DS	40	1.0	10M	0.1N	2.0				
1N4244	S			DS	10	1.0	20M	0.1*	0.75				
1N4245	S	1N4003	1N4001	R*	200	1.64	1.0	0.05	25				
1N4246	S	1N4004	1N4001	R*	400	1.64	1.0	0.05	25				
1N4247	S	1N4005	1N4001	R*	600	1.64	1.0	0.05	25				
1N4248	S	1N4006	1N4001	R*	800	1.64	1.0	0.05	25				
1N4249	S	1N4007	1N4001	R*	1000	1.64	1.0	0.05	25				
1N4250	S	1N4006	1N4001	R*	800		0.5	0.05	10				
1N4251	S	1N4007	1N4001	R*	1000		0.5	0.05	10				
1N4252	S			R*	1200		0.5	0.05	10				
1N4253	S			R*	1500		0.5	0.05	10				
1N4254	S	MR991A	MR990A	R*	1500	4.8	0.25	0.05	6.25				
1N4255	S	MR992A	MR990A	R*	2000	4.8	0.25	0.05	6.25				
1N4256	S	MR993A	MR990A	R*	2500	4.8	0.25	0.05	6.25				
1N4257	S	MR994A	MR990A	R*	3000	4.8	0.25	0.05	6.25				
1N4258	S	1N2970	1N2970	DZ							6.8*	20	10W
1N4258A	S	1N2970A	1N2970	DZ							6.8*	10	10W
1N4258B	S	1N2970B	1N2970	DZ							6.8*	5.0	10W
1N4259	S	1N2971	1N2970	DZ							7.5*	20	10W
1N4259A	S	1N2971A	1N2970	DZ							7.5*	10	10W
1N4259B	S	1N2971B	1N2970	DZ							7.5*	5.0	10W
1N4260	S	1N2972	1N2970	DZ							8.2*	20	10W
1N4260A	S	1N2972A	1N2970	DZ							8.2*	10	10W
1N4260B	S	1N2972B	1N2970	DZ							8.2*	5.0	10W
1N4261	S	1N2973	1N2970	DZ							9.1*	20	10W
1N4261A	S	1N2973A	1N2970	DZ							9.1*	10	10W
1N4261B	S	1N2973B	1N2970	DZ							9.1*	5.0	10W
1N4262	S	1N2974	1N2970	DZ							10*	20	10W
1N4262A	S	1N2974A	1N2970	DZ							10*	10	10W
1N4262B	S	1N2974B	1N2970	DZ							10*	5.0	10W
1N4263	S	1N2975	1N2970	DZ							11*	20	10W
1N4263A	S	1N2975A	1N2970	DZ							11*	10	10W
1N4263B	S	1N2975B	1N2970	DZ							11*	5.0	10W
1N4264	S	1N2976	1N2970	DZ							12*	20	10W
1N4264A	S	1N2976A	1N2970	DZ							12*	10	10W
1N4264B	S	1N2976B	1N2970	DZ							12*	5.0	10W
1N4265	S	1N2977	1N2970	DZ							13*	20	10W
1N4265A	S	1N2977A	1N2970	DZ							13*	10	10W
1N4265B	S	1N2977B	1N2970	DZ							13*	5.0	10W
1N4266	S	1N2979	1N2970	DZ							15*	20	10W
1N4266A	S	1N2979A	1N2970	DZ							15*	10	10W
1N4266B	S	1N2979B	1N2970	DZ							15*	5.0	10W
1N4267	S	1N2980	1N2970	DZ							16*	20	10W
1N4267A	S	1N2980A	1N2970	DZ							16*	10	10W
1N4267B	S	1N2980B	1N2970	DZ							16*	5.0	10W
1N4268	S	1N2982	1N2970	DZ							18*	20	10W
1N4268A	S	1N2982A	1N2970	DZ							18*	10	10W
1N4268B	S	1N2982B	1N2970	DZ							18*	5.0	10W
1N4269	S	1N2984	1N2970	DZ							20*	20	10W
1N4269A	S	1N2984A	1N2970	DZ							20*	10	10W
1N4269B	S	1N2984B	1N2970	DZ							20*	5.0	10W
1N4270	S	1N2985	1N2979	DZ							22*	20	10W
1N4270A	S	1N2985A	1N2970	DZ							22*	10	10W
1N4270B	S	1N2985B	1N2970	DZ							22*	5.0	10W
1N4271	S	1N2986	1N2970	DZ							24*	20	10W
1N4271A	S	1N2986A	1N2970	DZ							24*	10	10W
1N4271B	S	1N2986B	1N2970	DZ							24*	5.0	10W
1N4272	S	1N2988	1N2970	DZ							27*	20	10W
1N4272A	S	1N2988A	1N2970	DZ							27*	10	10W
1N4272B	S	1N2988B	1N2970	DZ							27*	5.0	10W
1N4273	S	1N2989	1N2970	DZ							30*	20	10W
1N4273A	S	1N2989A	1N2970	DZ							30*	10	10W
1N4273B	S	1N2989B	1N2970	DZ							30*	5.0	10W
1N4274	S	1N2990	1N2970	DZ							33*	20	10W
1N4274A	S	1N2990A	1N2970	DZ							33*	10	10W
1N4274B	S	1N2990B	1N2970	DZ							33*	5.0	10W
1N4275	S	1N2991	1N2970	DZ							36*	20	10W
1N4275A	S	1N2991A	1N2970	DZ							36*	10	10W
1N4275B	S	1N2991B	1N2970	DZ							36*	5.0	10W
1N4276	S	1N2992	1N2970	DZ							39*	20	10W
1N4276A	S	1N2992A	1N2970	DZ							39*	10	10W
1N4276B	S	1N2992B	1N2970	DZ							39*	5.0	10W
1N4277	S	1N2993	1N2970	DZ							43*	20	10W
1N4277A	S	1N2993A	1N2970	DZ							43*	10	10W
1N4277B	S	1N2993B	1N2970	DZ							43*	5.0	10W
1N4278	S	1N2995	1N2970	DZ							47*	20	10W
1N4278A	S	1N2995A	1N2970	DZ							47*	10	10W
1N4278B	S	1N2995B	1N2970	DZ							47*	5.0	10W
1N4279	S	1N2997	1N2970	DZ							51*	20	10W
1N4279A	S	1N2997A	1N2970	DZ							51*	10	10W
1N4279B	S	1N2997B	1N2970	DZ							51*	5.0	10W

www.datasheetcatalog.com

NUMERICAL INDEX

1N--- TYPE NUMBERS — COMPLETE INDEX and SHORT-FORM DEVICE SPECIFICATIONS

The following table lists, in numberical sequence, all EIA-registered devices with 1N---- type numbers. This also provides major electrical specifications for rectifier diodes, signal diodes, zener diodes, and reference diodes. The "key" to proper interpretation of these specifications is given below.

Other types of devices with 1N----numbers, including varactor diodes, tunnel diodes, and 4-layer diodes, are identified in the table but, due to the differences in major specifications, they are "specified" separately in succeeding tables.

www.datasheetcatalog.com

KEY

RECTIFIERS

V_R = DC Blocking Voltage
V_F = Average Forward Voltage Drop
I_O = Average Rectifier Forward Current
I_R = Average Reverse Current
I_{surge} = Peak Surge Current

ZENER DIODES

V_Z (min) = Minimum Zener Breakdown Voltage (Volts)
V_Z (max) = Maximum Zener Breakdown Voltage (used only when a corresponding **V_Z (min)** is specified. Otherwise, this column refers to **V_Z (nom)*** Nominal Zener Breakdown Voltage.)
Tol = Tolerance, for specified Nominal Breakdown Voltage
P_D = Maximum Power Dissipation. **M** = milliwatts. **W** = watts

TYPE	MATERIAL	REPLACEMENT	REF.	IDENTIFICATION	RECTIFIERS					ZENER DIODES			
					V_R (volts)	V_F (volts)	I_O (Amps)	I_R (mA)	I_{surge} (Amps)	V_Z (min)	V_Z (nom)* V_Z (max)	Tol V_Z %	P_D
					SIGNAL DIODES					REFERENCE DIODES			
					PRV (volts)	V_F @ I_F (volts)		I_R	t_{rr} (μS)	TC %/°C	V_Z	T (min) °C	T (max) °C
Numerical Listing of Registered Type Numbers					**SHADING INDICATES SIGNAL DIODES** **PRV** = Peak Reverse Voltage **V_F @ I_F** = Maximum Forward Voltage at Indicated Forward Current — M = milliamps, A = amps **I_R** = Reverse Current — M = milliamps, * = microamps N = nanoamps **t_{rr}** = Reverse Recovery Time					**SHADING INDICATES REFERENCE DIODES** **TC** = Temperature Coefficient **V_Z** = Zener Breakdown Voltage **T (min)** } Temperature Range **T (max)** } over which indicated temperature coefficient is applicable.			
S = Silicon G = Germanium SE = Selenium													
Type number of recommended replacement or of nearest electrical equivalent fully characterized in this book.													
Reference device number indicates specific Data Sheet on which device is characterized.													

The codes listed below define the listed device and indicates the appropriate specification column heading.

R* — Rectifiers
DR — Diode, Reference
DZ — Diode, Zener
DS — Diode, Signal