channel-html-compare analytics

Table of contents

- Introduction
- Usage
- Event Definitions
  - channel:buy-button-click
  - channel:user-select
  - channel:viewport-change
  - channel:orientation-change
  - channel:reorder-dom

Introduction

The `channel-html-compare` component ships with an analytics layer which allows vendors to track key events from end-users during interaction.

These events can be subscribed to and provide a rich level of detail denoting user behaviour during a session.

Each `event.detail` delivers a payload containing useful information about user interaction.

Usage

To access the different reporting events use the method below:

```
window.addEventListener('channel:buy-button-click', (event) => {
  console.log(`channel:buy-button-click`, event.detail); // Logs the data for this event
});
```

> *See below for a full list of possible event types.*

Event Definitions

`channel:buy-button-click`

- Emits when a user interacts with the "Buy Now" CTA in the component

Example:

```
{
  "productName": "Product A",
  "eventSource": "Mouse Click"
}
```

Detail Key	Type	Description
`productName`	`string`	Human readable product description
`eventSource`	`string`	Returns either `"Mouse Click"` or `"Keyboard Interaction"`

`channel:user-select`

- Emits when a user interacts with the device selection menu

Example:

- The `event.detail` returns an `array[]` of objects currently visible to the user
- In the example below, there are three columns visible, with the first being the selected column

```
// event.detail
{
  "deviceLineup": {
    "0": {
      "columnIndex": 0,
      "deviceName": "Product A",
      "hasChanged": true
    },
    "1": {
      "columnIndex": 1,
      "deviceName": "Product B",
      "hasChanged": false
    },
    "2": {
      "columnIndex": 2,
      "deviceName": "Product C",
      "hasChanged": false
    }
  }
}
```

Detail Key	Type	Description
`deviceLineup[i].columnIndex`	`number`	Zero based index of the column this product occupies
`deviceLineup[i].deviceName`	`string`	Human readable product description
`deviceLineup[i].hasChanged`	`boolean`	The most recent state of the device interaction

`channel:viewport-change`

- Emits when the viewport changes between viewport ranges
- Returns a `string` defined by the range below

Value	Minimum	Maximum
`small`	320px	734px
`medium`	735px	1068px
`large`	1069px	1440px
`xlarge`	1441px	3008px

`channel:orientation-change`

- Emits when the user's browser changes orientation
- Returns a `string` containing either one of `landscape` or `portrait`

`channel:reorder-dom`

- Emits the current active configuration of the component
- Occurs on viewport change, orientation change, and after a user selection is made

Detail Key	Type	Description
`max`	`number`	The maximum number of devices for the active viewport

`order`	`array`	An array indicating the selected index for each menu, in the order of appearance left to right
`selectorIndex`	`number`	A zero index of the menu which has changed from the left to right
`useStatic`	`boolean`	A constant value indicating whether the interactive menu is enabled

---